

EQUIP MENT		PAGE 2 OF 2 CG 20 CODE BT-425-D (F)	USE LBS	N-CODE	ACCT LBS
SV	1	RECORD: PH <u>10.0</u> (8.5-10.0)			
CONT	2	IF NECESSARY, ADJ TO PH 8.5-10.0 ASSUME 50% & RECORD PH _____ ASSUME 77%		7-D 27-D	
313	9	RUN 24" (355G) WATER INTO V-313			
2	10	TURN ON AGITATOR & HEAT TO 80-100 DEG F			
		NOTE : VENT ON SOD.DRESINATE TANK OR VAT			
		USED FOR THIS SOL'N SHOULD BE CHECKED FOR			
		DRAFT PRIOR TO DUMPING THE SOD.DRESINATE			
	11	SIFT IN (+/-1 MIN PER BAG)	320	530-A	320
	12	STIR 5 MIN & RECORD: PH <u>10.2</u> (10.0-10.5)			
	13	STIR AN ADDITIONAL 15 MIN OR LONGER TO DISSOLVE FOR S16			
304	14	RUN 10" (122G) WATER INTO V-304			
3	15	DUMP IN & STIR TO DISSOLVE FOR S17	100	20-A	100
SV	16	RUN V-313 THRU 20 MESH SCREEN INTO SV &			
4		STIR 5 MIN.			
	17	RUN IN V-304 IN 5-10 MIN & STIR 15 MIN			
	18	RECORD: PH <u>9.9</u> (9.0-10.0)			
	19	FLOOD TO <u>8.8</u> & STOP AGITATOR			
		SV 200 202 204 210 213 261			
		S19 77" 87" 88" 74" 52" 60"			
		GAL 5205 5150 5174 5143 5153 5220			
		START FIN OPTR			
		<u>3:00 PM</u> <u>11:00 PM</u> <u>101</u>			
		<u>11 PM</u> <u>12:43</u> <u>282</u>			