

BRAKE SHOE SPECIFICATIONS

PROCEDURES and
SPECIFICATIONS SECTION

5

ASSEMBLY or KIT PART NUMBER	SIZE (INCHES) (O.D. X WIDTH)	PRI. or SEC.	FOR LINING POSITION SEE TYPE	MINIMUM LINING THICKNESS (INCHES)	ASSEMBLY or KIT PART NUMBER	SIZE (INCHES) (O.D. X WIDTH)	PRI. or SEC.	FOR LINING POSITION SEE TYPE	MINIMUM LINING THICKNESS (INCHES)
†BTD 2001-A	12 1/8 x 2	P	3	.338	†C80Z 2001-E	10 x 2 1/2	P	1	.175
*†BBS 2001-A (Not replaced)	11 x 3 1/2	P	4	.175			S	2 (Bonded)	.230
		S	2	.330	*†C8SZ 2001-A r/b *C8SZ 2001-D Not replaced	11 x 3	P	3	.175
*†C0AZ 2001-A (Not replaced)	11 x 3 1/2	P	4	.175			S	2	.268
*†C0AZ 2001-C (Not replaced)	11 x 3	P	4	.175	†C9AZ 2001-A	11 x 3	P	1	.195
*†C0AZ 2001-E (Not replaced)	11 x 3	P	4	.175			S	2	.270
*†C0LY 2001-C (Not replaced)	11 x 3 1/2	P	3a	.205	*†C9AZ 2001-B	11 x 2 1/2	P	1	.185
*†C0LY 2001-D (Not replaced)	11 x 3 1/2	P	3a	.205	r/b DIAZ 2001-B		S	2	.270
		S	2b	.268	*†C9AZ 2001-C	11 x 3	P	1	.195
*†C0MY 2001-E (Not replaced)	11 x 3	P	3a	.205	r/b C9AZ 2001-C		S	2	.270
*†C0MY 2001-F (Not replaced)	11 x 3	P	3a	.205	*†C9AZ 2001-D	11 x 3	P	1	.195
†C0TZ 2001-A	11 x 2	P	4	.175	r/b C9AZ 2001-C		S	2	.230
		S	2	.330	*†C9DZ 2001-A	9 x 2 1/4	P	1	.175
†C0TZ 2001-A	11 x 2	P	4	.305	r/b C4DZ 2001-A		S	2	.230
		S	2	.353	*†C9SZ 2001-D Not replaced	11 x 3	P	1a	.205
*†C1AZ 2001-A	11 x 2 1/2	P	3	.195			S	2	.268
r/b DIAZ 2001-B		S	2	.270	†C4DZ 2001-A	9 x 2 1/4	P	1	.175
*†C1AZ 2001-B	11 x 3	P	3	.195			S	2	.230
r/b C9AZ 2001-C		S	2	.270	*†C4TZ 2001-A (Not replaced)	11 x 2	P	4	.205
*†C1AZ 2001-C	11 x 3	P	3	.195			S	2	.260
r/b C9AZ 2001-A		S	2 (Bonded)	.270	*†C4UZ 2001-A	10 x 2 1/2	P	1	.175
		S	2 (Bonded)	.270	r/b DIUZ 2001-A		S	2	.230
*†C1DZ 2001-A	9 x 2 1/4	P	1	.175	*†C5AZ 2001-A	11 x 2 1/2	P	1	.195
r/b C4DZ 2001-A		S	2	.230	r/b DIAZ 2001-B		S	2	.270
*†C1SZ 2001-B	11 x 3	P	3a	.205	†C5AZ 2001-C	11 x 3	P	1	.165
r/b *C3SZ 2001-D Not replaced		S	2b	.330			S	2	.270
*†C1SZ 2001-C	11 x 3	P	1	.185	*†C5MY 2001-A	11 x 2 1/2	P	1	.195
r/b *C3SZ 2001-D Not replaced		S	2	.330	r/b DIAZ 2001-B		S	2b	.230
*†C1SZ 2001-D	11 x 3	P	3	.175	*†C5TZ 2001-A	12 1/8 x 2	P & B	2	.238
r/b *C3SZ 2001-D Not replaced		S	2	.268	r/b C5TZ 2001-K		P	4	.205
*†C1UZ 2001-A	10 x 2 1/2	P	1	.175	*†C5TZ 2001-B	11 x 2	P	4	.205
r/b DIUZ 2001-A		S	2	.230	r/b C5TZ 2001-L		S	5	.260
*†C1VY 2001-C (Not replaced)	11 x 3	P	3	.205	*†C5TZ 2001-C	11 x 2	P	4	.205
*†C1VY 2001-E (Not replaced)	11 x 3	P	3	.205	r/b C5TZ 2001-L		S	5	.260
		S	2	.268	*†C5TZ 2001-E	10 x 2 1/2	P	1	.175
*†C1AZ 2001-A	11 x 3	P	1	.185	r/b DIUZ 2001-A		S	2	.230
r/b C9AZ 2001-A		S	2 (Bonded)	.270	†C5TZ 2001-P	10 x 2 1/2	P	1	.175
		S	2 (Bonded)	.270			S	2	.230
*†C1AZ 2001-B	11 x 2 1/2	P	1	.195	*†C5TZ 2001-Q	11 x 2	P	4	.205
r/b DIAZ 2001-B		S	2	.270	r/b C5TZ 2001-L		S	5	.260
*†C1AZ 2001-C	11 x 3	P	1	.195	*†C5TZ 2001-H	11 x 3	P	4	.205
r/b C9AZ 2001-C		S	2	.270			S	5	.260
*†C1AZ 2001-D	11 x 3	P	1	.195	r/b C5TZ 2001-B		S	5	.260
r/b C9AZ 2001-C		S	2	.270	*†C5TZ 2001-J	12 1/8 x 2	P & B	2	.238
*†C80Z 2001-A	10 x 2 1/4	P	1	.175	r/b C5TZ 2001-K		P	4	.205
r/b D10Z 2001-C		S	2	.230	†C5TZ 2001-L	11 x 2	P	4	.205
*†C80Z 2001-D	10 x 2 1/2	P	1	.175			S	5	.260
r/b C80Z 2001-A		S	2	.230			S	5	.260

* See illustrations on Opposite Page.

† Standard

‡ Overline

8008 0593

PRODUCED BY FORD