



Threshold Limit Values of Air-borne Contaminants For 1968

RECOMMENDED
AND INTENDED VALUES



Adopted at the 30th Annual Meeting of the American
Conference of Governmental Industrial Hygienists,
St. Louis, Missouri, May 13, 1968.

TX TINER
RMC0042488

THRESHOLD LIMIT VALUES FOR 1968

The Threshold Limit Values refer to air-borne concentrations of substances and represent conditions under which it is believed that nearly all workers may be repeatedly exposed, day after day, without adverse effect. Because of wide variation in individual susceptibility, exposure of an occasional individual at or even below the threshold limit may not prevent discomfort, aggravation of a pre-existing condition, or occupational illness.

Clinical tests are becoming available that permit detection of those individuals who will hyperreact upon exposure to certain industrial substances. Being predictive in character, they may be applied as screening tests in the preplacement job examination. Requests for further details of these tests should be directed to the Chairman of the Committee.

Threshold limits should be used as guides in the control of health hazards and should not be regarded as fine lines between safe and dangerous concentrations. Exceptions are the substances given in Appendix A and certain of the substances given a "C" listing. The values not given a "C" listing refer to time-weighted average concentrations for a conventional 8 hour workday.

Time-weighted average concentrations permit excursions above the limit, provided they are compensated by equivalent excursions below the limit during the work day. The degree of permissible excursion is pegged to the threshold limit value of the particular substance as given in table in Appendix C under "Test TLV Factor." Hence, it is not considered appropriate to interpret air concentration values as exceeding time-weighted average limits, if such values lie within the permissible excursions. (See section on Legislative Code.)

The amount by which these concentrations may be exceeded for short periods without injury to health depends upon a number of factors such as the nature of the contaminant, whether very high concentrations even for short periods produce acute poisoning, whether the effects are cumulative, the frequency with which high concentrations occur, and the duration of such periods. All must be taken into consideration in arriving at a decision as to whether a hazardous situation exists. Enlightened industrial hygiene practice inclines toward controlling exposures below the limit rather than maintenance at the limit.

Threshold limits are based on the best available information from industrial experience, from experimental human and animal studies, and when possible, from a combination of the three. The basis on which the values are established may differ from substance to substance: protection against impairment of health may be the guiding factor for some, whereas reasonable freedom from irritation, narcosis, nuisance or other forms of stress may dominate the basis for others. The Committee holds to the opinion that limits based on physical irritation should be considered no less binding than those based on

Copyright 1968, by American Conference of Governmental Industrial Hygienists.

The American Conference of Governmental Industrial Hygienists will welcome requests for permission to republish or reprint these Threshold Limit Values. Requests for such permission should be directed to the Secretary-Treasurer, 1014 Broadway, Cincinnati, Ohio 45202.

Price Each

1 - 49 Copies	50¢
50 - 999 Copies	49¢
1000 - 4999 Copies	30¢
5000 or more Copies	15¢

The 2nd edition of the Documentation of Threshold Limit Values, is currently out of print. Information concerning availability of reprints should be directed to the Secretary - Treasurer. The Documentation should be consulted when using the Threshold Limit Values herein.

physical impairment: growing bodies of evidence indicate that physical irritation may promote and accelerate physical impairment.

These limits are intended for use in the field of industrial hygiene and should be interpreted and applied only by persons trained in this field. They are not intended for use, or for modification for use, (1) as a relative index of toxicity, by making a ratio of two limits, (2) in the evaluation or control of community air pollution or air pollution nuisances, (3) in estimating the toxic potential of continuous uninterrupted exposures, (4) as proof or disproof of an existing disease or physical condition, or (5) for adoption by countries whose working conditions differ from those in the United States of America and where substances and processes differ.

Documentation of Threshold Limit Values. A separate companion piece to the TLVs is issued by ACGIH under this title. This publication gives the pertinent scientific information and data with reference to literature sources that were used to base each limit. Each documentation also contains a statement defining the type of response against which the limit is safeguarding the worker. For a better understanding of the TLVs it is essential that the Documentation be consulted when the TLVs are being used.

Ceiling vs Time-Weighted Average Limits. Although the time-weighted average concentration provides the most satisfactory, practical way of monitoring air-borne agents for compliance with the limits, there are certain substances for which it is inappropriate. In the latter group are substances which are predominantly fast acting and whose threshold limit is more appropriately based on this particular response. Substances with this type of response are best controlled by a ceiling "C" limit that should not be exceeded. It is implicit in these definitions that the manner of sampling to determine compliance with the limits for each group must differ; a single brief sample, that is applicable to a "C" limit, is not appropriate to the time-weighted limit; here, a sufficient number of samples are needed to permit a time-weighted average concentration throughout a complete cycle of operations or throughout the work shift.

Whereas the ceiling limit places a definite boundary which concentrations should not be permitted to exceed, the time-weighted average limit requires an explicit limit to the excursions that are permissible above the listed values. The magnitude of these excursions may be pegged to the magnitude of the threshold limit by an appropriate factor shown in Appendix C. It should be noted that the same factors are used by the Committee in making a judgment whether to include or exclude a substance for a "C" listing.

"Skin" Notation. Listed substances followed by the designation "Skin" refer to the potential contribution to the over-all exposure by the cutaneous route including mucous membranes and eye, either by air-borne, or more particularly, by direct contact with the substance. Vehicles can alter skin absorption.

2

This attention-calling designation is intended to suggest appropriate measures for the prevention of cutaneous absorption so that the threshold limit is not invalidated.

These values are reviewed annually by the Committee on Threshold Limits for revision or additions, as further information becomes available.

Mixtures. Special consideration should be given also to the application of these values in assessing the health hazards which may be associated with exposure to mixtures of two or more substances. A brief discussion of basic considerations involved in developing threshold limit values for mixtures, and methods for their development, amplified by specific examples are given in Appendix B.

"Inert" or Nuisance Particulates. A number of dusts or particulates that occur in the working environment ordinarily produce no specific effects upon prolonged inhalation. Some insoluble substances are classed as inert (e.g. iron and steel dusts, cement, silicon carbide, titanium dioxide, cellulose); others may be soluble (starch, soluble oils, calcium carbonate) but are of such a low order of activity that in concentrations ordinarily encountered do not cause physiologic impairment; still others may be rapidly eliminated or destroyed by the body (vegetable oils, glycerine, sucrose). In the case of the insoluble substances, there may be some accumulation in the respiratory passages. In the case of the soluble substances, this accumulation will ordinarily be temporary but may interfere to some extent with respiratory processes. Hence, it is desirable to control the concentrations of such particulates in the air breathed by any individual, in keeping with good industrial hygiene practice.

A threshold limit of $15\text{mg}/\text{m}^3$, or 50 mppcf, whichever is less, is recommended for substances in these categories and for which no specific threshold limits have been assigned. This limit, for a normal work day, does not apply to brief exposures at higher concentrations. Neither does it apply to those substances which may cause physiologic impairment at lower concentrations but for which a threshold limit has not yet been adopted. Some "inert" particulates are given in Appendix D.

Simple Asphyxiants - "Inert" Gases or Vapors. A number of gases and vapors, when present in high concentrations in air, act primarily as simple asphyxiants without other significant physiologic effects. A TLV may not be recommended for each simple asphyxiant because the limiting factor is the available oxygen. The minimal oxygen content should be 18 percent by volume under normal atmospheric pressure (equivalent to a partial pressure, pO_2 , of 135 mm Hg). Atmospheres deficient in O_2 do not provide adequate warning and most simple asphyxiants are odorless. Several simple asphyxiants present an explosion hazard. Account should be taken of this factor in limiting the concentration of the asphyxiant.

Physical Factors. It is recognized that such physical factors as heat, ultraviolet and ionizing radiation, humidity, abnormal

3

pressure and the like may place added stress on the body so that the effects from exposure at a threshold limit may be altered. Most of these stresses act adversely to increase the toxic response of a substance. Although most threshold limits have built-in safety factors to guard against adverse effects of moderate deviations from normal environments, the safety factors of most substances are not of such a magnitude as to take care of gross deviations. For example, continuous work at temperatures above 90°F or over-time extending the work-week more than 50%, might be considered gross deviations. In such instances judgment must be exercised in the proper adjustments of the threshold limit values.

"Notice of Intent" At the beginning of each year, proposed actions of the Committee for the forthcoming year are issued in the form of a "Notice of Intent." This Notice provides not only an opportunity for comment, but solicits suggestions of substances to be added to the list. The suggestions should be accompanied by substantiating evidence.

As Legislative Code. The Conference does not consider the Threshold Limit Values appropriate matter for adoption in legislative codes and regulations and recommends against such use. If, however, the list is so used, the intent of the concepts contained in the Preface should be maintained and provisions should be made to keep the list current.

Reprint Permission. This publication may be reprinted provided that written permission is obtained from the Secretary-Treasurer of the Conference and that it be published in its entirety.

RECOMMENDED VALUES (In Alphabetical Order)

Substance	a) ppm	b) Mg/M ³
Acetaldehyde	200	360
Acetic acid	10	25
Acetic anhydride	5	20
Acetone	1,000	2,400
Acetonitrile	40	70
Acetylene dichloride, see 1,2 Dichloro-ethylene		
Acetylene tetrabromide	1	14
Acrolein	0.1	0.25
Acrylamide-Skin	-	0.3
Acrylonitrile-Skin	20	45
Aldrin-Skin	-	0.25
Allyl alcohol-Skin	2	5
Allyl chloride	1	3
C Allyl glycidyl ether (AGE)	10	45
Allyl propyl disulfide	2	12
2-Aminoethanol, see Ethanolamine		
2-Aminopyridine	0.5	2
Ammonia	50	35
Ammonium sulfamate (Ammate)	-	15
n-Amyl acetate	100	525
sec-Amyl acetate	125	650
Aniline-Skin	5	19
Anisidine (o, p-isomers)-Skin	-	0.5
Antimony & compounds (as Sb)	-	0.5
ANTU (alpha naphthyl thiourea)	-	0.3
Arsenic & Compounds (as As)	-	0.5
Arsine	0.05	0.2
Azinphos-methyl-Skin	-	0.2
Barium (soluble compounds)	-	0.5
C Benzene (benzol)-Skin	25	80
Benzidine-Skin	-	A ¹
p-Benzoquinone, see Quinone		
Benzoyl peroxide	-	5
Benzyl chloride	1	5
Beryllium	-	0.002
Biphenyl, see Diphenyl		
Boron oxide	-	15
C Boron trifluoride	1	3
Bromine	0.1	0.7
Bromoform-Skin	0.5	5
Butadiene (1,3-butadiene)	1,000	2,200
Butanethiol, see Butyl mercaptan		

a) Parts of vapor or gas per million parts of contaminated air by volume at 25° C and 760 mm. Hg pressure.

b) Approximate milligrams of particulate per cubic meter of air.

A Numbers, See Appendix A

* 1968 Addition

** See Notice of Intended Changes

Substance	a) ppm	b) Mg/M ³
2-Butanone	200	590
2-Butoxy ethanol (Butyl Cellosolve)-Skin ..	50	240
Butyl acetate (n-butyl acetate)	150	710
n-Butyl acetate	150	710
sec-Butyl acetate	200	950
tert-Butyl acetate	200	950
Butyl alcohol	100	300
* sec-Butyl alcohol	150	450
tert. Butyl alcohol	100	300
C Butylamine-Skin	5	15
C tert. Butyl chromate (as CrO ₃)-Skin	—	0.1
n-Butyl glycidyl ether (BGE)	50	270
** Butyl mercaptan	10	35
p-tert. Butyltoluene	10	60
Cadmium (Metal dust and soluble salts).....	—	0.2
** Cadmium oxide fume	—	0.1
Calcium arsenate	—	1
Calcium oxide	—	5
** Camphor	—	2
Carbaryl (Sevin) (R)	—	5
Carbon black	—	3.5
Carbon dioxide	5,000	9,000
Carbon disulfide-Skin	20	60
Carbon monoxide	50	55
Carbon tetrachloride-Skin	10	65
Chlordane-Skin	—	0.5
Chlorinated camphene, -Skin	—	0.5
Chlorinated diphenyl oxide	—	0.5
**C Chlorine	1	3
Chlorine dioxide	0.1	0.3
C Chlorine trifluoride	0.1	0.4
C Chloroacetaldehyde	1	3
* Chloroacetophenone (phenacylchloride) ..	0.05	0.3
Chlorobenzene (monochlorobenzene)	75	350
o-Chlorobenzylidene malononitrile (OCBM)	0.05	0.4
Chlorobromomethane	200	1,050
2-Chloro-1,3 butadiene, see Chloroprene ..	—	—
Chlorodiphenyl (42% chlorine)-Skin	—	1
Chlorodiphenyl (54% chlorine)-Skin	—	0.5
1-Chloro, 2,3 epoxyp propane, see Epichlorhydrin	—	—
2, Chloroethanol, see Ethylene chlorohydrin	—	—
Chloroethylene, see Vinyl chloride	—	—
C Chloroform (trichloromethane)	50	240
1-Chloro-1-nitropropane	20	100
Chloropicrin	0.1	0.7
Chloroprene (2-chloro-1, 3-butadiene)-Skin ..	25	90
Chromic acid and chromates (as CrO ₃)	—	0.1
* Chromium, sol. chromic, chromous salts ..	—	0.5
as Cr	—	—
Metal & insol. salts	—	1
Coal tar pitch volatiles (benzene soluble fraction) (anthracene, BaP, phenanthrene, acridine, chrysene, pyrene) ..	—	0.2

** See Notice of Intended Changes

Substance	a) ppm	b) Mg/M ³
* Cobalt, metal fume & dust	—	0.1
Copper fume	—	0.1
Dusts and Mists	—	1.0
Cotton dust (raw)	—	1
Crag (R) herbicide	—	15
Cresol (all isomers)-Skin	5	22
Crtonaldehyde	2	6
Cumene-Skin	50	245
Cyanide (as CN)-Skin	—	5
Cyclohexane	300	1,050
Cyclohexanol	50	200
Cyclohexanone	50	200
Cyclohexene	300	1,015
Cyclopentadiene	75	200
2, 4-D	—	10
DDT-Skin	—	1
DDVP-Skin	—	1
Decaborane-Skin	0.05	0.3
Demeton (R)-Skin	—	0.1
Diacetone alcohol (4-hydroxy-4-methyl-2-pentanone)	50	240
1, 2 Diaminoethane, see Ethylenediamine ..	—	—
Diazomethane	0.2	0.4
Diborane	0.1	0.1
C 1, 2-Dibromoethane (ethylene dibromide)-Skin	25	190
* Dibutyl phosphate	1	5
* Dibutylphthalate	—	5
C o-Dichlorobenzene	50	300
p-Dichlorobenzene	75	450
Dichlorodifluoromethane	1,000	4,950
1, 3-Dichloro-5, 5-dimethyl hydantoin	—	0.2
1, 1, -Dichloroethane	100	400
1, 2-Dichloroethane	50	200
1, 2-Dichloroethylene	200	790
C Dichloroethyl ether-Skin	15	90
Dichloromethane, see Methylenechloride ..	—	—
Dichloromonofluoromethane	1,000	4,200
C 1, 1-Dichloro-1-nitroethane	10	60
1, 2-Dichloropropane, see Propylenedi-chloride	—	—
Dichlorotetrafluoroethane	1,000	7,000
Dieldrin-Skin	—	0.25
Diethylamine	25	75
Diethylamino ethanol-Skin	10	50
Diethylether, see Ethyl ether	—	—
Difluorodibromomethane	100	860
C Diglycidyl ether (DGE)	0.5	2.8
Dihydroxybenzene, see Hydroquinone	—	—
Diisobutyl ketone	50	290
* Diisopropylamine - Skin	5	20
Dimethoxymethane, see Methylal	—	—
Dimethyl acetamide-Skin	10	35
Dimethylamine	10	18
Dimethylaminobenzene, see Xylidene	—	—

* 1968 Addition

Substance	a) ppm	b) Mg M ²
Dimethylaniline (N-dimethylaniline)-Skin	5	25
Dimethylbenzene, see Xylene		
Dimethyl 1, 2-dibromo-2, 2-dichloroethyl phosphate, (Dibrom) *	—	3
Dimethylformamide-Skin	10	30
2,6 Dimethylheptanone, see Diisobutyl ketone		
1,1-Dimethylhydrazine-Skin	0.5	1
* Dimethylphthalate	—	5
Dimethyl sulfate - Skin	1	5
Dinitrobenzene (all isomers)-Skin	—	1
Dinitro-o-cresol-Skin	—	0.2
Dinitrotoluene-Skin	—	1.5
Dioxane (Diethylene dioxide)-Skin	100	360
* Diphenyl	0.2	1
Diphenylmethane diisocyanate (See Methylene bisphenyl isocyanate (MDI))		
Dipropylene glycol methyl ether-Skin	100	600
Di-sec, octyl phthalate (Di-2-ethylhexyl-phthalate)	—	5
Endrin-Skin	—	0.1
Epichlorohydrin-Skin	5	19
EPN-Skin	—	0.5
1,2-Epoxypropane, see Propyleneoxide		
2,3-Epoxy-1-propanol see Glycidol		
Ethanolthiol, see Ethylmercaptan		
Ethanolamine	3	6
2 Ethoxyethanol-Skin	200	740
2 Ethoxyethylacetate (Cellosolve acetate) -Skin	100	540
Ethyl acetate	400	1,400
Ethyl acrylate-Skin	25	100
Ethyl alcohol (ethanol)	1,000	1,900
Ethylamine	10	18
Ethyl sec-amyl ketone (5-methyl-3-heptanone)	25	130
Ethyl benzene	100	435
Ethyl bromide	200	890
Ethyl butyl ketone (3-Heptanone)	50	230
Ethyl chloride	1,000	2,600
Ethyl ether	400	1,200
Ethyl formate	100	300
**C Ethyl mercaptan	10	25
Ethyl silicate	100	850
Ethylene chlorohydrin-Skin	5	16
Ethylenediamine	10	25
Ethylene dibromide, see 1,2-Dibromo-ethane		
Ethylene dichloride, see 1,2-Dichloro-ethane		
*C Ethylene glycol dinitrate and/or Nitroglycerin - Skin	0.2 d)	1

d) An atmospheric concentration of not more than 0.02 ppm, or personal protection may be necessary to avoid headache.

** See Notice of Intended Changes

Substance	a) ppm	b) Mg M ²
Ethylene glycol monomethyl ether acetate, see Methyl cellosolve acetate		
Ethylene imine-Skin	0.5	1
Ethylene oxide	50	90
Ethylidene chloride, see 1,1-Dichloro-ethane		
N-Ethylmorpholine-Skin	20	94
Ferbam	—	15
Ferrovandium dust	—	1
Fluoride (as F)	—	2.5
Fluorine	0.1	0.2
Fluorotrichloromethane	1,000	5,600
C Formaldehyde	5	6
Formic acid	5	9
Furfural-Skin	5	20
Furfuryl alcohol	50	200
Gasoline	—	A6
Glycidol (2,3-Epoxy-1-propanol)	50	150
Glycol monoethyl ether, see 2-Ethoxy-ethanol		
Guthion, * see Azinphosmethyl		
Hafnium	—	0.5
Heptachlor-Skin	—	0.5
** Heptane (n-heptane)	500	2,000
Hexachloroethane-Skin	1	10
* Hexachloronaphthalene - Skin	—	0.2
Hexane (n-hexane)	500	1,800
2-Hexanone	100	410
Hexone	100	410
sec-Hexyl acetate	50	300
Hydrazine-Skin	1	1.3
Hydrogen bromide	3	10
C Hydrogen chloride	5	7
Hydrogen cyanide-Skin	10	11
Hydrogen fluoride	3	2
Hydrogen peroxide, 90%	1	1.4
Hydrogen selenide	0.05	0.2
Hydrogen sulfide	10	15
Hydroquinone	—	2
C Iodine	0.1	1
Iron oxide fume	—	10
Isoamyl acetate	100	525
Isoamyl alcohol	100	360
Isobutyl acetate	150	700
* Isobutyl alcohol	100	300
Isophorone	25	140
Isopropyl acetate	250	950
Isopropyl alcohol	400	980
Isopropylamine	5	12
Isopropylether	500	2,100
Isopropyl glycidyl ether (IGE)	50	240
Ketene	0.5	0.9
Lead	—	0.2
Lead arsenate	—	0.15
Lindane-Skin	—	0.5

* 1968 Addition

Substance	ppm ^{a)}	Mg M ³ b)
Lithium hydride	—	0.025
L. P. G. (Liquified petroleum gas)	1,000	1,800
Magnesium oxide fume	—	15
Malathion-Skin	—	15
* Maleic anhydride	0.25	1
C Manganese	—	5
Mercury-Skin	—	0.1
Mercury organic compounds-Skin	—	0.01
Mesityl oxide	25	100
Methanethiol, see Methyl mercaptan	—	—
Methoxychlor	—	15
2-Methoxyethanol, see Methyl cellosolve	—	—
Methyl acetate	200	610
Methyl acetylene (propyne)	1,000	1,650
Methyl acetylene-propadiene mixture (MAPP)	1,000	1,800
Methyl acrylate-Skin	10	35
Methylal (dimethoxymethane)	1,000	3,100
Methyl alcohol (methanol)	200	260
Methylamine	10	12
Methyl amyl alcohol, see Methyl iso-butyl carbinol	—	—
Methyl (n-amyl) ketone (2-Heptanone)	100	465
C Methyl bromide-Skin	20	80
Methyl butyl ketone, see 2-Hexanone	—	—
Methyl cellosolve-Skin	25	80
Methyl cellosolve acetate-Skin	25	120
C Methyl chloride	100	210
Methyl chloroform	350	1,900
Methylcyclohexane	500	2,000
Methylcyclohexanol	100	470
o-Methylcyclohexanone-Skin	100	460
Methyl ethyl ketone (MEK), see 2-Butanone	—	—
Methyl formate	100	250
Methyl iodide - Skin	5	28
Methyl isobutyl carbinol-Skin	25	100
Methyl isobutyl ketone, see Hexone	—	—
Methyl isocyanate - Skin	0.02	0.05
**C Methyl mercaptan	10	20
Methyl methacrylate	100	410
Methyl propyl ketone, see 2-Pentanone	—	—
C αMethyl styrene	100	480
C Methylene bisphenyl isocyanate (MDI)	0.02	0.2
Methylene chloride (dichloromethane)	500	1,740
Molybdenum (soluble compounds)	—	5
(insoluble compounds)	—	15
Monomethyl aniline-Skin	2	9
C Monomethyl hydrazine - Skin	0.2	0.35
Morpholine-Skin	20	70
* Naphtha (coal tar)	100	400
Naphthalene	10	50
β-Naphthylamine	—	A ²
Nickel carbonyl	0.001	0.007
Nickel, metal and soluble compounds	—	1

** See Notice of Intended Changes

10

Substance	ppm ^{a)}	Mg M ³ b)
Nicotine-Skin	—	0.5
Nitric acid	2	5
* Nitric oxide	25	30
p-Nitroaniline-Skin	1	6
Nitrobenzene-Skin	1	5
p-Nitrochlorobenzene-Skin	—	i
Nitroethane	100	310
C Nitrogen dioxide	5	9
Nitrogen trifluoride	10	29
C Nitroglycerin-Skin	0.2	2
Nitromethane	100	250
1-Nitropropane	25	90
2-Nitropropane	25	90
N-Nitrosodimethyl-amine (Di-methyl-nitrosoamine)-Skin	—	A ³
Nitrotoluene-Skin	5	30
Nitrotrichloromethane, see Chloropicrin	—	—
* Octachloronaphthalene - Skin	—	0.1
** Octane	500	2,350
** Oil mist (mineral)	—	5
Osmium tetroxide	—	0.002
Oxalic acid	—	1
Oxygen difluoride	0.05	0.1
Ozone	0.1	0.2
* Paraquat - Skin	—	0.5
Parathion-Skin	—	0.1
Pentaborane	0.005	0.01
Pentachloronaphthalene-Skin	—	0.5
Pentachlorophenol-Skin	—	0.5
** Pentane	1,000	2,950
2-Pentanone	200	700
Perchloroethylene	100	670
Perchloromethyl mercaptan	0.1	0.8
Perchloryl fluoride	3	13.5
** Petroleum Distillates (naphtha)	500	2,000
Phenol-Skin	5	19
p-Phenylene diamine-Skin	—	0.1
Phenyl ether (vapor)	1	7
Phenyl ether-Biphenyl mixture (vapor)	1	7
Phenylethylene, see Styrene	—	—
* Phenyl glycidyl ether (PGE)	10	60
Phenylhydrazine-Skin	5	22
Phosdrim (Mevinphos)® -Skin	—	0.1
Phosgene (carbonyl chloride)	0.1	0.4
Phosphine	0.3	0.4
Phosphoric acid	—	1
Phosphorus (yellow)	—	0.1
Phosphorus pentachloride	—	1
Phosphorus pentasulfide	—	1
Phosphorus trichloride	0.5	3
Phthalic anhydride	2	12
Picric acid-Skin	—	0.1
Pival® (2-Pivalyl-1,3-indandione)	—	0.1
Platinum (Soluble Salts)	—	0.002
Polytetrafluoroethylene decomposition products	—	A ⁴

* 1968 Addition

11

TX TINER
RMC0042494

Substance	a) ppm	b) Mg M ³
products.....	—	A
Propane.....	1,000	1,600
Propiolactone.....	—	A ²
n-Propyl acetate.....	200	840
Propyl alcohol.....	200	500
n-Propyl nitrate.....	25	110
Propylene dichloride.....	75	350
Propylene imine - Skin.....	2	5
Propylene oxide.....	100	240
Propyne, see Methylacetylene.....	—	—
Pyrethrum.....	—	5
Pyridine.....	5	15
Quinone.....	0.1	0.4
Rhodium, Metal fume and dusts.....	—	0.1
Soluble salts.....	—	0.001
* Ronnel.....	—	15
Rotenone (commercial).....	—	5
Selenium compounds (as Se).....	—	0.2
Selenium hexafluoride.....	0.05	0.4
Silver, metal and soluble compounds.....	—	0.01
Sodium fluoroacetate (1080) - Skin.....	—	0.05
Sodium hydroxide.....	—	2
Stibine.....	0.1	0.5
** Stoddard solvent.....	500	2,900
Strychnine.....	—	0.15
**C Styrene monomer (phenylethylene).....	100	420
Sulfur dioxide.....	5	13
Sulfur hexafluoride.....	1,000	6,000
Sulfuric acid.....	—	1
Sulfur monochloride.....	1	6
Sulfur pentafluoride.....	0.025	0.25
Sulfuryl fluoride.....	5	20
Systox, see Demeton®.....	—	—
2, 4, 5 T.....	—	10
Tantalum.....	—	5
TEDP - Skin.....	—	0.2
Teflon® decomposition products.....	—	A ⁴
Tellurium.....	—	0.1
Tellurium hexafluoride.....	0.02	0.2
TEPP - Skin.....	—	0.05
*C Terphenyls.....	1	9
1, 1, 1, 2-Tetrachloro-2, 2-difluoroethane.....	500	4,170
1, 1, 2, 2-Tetrachloro-1, 2-difluoroethane.....	500	4,170
1, 1, 2, 2-Tetrachloroethane-Skin.....	5	35
Tetrachloroethylene, see Perchloroethylene.....	—	—
Tetrachloromethane, see Carbon tetrachloride.....	—	—
* Tetrachloronaphthalene - Skin.....	—	2
** Tetraethyl lead (as Pb) - Skin.....	—	0.075
Tetrahydrofuran.....	200	590
** Tetramethyl lead (TML) (as Pb) - Skin.....	—	0.075
Tetramethyl succinonitrile - Skin.....	0.5	3
Tetranitromethane.....	1	8
Tetryl (2, 4, 6-trinitrophenylmethylnitramine) - Skin.....	—	1.5

** See Notice of Intended Changes

12

Substance	a) ppm	b) Mg M ³
Thallium (soluble compounds) - Skin.....	—	0.1
Thiram.....	—	5
Tin (inorganic cmpds, except oxide).....	—	2
Tin (organic cmpds).....	—	0.1
Titanium dioxide.....	—	15
Toluene (toluol).....	200	750
C Toluene-2, 4-diisocyanate.....	0.02	0.14
o-Toluidine - Skin.....	5	22
Toxaphene, see Chlorinated camphene.....	—	—
* Tributyl phosphate.....	—	5
1, 1, 1-Trichloroethane, see Methyl chloroform.....	—	—
1, 1, 2-Trichloroethane - Skin.....	10	45
Trichloroethylene.....	100	535
Trichloromethane, see Chloroform.....	—	—
Trichloronaphthalene - Skin.....	—	5
1, 2, 3-Trichloropropane.....	50	300
1, 1, 2-Trichloro 1, 2, 2-trifluoroethane.....	1,000	7,600
Triethylamine.....	25	100
Trifluoromonomobromomethane.....	1,000	6,100
2, 4, 6-Trinitrophenol see Picric acid.....	—	—
2, 4, 6-Trinitrophenylmethylnitramine, see Tetryl.....	—	—
Trinitrotoluene - Skin.....	—	1.5
Triorthocresyl phosphate.....	—	0.1
Triphenyl phosphate.....	—	3
Turpentine.....	100	560
** Uranium (soluble compounds).....	—	0.05
(insoluble compounds).....	—	0.25
C Vanadium (V ₂ O ₅ dust).....	—	0.5
(V ₂ O ₅ fume).....	—	0.1
Vinyl benzene, see Styrene.....	—	—
C Vinyl chloride.....	500	1,300
Vinylcyanide, see Acrylonitrile.....	—	—
Vinyl toluene.....	100	480
Warfarin.....	—	0.1
Xylene (xylol).....	100	435
Xylidine - Skin.....	5	25
Yttrium.....	—	1
* Zinc chloride fume.....	—	1
Zinc oxide fume.....	—	5
Zirconium compounds (as Zr).....	—	5

Radioactivity: For permissible concentrations of radioisotopes in air, see U. S. Department of Commerce, National Bureau of Standards, Handbook 69, "Maximum Permissible Body Burdens and Maximum Permissible Concentrations of Radionuclides in Air and in Water for Occupational Exposure," June 5, 1959. Also, see U. S. Department of Commerce National Bureau of Standards, Handbook 59, "Permissible Dose from External Sources of Ionizing Radiation," September 24, 1954, and addendum of April 15, 1958.

* 1968 Addition

13

TX TINER
RMC0042495

MINERAL DUSTS

Substance m. p. p. c. f. ^{a)}

SILICA

Crystalline

** Quartz, Threshold Limit calculated from the formula

$$\frac{250 f)}{\%SiO_2 + 5}$$

** Cristobalite " " "

Amorphous, including natural

diatomaceous earth..... 20

Tremolite..... 5

SILICATES (less than 1% crystalline silica)

** Asbestos..... 5

Mica..... 20

Soapstone..... 20

Talc..... 20

Portland Cement..... 50

GRAPHITE (natural)..... 15

"Inert" or Nuisance Particulates 50 (or 15 mg m³

whichever is the smaller)

see Appendix D

Conversion factors

mppcf x 35.3 = million particles per cubic meter
= particles per c. c.

e) Millions of particles per cubic foot of air, based on impinger samples counted by light-field technics.

f) The percentage of crystalline silica in the formula is the amount determined from air-borne samples, except in those instances in which other methods have been shown to be applicable.

** See Notice of Intended Changes

14

NOTICE OF INTENDED CHANGES

These substances, with their corresponding values, comprise those for which either a limit has been proposed for the first time, or for which a change in the "Recommended" listing has been proposed. In both cases, the proposed limits should be considered trial limits that will remain in this listing for a period of at least two years. During this time, the previously Recommended limit will remain in effect. If, after two years no evidence comes to light that questions the appropriateness of the values herein, the values will be placed in the "Recommended" list. Documentation is available for each of these substances.

Substance	a) ppm	b) Mg m ³
Abate.....	-	15
Boron tribromide.....	1.0	-
Bromine pentafluoride.....	0.1	-
+ Butyl mercaptan.....	0.5	-
+ Cadmium oxide fume (as Cd).....	-	0.1
Camphor.....	2	-
Chlorine.....	1	-
Cyanogen.....	10	-
+ Dichloroacetylene.....	0.1	-
C Diethylene triamine - Skin.....	10	-
Diphenyl amine.....	-	10
+ Endosulfan (Thiodan®) - Skin.....	-	0.1
+ Ethyl mercaptan.....	0.5	-
Fibrous glass.....	-	5
+ Heptane.....	500	2,000
+ Indene.....	10	-
Indium and compounds, as In.....	-	0.1
Iron salts, soluble, as Fe.....	-	1
+ Methyl isoamyl ketone.....	100	475
+ Methyl mercaptan.....	0.5	-
C Methyl silicate.....	5	-
+ Octane.....	400	1,900
+ Oil mist (particulate).....	-	5 ^{g)}
+ Oil vapors.....	h) A 6	-
+ Pentaerythritol (tetramethylmethane).....	-	15
+ Pentane.....	500	1,500

a) Parts of vapor or gas per million parts of contaminated air by volume at 25° C and 760 mm. Hg pressure.

b) Approximate milligrams of particulate per cubic meter of air.

+ 1968 Revision

+ 1968 Addition

15

TX TINER
RMC0042496

Substance	a)	b)
	ppm	Mg m ³
- Petroleum distillates.....	h) A 6	-
- Propargyl alcohol - Skin.....	1	-
- RDX - Skin.....	-	1.5
- Stoddard Solvent.....	200	-
- Styrene.....	50	-
- Tetraethyl lead as Pb - Skin.....	-	0.100 i)
- Tetramethyl lead as Pb - Skin.....	-	0.150 i)
- Trimethyl benzene.....	25	-
- Tungsten & compounds, as W	-	-
Soluble.....	-	1
Insoluble.....	-	5
- Uranium, sol. & insol. compounds as U.....	-	0.2

NOTICE OF INTENDED CHANGES (CONTINUED)

Substance

- Asbestos 12 fibers ml⁻¹ > 5μ in length¹⁾ or 2 mppcf⁴⁾
- Cristobalite Use one-half the value calculated from the count or mass formulae for quartz.

- Quartz (1) TLV for respirable dust in mg m⁻³ :

$$\frac{10 \text{ mg m}^{-3}}{\% \text{ Respirable Quartz} + 2}$$

(2) "Total dust" respirable and nonrespirable:

$$\frac{30 \text{ mg m}^{-3}}{\% \text{ Quartz} + 2}$$

- Tridymite Use one-half the value calculated from formulae for quartz.

- j) As determined by the membrane filter method at 430 X phase contrast magnification.

- k) As counted by the standard impinger, light-field count technique.

- m) Both concentration and per cent quartz for the application of this limit are to be determined from the fraction passing a size-selector with the following characteristics:

Aerodynamic Diameter (μ) (unit density sphere)	% passing selector
≤ 2	90
2.5	75
3.5	50
5.0	25
10	0

g) As sampled by method that does not collect vapors.

h) According to analytically determined composition.

i) For control of general room air; biologic monitoring is essential for personnel control.

- 1968 Revision
+ 1968 Addition

+ 1968 Revision
++ 1968 Addition

Appendix A

- A¹ **Benzidine.** Because of high incidence of bladder tumors in man, any exposure, including skin, is extremely hazardous.
- A² **β-Naphthylamine.** Because of the extremely high incidence of bladder tumors in workers handling this compound and the inability to control exposures, β-naphthylamine has been prohibited by the State of Pennsylvania from manufacture, use and other activities that involve human contact.
- A³ **N-Nitrosodimethylamine.** Because of extremely high toxicity and presumed carcinogenic potential of this compound, contact by any route should not be permitted.
- A⁴ **Polytetrafluoroethylene* decomposition products.** Thermal decomposition of the fluorocarbon chain in air leads to the formation of oxidized products containing carbon, fluorine and oxygen. Because these products decompose in part by hydrolysis in alkaline solution, they can be quantitatively determined in air as fluoride to provide an index of exposure. No TLV is recommended pending determination of the toxicity of the products, but air concentrations should be minimal.
- A⁵ **β-Propiolactone.** Because of high acute toxicity and demonstrated skin tumor production in animals, contact by any route should be avoided.
- A⁶ **Gasoline and/or Petroleum Distillates.** The composition of these materials varies greatly and thus a single TLV for all types of these materials is no longer applicable. In general, the aromatic hydrocarbon content will determine what TLV applies. Consequently the content of benzene, other aromatics and additives should be determined to arrive at the appropriate TLV (Elkins, et al. A.I.H.A.J. 24, 99, 1983).

*Trade Names: Algonon, Fluon, Halon, Teflon, Tetran

Appendix B

B.1 THRESHOLD LIMIT VALUES FOR MIXTURES

When two or more hazardous substances are present, their combined effect, rather than that of either individually, should be given primary consideration. In the absence of information to the contrary, the effects of the different hazards should be considered as additive. That is, if the sum of the following fractions,

$$\frac{C_1}{T_1} + \frac{C_2}{T_2} + \dots + \frac{C_n}{T_n}$$

18

exceeds unity, then the threshold limit of the mixture should be considered as being exceeded. C_1 indicates the observed atmospheric concentration, and T_1 the corresponding threshold limit. (See Example 1A.a.).

Exceptions to the above rule may be made when there is good reason to believe that the chief effects of the different harmful substances are not in fact additive, but independent as when purely local effects on different organs of the body are produced by the various components of the mixture. In such cases the threshold limit ordinarily is exceeded only when at least one member of the series $\frac{C_1}{T_1}$, or $\frac{C_2}{T_2}$, etc., itself has a value exceeding unity. (See Example 1A.b.)

Antagonistic action or potentiation may occur with some combinations of atmospheric contaminants. Such cases at present must be determined individually. Potentiating or antagonistic agents are not necessarily harmful by themselves. Potentiating effects of exposure to such agents by routes other than that of inhalation is also possible, e.g. inhibited alcohol and inhaled narcotic (trichloroethylene). Potentiation is characteristically exhibited at high concentrations, less probably at low.

When a given operation or process characteristically emits a number of harmful dusts, fumes, vapors or gases, it will frequently be only feasible to attempt to evaluate the hazard by measurement of a single substance. In such cases, the threshold limit used for this substance should be reduced by a suitable factor, the magnitude of which will depend on the number, toxicity and relative quantity of the other contaminants ordinarily present.

Examples of processes which are typically associated with two or more harmful atmospheric contaminants are welding, automobile repair, blasting, painting, lacquering, certain foundry operations, diesel exhausts, etc. (Example 2.)

19

THRESHOLD LIMIT VALUES FOR MIXTURES EXAMPLES

1A. General case, where air is analyzed for each component.

a. ADDITIVE EFFECTS

$$\frac{C_1}{T_1} + \frac{C_2}{T_2} + \frac{C_3}{T_3} + \dots + \frac{C_n}{T_n} = 1$$

Air contains 5 ppm of carbon tetrachloride (TLV, 10), 20 ppm of ethylene dichloride (TLV, 50) and 10 ppm of ethylene dibromide, (TLV, 25).

$$\frac{5}{10} + \frac{20}{50} + \frac{10}{25} = \frac{65}{50} = 1.3$$

Threshold limit is exceeded.

b. INDEPENDENT EFFECTS

Air contains 0.15 mg/m³ of lead (TLV, 0.2) and 0.7 mg/m³ of sulfuric acid (TLV, 1).

$$\frac{0.15}{0.20} = 0.75; \quad \frac{0.7}{1} = 0.7$$

Threshold limit is not exceeded.

1B. Special case when source of contaminant is a mixture and atmospheric composition is assumed similar to that of original material, i.e. vapor pressure of each component is the same at the observed temperature.

a. ADDITIVE EFFECTS, approximate solution.

1. A mixture of equal parts (1) trichloroethylene (TLV, 100), and (2) methyl chloroform (TLV, 350).

$$\frac{C_1}{100} + \frac{C_2}{350} = \frac{C_m}{T_m}$$

Solution applicable to "spot" solvent mixture usage, where all or nearly all, solvent evaporates.

$$C_1 = C_2 = \frac{1}{2} C_m$$

$$\frac{C_1}{100} + \frac{C_1}{350} = \frac{2C_1}{T_m}$$

$$\frac{7C_1}{700} + \frac{2C_1}{700} = \frac{2C_1}{T_m}$$

$$T_m = 700 \times \frac{2}{9} = 155 \text{ ppm}$$

1B. b. General Exact Solution for Mixtures of N Components With Additive Effects and Different Vapor Pressures.

$$(1) \frac{C_1}{T_1} + \frac{C_2}{T_2} + \dots + \frac{C_n}{T_n} = 1;$$

$$(2) C_1 + C_2 + \dots + C_n = T;$$

$$(2.1) \frac{C_1}{T} + \frac{C_2}{T} + \dots + \frac{C_n}{T} = 1.$$

By the Law of Partial Pressures,

$$(3) C_1 = ap_1,$$

And by Raoult's Law,

$$(4) p_1 = F_1 p_1^o.$$

Combine (3) and (4) to obtain

$$(5) C_1 = aF_1 p_1^o.$$

Combining (1), (2, 1) and (5), we obtain

$$(6) \frac{F_1 p_1^o}{T} + \frac{F_2 p_2^o}{T} + \dots + \frac{F_n p_n^o}{T} = 1$$

$$\frac{F_1 p_1^o}{T_1} + \frac{F_2 p_2^o}{T_2} + \dots + \frac{F_n p_n^o}{T_n}$$

and solving for T,

$$(6.1) T = \frac{F_1 p_1^o + F_2 p_2^o + \dots + F_n p_n^o}{\frac{F_1 p_1^o}{T_1} + \frac{F_2 p_2^o}{T_2} + \dots + \frac{F_n p_n^o}{T_n}}$$

$$\text{or } \sum_{i=1}^n \frac{1}{T_i} = n \quad F_1 p_1^o$$

$$(6.2) T = \frac{i = 1}{\sum_{i=1}^n \frac{1}{T_i}} \quad \frac{F_1 p_1^o}{T_1}$$

T = Threshold Limit Value in ppm.

C = Vapor concentration in ppm.

p = Vapor pressure of component in solution.

p° = Vapor pressure of pure component.
 F = Mol fraction of component in solution.
 a = A constant of proportionality.
 Subscripts 1, 2, . . . n relate the above quantities to components 1, 2, . . . n, respectively.
 Subscript i refers to an arbitrary component from 1 to n.
 Absence of subscript relates the quantity to the mixture.

Solution to be applied when there is a reservoir of the solvent mixture whose composition does not change appreciably by evaporation.

Exact Arithmetic Solution of Specific Mixture

	Mol. wt.	Density	T	p° at 25°C	Mol fraction in half-and-half solution by volume
Trichloroethylene (1)	131.4	1.46 g/ml	100	73mm Hg	0.527
Methylchloroform (2)	133.42	1.33 g/ml	350	125mm Hg	0.473

$$F_{1p1^\circ} = (0.527) (73) = 38.2$$

$$F_{2p2^\circ} = (0.473) (125) = 59.2$$

$$T = \frac{38.2 + 59.2}{\frac{38.2}{100} + \frac{59.2}{350}} = \frac{(97.4) (350)}{133.8 + 59.2} = \frac{(97.4) (350)}{193.0} = 177$$

$T = 177$ ppm (Note difference in T. L. V. when account is taken of vapor pressure and mol fraction in comparison with above example where such account is not taken).

2. A mixture of one part of (1) parathion (TLV, 0.1) and two parts of (2) EPN (TLV, 0.5).

$$\frac{C_1}{0.1} + \frac{C_2}{0.5} = \frac{C_m}{T_m} \quad C_2 = 2C_1$$

$$C_m = 3C_1$$

$$\frac{C_1}{0.1} + \frac{2C_1}{0.5} = \frac{3C_1}{T_m}$$

$$\frac{7C_1}{0.5} = \frac{3C_1}{T_m}$$

$$T_m = \frac{1.5}{7} = 0.21 \text{ mg/m}^3$$

1C. T. L. V. for Mixtures of Mineral Dusts.

For mixtures of biologically active mineral dusts the general formula for mixtures may be used. With the exception of asbestos, pure minerals are assigned TLV of 2.5, 20 or 50.

For a mixture containing 80% talc and 20% quartz, the TLV for 100% of the mixture "C" is given by:

$$TLV = \frac{1}{\frac{0.8}{20} + \frac{0.2}{2.5}} = 8.4 \text{ mppcf}$$

Essentially the same result will be obtained if the limit of the more (most) toxic component is used provided the effects are additive. In the above example the limit for 20% quartz is 10 mppcf.

For another mixture of 25% quartz 25% amorphous silica and 50% talc:

$$TLV = \frac{1}{\frac{0.25}{2.5} + \frac{0.25}{20} + \frac{0.5}{20}} = 7.3 \text{ mppcf}$$

The limit for 25% quartz approximates 8 mppcf.

Appendix C

BASES FOR ASSIGNING LIMITING "C" VALUES

By definition in the Preface, a listed value bearing a "C" designation refers to 'ceiling' value that should not be exceeded; all values should fluctuate below the listed value. In general the bases for assigning or not assigning a "C" value rest on whether excursions of concentration above a proposed limit for periods up to 15 minutes may result in a) intolerable irritation, b) chronic, or irreversible tissue change, or c) narcosis of sufficient degree to increase accident proneness, impair self rescue or materially reduce work efficiency.

In order for the Committee to decide whether a substance is a candidate for a "C" listing, some guidelines must be formulated on the permissive fluctuation above the limit in terms of the seriousness of the response in the categories a, b, c, given above. For this the factors given in the table below have been used by the Committee. For both technical and practical reasons, the factors have been pegged to the concentration in an inverse manner. It will be noted that as the magnitude of the T. L. V. increases a correspondingly decreased range of fluctuation is permitted; not to decrease the factor for T. L. V. s of increasing magnitude would permit exposures to large absolute quantities, an undesirable condition, a condition that is minimized at low T. L. V. s. Moreover, larger factors at the lower T. L. V. s are consistent with the difficulties in analyzing and controlling trace quantities.

T.L.V. RANGE ppm* or mg/m ³	Test T.L.V. Factor	Examples
0 to 1	3	Toluene diisocyanate-T. L. V., 0.02 ppm, if permitted to rise above 0.06 ppm may result in sensitization in a single subsequent exposure! "C" listing recommended on category b.
1 + to 10	2	Manganese -T.L.V., 5mg/m ³ , contains little or no safety factor. All values should fluctuate below 5mg/m ³ . "C" listing recommended on category b.

24

T.L.V. RANGE ppm* or mg/m ³	Test T.L.V. Factor	Examples
10 + to 100	1.5	Methyl styrene-T. L. V. 100 if encountered at levels of 150 ppm will prove intensely irritating. "C" listing recommended on category a.
100 + to 1000	1.25	Methyl chloroform-T. L. V. 350ppm, at 438 ppm for periods not exceeding 15 minutes is not expected to result in untoward effects relating to category c. No "C" listing recommended.

* Whichever unit is applicable

PERMISSIBLE EXCURSIONS FOR TIME- WEIGHTED AVERAGE (TWA) LIMITS

As stated in the preface, the same factors may be used as guides for reasonable excursions above the limit for substances to which the time-weighted average applies. The time-weighted average implies that each excursion above the limit is compensated by a comparable excursion below the limit. Thus, a value of 6 -ppm HF is permissible for periods not exceeding 15 minutes, provided an equivalent decrease below the limit of 3 -ppm obtains.

Appendix D

Some "Inert" or Nuisance Particulates*

Alundum (Al ₂ O ₃)	Limestone
Calcium carbonate	Magnesite
Cellulose	Marble
Portland Cement	Pentaerythritol
Corundum (Al ₂ O ₃)	Plaster of Paris
Emery	Rouge
Glycerine Mist	Silicon Carbide
Graphite (synthetic)	Starch
Gypsum	Sucrose
Vegetable oil mists	Tin Oxide
(except castor, cashew nut, or similar irritant oils)	Titanium Dioxide

*When toxic impurities are not present.

25

Appendix E

Some Simple Asphyxiants -- "Inert" Gases and Vapors.

Acetylene	Hydrogen
Argon	Methane
Ethane	Neon
Ethylene	Nitrogen
Helium	Nitrous Oxide
	Propane

E.J. Baier
Hervey B. Elkins, Ph.D.
W.W. Fredrick, Ph.D.
Bernard Graboys, P.E.
Paul Gross, M.D.
Wayland J. Hayes, Jr., M.D.

Harold N. MacFarland, Ph.D.
Consultant
Fredrick T. McDermott
E. Mastromatteo, M.D.
Walter W. Melvin, M.D.
Ralph G. Smith, Ph.D.
Mitchell R. Zavon, M.D.

Herbert E. Stokinger, Ph.D., Chairman
William D. Wagner, Recording Sec'y

28



TX Tiner
RMC0042503