

Fuel oil (continued)

- grade of, 160
- heating value, 710
- maximum carbon dioxide values, 149
- theoretical air requirements, 147
- viscosity, 160

Fumes, 525, 794**Furnace, furnaces, 360, 794**

- capacity, 351
- casings, 360
- design, 190, 224
- fan, 794
- gas-fired units, 199
- gravity systems, 345
- mechanical systems, 359
- oil-fired units, 195
- stoker-fired units, 188
- volume, 159, 794

G**Gage, gages**

- draft, 630
- pressure, 630, 794

Garage ventilation, 725**Gas, gases**

- burner controls, 623
- chimneys for heating, 181
- classification of, 161
- cleaning of, 540
- centrifugal separators, 540
- cloth filters, 541
- cyclones, 540
- gravitational settling chambers, 540
- combustion of, 162
- estimating consumption, 215
- fuel burning rate chart, 210
- specific heat, 807

Gas-fired appliances, 199

- boilers, 199, 223
- combustion process, 202
- controls, 203
- conversion burners, 202
- furnaces, 199
- measurement of efficiency of combustion, 202
- ratings for, 203
- sizing heating plants, 203
- space heaters, 201

Gaseous fuels

- classification of, 161
- combustion of, 162
- flame temperature, 162
- maximum carbon dioxide values, 149
- products of combustion, 162
- properties of, 162
- specific gravity, 162
- theoretical air requirements, 147

Glass

- solar heat transmitted, 132

Glass blocks

- coefficients of transmission, 97
- heat gain through, 135

Globe thermometer, 68, 637, 768**Graphical symbols for drawing, 803**

- duct work, 804, 805
- heating, 806
- piping, 803
- ventilating, 806

Grate area, 794**Gravity convectors, 239**

- codes, 247
- concealed, 245
- electric heaters, 751
- heat emission of, 239
- heating up, 243
- selection, 246

Gravity furnace systems, 345, 794

- capacity, 351
- design procedure, 345
- leader sizes, 346
- proportioning wall stacks, 348
- recirculating ducts, 349
- recirculating grilles, 349
- register selections, 349
- return connection, 351
- typical design, 355
- warm air, 345

Grille, grilles, 557 (see Registers)

- locations, 558
- for mechanical furnace systems, 363
- noises, 564
- railway car, 666
- recirculating, 349
- types of, 569

Guarded hot plate, 637**Gun type oil burners, 193****H****Hay fever symptoms, 661****Health, 528****Heat, 205, 794**

- auxiliary sources, 119
- coefficients, 69
 - by convection, 727
 - by radiation, 727
- of combustion, 145
- emission of appliances, 136
- emission of occupants, 135
- flow through roofs, 131
- flow through walls, 131
- generated by motors, 137
- humid, 794
- infiltration equivalent, 109
- introduced by outside air, 136
- latent, loss, 109
- of the liquid, 794

losses

- from bare pipes, 732
- control of, 759
- from ducts, 738
- from insulated pipes, 736
- mechanical equivalent of, 795
- methods of, transfer, 69
- production, rate of, 760
- removal, natural ventilation, 722
- residence, loss problems, 121
- sensible, 796
- sensible, loss, 109
- total, 797
- transfer, 473, 483, 492
 - boiler rates, 226
 - through building materials, 637
 - overall coefficient of, 484, 492
 - surface coils, 473
 - transmission, 727

Heat exchange

- measurement of, 637

Heat gain, 125

- appliances, 136
- components of, 125
- electrical heating equipment, 138
- gas burning equipment, 138
- glass, 132
- through glass blocks, 135
- insulated cold pipes, 742
- for insulated ducts, 743
- for insulated pipes, 743
- latent, 127
- light, 137
- occupants, 135
- outside air, 136
- people, 135
- roof, 127
- sensible, 127
- steam heated equipment, 138
- unit, 390
- from various sources, 138
- wall, 127

Heater, heaters,

- electric, 750
- water, 785

Heating,

- for air conditioning units, 408
- boilers, 221
 - surface, 791
- boiler surface, 225
- coil selection, 497
- cycle control, 610
- district, 307
- domestic water by electricity, 755
- electric, 749
 - hot water, 754
- extended surface, 793
- load, 111
 - calculations, 377
- performance of coils, 484
- physiological objectives of, 60
- radiant, 759 (see *Radiant Heating*)
- steam systems, 249
 - vapor, 797
- surface, 794
 - prime, 796
 - square foot of, 796
- symbols for drawing, 806
- vacuum systems, 797
- warm air, system, 345, 359, 798
- water, 769

High duty humidifiers, 506**Hood, hoods, 687****Horsepower,**

- boiler, 792

Hospital, hospitals,

- air conditioning in, 664
- noise level, 593
- operating rooms, 653
 - air conditions, 655
 - reducing explosion hazard, 653
 - sterilization of air, 656
 - ventilation requirements, 656
- plumbing fixture water demand, 789

Hot water,

- boiler allowances, 788
- boiler supply load, 229
- consumption in buildings, 789
- demand for fixtures, 789
- electric heating, 754
- estimating demand by fixtures, 790
- panel heating, 762

Hot water (continued)

- radiant heating, 762
- storage capacity, 788
- storage tanks, 784
- supply boilers, 224
- supply systems, 780, 783

Hot water heating systems, 291, 794

- direct return system, 292
- elbow equivalents, 298
- friction heads, 296
- gravity pressure heads, 300
- installation details, 306
- mechanical circulators, 292
- orifice friction heads, 302
- pipe sizes, 292
- reversed return system, 292
- systems of piping, 291

Hot-wire anemometer, 68, 633**Human body**

- adaptation, 42
 - to cold conditions, 47
 - to hot conditions, 45
- heat emission, 135
- heat gain, 135
- odors, 38
- temperature, 41
- weight loss, 46
- zone of body cooling, 43
- zone of evaporative regulation, 42

Humid heat, 794**Humidification, 503**

- control, 611
- for mechanical furnace systems, 369
- residence requirements, 370

Humidifier, humidifiers

- atomizing, 505
- high duty, 506
- spray, 506
- units, 405

Humidity, 794

- absolute, 791
- chart for drying work, 704
- for drying, 702
- influence of, 64
- measurement of, 636
- nurseries for premature infants, 658
- permissible relative, 99
- ratio, 9, 794
- relative, 19, 792

Hygostat, 794**I****Ice**

- systems, 466
- impulse trap, 266
- Inch of water, 795
- Induction drier, 698

Industrial,

- air conditioning 673
- exhaust systems, 683 (see *Exhaust Systems*)
- processes, 673
- humidities for processing, 674
- temperatures for processing, 674

Industrial buildings

- hot water consumption, 789
- noise level, 593
- plumbing fixture demand, 789