

Golden Notes #109-1 (back) Product No. 12,576, 2 -

C & R FORMULA

Date

Formula No.

CLASS

CODES

Product

DESCRIPTORS (20 spaces-limit)

Label Warning

Trade Name

Customer

ANALYSIS

Substrate and Treatment

Pigment

End Use

Vehicle

Specifications

Royalty

Yes ☐

No ☐

Silicone

Yes ☐

No ☐

Pigment

Resins

Color

Glaze

For Use On

Resistance

Manufactured at Plants

Y-Plant Lab

8-1-67 (2)

(Tech Only)

#5-8-11-15-16-17

"

Vehicle

#30 (Cryotom)

"

Manufacturing Instructions or Remarks

C. Rio, P. Lima, Mexico

Guatemala 2-8-68 (6)

GLD059404

Product **Japalac Enamel - Dawn Gray**

Customer

Formula Number **Y-1219-H**

Laboratory Number

R.M. Cast

Date **3/1/67**

Mill **Mix**

Grind

MPVLA **Lead -1**

Label Warning **11-62**

METHOD

Wt./Gal. **8.5**

Flash Pt. **°F100**

N.V.W.

N.V.Vol.

Visc. F. **90-100**

VISC. #4 F.C.

Reducer **S-340**

Ratio

P.V.C.

pH

Color **Gray**

Match **Y-3414**

Glass **Over 85**

Method

Strainer

Containers

Application

Cure **Air Dry: 3-4 hrs.**

Recoat: **Overnight**

Remarks

Formulator **J. E. Southwick**

Approved by

Yield

100.07 862.5

GLD059405

Date 3/1/67

Formula No. Y-1219-H

CLASS

CODES

DESCRIPTORS (20 spaces-limit)

Trade Name

Customer

Substrate and Treatment

End Use

Specifications

Royalty

Yes ☐

No ☐

Silicone

Yes ☐

No ☐

Resins

Color

Glass

For Use On

Resistance

Manufactured at Plant #1-2-4-12-14

2-16-67

Manufacturing Instructions or Remarks

3-30-67

Product

Jepalac Enamel

Label Warning

Down Gray
#11-62 NPVL-A
ANALYSIS

Pigment

Vehicle

17.7

82.3

100.03

Pigment

Titanium Dioxide

100%

Wetting material

less than 5%

Vehicle

Soya Alkyd Resin

42%

Mineral Spirits &

Driers

58%

100%

NO CHANGE IN ANALYSIS

Y-1219

065

GLD059406

COST	DATE	ANALYSIS	CUSTOMERS
1.00	(Back)	5-4-64 PIGMENT	
		VEHICLE 82.3	
2.30	(Back)	100.00	3/21/63
12-11-64			U.S. Coast Guard
		PIGMENT	
2.30	(Back)	TITANIUM DIOXIDE 100%	
2-1-64			
Rebore			Warning No. 11-52 HZELA
1-4-67			11/14/62
		MINING MATERIAL LOSS CHART	
			No change in analysis
		Spec 5-5-64 (3)	
		VEHICLE	Y Enamel Test 3-27-63
		Boys Alkyd Resin 425	#1-2-4-5-8-12-14-15-16-17
		Mineral Spirits & Solers 588	Stamped
		100%	#11 3-29-63
		Guatemala 3-9-64	
		Manila 3-31-64	Italy 9-3-63
		Eng. Br. Pts 4-6-64	Panama 9-25-63
		P. Rica 4-22-64	Lat. Japan 2-10-64
		Colombia 4-24-64	Mexico 2-21-64
		Y-1219 065	
		Ecuador 4-27-64	West Indies 3-3-64

GLD059408

FORMULA NO. Y-1219-G 3132

GOODS Japalac Enamel - Dawn Gray (1-10-63) LABORATORY NO. Tallate Driers
 CONSISTENCY Mfg. at plants #1-2-4-5-8-12-14-15-16-17 COST CLASS. DATE 9/6/62 #
 FOR USE ON This Production Must Not Contain Lead STRAINER GRIND 7-8
 CUSTOMER (Less than 1% Lead) MILL Mix WT. OR BE 8.5#

CODE NUMBER	Gals. SMALL BATCH			LARGE BATCH			IS AGITATOR REQUIRED	
	XXXX	LBS.	OZS.	GALS.	LBS.	OZS.	VISC. F.B.	TEMP.
40-W-127-M	1176	10,000		99.1	845.0		90-100"	
318-B-7 or Y-1720		46			3.9		VISC. RED.	TEMP.
318-Y-37		27			2.3		VISCOSIMETER #4 Ford Cup	
318-R-210		9			0.8		COLOR	SHEEN GLOSS
							NON VOL.	FLASH PT.
							WATCH FOR	Y-3414
							REDUCER	S-43
							AMT. FOR BRUSHING	F.B.
							SPRAYING	FLAGGING
							DIPPING	DRIP-TIME
							BAKE	TEMP.
							AIR DRIES IN	3-4 hrs.
							A. D. TO RECOAT IN	O.N.
							REMARKS:	
							*Reissued	Oct 1-1962
								(1-10-63)
							FORMULATOR	J. E. Southwick
YIELD	1185	10,072		100	852			

DISCONTINUED

SEE

Y-1219-H

Standard formula.
 Not to be taken
 from file.

GLD059409

FORMULA RECORD

FORMULA NO. 7-1219-G

GOODS Japalac Enamel - Dawn Gray

LABORATORY NO.

CONSISTENCY 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17

COST CLASS.

DATE 5/1/51

FOR USE ON THIS PRODUCTION MUST NOT CONTAIN LEAD

STRAINER

GRIND 7-8

CUSTOMER (Less than 1% Lead)

MILL MIX

WT. OR BE 8.5#

CODE NUMBER	SMALL BATCH			LARGE BATCH			IS AGITATOR REQUIRED	
	WTS.	LBS.	OZS.	GALS.	LBS.	OZS.	VISC. F.B.	TEMP.
10-W-127-D	1176	10.000		99.1	845.0		90-100"	
110-B-7 CT							VISC. RED.	TEMP.
Y-1720		46			3.9		VISCOSIMETER #1	Port Cup
113-Y-37		27			2.3		COLOR	SHEEN GLOSS
119-R-210		9			0.8		NON VOL.	FLASH PT.
							WATCH FOR	Y-3414
							REDUCER	S-43
							WMT. FOR BRUSHING	F.E.
							SPRAYING	TUMBLING
							DIPPING	DRIP TIME
							BAKE	TEMP.
							AIR DRIES IN	3 1/2 hrs.
							A. D. TO RECOAT IN	0.5
							REMARKS:	
							111	Y-117
							112	
							113	Discontinued
							FORMULATOR	J.E. Southwick
YIELD	1176	10.071		100	852			

DISCONTINUED

SEE 7-1219 Formula

Standard Formula.
Not to be taken
from File

COST	DATE	ANALYSIS	CUSTOMERS
		PIGMENT 17.7 % VEHICLE 82.3 % 100.0%	Y-1219-G Japalac Enamel - Dawn Gray 5/12/60
		PIGMENT Titanium Dioxide 100%	No. 1 Label Warning Also Y-4115 Y-4132
		Tinting material less than 5%	<i>Y-1219-G 7-23-61</i> <i>Y-4115 7-23-61</i> <i>Y-4132 7-23-61</i> <i>Y-4115 7-23-61</i> <i>Y-4132 7-23-61</i>
		VEHICLE Soya Alkyd Resin 42% Mineral Spirits & Driers 58 100%	<i>Chile - Columbia - Douglas 1-2-61</i> <i>Panama - Panama 1-2-61</i> <i>Mexico (Texas) 8-2-61 (41)</i> <i>Vietnam - Saigon 12-1-61</i> <i>Costa Rica 6-11-62</i>
		Y-1219 065	

GOODS

Japalac Enamel. - Dawn Gray

LABORATORY NO.

CONSISTENCY

COST CLASS.

DATE

11/2/59**

FOR USE ON

THIS PRODUCTION MUST NOT CONTAIN LEAD

STRAINER

GRIND

7-8

CUSTOMER

(Less than 1% Lead)

MILL Mix

WT. OR BE 8.5#

CODE NUMBER	GALVON GALLON BATCH			LARGE BATCH			IS AGITATOR REQUIRED
	LBS.	OZS.	GALS.	LBS.	OZS.		
10-W-127-K	1176	10,000	99.1	845.0		VISC. F.B. 90-100"	TEMP.
318-B-7 or Y-1720	46			3.9		VISC. RED.	TEMP.
318-Y-37	27			2.3		VISCOSIMETER #4 Ford Cup	
318-R-210	9			0.8		COLOR	SHEEN Gloss
						NON VOL.	FLASH PT.
						MATCH FOR Y-3414	
						REDUCER 8-43	
						AMT. FOR BRUSHING F.B.	
						SPRAYING	TUMBLING
						DIPPING	DRIP TIME
						BAKE	TEMP.
						AIR DRIES IN 3-4 hrs.	
						A. D. TO RECOAT IN 0.N.	
						REMARKS:	
						**DESTROY COPY DATED 10/22/59.	
						File Y-4115	
						FORMULATOR J.E. Southwick	
YIELD	1185	10,072	100	852			30-12-12

GLD059413

COST	DATE	ANALYSIS	CUSTOMERS Y-1219-F
		PIGMENT 16.2 %	Japalac Enamel - Dawn Gray
		VEHICLE 83.8 %	
		100.0%	
		PIGMENT	11/2/59
		Aluminum Oxide 100%	
			No. 1 Label
		Extender material less than	5%
			No change in analysis.
			Y Enamel test 11-5-59
		VEHICLE	March 1 (Batch) 11-5-59
		Soya Alkyd 42.0%	11-5-59
		Mineral Spirits & Driers 58.0	11-5-59
		100.0%	2-12-60
			Aluminum
			Catal
			Extender
			Mineral
			Primer
			Wash Primer 2-12-60
		Y-1219	959

GLD059414

[illegible]

FORMULA RECORD

NAME Japalec Enamel - Dawn Gray

FORMULA NO. V-1219-E

CODE

LABORATORY NO.

CONSISTENCY

COST CLASS.

DATE 11/5/57

FOR USE ON

STRAINER

GRIND

CUSTOMER

MILL Pebble

MT. OR EE

10-1/2

CODE NUMBER	ONE GALLON BATCH			LARGE BATCH		
	PINTS	LBS.	OZS.	GALS.	LBS.	OZS.
W-208		2	12			
			10			
			8			
			7			
			1			
V-672	0-5/8					
S-320	1/4					
S-43	1-1/8					
D-29			2 Loz.			
W-520			1/2 Loz.			
CH-243			1/8 Loz.			
146-C-200			1/8 Loz.			
93-B-7			2-1/8			
93-B-37			1-3/8			
93-B-7			1/2			
93-D-17			1-3/8			
67-T-50			1 Loz. for sagging.			
YIELD						

Standard Formula.
Not to be taken
from File.

IS AGITATOR REQUIRED

VISC. F.P. 95-105

TEMP.

VISC. RED.

TEMP.

VISCOSIMETER

1000 Cup

COLOR

SHEEN Gloss

NET VOL.

FLASH PT.

WATER FOR

REDUCER S-43

ANT. FOR BRUSHING

N.B.

SPRAYING

TIDBLING

DIPPING

DRIP TIME

FRAME

TEMP.

AIR DRIES IN 1-5

HRS.

A. D. TO RECOAT IN

24 HRS.

CATALYST

Formula

AMT. OF CATALYST

10/25/56

POT LIFE

reassigned to

STABILITY AT 200°F

W-208.

STABILITY AT 135°F

STABILITY AT

Y-4/32

REMARKS

Y-111-

FORMULATOR J.E.S.

28-8-8

FORMULA RECORD

FORMULA NO. Y-1219-E

COCOS Japalac Enamel - Dawn Gray

LABORATORY NO.

CONSISTENCY

COST CLASS.

DATE 10/25/56

FOR USE OF

STRAINER

GRIND 7-3

CUSTOMER

MILL Pebble

WT. OR EE 10-1/4

11-2-56

CODE NUMBER	ONE GALLON BATCH			LARGE BATCH			IS AGITATOR REQUIRED
	PINTS	LBS.	OZS.	GALS.	LBS.	OZS.	
B-180		2	12				VISC. F.B. 95-105" TEMP.
B-170 W-202			10				VISC. RED. TEMP.
W-140			8				VISCOSIMETER #4 Ford Cup
B-333			1				COLOR SHEEN Gloss
CH-185			1				NON VOL. FLASH PT.
V-872	6-5/8						WATER FOR
O-320	1/4						REDUCER S-43
S-43	1-1/8						AMT. FOR BRUSHING F.B.
D-29			2 Loz.				SPRAYING TUBING
WH-530			1/2 Loz.				DIPPING DRIE TIME
CH-269 CH-245			1/8 Loz.				BAKE TEMP.
146-C-200			1/8 Loz.				AIR DRIES 4-6 hrs.
93-B-7			2-1/8				A. D. TO RECOAT IN 24 hrs.
93-V-37			1-3/8				CATALYST
93-R-7			1/2				AMT. OF CATALYST
93-D-17			1-3/8				POT LIFE TEMP.
57-T-50			1 Loz. for sagging.				STABILITY AT 200°F
YIELD							STABILITY AT 135°F
							STABILITY AT °F
							REMARKS
							FORMULATOR J.E.S.
							28-8-5

Standard Formula
Not to be taken
from file

GLD059420

FORMULA NO. Y-1219-D

LABORATORY NO.

COST CLASS.

DATE 2-6-52

STRAINER

CRIND MIX

MILL

AT. CR BE 10-1/4

IS AGITATOR REQUIRED

95-105"

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

TEMP.

FORMULA RECORD

Liquid

CONSISTENCY

PRINTING

CERTAIN

CODE

NUMBER

40-W-127-H

8

33-B-7

2-1/8

93-Y-37

1-3/8

33-R-7

1/2

93-D-17

1-3/8

RI-A721

1/8 Loz.

FORMULA NO. Y-1219-D

Liquid

CONSISTENCY

PRINTING

CERTAIN

CODE

NUMBER

40-W-127-H

8

33-B-7

2-1/8

93-Y-37

1-3/8

33-R-7

1/2

93-D-17

1-3/8

RI-A721

1/8 Loz.

FORMULA NO. Y-1219-D

Liquid

CONSISTENCY

PRINTING

CERTAIN

CODE

NUMBER

40-W-127-H

8

33-B-7

2-1/8

93-Y-37

1-3/8

33-R-7

1/2

93-D-17

1-3/8

RI-A721

1/8 Loz.

FORMULA NO. Y-1219-D

Liquid

CONSISTENCY

PRINTING

CERTAIN

CODE

NUMBER

40-W-127-H

8

33-B-7

2-1/8

93-Y-37

1-3/8

33-R-7

1/2

93-D-17

1-3/8

RI-A721

1/8 Loz.

FORMULA NO. Y-1219-D

Liquid

CONSISTENCY

PRINTING

CERTAIN

CODE

NUMBER

40-W-127-H

8

33-B-7

2-1/8</

COST	DATE	ANALYSIS		CUSTOMERS	
		PIGMENT	36.8		U.C. Plants 2-8-52
		VEHICLE	63.2		Attagay (2) 1-22-53
			100.0		Montreal & Small (Can) 5-26-53
					Kerrys 3 coats (S.A.) 7-14-54
					Plumbra 7-16-52
		PIGMENT			
		Titanium Calcium	71.0	%	
		Titanium Dioxide	16.2	%	
		Calcium Carbonate	6.4	%	
		Carbonate of White Lead	6.4	%	
			100.0	%	
		Tinting material less than 5%			
		VEHICLE			
		Soya Alkyd Resin	52.5	%	
		Mineral Spirits	44.6	%	
		Liquid Drier	2.8	%	
			100.0	%	

GLD059423

FEDERAL NO. Y-1219-C

Liquid

FOR USE OF

CUSTOMER

LABORATORY INC.

COST CLASS.

DATE 11/12/51

STATES

CRIT 7-2

214

WT. OF 11.0#

CODE NUMBER	ONE GALLON BATCH			LARGE BATCH		
	PINTS	LBs.	OZs.	GALS.	LBs.	OZs.
40-W-127	8					
93-B-7			2-1/8			
93-Y-37			1-3/8			
93-R-7			1/2			
93-D-17			1-3/8			
RL-8721			1/8	Loz.		
Analysis Change.						
Standard Formula Active Discontinued See 7-11-5						
YIELD						

IS AGITATOR REQUIRED

WIS. F. 11

SELF

W. SC. FLD

TELEF

WISCONSINETE

#4 Ford Cup

CCSR

Gray

545

GLCSB

12: VOL

FLASH FI

DATE: FC

Std. Y-1219

PRICE

S-43

ART. FOR PROSECUTION

Only as needed

SPRAYING

1053 157

DUFFING

REF ID: A66184

fiA: [

TEMP.

AIR DRIES IN

6 hrs.

A. D. TO RECORD IN:

Övernite

RE: ARS

FORMULATOR

H G R

25-6-4

GLD059424

COST

DATE

ANALYSIS

CUSTOMERS

PERCENT 38.8

PERCENT 61.2

100.0 %

All Plants

12-4-51

PIGMENT

Lithopone 63.4%

Titanium Oxide 29.3

Basic Carbonate White Lead 2.4

Calcium Carbonate 4.9

100.0 %

Tinting materials less than 5%

VEHICLE

Varnish 94.2%

Mineral Spirits 2.8

Liquid Drier 3.0

100.0 %

% Non-Volatile (Alkyd Resin, P.E.

Ester Gum, Tung, Linseed Oil) 55.5%

Volatile (Mineral Spirits) 44.5

100.0 %

1511

GLD059425

FORMULA RECORD

Gold Japalac Enamel Dawn Gray

Formula No. Y-1219-B

Consistency Liquid

Laboratory No.

For use on

Coat Class

Date 3/29/49

Customer

Strainer

Grind 7-B

Mill

Code
Number

One Gallon Batch

Large Batch

Is agitator required

Pints

Lbs.

Ozs.

Gals.

Lbs.

Wt. or Bell. O/#

Temp.

40-W-127-E

8

Viscosity 110-120th Temp

93-B-7

2-1/8

Viscosimeter #4 Cup

Color Gray

Sheen Gloss

93-Y-37

1-3/8

Non Vol.

Flash Pt. 100^o

93-R-7

1/2

Match for Std-Y-1219

93-D-17

1-3/8

Reducer S-43

Amt. for brushing only as needed

Spraying

Tumbling

Dipping

Drip time

Bake

Temp.

Changed to increase hiding & Viscosity

Air dries in 5 hrs

A. D. to recoat in Overnite

Standard Formula

Remarks:

Yield

Formulator J. C. H.

GLD059426

Cost	Date	Analysis		Customers
		Pigment	38.8	
		Vehicle	61.2	
			100.0	
		Pigment		
		Lithopone	63.4	
		Titanium Oxide	29.3	
		Basic Carbonate White Lead	2.4	
		Calcium Carbonate	4.9	
			100.0	
		With necessary tinting color added		
		<i>all plants 4-8-49</i>		
		Vehicle		
		Varnish	92	
		Mineral Spirits	5	
		Liquid Drier	3	
			100.0%	
		Non-Volatile	51.5%	

GLD059427

Characteristic and Method of Using		Cost Data		Customers
Type of Goods				
Color				
Luster				
Match for				
Kind of Reducer				all plants 6-19-47
Amount of Reduction for				
Brushing				
Spraying	Pressure			
Dipping	Drip Time	Analysis		
Flooding	Drip Time			
Tumbling				
Air dry to recoat				
To Sand or Rub				
Bake Time	Temp.			
Rub with				
Polish with				
Schedule				
				</

4-100 5m 6-25

Formula Y-1219

Date 12-20-1920 Old No.

Classification

GLD059432

Varnish	44.35%	} 44.3
Zinc Oxide (wt. 33)	18.45	
Lithopone	29.75	} 66.7
Calcium Carbonate	6.15	
Carbon	.84	
Lead Chromate	.46	
	100.00%	

Pigment	55.7%
Liquid	44.3
	100.0%

Pigment	
Zinc Oxide	33.2
Lithopone	53.4
Calcium Carbonate	11.4
Lead Chromate	1.5
Carbon	0.5
	100.0%

Liquid	
Varnish	100.0%

Round cans 1s, 1/2s, 1/4s, 1/3s, 1/16s, 1/32s.

"Japalao" Label.

9/25/21

Y-1219-A
(Eagshell Jap-a-Lac French Gray)

Y-945-G 8 Pints

57-E-7 Trace

87-Y-1 Trace

Weight per gallon - 12#

Analysis:

Pigment	53%
Vehicle	47%
	100%

Pigment Analysis:

Titanolite	61%
Lithopone	30%
Magnesium Silicate	6%
Tinting Colors	1%
	100%

Vehicle Analysis:

Varnish	71%
Flowing Oil	15%
Mineral Spirits	14%
	100%

"Jap-a-Lac" Label

Round Cans - 1's - 1/2's - 1/4's - 1/8's - 1/16's
1/32's.

Revised

GLD059434