

NOTICE: If the film image shows a less clear than the
original, it is due to the quality of the document being reproduced.

CONFIDENTIAL

MATERIAL 7789 (C.C.3500)

ASBESTOS FELT, HIGH TEMPERATURE

FOR USE BY - South Philadelphia

FURNISHED BY - Union Asbestos & Rubber Co., 1823 S. 54th Ave,
Chicago (50), Illinois

ORDER FROM SUPPLIER AS - Insulation felt, stating size and
thickness.

CHARACTERISTICS - A brown or tan colored, stitched or quilted,
fibrous, asbestos base, loosely packed, high temperature felt.
Available in rolls in many sizes and thicknesses. Usually
obtained in strips 12 inches wide by 1 inch thick. Density
approximately 15 lbs per cubic foot. Temperature use limit
371 C (700 F).

APPLICATION - Used as a liner for metal jacket turbine covers to
prevent the turbine heat from burning the paint from the outside
surfaces of the jacket.

SPECIFY AS - FELT 7789

Issued by Mils & Stds Sec, Eng Labs & Stds Dept, East Pgh, Pa.

Printed in U.S.A.

PLAINTIFF'S
EXHIBIT

WA-61

DOCUMENTS PRODUCED DALLAS COUNTY CASES 3/18/92

0000730