

MAY -0-81-61508

() YE-698-D (R) POST, 05/14/81

(DATE)

(LOT NUMBER)

() () () ()

ESTIMATED WGT

3371

LBS.

STANDARD HRS.

TIME

M

JOB NAME: 01YE698DMR

EQUIP MENT	NAME: MOLYBDATE ORANGE	USE LBS	N-CODE	ACCT LBS
PREP	1 OBTAIN FOR S-22	25	108-A	25
1	2 WEIGH FOR S-25	65.04%	33-D	18.25
	3 OBTAIN FOR S-30	450	4-A	450
	4 OBTAIN FOR S-34	90	3-A	90
	5 OBTAIN FOR S-36	145	32-D	145
	6 OBTAIN FOR S-38	225	15-A	225
	7 OBTAIN FOR S-40	150	3-A	150
	8 WEIGH IN DRUM FOR S-42 M2, 32.0%	138	28-D	44
	9 OBTAIN FOR S-42	44	711-B	44
351	10 WEIGH INTO V-351 CHECKED BY: 64.269 30.39	222.0	10-D	1148
2				
359	11 WEIGH IN. OPTR 37, MK 52, T-360, 34.91%	530	423-D	185
3	OPTR 64, MK , T- , %			
SV	12 RUN 20" (996 G) WATER INTO V-241			
4	13 RUN IN FROM V-354, OPTR 225, MK 531, *F 10863		41-D	3047
	RECORD: G/ML 1.307 (1.270-1.328) 28.05%			
	RECORD: PH 1.5 (2.2-3.7)			
	14 ADJ TO 2850 GAL AT 67-69°F RECORD: 69 *F 660		57-A	660
	(58" V-240 & 246, 60" V-241, 242, 245)			
	15 STIR 5 MIN & RECORD: PH 2.3 (2.2-3.7)			
	16 IF NECESSARY, ADJ TO PH 3.0-3.1 ASSUME 66%		33-D	
	RECORD: PH 2.0			
	NOTE: DILUTE N-7-D 10:1 WITH WATER BEFORE			
	ADDING ASSUME 50%	4	7-D	2
	17 RECORD: 1.110 G/ML (1.107-1.110)			
	NOTE: IF G/ML OUT OF LIMITS FILL OUT			
	CHECK LIST & ATTACH			
	18 STIR AT 67-69°F FOR S 28			
358	19 RUN 10" (500 G) WATER INTO V-358			
5	20 RUN V-359 INTO V-351 & PUMP IN V-351			
	21 ADJ TO 55" (2600 G)			
	22 SIFT IN N-108-A FROM S 19.6			
	23 STIR 5 MIN & RECORD: PH 9.6 (9.0-10.0)			
	24 ADJ TO PH 9.8-9.9 & RECORD: PH 9.8			
	ASSUME 50%	4	7-D	2
	ASSUME 60%		33-D	
	25 ADD N-33-D FROM S 2 (PUMP FROM V-351,			
	FLUSH WITH 1000# WATER)			
	26 ADJ TO 62" (2933 G) AT 67-69°F			
	RECORD: VOL 62" & 68 *F			
	27 STIR 5 MIN & RECORD: PH 2.6 (7.4-7.6) &			
	G/ML 1.054 (1.051-1.054)			
	NOTE IF G/ML OUT OF LIMITS FILL OUT CHECK			
	LIST & ATTACH			

MAY 26 1981

28	OBTAIN 1 QT SAMPLES OF S-18 & S-27 SOLUTIONS & TITRATE TWICE RECORD: LOWEST PH <u>2.10</u> & ML N-10-D <u>900</u> LOWEST PH <u>2.10</u> & ML N-10-D <u>900</u> NOTIFY SUPV IF ML N-10-D IS NOT IN RANGE 8.4-8.8 OR IF THE TWO TITRATIONS DIFFER BY MORE THAN 0.10 ML N-10-D (IF YES, FLUSH ALL EQUIPMENT & REPEAT TITRATIONS) DO NOT PROCEED IF N-10-D TITRATION IS OUT OF RANGE ADJUST V-358 TO OBTAIN A TITRATION PH = <u>2.10</u> (2.00-2.10) <u>2.05-2.15</u>			
		26	33-D 7-D	17

SV 6	29 WHEN S-28 TITRATION OK, STRIKE V-358 THRU BOTH UNDERSURFACE DISTRIBUTORS INTO SV IN 16-18 MIN RECORD: START <u>1:10 AM</u> TOTAL MIN _____ NOTE: STRIKE TIME UP WHEN 1/2 VAT BOTTOM SHOWS & BUBBLES APPEAR IN SIGHT GLASSES 30 IMMEDIATELY DUMP IN N-4-A FROM S 3 & SET TIMER FOR 15 MINUTES 31 DURING S 30, WASH IN V-358 32 STIR 2 MIN & RECORD PH <u>2.0</u> (1.8-2.5) PBXS, <u>+</u> (MUST BE +) 33 STIR TOTAL OF 15 MIN FROM S-30 & RECORD: TEMP <u>72</u> *F (67-73*F) 34 DUMP N-3-A FROM S-4 35 STIR 3 MIN 36 POUR IN N-32-D FROM S-5 37 STIR 2 MIN 38 DUMP IN N-15 FROM S-6 39 STIR 3 MIN 40 DUMP IN N-3 FROM S-7 41 STIR 4 MIN FOR S-44			
---------	---	--	--	--

DRUM 7	42 DURING S-41 SIFT N-711-B FROM S-9 INTO DRUM OF N-28-D FROM S-8 IN 1-2 MIN. 43 STIR 1-2 MIN WITH PADDLE TO MILKY SOLUTION			
-----------	--	--	--	--

SV 8	44 WHEN S-41 COMPLETE, IMMEDIATELY POUR N-711-B SOLUTION GRADUALLY OVER 5 MIN PERIOD INTO SV WATCH FOAM!!! IF FOAMING IS EXCESSIVE, STOP POURING UNTIL FOAM SUBSIDES 45 DUMP IN 46 STIR 10 MIN 47 RECORD: PH <u>5.6</u> (5.8-6.0) 48 IF NECESSARY, ADJ TO PH <u>5.8-6.0</u> ASSUME 50% & RECORD: PH <u>5.9</u> ASSUME 66% 49 RECORD: TIME <u>2:30 AM</u> 50 FLOOD TO 153" (7619 G) 51 STOP AGITATOR	200	428-A	200
		20	7-D 33-D	10

START	FINISH	OPTR	HELPER
<u>1:10 PM</u>	<u>2:50 PM</u>	<u>86</u>	<u>225</u>