

FILE NAME: Talc (TALC)

DATE: 2006

DOC#: TALC172

DOCUMENT DESCRIPTION: Published OSHA Information RE Talc

40

**OSHA**Occupational Safety & Health Administration
U.S. Department of Labor[Home](#)
[Index](#)
[Search](#)

Chemical Sampling Information Talc (Containing asbestos)

[◀ Chemical Sampling Information - Table of Contents](#)[Field Definitions](#)
[Analytical Methods](#)
[Health Guidelines](#)

General Description

NAME: Talc (Containing asbestos)**SYNONYM(s):** Talc, Fibrous Tremolite
(see Asbestos) prior to 9/1/89**IMIS:** 9031**CAS:** 14807-96-6**DESCRIPTION:**

Solid

Exposure Limits

OSHA GENERAL INDUSTRY PEL:

Cancer & Lung Disease Hazard (29 CFR 1910.1001) . TWA 0.2 F/cc . STEL 1.0 F/cc . ACTION LEVEL 0.1 F/cc

ACGIH TLV: Use Asbestos TLV - TWA;
However, should not exceed 2 mg/m³ respirable particulates. 2 mg/m³ Ceiling**NIOSH REL:** 0.1 fiber / cc in 400 liter air sample (fibers > 5µm long) 100 min TWA ; (use 29 CFR 1910.1001), Potential carcinogen

Health Factors

IARC: Group 1, carcinogenic to humans

HEALTH EFFECTS: Lung cancer (HE1)

Monitoring

PRIMARY SAMPLING/ANALYTICAL METHOD (SLC1):

See Asbestos

◀ [Chemical Sampling Information - Table of Contents](#)

Revision Date: 01/15/1999

*** All Trademarks are the property of their respective owners.**