

No. 84 YGP

EFFECTIVE APRIL 12, 1939
SUBJECT TO CHANGE WITHOUT NOTICE

Suggested

RETAIL

PRICE LIST

**Glidden Paints
SPRED PRODUCTS**



THE GLIDDEN COMPANY, NATIONAL HEADQUARTERS, CLEVELAND 14, OHIO

GLD026621

INDEX

Product	A	Page
Ad-Et-Ite Paint and Varnish Remover	3	3
Alkali-Resisting Primer No. 6419	3	3
Alkyd Enamels	3	3
Aluminum Asphalt Roof Paint	3	3
Aluminum, Metallite	17	17
Spray Enamel, Japalac	16	16
Asbestos Shingle Paint	3	3
Asphalt Roof Coatings	3	3
B		
Bar Top Varnish, Glid-Tone Gloss	10	10
Barn Paint, Endurance	5	5
Basecoats:		
Endurance	6	6
Gliddencoat	8	8
Ripolin Undercoat	20	20
Speed-wall, Interior	22	22
SPRED Primer-Sealer	12	12
Surface Band	13	13
Basement Paints:		
PII-Name!l	19	19
Florenamel	8	8
SPRED Sotin	8	8
SPRED Tred	13	13
SPRED Glid-On	13	13
Black Asphaltum	3	3
Bleach, Glid-Tone Wood Bleach	15	15
Blending Colors - Dramatone	12	12
Colors-In-Oil	4	4
Blending Liquid, Endurance Shingle and Shake Stain	7	7
Boat Varnish, Glid-Tone Spar Varnish	10	10
Brick Paint, SPRED Glid-On	13	13
Brush Restorer, Glid-Strip	9	9
Brushes	4	4
Brushing Lacquer, Glid-Tone Crystalac	9	9
C		
Canvas Preservative, Neva-Rat	18	18
Caulking Compound	4	4
Cement and Stucco Paints		
SPRED Glid-On	13	13
Cleaner, Glid-N Liquid	9	9
Colors-In-Oil	4	4
Concrete Paints:		
PII-Name!l	19	19
SPRED Tred	13	13
SPRED Glid-On	13	13
Crack and Crevice Filler, SPRED Patch	14	14
Cresote Paint, Stock Farm White	21	21
Crystalac, Glid-Tone	9	9
D		
Deck Paint, Florenamel	8	8
Deep Colors - SPRED Sotin	12	12
Detergents, Glid-N Liquid Cleaner	9	9
Dramatone Tinting Colors	12	12
Drtwal Clear, Silicone	8	8
E		
Enamel:		
Florenamel	8	8
Japalac	15	15
Japalac Spray	16	16
PII-Name!l	19	19
Ripolin	20	20
Speedenamel	20	20
SPRED Lustre	15	15
Truck, Tractor & Machinery	22	22
Enamel Undercoats:		
Gliddencoat	8	8
Ripolin Undercoat	20	20
Speedenamel Red Oxide Metal Primer	20	20
Endurance:		
Barn Paint	5	5
Basecoat	6	6
House Paint	6	6
Imperial	6	6
Mildew & Fume Resistant	6	6
Pastel Colors	6	6
Shingle & Shake Stain	7	7
Trim & Shutter Colors	7	7
Velvet Flat	7	7
Everon House Paint	7	7
Exterior Basecoat	6	6
F		
Farm Building Paints:		
Endurance Paints	5-7	5-7
Speedenamel	20	20
Metallite	17	17
SPRED Products	12-14	12-14
Stock Farm White	21	21
Fence Paints:		
Metallite	17	17
Nev-A-Rust	18	18
Speedenamel	20	20
Stock Farm White	21	21
Filler, Glid-Tone	15	15
Florenamel	8	8
Floor Finishes:		
Florenamel	8	8
Glid-Tone Gloss Varnish	10	10
Penetrex	19	19
PII-Name!l	19	19
SPRED Tred	13	13
Floor Wax - Glid-N	9	9
Four Hour Enamels Japalac	15	15

Product	G	Page
Glidden Paste Wax		8
Gliddencast		8
Glid-N Floor Wax (Liquid)		9
Glid-N Liquid Cleaner (Detergent)		9
Glid Strip (Non-Flammable)		9
Glid-Tite Galvanized Iron Primer		9
Glid-Tone Gloss Varnish		10
Glid-Tone Products	9, 10,	13
Glid-Tone Re-Grain Ground Coat		10
Glid-Tone Satis-Shoon Varnish		10
Glid-Tone Spar Varnish		10
Glid-Tone Stain		10
Glid-Tone Varnish Stain		10
Glid-Tone Wood Bleach		10
Glid-Tone Wood Filler		10
Glid-On, SPRED		13
Gloss Finishes:		
Florenamel		8
Japalac		13
Ripolin		13
Speedenamel		20
Speed-wall		21
Gold, Spray - Japalac		13
Granulite		13
H		
Heat Resisting Aluminum		17
House Paints:		
Endurance		4-7
Everon		7
SPRED Glid-On		13
I		
Imperial House Paint		6
Interior Aluminum, Metalite		17
Interior Varnishes	10, 20	
Iron Primer, Glid-Tite		9
Iron Primer, Nev-A-Rust		18
Iron Primer, Speedenamel		20
J		
Japalac Enamel		18
Japalac Screen and Iron Enamel		18
Japalac Spray Enamel		16
L		
Lacquer, Glid-Tone Crystolacq		9
Latex Paints	18, 19	
Linoleum Coating, Crystolacq		9
Lined Oil		16
Liquid Cleaner Glid-N		9
Liquid Red Lead		16
Liquid Wax, Glid-N		9
M		
Machinery Enamel:		
Speedenamel		20
Japalac		18
Truck, Tractor and Machinery		22
Masonry Finishes:		
Drywel		5
SPRED Glid-On		13
Masticate		17
Masticate Primer		17
Metal Primers:		
Glid-Tite		9
Red Lead		16
Iron Primer, Nev-A-Rust		18
Iron Primer, Speedenamel		20
Metal Protective Paints:		
Glid-Tite		9
Metalite		17
Nev-A-Rust		18
Red Lead		16
Speedenamel		20
Metalite, Interior-Exterior		17
Mildew-Resisting Paints:		
Endurance		6
SPRED Glid-On		13
N		
Nev-A-Rot		18
Nev-A-Rust		18
Nev-A-Rust Primer		18
O		
Oil Colors:		
Colors-In-Oil		4
One-Coat House Paint, Endurance Imperial		6
P		
Paint and Varnish Remover	2, 9	
Paste Wood Filler, Glid-Tone		13
Patel House Paint Colors		4
Patching Plaster, SPRED Patch		14
Penetraz		19
Plastic Roof Cement		19
Pit-Hamel		19
Porch and Deck Enamel, Florenamel		8
Primers and Sealers:		
Alkali-Resisting 6419		3
Endurance Basecoat		6
Gliddencast		8

Product	Page
Interior Basecoat	21
Nav.-A.-Rust Primer	18
Ripolin Undercoat	20
SPRED Primer-Sealer	21
Speedenamel Red Oxide Primer	20
Speed-Wall Alkyd Interior-Basecoat	21
Surface Bond	13
Putty	19
R	
Red Lead	16
Redwood Finish	20
Ripolin Enamel	20
Ripolin Undercoat	20
Rockspar Varnish	20
Roof Paints:	
Aluminum Asphalt	3
Asphalt	3
Metallite	17
Nav.-A.-Rust	18
SPRED Glide-On	13
S	
Screen Enamel, Japalac	16
Semi-Gloss Enamels:	
Ripolin	20
Speed-Wall	21
SPRED Lustre	13
Shake Stain, Endurance	7
Shelfac	20
Shingle Stain, Endurance	7
Specding Compound, SPRED Patch	14
Spar Varnish, see Old-Tone Spar	10
Speedenamel	21
Speedenamel Red Oxide Metal Primer	21
Speed-Wall Alkyd Flat	21
Speed-Wall Alkyd Interior Basecoat	21
Speed-Wall Alkyd Semi-Gloss Enamel	21
Speed-Wall Gloss White Enamel	21
Spray Enamel, Japalac	16
SPRED Products	12-14
SPRED Flat	14
SPRED Glide-On	13
SPRED Grumviolet	12
SPRED Lustre	13
SPRED Patch	14
SPRED Primer-Sealer	12
SPRED Satin	12
SPRED Stipple Texture	14
SPRED Surfacing	14
SPRED Texture	14
SPRED Tred	13
Stains:	
Old-Tone, Wood	10
Endurance, Shingle and Shake	7
Stipple Texture, SPRED	14
Streak Proof White Paint	22
Stens and Iron Enamel, Japalac	15
Surface Bond	13
Surface Conditioner, SPRED Surfacing	14
T	
Table Top Varnish, Old-Tone Gloss	10
Texture Paint, SPRED	14
Tile Roof Paint, SPRED Glide-On	13
Tinners' Paint	22
Tinting Colors	A, 12
Trim and Shutter Colors, Endurance	12
Truck, Tractor & Machinery Enamel	22
Tube Painters	A, 12
Turpentine	22
U	
Undercoats:	
Endurance Exterior Basecoat	6
Old-Tonecoat	8
Ripolin Undercoat	20
Speed-Wall Interior Basecoat	21
SPRED Primer-Sealer	12
Surface Bond	13
V	
Vapor Barrier, SPRED Primer-Sealer	12
Varnishes:	
Old-Tone Gloss	10
Old-Tone Satin Sheen	10
Old-Tone Spar	10
Japalac Clear Spray Finish	16
Rockspar	20
Varnish Remover	3, 9
Vinyl-Lexel, SPRED Glide-On	13
Vismatic Green Chalkboard Coating	23
W	
Waxes:	
Glidden Paste Wax	8
Old-N Floor Wax	9
Wood Bleach	15
Wood Filler	15
Wood Finishes	9-11, 18
Wood Preservative, Neva-Rot	18
Wood Stain	10
Y	
Yacht and Boat Finishes	23

**DEALER NET PRICE LIST No. 84YGP*****AD-EL-ITE PAINT AND VARNISH REMOVER**

A top-quality remover. Contains no alkalies, acids, oils or water. Does not raise the grain or discolor the wood. Evaporates very slowly. Very effective in removing old paint, enamel, lacquer and baked japan.

APPLICATION—Brush

Gals.	Qts.	Pts.	1/2 Pts.
-------	------	------	----------

3.31	1.31	.83	.63
------	------	-----	-----

***ALKALI-RESISTING PRIMER No. 6419**

An easy to apply masonry primer-sealer for interior newly plastered or damp walls, and exterior masonry, brick, stucco and concrete blocks, which are to be painted with synthetic rubber-base or oil base paints. Penetrates deeply into the pores and adheres firmly to the surface, to create perfect bond for finish coat. Resists moisture and alkali. Seals in active lime. Prevents fresh plaster from burning through and discoloring the finish coat.

APPLICATION—Brush, Spray THINNER—Turpentine
DRYING TIME—16 hours Covers 350-400 Sq. Ft. per gal.
(Also See SPRED Primer-Sealer Alkali-Resisting Primer)

7.78	2.47	—	—
------	------	---	---

ALKYD ENAMELS

See: Speed-Wall Alkyd Flat and Gloss White; Japalac; Florenamel; Nev-A-Rust; Ripolin; Speed-Wall Interior Basecoat; Spred Lustre

***ALUMINUM ASPHALT ROOF PAINT**

Recommended for tar paper, composition and asphalt roofs. Will rejuvenate weathered roofs and insulate with a silvery sheet of aluminum, in one coat. Made with selected asphalt, finest grade aluminum flakes and solvents.

APPLICATION—Brush, Spray THINNER—Mineral Spirits or Turp.
DRYING TIME—10 hours Covers 275-400 Sq. Ft. per gal., depending on surface.

5.22	—	—	—
------	---	---	---

ALUMINUM PAINTS

See: Metallite; Japalac Spray Enamel, Aluminum

ASBESTOS SHINGLE PAINT

See: SPRED Glide-On

ASPHALT ROOF COATINGS (Plain, Fibrated, Plastic)

(PRICES UPON REQUEST)

BARN PAINT

See: Endurance Barn Paint

BASECOATS (Primers)

For Exteriors—See: Endurance Exterior Basecoat; Surface Bond

For Interiors—See: Gliddencat; Speed-Wall Interior Basecoat; SPRED Primer-Sealer; Ripolin Undercoat

BASEMENT PAINTS

For Floors—See: Pli-Namel; Florenamel; SPRED Tred

For Walls—See: SPRED SATIN; SPRED Glide-On

***BLACK ASPHALTUM**

A weather-resisting, quick-drying, gloss black asphaltum base paint. Recommended for exterior iron work, fences, metal rash and other exterior metal surfaces where an economical finish is desired.

APPLICATION—Brush, Spray DRYING TIME—2 to 3 hours
THINNER—Mineral Spirits or Turp. Covers 400-500 Sq. Ft. per gal.

3.68	1.40	.88	.66
------	------	-----	-----

* AVAILABLE IN 5-GAL CANS

AT 15c PER GALLON LESS THAN 1-GAL. PRICES.

PAGE 3

GLD026623



DEALER NET PRICE LIST No. 84 YGP

BLACKBOARD FINISHES

See: Vismatic Green Chalkboard Coating

BLEACH

See: Glid-Tone Wood Bleach

BLENDING COLORS

See: SPRED Dramatone Tinting Colors; Colors-In-Oil

BRICK PAINTS

See: SPRED Glide-On

BRUSHES, ALL TYPES

(PRICES UPON REQUEST)

BRUSHING LACQUER

See: Glid-Tone Crystalacq

BRUSH RESTORER

See: Glid-Strip

CANVAS PRESERVATIVE

See: Neva-Rot

CAULKING COMPOUND

(PRICES UPON REQUEST)

CEMENT AND STUCCO PAINT

See: SPRED Glide-On

CLEANER, LIQUID

See: Glid-N Liquid Cleaner

COLORS-IN-OIL

Unexcelled for tinting flat wall paints, Semi-Gloss and Gloss enamels, glazing liquids, white lead and white paste paint. Ground extremely fine in special pale linseed oil for quick and positive dispersion. The finest pigments are used to develop perfect tone and strength of color. Not to be used in latex, emulsion paints, or lacquer.

			1/2 Pts.	1" x 5" Tubes
Raw Umber, Burnt Umber.....	7.73	2.42	.90	.43
Raw Sienna, Burnt Sienna.....	9.08	2.74	1.00	.45
Ivory Drop Black.....	—	2.47	.93	.44
Lamp Black.....	6.88	2.14	.87	.43
Prussian Blue.....	—	2.87	1.03	.49
Chrome Green, Light; Chrome Green, Medium.....	12.03	3.52	1.21	.50
Perma-Green.....	—	5.52	1.71	.59
Chrome Yellow, Light and Medium.....	—	4.52	1.46	.54
Chrome Yellow, Dark.....	—	5.37	1.66	.58
Yellow Ochre.....	8.08	2.54	.94	.45
Venetian Red.....	7.12	2.24	.90	.44
American Vermillion (Interior Use Only).....	—	4.67	1.49	.56
Perma Blue.....	—	5.03	1.54	.58

CONCRETE PAINT

See: SPRED Glide-On; Pli-Namel; SPRED Tred

CRACK AND CREVICE FILLER

See: SPRED Patch, SPRED Stipple Texture

CREOSOTE PAINT

See: Stock Farm Paint

**DEALER NET PRICE LIST No. 84YGP****DECK PAINT**

See: Florenamel

DEEP COLORS

See: SPRED SATIN

DETERGENTS

See: Glid-N Liquid Cleaner

DRAMATONE MULTI-PURPOSE TINTING COLORS

See: SPRED Products Section

***DRIWAL (Clear)**

A damp-resisting, stain-resisting material designed for application on limestone, stucco, sandstone, concrete and other porous surfaces of masonry. It penetrates pores of surface and coats them with an insoluble substance which makes them fully water-repellent. Does not change texture nor discolor surface. Contains no paraffine.

APPLICATION—Brush, Spray

DRYING TIME—2 hours

THINNER—None Required

COVERAGE—125 to 275 Sq. Ft. per gallon depending on porosity of surface

3.93

***DRIWAL (Silicone)**

A transparent, water-repellent finish for exterior, above-ground brick, stone and masonry. Does the job in ONE COAT. Repels rain water from penetrating the pores. Resists efflorescence and staining. Masonry surfaces show no visible change in color or texture when treated with this material. Recommended for use on brick and mortar, concrete, cement-base paints, asbestos-cement combinations, sandstone, stucco and stones other than limestone. Not to be used on cinder block or other light weight aggregate concrete blocks with extremely porous surfaces. This invisible water-repellent coating contains silicone to combat masonry deterioration.

APPLICATION—Brush, Spray

DRYING TIME—2 hours

THINNER—None Required

COVERAGE—125 to 275 Sq. Ft. per gallon depending on porosity of surface

4.68

ENAMELS

See: Japalac; Ripolin; Speed-Wall Alkyd Flat; Truck, Tractor and Machinery; Florenamel; Pli-Namel; SPRED Lustre; Speedenamel

ENAMEL UNDERCOATER

See: Gliddencat; Ripolin Undercoat

***ENDURANCE BARN PAINT — No. 500 RED**

A new, highest quality paint with excellent hiding power. It dries to a tough glossy film that withstands the rigors of the roughest weather. Provides long-lasting protection for barns, sheds, granaries, silos, water tank exteriors, storehouses, fences, etc. Use it on exterior wood and metal.

APPLICATION—Brush, Spray

DRYING TIME—Overnight; 36 hours for recoating

THINNER—Mineral Spirits or Turpentine

COVERAGE—500 Sq. Ft. per gallon

4.72

1.66

* AVAILABLE IN 5-GAL. CANS

AT 15c PER GALLON LESS THAN 1-GAL. PRICES.

**DEALER NET PRICE LIST No. 84YGP*****ENDURANCE EXTERIOR BASECOAT**

Exterior primer for new wood and previously painted wood that is badly weathered or chalked. Use it to spot-prime bare spots resulting from peeling and flaking. Made from specially prepared oils to produce the elasticity, adhesion and control penetration necessary for finest exterior paint jobs.

APPLICATION—Brush, Spray DRYING TIME—48 hours for recoating
THINNER—Mineral Spirits or Turpentine
COVERAGE—450 to 500 Sq. Ft. per gallon

ENDURANCE HOUSE PAINT*FOR SIDING, TRIM AND SHUTTERS**

Contains more heavy-bodied, pure linseed oil per gallon for longer life; pure white lead for added strength, water-resistance and extra durability; titanium for whiteness and hiding; zinc oxide to combat mildew; magnesium silicate for protection against cracking and checking. The exclusive Glidden formula makes this the finest, longest-lasting, self-cleaning exterior house paint manufactured. May be tinted with DRAMATONE Tinting Colors.

Outside White No. 1800.....

Regular Colors and Black.....

Non-Chalking Trim White No. 1892.....

Crylite Green No. 1828.....

Deep Turquoise No. 150.....

Shutter Green No. 71.....

Chestnut Brown No. 92; Dark Blue No. 158.....

APPLICATION—Brush, Spray, Roller
DRYING TIME—16 hours; recoat in 72 hours
THINNER—Mineral Spirits or Turpentine
COVERAGE—550 Sq. Ft. per gallon

ENDURANCE HOUSE PAINT*MILDEW & FUME-RESISTANT**

A deluxe, Super White House Paint—Ideal for the finest homes. Excellent for exterior wood, masonry and metal in any climate. A Non-Staining House Paint that stays white and bright for years. Especially suited for industrial areas, where homes are subjected to chemical fumes, heavy smog and smoke. Its formulation makes it ideal for farm buildings and fences. Combats mold, mildew and the roughest year-round weather.

APPLICATION—Brush, Spray THINNER—Mineral Spirits or Turpentine
DRYING TIME—16 hours; 72 hours for recoating
COVERAGE—Up to 550 Sq. Ft. per gallon

ENDURANCE HOUSE PAINT, PASTEL COLORS

Pastel colors are easily obtained by tinting existing colors of ENDURANCE HOUSE PAINT or NON-CHALKING TRIM WHITE No. 1892 with DRAMATONE Tinting Colors. See ENDURANCE HOUSE PAINT Color Card.

ENDURANCE IMPERIAL ONE-COAT*WHITE HOUSE PAINT (Alkyd Fortified)**

Premium quality white exterior paint. Gives extra hiding and coverage with its built-in second coat. Has depth and richness of enamel. Easy brushing. Once over is enough with this amazing one-coat paint! Fortified with alkyds to give extra durability and lasting beauty.

APPLICATION—Brush, Spray THINNER—Mineral Spirits or Turpentine
DRYING TIME—48 hours
COVERAGE—550 Sq. Ft. per gallon

* AVAILABLE IN 5-GAL CANS
AT 15¢ PER GALLON LESS THAN 1-GAL. PRICES.



DEALER NET PRICE LIST No. 84YGP

ENDURANCE SHINGLE AND SHAKE STAIN

ENDURANCE SHINGLE AND SHAKE STAIN colors are made by mixing two parts ENDURANCE HOUSE PAINT with one part BLENDING LIQUID. This combination makes an ideal finish for use on grained cedar shakes, wood shingles, rough surface cedar, redwood and fir—on porous, rough or hand-split siding, fences, barns, and rough structures that have weathered a long time. ENDURANCE SHINGLE AND SHAKE STAIN embodies the finest quality paint pigments dispersed and blended in a strong wood preservative liquid that holds color after long exposure. It also acts as a protective finish against dry rot, decay, moisture and insects. ENDURANCE SHINGLE AND SHAKE STAIN penetrates deeply into the wood to retard warping, curling and splitting. It combats the roughest weather for many years. For combination prices, SEE: ENDURANCE HOUSE PAINT AND BLENDING LIQUID.

APPLICATION—Brush, Dip, Spray

DRYING TIME—16 hours; 48 hours for recoating

COVERAGE—Approx. 300 Sq. Ft. per gallon depending on type of surface

*BLENDING LIQUID

BLENDING LIQUID is a combination of treated oils and solvents specially formulated to be mixed with ENDURANCE HOUSE PAINT and TRIM AND SHUTTER COLORS. This combination produces ENDURANCE SHINGLE AND SHAKE STAIN, a quality preservative finish available in many modern colors.

Gals.	Qts.	Pts.	1/2 Pts.
-------	------	------	----------

3.38	1.32	—	—
------	------	---	---

*ENDURANCE VELVET (Flat Exterior Finish)

FOR WOOD SHINGLES, SHAKES, WOOD SIDING AND TRIM. May be used also on metal surfaces. It brushes easily and will produce a beautiful flat finish in one coat over most previously painted surfaces if the color contrast is not great. Dries dust free in one hour. It provides a "breather type" film which aids the elimination of internal moisture.

White and Colors.....

6.82	2.18	—	—
------	------	---	---

APPLICATION—Brush, Spray

DRYING TIME—Dust-free 1 hr.; 48 hours for recoating

THINNER—Mineral Spirits or Turpentine

COVERAGE—Up to 550 Sq. Ft. per gallon

*EVERON HOUSE PAINT (White)

An excellent paint that stays clean and bright because of its special formula which provides controlled chalking. A superior finish for all wood surfaces exposed to weather and changing climatic conditions. Resists fumes in industrial areas! EVERON HOUSE PAINT brushes easily, penetrates deeply when used as a primer, adheres tenaciously as a finish coat, dries with an elastic, high gloss finish that remains firm and durable. EVERON is truly the economical HOUSE PAINT.

APPLICATION—Brush, Roller, Spray

DRYING TIME—16 hours; recoat in 48 hours

THINNER—Mineral Spirits or Turpentine

COVERAGE—550 Sq. Ft. per gallon

6.28	2.05	—	—
------	------	---	---

* AVAILABLE IN 5-GAL CANS

AT 15c PER GALLON LESS THAN 1-GAL. PRICES.

PAGE 7

GLD026627

**DEALER NET PRICE LIST No. 84YGP**

Gals. Qts. Pts. 1/2 Pts.

FARM BUILDING PAINTS

For Exteriors—See: Endurance Paints, Metallite, SPRED Glide-On, Nev-A-Rust, Stock Farm White

For Interiors—See: SPRED Products

FENCE PAINTS

See: Stock Farm White; Metallite; Nev-A-Rust

FILLER, WOOD

See: Glid-Tone Wood Filler

FLOOR FINISHES

See: Pli-Namel; Florenamel; Penetrex; Glid-Tone Gloss Varnish; SPRED Tred

FLOOR WAX

See: Glidden Paste Wax; Glid-N Floor Wax

***FLORENAMEL (Alkyd)**

An alkyd enamel with extra durability, for use on porches, floors of wood and concrete, canvas decks, railings—inside and outside. Will not water-spot; standing pools of water do not affect it. FLORENAMEL gives concrete basement floors and walls a mirror-like enamel finish. It's scorbable. FLORENAMEL is made to take the roughest wear and weather. May be tinted with DRAMATONE Tinting Colors. All colors.....

7.48

2.42

—

—

APPLICATION—Brush, Spray

DRYING TIME—12 hours

THINNER—Turpentine or Mineral Spirits

COVERAGE—500 to 600 Sq. Ft. per gallon

***GLIDDENCOAT (White Enamel Undercoat)**

A perfect enamel undercoat for woodwork. Produces a firm opaque film to hold out succeeding coats of finishing enamel, making it possible to secure full luster and depth of gloss. Works easily, flows evenly without showing brush marks and requires only light sanding. Can be tinted with colors in oil or DRAMATONE Tinting Colors.....

6.58

2.12

1.24

.84

APPLICATION—Brush, Spray

DRYING TIME—Overnight for sanding and recoating

THINNER—Mineral Spirits or Turpentine

COVERAGE—500 Sq. Ft. per gallon

GLIDDEN PASTE WAX

For furniture, floors and automobiles; in fact, any surface where a wax finish is desired. It polishes quicker and easier than other similar products and will retain its gloss and finish over a period of several months. It dries hard and imparts longer protection to floor surfaces even when subjected to extreme hard usage.....

4 lbs.

1 lb.

3.50

1.03

—

—

APPLICATION—Cloth or Applicator

GLIDE-ON, SPRED

See: SPRED Products Section

GLID-N FLOOR WAX (Liquid)

For use on all types of floors. Dries to a gloss finish without polishing. The hard wax film resists wear, keeps dirt on surface where it can be removed easily with a stiff brush or damp mop. Resists water. Scorbable.....

3.31

1.14

—

—

* AVAILABLE IN 5-GAL CANS

AT 15c PER GALLON LESS THAN 1-GAL. PRICES.

**DEALER NET PRICE LIST No. 84YGP**

Gals.	Qts.	Pts.	1/2 Pts.
-------	------	------	----------

GLID-N LIQUID CLEANER (Detergent)

An excellent degreaser as well as cleaner. Does a remarkably easy job on walls, woodwork, floors, linoleum, tile, windows, dishes, mirrors and automobiles. Dries free from streaks. Harmless to the skin. Requires only two to three teaspoonsful to a gallon water.

4.31	1.31	.82	—
------	------	-----	---

GLID STRIP (Non-Flammable)**Wash Away Paint and Varnish Remover**

A non-flammable, water-flush paint and varnish remover that stays wet longer and permits working on larger areas. Has less tendency to run and sag on upright surfaces due to its heavy body. Easy to use. Just brush it on, wait a few minutes, then wash it off with water. GLID STRIP also acts as a cleaner for old, hardened nylon and pure bristle paint and varnish brushes. Will soften latex paints for easy removal.

6.82	2.31	1.26	.83
------	------	------	-----

***GLID-TITE GALVANIZED IRON PRIMER**

A primer for all galvanized metal, plymetal, galvaneal, or treated metal surfaces. The metal requires no previous etching with acids. Excellent for use on new eave troughs and gutters. Finish coat adhesive is better if application is thin rather than heavy.

6.18	2.02	—	—
------	------	---	---

APPLICATION—Brush

DRYING TIME—Overnight; 72 hours for recoating

THINNER—Turpentine or Mineral Spirits

COVERAGE—Up to 600 Sq. Ft. per gallon

GLID-TONE CRYSTALACQ (Brushing Lacquer)

A crystal clear, quick-drying, water- and wear-resistant lacquer finish for brush application. Easy to use. Excellent for floors, woodwork, furniture, linoleum, etc.

7.58	2.37	1.37	—
------	------	------	---

APPLICATION—Brush

DRYING TIME—1 to 6 hours, depending on surface

THINNER—Glid-Tone Crystalacq Reducer

COVERAGE—300 Sq. Ft. per gallon

GLID-TONE CRYSTALACQ REDUCER

—	—	1.05	—
---	---	------	---

GLID-TONE GLOSS VARNISH

A deluxe, general-purpose interior varnish. Epoxy resins give it extreme abrasion resistance, durability, and lasting beauty. Excellent on all interior wood surfaces, bar and tabletops, woodwork, furniture and floors. Especially suitable over newly stained woodwork where Glid-Tone Stains have been applied. May be rubbed.

8.68	2.67	1.52	.95
------	------	------	-----

APPLICATION—Brush

DRYING TIME—6 to 8 hours

THINNER—Mineral Spirits or Turpentine

COVERAGE—650 Sq. Ft. per gallon

* AVAILABLE IN 5-GAL CANS

AT 15c PER GALLON LESS THAN 1-GAL. PRICES.

**GLID-TONE RE-GRAIN GROUND COAT**

An enamel undercoater that produces a firm, opaque film, renews worn out finishes as described in "Step 1" in the Glid-Tone Re-Grain Process folder. For more detailed information see Glid-Tone Regrain Process Folder 04-112.

Gals.	Qts.	Pts.	½ Pts.
-------	------	------	--------

—	2.12	1.24	.84
---	------	------	-----

GLID-TONE SATIN-SHEEN VARNISH

A new satin sheen varnish that dries free from all cloudiness and preserves the natural beauty of the wood. Excellent for use over GLID-TONE stains and for all interior work where a dull finish or rubbed effect is desired. Sufficiently pale for use over light modern stains. DO NOT USE ON FLOORS.

APPLICATION—Brush

DRYING TIME—2 hours

THINNER—Mineral Spirits or Turpentine

COVERAGE—650 Sq. Ft. per gallon

7.68	2.37	1.37	.89
------	------	------	-----

GLID-TONE SPAR VARNISH

Extra durable spar varnish for exterior surfaces exposed to weather. Recommended as the finest varnish available for exterior use—spars, hulls, decks, house sidings, paneling, porch ceilings, outdoor furniture, etc. Makes perfect finish over Glid-Tone Stain on exterior surfaces.

APPLICATION—Brush

DRYING TIME—8 hours; 48 hours for recoating

THINNER—Mineral Spirits or Turpentine

COVERAGE—650 Sq. Ft. per gallon

9.43	2.81	1.59	1.02
------	------	------	------

GLID-TONE VARNISH STAIN

Stains and varnishes in one operation. Dries quickly, to a high lustre. For use on furniture, woodwork and floors. Unusually waterproof.

APPLICATION—Brush, Spray

DRYING TIME—4 to 6 hours; 24 hours for recoating

THINNER—Mineral Spirits or Turpentine

COVERAGE—600 Sq. Ft. per gallon

7.18	2.27	1.32	.88
------	------	------	-----

GLID-TONE WOOD STAIN

An all-purpose, pigmented wiping stain for all types of wood, plywood and veneer, exterior and interior surfaces. Especially suitable for knotty pine wood paneling in recreation rooms. Excellent for use on new or old furniture, woodwork, cabinets, wall paneling and floors. GLID-TONE Stain heightens the beauty of the wood grain. Holds color evenly. May be coated with varnish, shellac or lacquer. May be tinted with DRAMATONE Tinting Colors to produce additional beautiful colors.

APPLICATIONS—Wiping Cloth, Brush

DRYING TIME—12 hours Stains, All Colors.....

THINNER—Glid-Tone Stain Reducer

Glid-Tone Stain Reducer.....

5.58	1.86	1.15	.78
3.31	1.27	.82	.63