

BONDED BRAKE SHOE SETS

WITH *American Brakeblok*®

® FRICTIONEERED FOR POWER OR STANDARD BRAKES

Year		Model or Series	Application						
			Front	Rear					
DODGE TRUCK—Contd.									
½ ton (Contd.)									
1958-57	100: KD, LD		B-192	B-192A					
1956-48	B: 1, 2, 3, 4, B1-C3		B-145	B-192A					
	C: 3, 4		B-145	B-192A					
1947-45	WC		B-145	B-192					
1942-35	All		B-145	B-145					
¾ ton									
1961-59	200: MD, MP, MW, D, P, W		B-2026	B-2026					
	Opt.: Rear axle			B-2042					
1958-57	200: KW, LW, KD, LD		B-2026	B-2042					
1956-48	B: 1, 2, 3, 4		B-192	B-192A					
	C: 1, 3, 4		B-192	B-192A					
1947-46	WD 15		B-192	B-192					
1942-37	TD15, VD15, WD15		B-145	B-145					
1 ton									
1961-59	300: MW, W		B-1125	B-2042					
1961-57	300M: MW, KW, LWM, WM		B-1125	B-1125					
1961-57	300: MD, MP, KD, KP, LD, LP, D, P		B-2026	B-2042					
1958-57	300: KP, & LPW, W, HD Rear		B-2026	B-1224					
1956-46	B: 1, 2, 3, 4 Power Wagon		B-1125	B-1125					
	C: 1, 3, 4 Power Wagon		B-1125	B-1125					
1956	D: C3DN, C4		B-2026	B-2042					
1956-53	D: B-4, C1 & C3		B-192	B-1224A					
1952-48	D: B1, B2, B3		B-192	B-1224					
1947-36	LF, MF, RB, TF, TFA, VF, VFA, WF, WFA		B-1125	B-1127					
1½ ton and over—F thru H (48-56), 400 thru 500 (57-61)									
1961-58	400: MC, MD, MP, MS, LD, LP, LS, D, P, S		B-1224	B-2032A					
1957	400: KD, KP, KS		B-1224	B-1266					
	Optional rear			B-1267					
1956	H: CR, M, S		B-1127	B-1248					
	C4H, HM, HS Opt.: Front		B-1224						
1956-53	F:G:H: B1, B2, B3, B4, C1, C3, C4		B-1224	B-1223A					
	C1H, C3H Option		B-1127						
	C4G—option		B-1224	B-1223A					
1961-57	500: MW, LW, KW, W		B-1258						
1961-58	500: MC, MD, MS, LC, LD, LS, C, D, S		B-1127	B-2032A					
1957	500: KD, KS		B-1127	B-1267					
Due to the many options on Dodge trucks, the following may apply to front or rear axles. Determine the drum diameter, brake size, TYPE OF BRAKE; and make a comparison of brake shoes for correct application.									
Drum	Width	Thickness	Brake Type	Part No.	Drum	Width	Thickness	Brake Type	Part No.
14⅞	1¾	¼	Lockheed	B-1125	16	2½	¼	Lockheed	B-1127
14⅞	2	¼	Lockheed	B-1224	16	3	¼	Lockheed	B-1223
14⅞	2	¼	Timken DP	B-1224A	16	3	¼	Timken DP	B-1223A
15	4	¾	Bendix Twinplex	B-2032A	16	3	¾	Timken DP	B-1266
15	4	¾	Bendix Twinplex	B-2032E	16	3½	¾	Timken DP	B-1267
16	2¼	¼	Lockheed	B-1258	16	3½	¼	Timken DP	B-1248
Part No.	FMS Shoe		Size	Part No.	FMS Shoe		Size		
EDSEL									
B-2006	10 or 42		11 x 2	B-2030F	126		11 x 2½		
B-2025A	13 or 126		11 x 2½	B-2055	16 or 125		11 x 3		
*B-2030B	13 or 126		11 x 2½	B-2074	125		11 x 3		
1960	All (except Station Wagon)			B-2030F	*B-2030B				
	Station Wagon & Police Cars—3" Front			B-2074	*B-2030B				
1959	All			B-2025A	B-2006				
	Optional 3" front axle			B-2055					
1958	Ranger, Pacer			B-2025A	B-2006				
	Corsair, Citation			B-2055	B-2006				
*B-2030F may be used.									
FALCON—(Ford)									
B-2071	115		9 x 2¼	B-2072	113		9 x 1½		
1961-60	Falcon Passenger & Ranchero			B-2071	B-2072				
1961-60	Falcon Station Wagon			B-2071	B-2071				