PLAINTIFF'S EXHIBIT
Stabler
USG-441

SPECIAL BULLETIN

Operating Division * CONFIDENTIAL ** CONFIDENTIAL * No. 61-2-12-3
Date 12-12-75

PRODUCT PROCEDURE — PLASTERERS JOINT FINISHING COMPOUND GB-275A

Page 1
Cancels NEW
Dated

COPYRIGHT 1975 UNITED STATES GYPSUM. UNAUTHORIZED USE OR REPRODUCTION PROHIBITED.

This bulletin expires 12-1-76.

Shipments to be made only upon authorization of Dept. #991-M, R.C. Spahr.

DESCRIPTION

A non-asbestos, dry powder, setting compound which can be used to conceal and finish joints reinforced with glass fiber scrim.

MANUFACTURING PLANTS

New Brighton

IDENTIFICATION AND PACKAGING

To be shipped in plain white 25 lb. bags, without markings except "USG NON-ASBESTOS" stenciled on each bag.

FINISHED PRODUCT SPECIFICATION

Consistency	- 54 to 58 cc. for 500 ± 30 B.U. at 77°F.
pH	- 8.2 - 8.5
Bond	- 7 minimum
Application	- Must show no scratches when drawn down tightly over SHEETROCK panels.
Set Time	- 90 - 120 minutes.

DP001 0003