EATON TRAILER AXLE MODELS

ROUND

Beam Code	Tube Section	Spindle Size Inner	Spindle Size Outer	Bearing Cones Inner	Bearing Cones Outer	Bearing Capacity (lbs)	Beam Capacity (lbs)	Weight (lbs)	Nominal Track & Sprng.Cntrs. (in.)
HCE	5.0" O.D. 0.625" Wall	3.75"	2.62"	663	HM212049	23,000	23,000	230	71.5" Track & 38" Sprng. Cntrs. 77.5" Track & 44" Sprng. Cntrs.
HJ	5.0" O.D. 0.5" Wall	3.54"	2.62"	HM218248	HM212049	25,000	20,000	203	
HD	5.0" O.D. .05" Wall	3.75"	3.25"	594A	580	25,000	22,500		

SQUARE

H25LD	5" X 5" Square w/ 0.375" Wall	3.75"	3.25"	594A	580	25,000	22,500	180	71.5" Track & 38" Spring Centers

SINGLE ANCHOR PIN TRAILER BRAKES

Brake Size (Inches)	FMSI No.	Spider Mounting	Weight Per Axle	Brake Rating Pounds EE Med	GG High	Tire Max. RR	Air Chamber Slack Adjuster
16.5" X 7"	4311J	Welded	132 lbs	up to 21,200	up to 23,120	20.1	30 X 6

These nominal ratings are general sales guidelines.
Actual load rating varies with application and duty cycle.
All applications must be approved by our Engineering Department.

(1472S)

Supreme Court of NY, Erie Cty. Index No. 2008-405, 06/18/08
Kolasinski v. Acme Liquidating Corp., et al.