


NIOSH

Current Intelligence Bulletin

Reprints-Bulletins 1 thru 18 (1975-1977)

NO.	TITLE	DATE	PAGE
1	- CHLOROPRENE	January 20, 1975	(1)
2	- TRICHLOROETHYLENE (TCE)	June 6, 1975	(9)
3	- ETHYLENE DIBROMIDE (EDB)	July 7, 1975	(19)
4	- CHROME PIGMENT	June 24, 1975 October 7, 1975 October 8, 1976	(27)
5	- ASBESTOS Asbestos Exposure During Servicing of Motor Vehicle Brake and Clutch Assemblies	August 8, 1975	(35)
6	- HEXAMETHYLPHOSPHORIC TRIAMIDE (HMPA)	October 24, 1975	(43)
7	- POLYCHLORINATED BIPHENYLS (PCBs)	November 3, 1975	(51)
8	- 4,4-DIAMINODIPHENYLMETHANE (DDM)	January 30, 1976	(59)
9	- CHLOROFORM	March 15, 1976	(65)
10	- RADON DAUGHTERS	May 11, 1976	(77)
11	- DIMETHYLCARBAMOYL CHLORIDE (DMCC) REVISED	July 7, 1976	(81)
12	- DIETHYLCARBAMOYL CHLORIDE (DECC)	July 7, 1976	(85)
13	- EXPLOSIVE AZIDE HAZARD	August 16, 1976	(87)
14	- INORGANIC ARSENIC - RESPIRATORY PROTECTION	September 27, 1976	(93)
15	- NITROSAMINES IN CUTTING FLUIDS	October 6, 1976	(97)
16	- METABOLIC PRECURSORS OF A KNOWN HUMAN CARCINOGEN, BETA-NAPHTHYLAMINE	December 17, 1976	(103)
17	- 2-NITROPROPANE	April 25, 1977	(111)
18	- ACRYLONITRILE	July 1, 1977	(119)





U. S. DEPARTMENT OF HEALTH, EDUCATION, AND WELFARE
Public Health Service
Center for Disease Control
National Institute for Occupational Safety and Health

Current Intelligence Bulletin 5

August 8, 1975

ASBESTOS

ASBESTOS EXPOSURE DURING SERVICING OF
MOTOR VEHICLE BRAKE AND CLUTCH ASSEMBLIES





DEPARTMENT OF HEALTH, EDUCATION, AND WELFARE
PUBLIC HEALTH SERVICE
CENTER FOR DISEASE CONTROL

(36)

August 8, 1975

NATIONAL INSTITUTE FOR OCCUPATIONAL
SAFETY AND HEALTH
5600 FISHERS LANE
ROCKVILLE, MARYLAND 20852

Dear Colleague:

This communication is intended to alert you to recently gathered information indicating a potential health hazard for persons exposed to asbestos during the servicing of motor vehicle brake and clutch assemblies.

On July 21, 1975, the National Institute for Occupational Safety and Health convened a meeting of government and university scientists, industry representatives, and labor union officials to discuss the present state of knowledge with respect to this problem. Data was presented by investigators from the Mount Sinai School of Medicine in New York City indicating that workers engaged in the maintenance and repair of automobile and truck brake linings are exposed to potentially hazardous levels of airborne asbestos dust. Specific brake servicing operations studied included blow-out of automobile drum brake assemblies, grinding of used truck brake linings, and bevelling of new truck brake linings. Average peak asbestos air concentrations for these three activities based on personal samples taken within ten feet of the operator were, respectively, 10.5, 3.75, and 37.3 fibers (>5 microns in length) per ml. An analysis of samples of brake drum dust revealed that almost all of the asbestos fibers found were shorter than 0.4 microns in length.

Previous studies of the extent of asbestos emissions from automobile brake lining wear showed that only a very small fraction of the original asbestos content of the brake lining is found in brake drum dust (Ref. 1-3). It was presumed that this is due to thermal degradation of the fibers during braking. The present findings indicate that enough asbestos is preserved to produce significant exposures during certain brake servicing procedures.


The full extent of asbestos-related disease in brake servicing personnel is not known at present because this particular occupational group has not been studied systematically up to now. However, a review of the scientific literature on the association between asbestos exposure and mesothelial tumors of the pleura and peritoneum has revealed at least four cases of these rare tumors in persons who were employed in jobs involving automobile brake servicing (Ref. 4-6).

Page 2.

For your information and guidance, we are enclosing pertinent references, estimates of the population at risk, a NIOSH interim recommendation for brake and clutch servicing procedures, and a copy of the Department of Labor standard covering exposure to asbestos in the work place.

The environmental studies of brake lining servicing operations outlined above together with observations of mesothelial tumors in persons so employed affirms the necessity for instituting and maintaining recommended control measures in this industry so that the health hazards of asbestos are minimized.

Sincerely yours,



J. William Lloyd, Sc.D.
Director
Office of Occupational Health
Surveillance and Biometrics

Enclosures

REFERENCES

1. Lynch, J.R.: Brake Lining Decomposition Products. J Air Pollution Control Assoc, 18:824-26, 1968
2. Hickish, D.E. and Knight, K.L.: Exposure to Asbestos During Brake Maintenance. Ann Occup Hyg, 13:17-21, 1970
3. Jacko, M.G. and DuCharme, R.T.: Brake Emissions: Emission Measurements from Brake and Clutch Linings from Selected Sources. EPA Report 68-04-0020, 1973
4. Newhouse, M.L. and Thompson, H.: Mesothelioma of Pleura and Peritoneum Following Exposure to Asbestos in the London Area. Brit J Ind Med, 22:261-69, 1965
5. McDonald, A.D. et al.: Epidemiology of Primary Malignant Mesothelial Tumors in Canada. Cancer, 26:914-19, 1970
6. Greenberg, M. and Lloyd Davies, T.A.: Mesothelioma Register 1967-1968. Brit J Ind Med, 31:91-104, 1974

(39)

ESTIMATES OF THE WORKFORCE POTENTIALLY EXPOSED TO ASBESTOS
IN THE MANUFACTURING AND SERVICING OF BRAKE LININGS AND CLUTCHES

Auto Mechanics	833,535
Garage Workers	67,679
Manufacture (original and rebuilding)	<u>6,657</u>
TOTAL	907,871

SOURCE: Adapted from 1972 Census of Manufacturers, 1972 County
Business Patterns, and Census of Population: 1970 Occupation by
Industry (all are Department of Commerce, Census Bureau
publications)

001686

RECOMMENDED (INTERIM) PROCEDURES FOR
ASBESTOS BRAKE AND CLUTCH SERVICING

The National Institute for Occupational Safety and Health (NIOSH) has research underway concerning dust exposures during brake and clutch servicing. Due to preliminary data demonstrating significant asbestos exposures during presently used cleaning techniques, NIOSH has reviewed alternate techniques whereby asbestos exposures are reduced. The following are interim procedures recommended by NIOSH to minimize dust exposures.

1. If possible, an area shall be designated for all brake and clutch repairs. Entrances into this area shall be posted with an asbestos exposure warning sign as follows.

Asbestos
Dust Hazard
Avoid Breathing Dust
Wear Assigned Protective Equipment
Do Not Remain in Area Unless Your Work Requires It
Breathing Asbestos Dust May Cause Asbestosis and Cancer

2. During brake servicing, an air purifying respirator, either single use or with replaceable particulate filter(s), as approved by the Mining Enforcement and Safety Administration (formerly Bureau of Mines) or NIOSH, shall be worn during all procedures following removal of the wheels including reassembly. During manual clutch servicing, such a respirator shall be worn during removal and cleaning of the clutch, pressure plate and housing assembly and during installation of the new clutch assembly.
3. Dust shall first be cleaned from brake drums, brake backing plates, brake assemblies and clutch assemblies using an industrial type vacuum cleaner equipped with a high efficiency filter system (>99% efficiency for 0.3 μ m diameter aerosols). After vacuum cleaning, any remaining dust shall be removed using a rag soaked in water and wrung until nearly dry. Under no circumstances shall compressed air or dry brushing be used for cleaning.
4. During arcing and riveting operations, an approved respirator, as described in (2) above, shall be worn. Grinding (arc) machines shall be provided with local exhaust ventilation such that worker exposures are maintained at least below the 1976 OSHA asbestos standard (29 CFR 1910.1001).* At a minimum, the dust bag of the arcing machine shall be removed and replaced with the hose of the high efficiency industrial vacuum described in (3) above.

-2-

5. Industrial vacuum cleaner bags containing asbestos dust and cloths used for wiping brake and clutch assemblies shall be sealed in plastic bags and labeled with the following warning label printed in letters of sufficient size and contrast to be readily visible and legible:

Caution
Contains Asbestos Fibers
Avoid Breathing Dust
Breathing Asbestos Dust May Cause Asbestosis and Cancer

All asbestos waste shall be disposed of in accordance with the OSHA asbestos regulation, 29 CFR 1910.1001(h). During removal of vacuum bags, an approved respirator, as described in (2) above, shall be worn.

6. All floor cleaning in areas where brakes and clutches are repaired shall be done with the high efficiency industrial vacuum cleaner as described in (3) above. Grinding (arcing) machines shall also be cleaned with such a vacuum cleaner and any remaining dust wiped with a damp cloth. An approved respirator, as described in (2) above, shall be used during this cleaning.
7. Although adherence to the above procedures should minimize any contamination of work clothing, it is required that the appropriate portions of the OSHA regulations on asbestos (29 CFR 1910.1001(d) (3 and 4)) concerning special clothing, change rooms, etc. be followed.

NOTE: Strict adherence to the above procedures should minimize exposures to mechanics during brake and clutch servicing. These are interim recommendations and are subject to revision pending results of ongoing NIOSH research.

- * Section 1910.1001 of the Code of Federal Regulations was formerly Section 1910.93a. This change was noted in the Federal Register, May 28, 1975.

Prepared By
Division of Field Studies and Clinical Investigations
National Institute for Occupational Safety and Health
Cincinnati, Ohio

6

001688

air, as determined by the method prescribed in paragraph (d) of this section.

(c) *Methods of compliance.*—(i) *Engineering methods.* (1) *Engineering controls.* Engineering controls, such as, but not limited to, isolation, enclosure, exhaust ventilation, and dust collection, shall be used to meet the exposure limits prescribed in paragraph (b) of this section.

(ii) *Local exhaust ventilation.* (a) Local exhaust ventilation and dust collection systems shall be designed, constructed, installed, and maintained in accordance with the American National Standard Fundamentals Governing the Design and Operation of Local Exhaust Systems, ANSI Z9.2-1971, which is incorporated by reference herein.

(b) See § 1910.6 concerning the availability of ANSI Z9.2-1971 and the maintenance of a historic file in connection therewith. The address of the American National Standards Institute is given in § 1910.100.

(iii) *Particular tools.* All hand-operated and power-operated tools which may produce or release asbestos fibers in excess of the exposure limits prescribed in paragraph (b) of this section, such as, but not limited to, saws, scrapers, abrasive wheels, and drills, shall be provided with local exhaust ventilation systems in accordance with subdivision (ii) of this subparagraph.

(2) *Work practices.*—(i) *Work methods.* Insofar as practicable, asbestos shall be handled, mixed, applied, removed, cut, scored, or otherwise worked in a way so as to prevent the emission of airborne fibers in excess of the exposure limits prescribed in paragraph (b) of this section, unless the usefulness of the product would be diminished thereby.

(ii) *Particular products and operations.* No asbestos cement, mortar, coating, grout, plaster, or similar material containing asbestos shall be removed from bags, cartons, or other containers in which they are shipped, without being either wetted, or enclosed, or ventilated so as to prevent effectively the release of airborne asbestos fibers in excess of the limits prescribed in paragraph (b) of this section.

(iii) *Spraying, demolition, or removal.* Employees engaged in the spraying of asbestos, the removal, or demolition of pipes, structures, or equipment covered or insulated with asbestos, and in the removal or demolition of asbestos insulation or coverings shall be provided with respiratory equipment in accordance with paragraph (d) (2)(iii) of this section and with special clothing in accordance with paragraph (d) (3) of this section.

(d) *Personal protective equipment.*—(1) Compliance with the exposure limits prescribed by paragraph (b) of this section may not be achieved by the use of respirators or suit rotation of employees, except:

(2) During the time period necessary to install the engineering controls and to institute the work practices required by paragraph (c) of this section:

§ 1910.93. Asbestos.

(a) *Definitions.* For the purpose of this section, (1) "Asbestos" includes chrysotile, amosite, crocidolite, tremolite, anthophyllite, and actinolite.

(2) "Asbestos fibers" means asbestos fibers longer than 5 micrometers.

(b) *Permissible exposure to airborne concentrations of asbestos fibers.*—(1) *Standard effective July 7, 1972.* The 8-hour time-weighted average airborne concentrations of asbestos fibers to which any employee may be exposed shall not exceed five fibers, longer than 5 micrometers, per cubic centimeter of air, as determined by the method prescribed in paragraph (e) of this section.

(2) *Standard effective July 1, 1976.* The 8-hour time-weighted average airborne concentrations of asbestos fibers to which any employee may be exposed shall not exceed two fibers, longer than 5 micrometers, per cubic centimeter of air, as determined by the method prescribed in paragraph (e) of this section.

(3) *Ceiling concentration.* No employee shall be exposed at any time to airborne concentrations of asbestos fibers in excess of 10 fibers, longer than 5 micrometers, per cubic centimeter of

RULES AND REGULATIONS

(ii) In work situations in which the methods prescribed in paragraph (c) of this section are either technically not feasible or feasible to an extent insufficient to reduce the airborne concentrations of asbestos fibers below the limits prescribed by paragraph (b) of this section; or

(iii) In emergencies.

(iv) Where both respirators and personnel rotation are allowed by subdivisions (i), (ii), or (iii) of this subparagraph, and both are practicable, personnel rotation shall be preferred and used.

(2) Where a respirator is permitted by subparagraph (1) of this paragraph, it shall be selected from among those approved by the Bureau of Mines, Department of the Interior, or the National Institute for Occupational Safety and Health, Department of Health, Education, and Welfare, under the provisions of 30 CFR Part 11 (37 F.R. 6244, Mar. 25, 1972) and shall be used in accordance with subdivisions (i), (ii), (iii), and (iv) of this subparagraph.

(i) **Air purifying respirators.** A reusable or single use air purifying respirator, or a respirator described in subdivision (ii) or (iii) of this subparagraph, shall be used to reduce the concentrations of airborne asbestos fibers in the respirator below the exposure limits prescribed in paragraph (b) of this section, when the ceiling or the 8-hour time-weighted average airborne concentrations of asbestos fibers are reasonably expected to exceed no more than 10 times those limits.

(ii) **Powered air purifying respirators.** A full facepiece powered air purifying respirator, or a powered air purifying respirator, or a respirator described in subdivision (i) of this subparagraph, shall be used to reduce the concentrations of airborne asbestos fibers in the respirator below the exposure limits prescribed in paragraph (b) of this section, when the ceiling or the 8-hour time-weighted average concentrations of asbestos fibers are reasonably expected to exceed 10 times, but not 100 times, those limits.

(iii) **Type "C" supplied-air respirators, continuous flow or pressure-demand class.** A type "C" continuous flow or pressure-demand, supplied-air respirator shall be used to reduce the concentrations of airborne asbestos fibers in the respirator below the exposure limits prescribed in paragraph (b) of this section, when the ceiling or the 8-hour time-weighted average airborne concentrations of asbestos fibers are reasonably expected to exceed 100 times those limits.

(iv) **Establishment of a respirator program.** (a) The employer shall establish a respirator program in accordance with the requirements of the American National Standards Practices for Respiratory Protection, ANSI Z89.2-1959, which is incorporated by reference herein.

(b) See § 1910.6 concerning the availability of ANSI Z89.2-1969 and the maintenance of an historic file in connection therewith. The address of the American National Standards Institute is given in 1910.100.

(c) No employee shall be assigned to tasks requiring the use of respirators if, based upon his most recent examination, an examining physician determines that the employee will be unable to function normally wearing a respirator, or that the safety or health of the employee or other employees will be impaired by his use of a respirator. Such employees shall be rotated to another job or given the opportunity to transfer to a different position whose duties he is able to perform with the same employer, in the same geographical area and with the same seniority, status, and rate of pay he had just prior to such transfer, if such a different position is available.

(3) **Special clothing.** The employer shall provide, and require the use of, special clothing, such as coveralls or similar whole body clothing, head coverings, gloves, and foot coverings for any employee exposed to airborne concentrations of asbestos fibers, which exceed the ceiling level prescribed in paragraph (b) of this section.

(4) **Change rooms.** (i) At any fixed place of employment exposed to airborne concentrations of asbestos fibers in excess of the exposure limits prescribed in paragraph (b) of this section, the employer shall provide change rooms for employees working regularly at the place.

(ii) **Clothes lockers.** The employer shall provide two separate lockers or containers for each employee, so separated or isolated as to prevent contamination of the employee's street clothes from his work clothes.

(iii) **Laundrying.** (a) Laundrying of asbestos contaminated clothing shall be done so as to prevent the release of airborne asbestos fibers in excess of the exposure limits prescribed in paragraph (b) of this section.

(b) Any employer who gives asbestos-contaminated clothing to another person for laundering shall inform such person of the requirement in (c) of this subdivision to effectively prevent the release of airborne asbestos fibers in excess of the exposure limits prescribed in paragraph (b) of this section.

(c) Contaminated clothing shall be transported in sealed impermeable bags, or other closed, impermeable containers, and labeled in accordance with paragraph (g) of this section.

(d) **Method of measurement.** All determinations of airborne concentrations of asbestos fibers shall be made by the membrane filter method at 400-450 X (magnification) (4 millimeter objective) with phase contrast illumination.

(i) **Monitoring.**—(1) **Initial determinations.** Within 6 months of the publication of this section, every employer shall cause every place of employment where asbestos fibers are released to be monitored in such a way as to determine whether every employee's exposure to asbestos fibers is below the limits prescribed in paragraph (b) of this section. If the limits are exceeded, the employer shall immediately undertake a compliance program in accordance with paragraph (c) of this section.

(2) **Personal monitoring.**—(i) Samples shall be collected from within the breathing zone of the employees, on membrane filters of 0.8 micrometer porosity mounted in an open-face filter holder. Samples shall be taken for the determination of the 8-hour time-weighted average airborne concentrations and of the ceiling concentrations of asbestos fibers.

(ii) **Sampling frequency and patterns.** After the initial determinations required by subparagraph (1) of this paragraph, samples shall be of such frequency and pattern as to represent with reasonable accuracy the levels of exposure of employees. In no case shall the sampling be done at intervals greater than 6 months for employees whose exposure to asbestos may reasonably be foreseen to exceed the limits prescribed by paragraph (b) of this section.

(3) **Environmental monitoring.**—(i) Samples shall be collected from areas of a work environment which are representative of the airborne concentrations of asbestos fibers which may reach the breathing zone of employees. Samples shall be collected on a membrane filter of 0.8 micrometer porosity mounted in an open-face filter holder. Samples shall be taken for the determination of the 8-hour time-weighted average airborne concentrations and of the ceiling concentrations of asbestos fibers.

(ii) **Sampling frequency and patterns.** After the initial determinations required by subparagraph (1) of this paragraph, samples shall be of such frequency and pattern as to represent with reasonable accuracy the levels of exposure of the employees. In no case shall sampling be at intervals greater than 6 months for employees whose exposures to asbestos may reasonably be foreseen to exceed the exposure limits prescribed in paragraph (b) of this section.

(4) **Employee observation of monitoring.** Affected employees, or their representatives, shall be given a reasonable opportunity to observe any monitoring required by this paragraph and shall have access to the records thereof.

(c) **Caution signs and labels.** (1) **Caution signs.** (i) **Posting.** Caution signs shall be provided and displayed at each location where airborne concentrations of asbestos fibers may be in excess of the exposure limits prescribed in paragraph (b) of this section. Signs shall be posted at such a distance from such a location so that an employee may read the signs and take necessary protective steps before entering the area marked by the signs. Signs shall be posted at all approaches to areas containing excessive concentrations of airborne asbestos fibers.

(ii) **Sign specifications.** The warning signs required by subdivision (1) of this subparagraph shall conform to the requirements of 20" x 24" vertical format signs specified in § 1910.145(d)(4), and to this subdivision. The signs shall display the following legend in the lower panel, with letter sizes and styles of a visibility at least equal to that specified in this subdivision.

Legend	Notation
Asbestos.....	1" Sans Serif, Gothic or Block.
Dust Hazard.....	½" Sans Serif, Gothic or Block.
Avoid Breathing Dust... Wear Assigned Protective Equipment.	¼" Gothic.
Do Not Remain In Area Unless Your Work Requires It.	¼" Gothic.
Breathing Asbestos Dust May Be Hazardous To Your Health.	14 point Gothic.

Spacing between lines shall be at least equal to the height of the upper of any two lines.

(2) **Caution labels.**—(i) **Labeling.** Caution labels shall be affixed to all raw materials, mixtures, scrap, waste, debris, and other products containing asbestos fibers, or to their containers, except that no label is required where asbestos fibers have been modified by a bonding agent, coating, binder, or other material so that during any reasonably foreseeable use, handling, storage, disposal, processing, or transportation, no airborne concentrations of asbestos fibers in excess of the exposure limits prescribed in paragraph (b) of this section will be released.

(ii) **Label specifications.** The caution labels required by subdivision (i) of this subparagraph shall be printed in letters of sufficient size and contrast as to be readily visible and legible. The label shall state:

CAUTION
Contains Asbestos Fibers
Avoid Creating Dust
Breathing Asbestos Dust May Cause
Serious Bodily Harm

(b) **Housekeeping.**—(1) **Cleaning.** All external surfaces in any place of employment shall be maintained free of accumulations of asbestos fibers if, with their dispersion, there would be an excessive concentration.

(2) **Waste disposal.** Asbestos waste, scrap, debris, bags, containers, equipment, and asbestos-contaminated clothing, consigned for disposal, which may produce in any reasonably foreseeable use, handling, storage, processing, disposal, or transportation airborne concentrations of asbestos fibers in excess of the exposure limits prescribed in paragraph (b) of this section shall be collected and disposed of in sealed impermeable bags, or other closed, impermeable containers.

(i) **Recordkeeping.**—(1) **Exposure records.** Every employer shall maintain records of any personal or environmental monitoring required by this section. Records shall be maintained for a period of at least 3 years and shall be made available upon request to the Assistant Secretary of Labor for Occupational Safety and Health, the Director of the National Institute for Occupational Safety and Health, and to authorized representatives of either.

(2) **Employee access.** Every employee and former employee shall have reasonable access to any record required to be maintained by subparagraph (1) of this

paragraph, which indicates the employee's own exposure to asbestos fibers.

(3) **Employee notification.** Any employee found to have been exposed at any time to airborne concentrations of asbestos fibers in excess of the limits prescribed in paragraph (b) of this section shall be notified in writing of the exposure as soon as practicable but not later than 5 days of the finding. The employee shall also be timely notified of the corrective action being taken.

(i) **Medical examinations.**—(1) **General.** The employer shall provide or make available at his cost, medical examinations relative to exposure to asbestos required by this paragraph.

(2) **Preplacement.** The employer shall provide or make available to each of his employees, within 30 calendar days following his first employment in an occupation exposed to airborne concentrations of asbestos fibers, a comprehensive medical examination, which shall include, as a minimum, a chest roentgenogram (posterior-anterior 14 x 17 inches), a history to elicit symptomatology of respiratory disease, and pulmonary function tests to include forced vital capacity (FVC) and forced expiratory volume at 1 second (FEV_{1.0}).

(3) **Annual examinations.** On or before January 31, 1973, and at least annually thereafter, every employer shall provide, or make available, comprehensive medical examinations to each of his employees engaged in occupations exposed to airborne concentrations of asbestos fibers. Such annual examination shall include, as a minimum, a chest roentgenogram (posterior-anterior 14 x 17 inches), a history to elicit symptomatology of respiratory disease, and pulmonary function tests to include forced vital capacity (FVC) and forced expiratory volume at 1 second (FEV_{1.0}).

(4) **Termination of employment.** The employer shall provide, or make available, within 30 calendar days before or after the termination of employment of any employee engaged in an occupation exposed to airborne concentrations of asbestos fibers, a comprehensive medical examination which shall include, as a minimum, a chest roentgenogram (posterior-anterior 14 x 17 inches), a history to elicit symptomatology of respiratory disease, and pulmonary function tests to include forced vital capacity (FVC) and forced expiratory volume at 1 second (FEV_{1.0}).

(5) **Recent examinations.** No medical examination is required of any employee, if adequate records show that the employee has been examined in accordance with this paragraph within the past 1-year period.

(6) **Medical records.**—(1) **Maintenance.** Employers of employees examined pursuant to this paragraph shall cause to be maintained complete and accurate records of all such medical examinations. Records shall be retained by employers for at least 20 years.

(ii) **Access.** The contents of the records of the medical examinations required by this paragraph shall be made available, for inspection and copying,

to the Assistant Secretary of Labor for Occupational Safety and Health, the Director of NIOSH, to authorized physicians and medical consultants of either of them, and, upon the request of an employee or former employee, to his physician. Any physician who conducts a medical examination required by this paragraph shall furnish to the employer of the examined employee all the information specifically required by this paragraph, and any other medical information related to occupational exposure to asbestos fibers.

CURRENT 5

ASBESTOS

ASBESTOS EXPOSURE DURING SERVICING OF MOTOR VEHICLE BRAKE AND CLUTCH ASSEMBLIES

August 8, 1975

TABLE OF CONTENTS

J. William Lloyd Correspondence

Exposure Estimates

Recommended Procedures

Notes

References

**DEPARTMENT OF HEALTH, EDUCATION, AND WELFARE
PUBLIC HEALTH SERVICE
CENTER FOR DISEASE CONTROL**

**NATIONAL INSTITUTE FOR OCCUPATIONAL
SAFETY AND HEALTH
5600 FISHERS LANE
ROCKVILLE, MARYLAND 20852**

August 8, 1975

Dear Colleague:



This communication is intended to alert you to recently gathered information indicating a potential health hazard for persons exposed to asbestos during the servicing of motor vehicle brake and clutch assemblies.

On July 21, 1975, the National Institute for Occupational Safety and Health convened a meeting of government and university scientists, industry representatives, and labor union officials to discuss the present state of knowledge with respect to this problem. Data was presented by investigators from the Mount Siani School of Medicine in New York City indicating that workers engaged in the maintenance and repair of automobile and truck brake linings are exposed to potentially hazardous levels of airborne asbestos dust. Specific brake servicing operations studied included blow-out of

automobile drum brake assemblies, grinding of used truck brake linings, and bevelling of new truck brake linings. Average peak asbestos air concentrations for these three activities based on personal samples taken within ten feet of the operator were, respectively, 10.5, 3.75, and 37.3 fibers (>5 microns in length) per ml. An analysis of samples of brake drum dust revealed that almost all of the asbestos fibers found were shorter than 0.4 microns in length.

Previous studies of the extent of asbestos emissions from automobile brake lining wear showed that only a very small fraction of the original asbestos content of the brake lining is found in brake drum dust ¹⁻³. It was presumed that this is due to thermal degradation of the fibers during braking. The present findings indicate that enough asbestos is preserved to produce significant exposures during certain brake servicing procedures.

The full extent of asbestos-related disease in brake servicing personnel is not known at present because this particular occupational group has not been studied systematically up to now. However, a review of the scientific literature on the association between asbestos exposure and mesothelial tumors of the pleura and peritoneum has revealed at least four cases of these rare tumors in persons who were employed in jobs involving automobile brake servicing ⁴⁻⁶.

For your information and guidance, we are enclosing pertinent references, estimates of the population at risk, a NIOSH interim recommendation for brake and clutch servicing procedures, and a copy of the Department of Labor standard covering exposure to asbestos in the work place.

The environmental studies of brake lining servicing operations outlined above together with observations of mesothelial tumors in persons so employed affirms the necessity for instituting and maintaining recommended control measures in this industry so that the health hazards of asbestos are minimized.

[signature]

J. William Lloyd, Sc.D., Director
Office of Occupational Health
Surveillance and Biometrics

**Estimates of the Workforce Potentially Exposed to Asbestos
in the Manufacturing and Servicing of Brake Linings and Clutches**

Auto Mechanics	833,535
Garage Workers	67,679
Manufacture (original and rebuilding)	<u>6,657</u>
	907,871

[Source:] from 1972 Census of Manufacturers, 1972 County Business Patterns, and Census of Population: 1970 Occupation by Industry (all are Department of Commerce, Census Bureau publications)

**Recommended (Interim) Procedures for
Asbestos Brake and Clutch Servicing**

The National Institute for Occupational Safety and Health (NIOSH) has research underway concerning dust exposures during brake and clutch servicing. Due to preliminary data demonstrating significant asbestos exposures during presently used cleaning techniques, NIOSH has reviewed alternate techniques whereby asbestos exposures are reduced. The following are interim procedures recommended by NIOSH to minimize dust exposures.

1. If possible, an area shall be designated for all brake and clutch repairs. Entrances into this area shall be posted with an asbestos exposure warning sign as follows:

**Asbestos
Dust Hazard
Avoid Breathing Dust
Wear Assigned Protective Equipment
Do Not Remain in Area Unless Your Work Requires It
Breathing Asbestos Dust May Cause Asbestosis and Cancer**

2. During brake servicing, an air purifying respirator, either single use or with replaceable particulate filter(s), as approved by the Mining Enforcement and Safety Administration (formerly Bureau of Mines) or NIOSH, shall be worn during all procedures following removal of the wheels including reassembly. During manual clutch servicing, such a respirator shall be worn during removal and cleaning of the clutch, pressure plate and housing assembly and during installation of the new clutch assembly.
3. Dust shall first be cleaned from brake drums, brake backing plates, brake assemblies and clutch assemblies using an industrial type vacuum cleaner equipped with a high efficiency filter system (>99% efficiency for 0.3 μ m diameter aerosols). After vacuum cleaning, any remaining dust shall be removed using a rag soaked in water and wrung until nearly dry. Under no circumstances shall compressed air or dry brushing be used for cleaning.
4. During arcing and riveting operations, an approved respirator, as described in (2) above, shall be worn. Grinding (arc)ing machines shall be provided with local exhaust ventilation such that worker exposures are maintained at least below the 1976 OSHA asbestos standard (29 CFR 1910.1001).^{*} a minimum, the dust bag of the arcing machine shall be removed and replaced with the hose of the high efficiency industrial vacuum described in (3) above.
5. Industrial vacuum cleaner bags containing asbestos dust and cloths used for wiping brake and clutch assemblies shall be sealed in plastic bags and labeled with the following warning label printed in letters, of sufficient size and contrast to be readily visible and legible:

**Caution
Contains Asbestos Fibers
Avoid Breathing Dust**

Breathing Asbestos Dust May Cause Asbestosis and Cancer

All asbestos waste shall be disposed of in accordance with the OSHA asbestos regulation, 29 CFR 1910.1001(h). During removal of vacuum bags, an approved respirator, as described in (2) shall be worn.

6. All floor cleaning in areas where brakes and clutches are repaired shall be done with the high efficiency industrial vacuum cleaner as described in (3) above. Grinding (arcing) machines shall also be cleaned with such a vacuum cleaner and any remaining dust wiped with a damp cloth. An approved respirator, as described in (2) above, shall be used during this cleaning.
7. Although adherence to the above procedures should minimize any contamination of work clothing, it is required that the appropriate portions of the OSHA regulations on asbestos (29 CFR 1910.1001(d) (3 and 4)) concerning special clothing, change rooms, etc. be followed.

NOTE: adherence to the above procedures should minimize exposures to mechanics during brake and clutch servicing. These are interim recommendations and are subject to revision pending results of ongoing NIOSH research.

Prepared By
Division of Field Studies and Clinical Investigations
National Institute for Occupational Safety and Health
Cincinnati, Ohio

Notes

*Section 1910.1001 of the Code of Federal Regulations was formerly Section 1910.93a. This change was noted in the Federal Register, May 28, 1975. [[return to main text](#)]

References

1. Lynch, J.R.: Lining Decomposition Products. J Air Pollution Control Assoc, 18:824-26, 1968
2. Hickish, D.E. and Knight, K.L.: Exposure to Asbestos During Brake Maintenance. Ann Occup Hyg, 13:17-21, 1970
3. Jacko, M.G. and DuCharme, R.T.: Emissions: Measurements from Brake and Clutch Linings from Selected Sources. EPA Report 68-04-0020, 1973
4. Newhouse, M.L. and Thompson, H.: of Pleura and Peritoneum Following Exposure to Asbestos in the London Area. Brit J Ind Med, 22:261-69, 1965
5. McDonald, A.D. et al.: Epidemiology of Primary Malignant Mesothelial Tumors in Canada. Cancer, 26:914-19, 1970

6. Greenberg, M. and Lloyd Davies, T.A.: Mesothelioma Register 1967-1968. Brit J Ind Med, 31:91-104, 1974

Copies of this and other NIOSH documents are available from:

National Institute for Occupational Safety and Health
4676 Columbia Parkway
Cincinnati, OH 45226-1998
FAX (513) 533-8573

For further information about occupational safety and health, call



This page was last updated: 27, 1997

Go back to the NIOSH home page



or to the CDC home page.

