

SEP 29 1982

K21117

3098* LBS.

COMTYP JOB NAME: 01YC016BMA

(DATE)

(LOT)

(EST WT)

BLENDED BACK: CG 01, PQ 98,

(CODE)

(LOT)

(POUNDS)

EQUIP MENT	NAME: MOLYBDATE ORANGE	USE LBS	N-CODE (RMCON)	ACCT LBS
PREP 1	1 WEIGH FOR S 33	90	3-A	90
	2 WEIGH FOR S-41	80	3-A	80
	3 WEIGH IN DRUM FOR S-37	145	32-D	145
	4 WEIGH FOR S-27	250	4-A	250
356 2	5 RUN 25" (451 G) WATER INTO V-356			
	6 TURN ON AGITATOR AND STEAM			
	7 WEIGH AND SIFT IN	270	131-B	270
	8 HEAT TO AND MAINTAIN 60-66* C FOR S 35			
359 3	9 WEIGH IN. OPTR _____, MK <u>57</u> , T- <u>370</u> , <u>33.20</u> %	645	423-D	214
	OPTR _____, MK _____, T- _____, %			
351 4	10 WEIGH IN OPTR _____, MK <u>224</u> , <u>38.72</u> %	2978	10-D	1141
	OPTR _____, MK _____, %			
4	11 RUN IN V-359			
358 5	12 RUN 10" (473 G) WATER INTO V-358			
	13 PUMP V-351 INTO V-358			
	14 ADJ TO 68" (3216 G) AT 67-69*F. RECORD: _____			
	15 STIR 3 MIN. RECORD: <u>68</u> *F & PH <u>10.5</u>			
	16 IF NECESSARY, ADJ TO PH 9.8-9.9 ASSUME 50% RECORD: PH <u>9.9</u> ASSUME 66%	2	7-D 33-D	
	17 RECORD: G/ML <u>1.047</u> (1.044-1.047)			
SV 6	18 RUN 40" (1908 G) WATER INTO V- <u>245</u>			
	19 RUN IN FROM V-354			
	OPTR _____, MK <u>METER</u> , _____*F, _____%	300 gal.	41-D	3647
	OPTR _____, MK _____, _____*F, _____%	683 gal.		
	20 ADJ TO 3148 G AT 67-69*F (64" IN V-240 & V-246; 66" IN V-241, V-242, & V-245)	108		
	21 STIR 3 MIN RECORD: _____*F	2970		2970
	22 RECORD: PH <u>4.5</u> (2.8-3.6)			
	23 ADJ TO PH 3.8-3.9 ASSUME 66% RECORD: PH <u>3.9</u> & VOL <u>66</u> " ASSUME 50%	3	7-D	1
	NOTE: DILUTE N-7-D 10:1 WITH WATER			
	24 RECORD: G/ML <u>1.099</u> (1.098-1.100)			
	25 OBTAIN 1 QT. SAMPLES OF S-17 & S-24 SOLUTIONS & TITRATE TWICE			
	RECORD: LOWEST PH <u>5.07</u> & ML N-10-D <u>8.43</u>			
	LOWEST PH <u>5.03</u> & ML N-10-D <u>8.34</u>			
	NOTIFY SUPV IF ML N-10-D IS NOT IN RANGE 8.0-8.6 OR IF THE TWO TITRATIONS DIFFER BY MORE THAN 0.10 ML N-10-D (IF YES, FLUSH ALL EQUIPMENT & REPEAT TITRATIONS) DO NOT PROCEED IF N-10-D TITRATION IS OUT OF RANGE			

PROCEED TO PAGE 2

EQUIP MENT	PAGE 02 OF 2 CG 01 CODE YC-016-B	USE LBS	N-CODE	ACCT LBS
26	RUN V-358 AT 67-69*F THRU BOTH UNDERSURFACE DISTRIBUTORS INTO SV AT 67-69*F IN 17-19 MIN			
	RECORD: START <u>1:40 PM</u> & TOTAL MIN <u>17</u>			
	NOTE: V-358 STRIKE TIME UP WHEN 1/2 VAT BOTTOM SHOWS MT			
SV 6	27 WHEN S 26 COMPLETED AND BEFORE WASHING IN V-358, DUMP IN N-4-A FROM S-4			
(CONT)	28 RUN IN USING WEIGHT AND FLOW CONTROL PANEL			
	OPTR _____, MK _____, <u>31.01</u> %	<u>71</u>	28-D	22
	OPTR _____, MK _____, _____%		28-D	
	29 DURING S'S 27 AND 28 (IF ALONE, AFTER S'S 27 & 28) WASH IN V-358			
	30 STIR 2 MIN			
	31 RECORD: PH <u>2.3</u> (2.2-2.5) & PB XS _____ (+)			
	32 STIR TOTAL OF 15 MIN FROM COMPLETION OF S 26 RECORD: START <u>1:57 PM</u> TOTAL MIN <u>15</u>			
	33 DUMP IN N-3-A FROM S 1			
	34 STIR 3 MIN			
	35 RUN IN N-131-B FROM S 3 IN 7 MIN			
	36 STIR 3 MIN			
	37 POUR IN N-32-D FROM S-3	<u>225</u>	<u>15-D</u>	
	38 STIR 2 MIN	<u>450</u>	<u>145-D</u>	<u>225</u>
	39 RUN IN USING BADGER METER			
	40 STIR 3 MIN & FLUSH ALUM LINES WITH WATER			
	41 DUMP IN N-3-A FROM S 2			
	42 STIR 3 MIN			
	43 RECORD: PH <u>4.8</u> (5.8-6.0)	<u>40</u>	7-D	<u>20</u>
	44 IF NECESSARY, ADJ TO PH 5.8-6.0 ASSUME 50% RECORD: PH <u>5.95</u> ASSUME 66%		33-D	
	45 DUMP IN THE SUB-STANDARD TO BE BLENDED BACK (IF ANY IS SHOWN ON TOP FRONT OF CARD)			
	46 STIR 20 MINUTES AFTER DUMPING SUB-STANDARD			
	47 FLOOD TO 153" (7298 G) & STOP AGITATOR			
	START <u>10:30 AM</u> FINISH <u>2:45 PM</u> OPTR <u>86-64</u>			

100 #, YE-698-D, E2H08 ✓