

NOTICE: If the film shows signs of wear, it is not to be used. If the film shows signs of wear, it is not to be used.

CONFIDENTIAL

DOCUMENTS PRODUCED
DALLAS COUNTY CASES 3/18/92

Rev C Oct 20, 1971
CORPOND, SEALING, ALUMINUM AND ASBESTOS FILLED
CAUTION: GROUP 2B FLAMMABLE LIQUID. KEEP SPARKS AND FLAMES AWAY.
AVOID PROLONGED BREATHING OF VAPOR. USE WITH ADEQUATE VENTILATION.
AVOID PROLONGED OR REPEATED SKIN CONTACT. SEE SPDS G-8.

SUPPLIERS - Part, Inc. 18400 Syracuse Ave. Cleveland, Ohio 44110
ORDER FROM SUPPLIER AS - Alumilastic "C" Cartridges for cradle
type gun.

WARNING: Permanently mark all containers with Westinghouse
H number.
CHARACTERISTICS - (Dow:DA) Heavily fortified aluminum and
phenolic fiber sealing compound containing treated vegetable oils
and a aliphatic thinner. Resists weather degradation for long
periods. Cures to a tough, resilient compound with excellent
adhesion. Forms a flexible, semi-metallic bright aluminum
surface. Provides effective protection from -40 to 82 C (-40 to
180 F) in moist and dry atmospheres. Has excellent ultra-violet
weather resistance.

APPLICATION - Seals capacitor equipment housings
SPECIFY AS - Specify by P H Spec & Size Code

Example: CORPOND 513280000
Printed in U.S.A. W Corp Spd M3 (Pat. CODE IDENT NO. 79500)

63115034

PLAINTIFF'S
EXHIBIT

WH-100

DOCUMENTS PRODUCED DALLAS COUNTY CASES 3/18/92