

Page
7423
7423
7130
7424
7134
6707
6707
5488
5488
3708
7134
7134

620
220
130
737
17,
20,

134
34
31
60

24
30
19
7,
5
8
0
7
1

Test Procedures

No. 39—Pt. II—1

TUESDAY, FEBRUARY 26, 1974
WASHINGTON, D.C.

Volume 39 ■ Number 39

PART II



ENVIRONMENTAL PROTECTION AGENCY

ASBESTOS MANUFACTURING POINT SOURCE CATEGORY

Effluent Limitations Guidelines

0006347

Title 40—Protection of the Environment
 CHAPTER I—ENVIRONMENTAL
 PROTECTION AGENCY
 SUBCHAPTER N—EFFLUENT GUIDELINES
 AND STANDARDS

PART 427—ASBESTOS MANUFACTURING
 POINT SOURCE CATEGORY

On October 30, 1973, notice was published in the FEDERAL REGISTER, (38 FR 22606) that the Environmental Protection Agency (EPA or Agency) was proposing effluent limitations guidelines for existing sources and standards of performance and pretreatment standards for new sources within the asbestos-cement pipe, asbestos-cement sheet, asbestos paper (starch binder), asbestos paper (elastomeric binder), asbestos millboard, asbestos roofing products, and asbestos floor tile subcategories of the asbestos manufacturing category of point sources.

The purpose of this notice is to establish final effluent limitations guidelines for existing sources and standards of performance and pretreatment standards for new sources in the asbestos manufacturing category of point sources, by amending 40 CFR Chapter I, Subchapter N, to add a new Part 427. This final rulemaking is promulgated pursuant to sections 301, 304 (b) and (c), 306 (b) and (c) and 307(c) of the Federal Water Pollution Control Act, as amended, (the Act); 33 U.S.C. 1251, 1311, 1314 (b) and (c), 1316 (b) and (c), and 1317(c); 86 Stat. 816 et seq.; Pub. L. 92-500. Regulations regarding cooling water intake structures for all categories of point sources under section 316(b) of the Act will be promulgated in 40 CFR 402.

In addition, the EPA is simultaneously proposing a separate provision which appears in the proposed rules section of the FEDERAL REGISTER, stating the application of the limitations and standards set forth below to users of publicly owned treatment works which are subject to pretreatment standards under section 307(b) of the Act. The basis of that proposed regulation is set forth in the associated notice of proposed rulemaking.

The legal basis, methodology and factual conclusions which support promulgation of this regulation were set forth in substantial detail in the notice of public review procedures published August 6, 1973 (38 FR 21202) and in the notice of proposed rulemaking for the asbestos-cement pipe, asbestos-cement sheet, asbestos paper (starch binder), asbestos paper (elastomeric binder), asbestos millboard, asbestos roofing products, and asbestos floor tile subcategories. In addition, the regulations as proposed were supported by two other documents: (1) the document entitled "Development Document for Proposed Effluent Limitations Guidelines and New Source Performance Standards for the Building, Construction and Paper Segment of the Asbestos Manufacturing Point Source Category" (October 1973), and (2) the document entitled "Economic Analysis of Proposed Effluent Guidelines, the As-

bestos Products Manufacturing Industry (September 1973). Both of these documents were made available to the public and circulated to interested persons at approximately the time of publication of the notice of proposed rulemaking.

Interested persons were invited to participate in the rulemaking by submitting written comments within 30 days from the date of publication. Prior public participation in the form of solicited comments and responses from the States, Federal agencies, and other interested parties were described in the preamble to the proposed regulation. The EPA has considered carefully all of the comments received and a discussion of these comments with the Agency's response there-to follows in this document.

(a) *Summary of comments.* The following responded to the request for comments which was made in the preamble to the proposed regulation: Colorado Dept. of Public Health, Michigan Dept. of Natural Resources, Center for Science in the Public Interest, the Mead Corporation, Armstrong Cork Company, Dept. of Health, Education and Welfare, County Sanitation Districts of Los Angeles County, Johns-Manville Corporation, the Flintkote Company, and the Effluent Standards and Water Quality Information Advisory Committee.

Each of the comments received was carefully reviewed and analyzed. The following is a summary of the significant comments and EPA's response to those comments.

(1) A commenter was concerned that the limitations could be interpreted as gross values without consideration of pollutants in incoming waters. This comment applies in general to BOD₅ and COD limitations for most of the subcategories.

The limitations on BOD and COD have been reevaluated. The above comment is significant in all subcategories with a BOD or COD limitation. In the asbestos-cement pipe and asbestos-cement sheet subcategories, the small quantities of BOD added by the process do not warrant a limitation. In the paper subcategories, BOD is incidentally removed by the best practicable control technology currently available (sedimentation). If the suspended solids are controlled to the extent required by the limitations, BOD concentrations will also be reduced. Therefore, the BOD₅ limitation has been eliminated from these subcategories. In the roofing and floor tile subcategories, COD must be retained as a significant control parameter. The raw water entering the processes may contain significant amounts of COD. It is the intent of the Agency that the limitations in these subcategories be considered as net values over water entering the process. This is accomplished by the special definition for COD in the roofing and floor tile subcategories.

(2) Comments were received objecting to the use of the BOD₅ parameter when COD and/or TOC would be a more accurate measure of the organic matter in waste waters from this industry.

EPA agrees with this comment, however, BOD₅ is being dropped as a control parameter for the reasons cited in the above comment.

(3) One commenter pointed out ambiguous statements in the Development Document and the preamble to the proposed regulation where the asbestos content of suspended solids was discussed. On the one hand, the documents claim asbestos may be a large percentage of the suspended solids, and then state that in general this percentage is small.

It is acknowledged that an erroneous conclusion could have been drawn that all subcategories produce suspended solids in process waste waters with a large percentage of asbestos fibers. This conclusion is true in only five of the identified subcategories. In the roofing and floor tile subcategories, suspended solids contain little, if any, asbestos fibers.

(4) One comment stated that asbestos-cement pipe plants should have a no discharge requirement for 1977, since some multi-product plants making asbestos-cement pipe already have no discharge. Allowing pipe plants to have a discharge will encourage the construction of single product, asbestos-cement pipe plants.

EPA has determined that the technology is not available to allow the setting of a no discharge limitation for 1977 or for new sources in the asbestos-cement pipe subcategory. However, there are many incentives for the construction of multiproduct plants. These incentives include substantial savings from decreased water consumption, raw water and waste water treatment, land use, and monitoring requirements. Such built in incentives will not be ignored by industry.

(5) Another comment argued that the existence of one or two plants in a subcategory with no discharge was sufficient basis to set a no discharge limitation for that subcategory. A specific case mentioned was the asbestos paper (starch binder) subcategory.

The experience at the one plant which is apparently achieving no discharge has not been sufficiently documented or been continuous for a substantial period of time to justify applying the technology to all other plants in this subcategory by 1977 accordingly, it is the opinion of EPA that this technology would not qualify as best practicable control technology currently available as defined by the Act.

(6) A question was raised during the comment period concerning the application of best available technology economically achievable to some of the new source performance standards. The commenter claimed that new plants should use best practicable control technology currently available.

In the case of the asbestos paper, asbestos-cement sheet, and asbestos roofing subcategories, the technology does exist for total recycle as proven by a few plants in each subcategory. As mentioned in the previous comment, these few plants were not sufficient to set a no discharge using

best practicable control technology currently available as defined by the Act. A more stringent limitation for new sources is deemed feasible since they have additional flexibilities to optimize in-process controls and end-of-line pollution control measures.

(7) A question was raised with respect to the logic for different ratios of daily to monthly limitations employed in the various subcategories.

These numbers were based on the data available on raw waste loads and treatment efficiencies, and the fluctuations normally experienced in each subcategory. The manufacturing of asbestos-cement products produced greater fluctuations in raw loads than the other subcategories. The regulations therefore reflect this finding, the ratio of daily maximum to monthly average limitations are higher for the asbestos-cement pipe and asbestos-cement sheet subcategories than the other subcategories with allowable discharges.

(b) *Revisions of the proposed regulations prior to promulgation.* As a result of public comments, continuing review and evaluation of the proposed regulation by EPA, the following changes have been made in the regulation.

(1) Sections 427.21, 427.31, 427.41, 427.51, 427.61, and 427.71 entitled "Specialized Definitions" now include references to general definitions and methods of analysis in 40 CFR 401 which reduces the need for some specialized definitions in this regulation.

(2) The BOD5 limitations in the asbestos-cement pipe, asbestos-cement sheet, asbestos paper (starch binder) and asbestos paper (elastomeric binder) subcategories have been eliminated. In the asbestos-cement subcategories, the low levels of BOD5 do not warrant a limitation. The incoming water often contains equal or greater amounts of BOD5 than the limitations. In the paper subcategories, the BOD5 is present as starch which is removed by settling. The efficiency of treatment is more accurately measured by the suspended solids parameter.

(3) The COD limitations in the roofing and floor tile subcategories have been retained. However, these limitations can not be used as gross figures due to the presence of relatively high COD values in incoming waters. The regulations as promulgated for these subcategories define COD as the COD added to the process waste waters.

(4) The preamble to the proposed regulations recommended that solid wastes from all subcategories should be disposed of so as to prevent horizontal or vertical migration of asbestos fibers. As explained above in the comment section, not all subcategories produce a solid waste with a significant amount of asbestos fibers. Therefore, in the preamble to the proposed regulation, the discussion of solid waste control in the "Non-water Quality Aspects" section should not be considered to be applicable to solid waste generated by the waste water treatment processes from the roofing and floor tile subcategories.

(5) Section 304(b)(1)(B) of the Act provides for "guidelines" to implement the uniform national standards of section 301(b)(1)(A). Thus Congress recognized that some flexibility was necessary in order to take into account the complexity of the industrial world with respect to the practicability of pollution control technology. In conformity with the Congressional intent and in recognition of the possible failure of these regulations to account for all factors bearing on the practicability of control technology, it was concluded that some provision was needed to authorize flexibility in the strict application of the limitations contained in the regulation where required by special circumstances applicable to individual dischargers. Accordingly, a provision allowing flexibility in the application of the limitations representing best practicable control technology currently available has been added to each subpart, to account for special circumstances that may not have been adequately accounted for when these regulations were developed.

(c) *Economic impact.* The changes to the regulations mentioned above will not affect the results of the economic analysis prepared for the proposed regulation.

(d) *Cost-benefit analysis.* The detrimental effects of the constituents of waste waters now discharged by point sources within the building, construction and paper segment of the asbestos manufacturing point source category are discussed in Section VI of the report entitled "Development Document for Effluent Limitations Guidelines for the Building, Construction and Paper Segment of the Asbestos Manufacturing Point Source Category" (February 1974). It is not feasible to quantify in economic terms, particularly on a national basis, the costs resulting from the discharge of these pollutants to our Nation's waterways. Nevertheless, as indicated in Section VI, the pollutants discharged have substantial and damaging impacts on the quality of water and therefore on its capacity to support healthy populations of wildlife, fish and other aquatic wildlife and on its suitability for industrial, recreational and drinking water supply uses.

The total cost of implementing the effluent limitations guidelines includes the direct capital and operating costs of the pollution control technology employed to achieve compliance and the indirect economic and environmental costs identified in Section VIII and in the supplementary report entitled "Economic Analysis of Proposed Effluent Guidelines the Asbestos Products Manufacturing Industry" (September 1973). Implementing the effluent limitations guidelines will substantially reduce the environmental harm which would otherwise be attributable to the continued discharge of polluted waste waters from existing and newly constructed plants in the asbestos manufacturing industry. The Agency believes that the benefits of thus reducing the pollutants discharged justify the associated costs which, though substantial in absolute terms,

represent a relatively small percentage of the total capital investment in the industry.

(e) *Solid waste control.* Solid waste control must be considered. The waterborne wastes from the asbestos industry may contain a considerable volume of asbestos particles as a part of the suspended solids pollutant. Best practicable control technology and best available control technology as they are known today, require disposal of the pollutants control technology as they are known removed from waste waters in this industry in the form of solid wastes and liquid concentrates. In some cases these are nonhazardous substances requiring only minimal custodial care. However, some constituents may be hazardous and may require special consideration. In order to ensure long term protection of the environment from these hazardous or harmful constituents, special consideration of disposal sites must be made. All landfill sites where such hazardous wastes are disposed should be selected so as to prevent horizontal and vertical migration of these contaminants to ground or surface waters. In cases where geologic conditions may not reasonably ensure this, adequate precautions (e.g., impervious liners) should be taken to ensure long term protection to the environment from hazardous materials. Where appropriate the location of solid hazardous materials disposal sites should be permanently recorded in the appropriate office of the legal jurisdiction in which the site is located.

(f) *Publication of information on processes, procedures, or operating methods which result in the elimination or reduction of the discharge of pollutants.* In conformance with the requirements of section 304(c), a manual entitled, "Development Document for Effluent Limitations Guidelines and New Source Performance Standards for the Building, Construction and Paper Segment of the Asbestos Manufacturing Point Source Category," has been published and is available for purchase from the Government Printing Office, Washington, D.C. 20401, for a nominal fee.

(g) *Final rulemaking.* In consideration of the foregoing, 40 CFR Chapter I, Subchapter N is hereby amended by adding a new Part 427, Asbestos Manufacturing Point Source Category, to read as set forth below. This final regulation is promulgated as set forth below and shall be effective April 29, 1974.

Dated: February 15, 1974.

JOHN QUARLES,
Acting Administrator.

PART 427—ASBESTOS MANUFACTURING POINT SOURCE CATEGORY

Subpart A—Asbestos-Cement Pipe Subcategory

- Sec.
- 427.10 Applicability; description of the asbestos-cement pipe subcategory.
- 427.11 Specialized definitions.
- 427.12 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

- Sec. 427.13 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.
- 427.14 [Reserved]
- 427.15 Standards of performance for new sources.
- 427.16 Pretreatment standards for new sources.
- Subpart B—Asbestos-Cement Sheet Subcategory**
- 427.20 Applicability; description of the asbestos-cement sheet subcategory.
- 427.21 Specialized definitions.
- 427.22 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 427.23 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.
- 427.24 [Reserved]
- 427.25 Standards of performance for new sources.
- 427.26 Pretreatment standards for new sources.
- Subpart C—Asbestos Paper (Starch Binder) Subcategory**
- 427.30 Applicability; description of the asbestos paper (starch binder) subcategory.
- 427.31 Specialized definitions.
- 427.32 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 427.33 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.
- 427.34 [Reserved]
- 427.35 Standards of performance for new sources.
- 427.36 Pretreatment standards for new sources.
- Subpart D—Asbestos Paper (Elastomeric Binder) Subcategory**
- 427.40 Applicability; description of the asbestos paper (elastomeric binder) subcategory.
- 427.41 Specialized definitions.
- 427.42 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 427.43 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.
- 427.44 [Reserved]
- 427.45 Standards of performance for new sources.
- 427.46 Pretreatment standards for new sources.
- Subpart E—Asbestos Millboard Subcategory**
- 427.50 Applicability; description of the asbestos millboard subcategory.
- 427.51 Specialized definitions.
- 427.52 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 427.53 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.

- Sec. 427.54 Reserved.
- 427.55 Standards of performance for new sources.
- 427.56 Pretreatment standards for new sources.

Subpart F—Asbestos Roofing Subcategory

- 427.60 Applicability; description of the asbestos roofing products subcategory.
- 427.61 Specialized definitions.
- 427.62 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 427.63 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.
- 427.64 [Reserved]
- 427.65 Standards of performance for new sources.
- 427.66 Pretreatment standards for new sources.

Subpart G—Asbestos Floor Tile Subcategory

- 427.70 Applicability; description of the asbestos floor tile subcategory.
- 427.71 Specialized definitions.
- 427.72 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 427.73 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.
- 427.74 [Reserved]
- 427.75 Standards of performance for new sources.
- 427.76 Pretreatment standards for new sources.

Subpart A—Asbestos-Cement Pipe Subcategory

- § 427.10 Applicability; description of the asbestos-cement pipe subcategory.

The provisions of this subpart are applicable to discharges resulting from the process in which asbestos, Portland cement, silica and other ingredients are used in the manufacturing of asbestos-cement pipe.

§ 427.11 Specialized definitions.

For the purpose of this subpart: (a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in 40 CFR 401 shall apply to this subpart.

§ 427.12 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

(a) In establishing the limitations set forth in this section, EPA took into account all information it was able to collect, develop and solicit with respect to factors (such as age and size of plant, raw materials, manufacturing processes, products produced, treatment technology available, energy requirements and costs) which can affect the industry subcategory and effluent levels established. It is, however, possible that data which would affect these limitations have not been available and, as a result, these

limitations should be adjusted for certain plants in this industry. An individual discharger or other interested person may submit evidence to the Regional Administrator (or to the State, if the State has the authority to issue NPDES permits) that factors relating to the equipment or facilities involved, the process applied, or other such factors related to such discharger are fundamentally different from the factors considered in the establishment of the guidelines. On the basis of such evidence or other available information, the Regional Administrator (or the State) will make a written finding that such factors are or are not fundamentally different for that facility compared to those specified in the Development Document. If such fundamentally different factors are found to exist, the Regional Administrator or the State shall establish for the discharger effluent limitations in the NPDES permit either more or less stringent than the limitations established herein, to the extent dictated by such fundamentally different factors. Such limitations must be approved by the Administrator of the Environmental Protection Agency. The Administrator may approve or disapprove such limitations, specify other limitations, or initiate proceedings to revise these regulations.

(b) The following limitations establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a point source subject to the provisions of this subpart after application of the best practicable control technology currently available:

Effluent characteristic	Effluent Limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not exceed—
Metric units (mg/kg of product)		
TSS.....	0.57	0.19
pH.....	Within the range 6.0 to 9.0	
English units (lb/ton of product)		
TSS.....	1.14	0.38
pH.....	Within the range 6.0 to 9.0	

§ 427.13 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.

The following limitations establish the quantity or quality of pollutants or pollutant properties which may be discharged by a point source subject to the provisions of this subpart after application of the best available technology economically achievable: there shall be no discharge of process waste water pollutants to navigable waters.

§ 427.14 [Reserved]

§ 427.15 Standards of performance for new sources.

The following standards of performance establish the quantity or quality of

pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

Effluent characteristic	Effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not exceed—
Metric units (kg/kg of product)		
TSS.....	0.5%	0.19
pH.....	Within the range 6.0 to 9.0.	
English units (lb/ton of product)		
TSS.....	1.1	0.39
pH.....	Within the range 6.0 to 9.0.	

§ 427.16 Pretreatment standards for new sources.

The pretreatment standards under section 307(c) of the Act for a source within the asbestos-cement pipe subcategory, which is a user of a publicly owned treatment works (and which would be a new source subject to section 306 of the Act, if it were to discharge pollutants to the navigable waters), shall be the standard set forth in 40 CFR 128, except that, for the purpose of this section, 40 CFR 128.133 shall be amended to read as follows:

In addition to the prohibitions set forth in 40 CFR 128.131, the pretreatment standard for incompatible pollutants introduced into a publicly owned treatment works shall be the standard of performance for new sources specified in 40 CFR 427.15: *Provided*, That, if the publicly owned treatment works which receives the pollutants is committed, in its NPDES permit, to remove a specified percentage of any incompatible pollutant, the pretreatment standard applicable to users of such treatment works shall, except in the case of standards providing for no discharge of pollutants, be correspondingly reduced in stringency for that pollutant.

Subpart B—Asbestos-Cement Sheet Subcategory

§ 427.20 Applicability: description of the asbestos-cement sheet subcategory.

The provisions of this subpart are applicable to discharges resulting from the process in which asbestos, Portland cement, silica, and other ingredients are used in the manufacturing of asbestos-cement sheets. Discharges resulting from manufacture of asbestos-cement sheet laboratory tops are specifically excluded from the provisions of this subpart.

§ 427.21 Specialized definitions.

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in 40 CFR 401 shall apply to this subpart.

§ 427.22 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

(a) In establishing the limitations set forth in this section, EPA took into account all information it was able to col-

lect, develop and solicit with respect to factors (such as age and size of plant, raw materials, manufacturing processes, products produced, treatment technology available, energy requirements and costs) which can affect the industry subcategory and effluent levels established. It is, however, possible that data which would affect these limitations have not been available and, as a result, these limitations should be adjusted for certain plants in this industry. An individual discharger or other interested person may submit evidence to the Regional Administrator (or to the State, if the State has the authority to issue NPDES permits) that factors relating to the equipment or facilities involved, the process applied, or other such factors related to such discharger are fundamentally different from the factors considered in the establishment of the guidelines. On the basis of such evidence or other available information, the Regional Administrator (or the State) will make a written finding that such factors are or are not fundamentally different for that facility compared to those specified in the Development Document. If such fundamentally different factors are found to exist, the Regional Administrator or the State shall establish for the discharger effluent limitations in the NPDES permit either more or less stringent than the limitations established herein, to the extent dictated by such fundamentally different factors. Such limitations must be approved by the Administrator of the Environmental Protection Agency. The Administrator may approve or disapprove such limitations, specify other limitations, or initiate proceedings to revise these regulations.

(b) The following limitations establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a point source subject to the provisions of this subpart after application of the best practicable control technology currently available:

Effluent characteristic	Effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not exceed—
Metric units (kg/kg of product)		
TSS.....	0.65	0.23
pH.....	Within the range 6.0 to 9.0.	
English units (lb/ton of product)		
TSS.....	1.35	0.45
pH.....	Within the range 6.0 to 9.0.	

§ 427.23 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.

The following limitations establish the quantity or quality of pollutants or pollutant properties which may be discharged by a point source subject to the provisions of this subpart after application of the best available technology economically achievable: there shall be no

discharge of process waste water pollutants to navigable waters.

§ 427.24 [Reserved]

§ 427.25 Standards of performance for new sources.

The following standards of performance establish the quantity or quality of pollutants or pollutant properties which may be discharged by a new source subject to the provisions of this subpart: there shall be no discharge of process waste water pollutants to navigable waters.

§ 427.26 Pretreatment standards for new sources.

The pretreatment standards under section 307(c) of the Act for a source within the asbestos-cement sheet subcategory, which is a user of a publicly owned treatment works (and which would be a new source subject to section 306 of the Act, if it were to discharge pollutants to the navigable waters), shall be the standard set forth in 40 CFR 128, except that, for the purpose of this section, 40 CFR 128.133 shall be amended to read as follows:

In addition to the prohibitions set forth in 40 CFR 128.131, the pretreatment standard for incompatible pollutants introduced into a publicly owned treatment works shall be the standard of performance for new sources specified in 40 CFR 427.25: *Provided*, That, if the publicly owned treatment works which receives the pollutants is committed, in its NPDES permit, to remove a specified percentage of any incompatible pollutant, the pretreatment standard applicable to users of such treatment works shall, except in the case of standards providing for no discharge of pollutants, be correspondingly reduced in stringency for that pollutant.

Subpart C—Asbestos Paper (Starch Binder) Subcategory

§ 427.30 Applicability: description of the asbestos paper (starch binder) subcategory.

The provisions of this subpart are applicable to discharges resulting from the process in which asbestos, starch binders and other ingredients are used in the manufacture of asbestos paper (starch binder).

§ 427.31 Specialized definitions.

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in 40 CFR Part 401 shall apply to this subpart.

§ 427.32 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

(a) In establishing the limitations set forth in this section, EPA took into account all information it was able to collect, develop and solicit with respect to factors (such as age and size of plant, raw materials, manufacturing processes, products produced, treatment technology available, energy requirements and costs) which can affect the industry subcategory and effluent levels established.

It is, however, possible that data which would affect these limitations have not been available and, as a result, those limitations should be adjusted for certain plants in this industry. An individual discharger or other interested person may submit evidence to the Regional Administrator (or to the State, if the State has the authority to issue NPDES permits) that factors relating to the equipment or facilities involved, the process applied, or other such factors related to such discharger are fundamentally different from the factors considered in the establishment of the guidelines. On the basis of such evidence or other available information, the Regional Administrator (or the State) will make a written finding that such factors are or are not fundamentally different for that facility compared to those specified in the Development Document. If such fundamentally different factors are found to exist, the Regional Administrator or the State shall establish for the discharger effluent limitations in the NPDES permit either more or less stringent than the limitations established herein, to the extent dictated by such fundamentally different factors. Such limitations must be approved by the Administrator of the Environmental Protection Agency. The Administrator may approve or disapprove such limitations, specify other limitations, or initiate proceedings to revise these regulations.

(b) The following limitations establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a point source subject to the provisions of this subpart after application of the best practicable control technology currently available:

Effluent characteristic	Effluent Limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not exceed—
Metric units (kg/kg of product)		
TSS.....	0.55	0.35
pH.....	Within the range 6.0 to 9.0	
English units (lb/ton of product)		
TSS.....	1.10	0.70
pH.....	Within the range 6.0 to 9.0	

§ 427.33 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.

The following limitations establish the quantity or quality of pollutants or pollutant properties which may be discharged by point source subject to the provisions of this subpart after application of the best available technology economically achievable: there shall be no discharge of process waste water pollutants to navigable waters.

§ 427.34 [Reserved]

§ 427.35 Standards of performance for new sources.

The following standards of performance establish the quantity or quality of

pollutants or pollutant properties which may be discharged by a new source subject to the provisions of this subpart: there shall be no discharge of process waste water pollutants to navigable waters.

§ 427.36 Pretreatment standards for new sources.

The pretreatment standards under section 307(c) of the Act for a source within the asbestos paper (starch binder) subcategory, which is a user of a publicly owned treatment works (and which would be a new source subject to section 306 of the Act, if it were to discharge pollutants to the navigable waters), shall be the standard set forth in 40 CFR Part 128, except that, for the purpose of this section, 40 CFR 128.133 shall be amended to read as follows:

In addition to the prohibitions set forth in 40 CFR 128.131, the pretreatment standard for incompatible pollutants introduced into a publicly owned treatment works shall be the standard of performance for new sources specified in 40 CFR 427.35; *Provided*, That, if the publicly owned treatment works which receives the pollutants is committed, in its NPDES permit, to remove a specified percentage of any incompatible pollutant, the pretreatment standard applicable to users of such treatment works shall, except in the case of standards providing for no discharge of pollutants, be correspondingly reduced in stringency for that pollutant.

Subpart D—Asbestos Paper (Elastomeric Binder) Subcategory

§ 427.40 Applicability; description of the asbestos paper (elastomeric binder) subcategory.

The provisions of this subpart are applicable to discharges resulting from the process in which asbestos, elastomeric binder, and other ingredients are used in the manufacture of asbestos paper (elastomeric binder).

§ 427.41 Specialized definitions.

For the purpose of this subpart: (a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in 40 CFR 401 shall apply to this subpart.

§ 427.42 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

(a) In establishing the limitations set forth in this section, EPA took into account all information it was able to collect, develop and solicit with respect to factors (such as age and size of plant, raw materials, manufacturing processes, products produced, treatment technology available, energy requirements and costs) which can affect the industry subcategory and effluent levels established. It is, however, possible that data which would affect these limitations have not been available and, as a result, these limitations should be adjusted for certain plants in this industry. An individual discharger or other interested person may submit evidence to the Regional

Administrator (or to the State, if the State has the authority to issue NPDES permits) that factors relating to the equipment or facilities involved, the process applied, or other such factors related to such discharger are fundamentally different from the factors considered in the establishment of the guidelines. On the basis of such evidence or other available information, the Regional Administrator (or the State) will make a written finding that such factors are or are not fundamentally different for that facility compared to those specified in the Development Document. If such fundamentally different factors are found to exist, the Regional Administrator or the State shall establish for the discharger effluent limitations in the NPDES permit either more or less stringent than the limitations established herein, to the extent dictated by such fundamentally different factors. Such limitations must be approved by the Administrator of the Environmental Protection Agency. The Administrator may approve or disapprove such limitations, specify other limitations, or initiate proceedings to revise these regulations.

(b) The following limitations establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a point source subject to the provisions of this subpart after application of the best practicable control technology currently available:

Effluent characteristic	Effluent Limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not exceed—
Metric units (kg/kg of product)		
TSS.....	0.55	0.35
pH.....	Within the range 6.0 to 9.0	
English units (lb/ton of product)		
TSS.....	1.10	0.70
pH.....	Within the range 6.0 to 9.0	

§ 427.43 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.

The following limitations establish the quantity or quality of pollutants or pollutant properties which may be discharged by a point source subject to the provisions of this subpart after application of the best available technology economically achievable: there shall be no discharge of process waste water pollutants to navigable waters.

§ 427.44 [Reserved]

§ 427.45 Standards of performance for new sources.

The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

Effluent characteristics	Effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not exceed
	Metric units (kg/kg of product)	
TSS.....	0.55	0.35
pH.....	Within the range 6.0 to 9.0	
	English units (lb/ton of product)	
TSS.....	1.10	0.70
pH.....	Within the range 6.0 to 9.0	

§ 427.46 Pretreatment standards for new sources.

The pretreatment standards under section 307(c) of the Act for a source within the asbestos paper (elastomeric binder) subcategory, which is a user of a publicly owned treatment works (and which would be a new source subject to section 306 of the Act, if it were to discharge pollutants to the navigable waters), shall be the standard set forth in 40 CFR Part 128, except that, for the purpose of this section, 40 CFR 128.133 shall be amended to read as follows:

In addition to the prohibitions set forth in 40 CFR 128.131, the pretreatment standard for incompatible pollutants introduced into a publicly owned treatment works shall be the standard of performance for new sources specified in 40 CFR 427.48; *Provided*, That, if the publicly owned treatment works which receives the pollutants is committed, in its NPDES permit, to remove a specified percentage of any incompatible pollutant, the pretreatment standard applicable to users of such treatment works shall, except in the case of standards providing for no discharge of pollutants, be correspondingly reduced in stringency for that pollutant.

Subpart E—Asbestos Millboard Subcategory

§ 427.50 Applicability; description of the asbestos millboard subcategory.

The provisions of this subpart are applicable to discharges resulting from the process in which asbestos in combination with various other materials such as cement, starch, clay, lime, and mineral wool are used in the manufacture of asbestos millboard.

§ 427.51 Specialized definitions.

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in 40 CFR Part 401 shall apply to this subpart.

§ 427.52 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

(a) In establishing the limitations set forth in this section, EPA took into account all information it was able to collect, develop and solicit with respect to factors (such as age and size of plant, raw materials, manufacturing processes, products produced, treatment technology available, energy requirements and costs) which can affect the industry subcategory and effluent levels established.

It is, however, possible that data which would affect these limitations have not been available and, as a result, these limitations should be adjusted for certain plants in this industry. An individual discharger or other interested person may submit evidence to the Regional Administrator (or to the State, if the State has the authority to issue NPDES permits) that factors relating to the equipment or facilities involved, the process applied, or other such factors related to such discharger are fundamentally different from the factors considered in the establishment of the guidelines. On the basis of such evidence or other available information, the Regional Administrator (or the State) will make a written finding that such factors are or are not fundamentally different for that facility compared to those specified in the Development Document. If such fundamentally different factors are found to exist, the Regional Administrator or the State shall establish for the discharger effluent limitations in the NPDES permit either more or less stringent than the limitations established herein, to the extent dictated by such fundamentally different factors. Such limitations must be approved by the Administrator of the Environmental Protection Agency. The Administrator may approve or disapprove such limitations, specify other limitations, or initiate proceedings to revise these regulations.

(b) The following limitations establish the quantity or quality of pollutants or pollutant properties which may be discharged by a point source subject to the provisions of this subpart after application of the best practicable control technology currently available: there shall be no discharge of process waste water pollutants to navigable waters.

§ 427.53 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.

The following limitations establish the quantity or quality of pollutants or pollutant properties which may be discharged by a point source subject to the provisions of this subpart after application of the best available technology economically achievable: there shall be no discharge of process waste water pollutants to navigable waters.

§ 427.54 [Reserved]

§ 427.55 Standards of performance for new sources.

The following standards of performance establish the quantity or quality of pollutants or pollutant properties which may be discharged by a new source subject to the provisions of this subpart: there shall be no discharge of process waste water pollutants to navigable waters.

§ 427.56 Pretreatment standards for new sources.

The pretreatment standards under section 307(c) of the Act for a source

within the asbestos millboard subcategory, which is a user of a publicly owned treatment works (and which would be a new source subject to section 306 of the Act, if it were to discharge pollutants to the navigable waters), shall be the standard set forth in 40 CFR 128, except that, for the purpose of this section, 40 CFR 128.133 shall be amended to read as follows:

In addition to the prohibitions set forth in 40 CFR 128.131, the pretreatment standard for incompatible pollutants introduced into a publicly owned treatment works shall be the standard of performance for new sources specified in 40 CFR 427.55; *Provided*, That, if the publicly owned treatment works which receives the pollutants is committed, in its NPDES permit, to remove a specified percentage of any incompatible pollutant, the pretreatment standard applicable to users of such treatment works shall, except in the case of standards providing for no discharge of pollutants, be correspondingly reduced in stringency for that pollutant.

Subpart F—Asbestos Roofing Subcategory

§ 427.60 Applicability; description of the asbestos roofing subcategory.

The provisions of this subpart are applicable to discharges resulting from the process in which asbestos paper is saturated with asphalt or coal tar with the subsequent application of various surface treatments to produce asbestos roofing products.

§ 427.61 Specialized definitions.

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in 40 CFR Part 401 shall apply to this subpart.

(b) COD shall mean COD added to the process waste water.

§ 427.62 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

(a) In establishing the limitations set forth in this section, EPA took into account all information it was able to collect, develop and solicit with respect to factors (such as age and size of plant, raw materials, manufacturing processes, products produced, treatment technology available, energy requirements and costs) which can affect the industry subcategory and effluent levels established. It is, however, possible that data which would affect these limitations have not been available and, as a result, these limitations should be adjusted for certain plants in this industry. An individual discharger or other interested person may submit evidence to the Regional Administrator (or to the State, if the State has the authority to issue NPDES permits) that factors relating to the equipment or facilities involved, the process applied, or other such factors related to such discharger are fundamentally different from the factors considered in the establishment of the guidelines. On the basis of such evidence or other available information, the Regional Administrator

(or the State) will make a written finding that such factors are or are not fundamentally different for that facility compared to those specified in the Development Document. If such fundamentally different factors are found to exist, the Regional Administrator or the State shall establish for the discharger effluent limitations in the NPDES permit either more or less stringent than the limitations established herein, to the extent dictated by such fundamentally different factors. Such limitations must be approved by the Administrator of the Environmental Protection Agency. The Administrator may approve or disapprove such limitations, specify other limitations, or initiate proceedings to revise these regulations.

(b) The following limitations establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a point source subject to the provisions of this subpart after application of the best practicable control technology currently available:

Effluent characteristic	Effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not exceed—
Metric units (kg/kg of product)		
COD.....	0.015	0.008
TSS.....	0.010	0.006
pH.....	Within the range 6.0 to 9.0.	
English units (lb/ton of product)		
COD.....	0.029	0.016
TSS.....	0.020	0.012
pH.....	Within the range 6.0 to 9.0.	

§ 427.63 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.

The following limitations establish the quantity or quality of pollutants or pollutant properties which may be discharged by a point source subject to the provisions of this subpart after application of the best available technology economically achievable: there shall be no discharge of process waste water pollutants to navigable waters.

§ 427.64 [Reserved].

§ 427.65 Standards of performance for new sources.

The following standards of performance establish the quantity or quality of pollutants or pollutant properties which may be discharged by a new source subject to the provisions of this subpart: there shall be no discharge of process waste water pollutants to navigable waters.

§ 427.66 Pretreatment standards for new sources.

The pretreatment standards under section 307(c) of the Act for a source within the asbestos millboard subcategory, which is a user of a publicly owned treatment works (and which would be a

new source subject to section 306 of the Act, if it were to discharge pollutants to the navigable waters), shall be the standard set forth in 40 CFR Part 128, except that, for the purpose of this section 40 CFR 128.133 shall be amended to read as follows:

In addition to the prohibitions set forth in 40 CFR 128.131, the pretreatment standard for incompatible pollutants introduced into a publicly owned treatment works shall be the standard of performance for new sources specified in 40 CFR 427.65; Provided, That, if the publicly owned treatment works which receives the pollutants is committed, in its NPDES permit, to remove a specified percentage of any incompatible pollutant, the pretreatment standard applicable to users of such treatment works shall, except in the case of standards providing for no discharge of pollutants, be correspondingly reduced in stringency for that pollutant.

Subpart G—Asbestos Floor Tile Subcategory

§ 427.70 Applicability; description of the asbestos floor tile subcategory.

The provisions of this subpart are applicable to discharges resulting from the process, in which asbestos, polyvinyl chloride resin, chemical stabilizers, limestone, and other fillers are used in the manufacture of asbestos floor tile.

§ 427.71 Specialized definitions.

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in 40 CFR 401 shall apply to this subpart.

(b) The abbreviation "mpc" shall mean 1000 pieces of floor tile.

(c) The term "pieces" shall mean floor tile measured in the standard size of 12" x 12" x 3/8".

(d) COD shall mean COD added to the process waste water.

§ 427.72 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

(a) In establishing the limitations set forth in this section, EPA took into account all information it was able to collect, develop and solicit with respect to factors (such as age and size of plant, raw materials, manufacturing processes, products produced, treatment technology available, energy requirements and costs) which can affect the industry subcategory and effluent levels established. It is, however, possible that data which would affect these limitations have not been available and, as a result, these limitations should be adjusted for certain plants in this industry. An individual discharger or other interested person may submit evidence to the Regional Administrator (or to the State, if the State has the authority to issue NPDES permits) that factors relating to the equipment or facilities involved, the process applied, or other such factors related to such discharger are fundamentally different from the factors considered in the establishment of the guidelines. On the basis

of such evidence or other available information, the Regional Administrator (or the State) will make a written finding that such factors are or are not fundamentally different for that facility compared to those specified in the Development Document. If such fundamentally different factors are found to exist, the Regional Administrator or the State shall establish for the discharger effluent limitations in the NPDES permit either more or less stringent than the limitations established herein, to the extent dictated by such fundamentally different factors. Such limitations must be approved by the Administrator of the Environmental Protection Agency. The Administrator may approve or disapprove such limitations, specify other limitations, or initiate proceedings to revise these regulations.

(b) The following limitations establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a point source subject to the provisions of this subpart after application of the best practicable control technology currently available:

Effluent characteristic	Effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not exceed
Metric units (kg/mpc of product)		
COD.....	0.14	0.08
TSS.....	0.08	0.04
pH.....	Within the range 6.0 to 9.0.	
English units (lb/mpc of product)		
COD.....	0.30	0.18
TSS.....	0.13	0.06
pH.....	Within the range 6.0 to 9.0.	

§ 427.73 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.

The following limitations establish the quantity or quality of pollutants or pollutant properties which may be discharged by a point source subject to the provisions of this subpart after application of the best available technology economically achievable: there shall be no discharge of process waste water pollutants to navigable waters.

§ 427.74 [Reserved].

§ 427.75 Standards of performance for new sources.

The following standards of performance establish the quantity or quality of pollutants or pollutant properties which may be discharged by a new source subject to the provisions of this subpart: there shall be no discharge of process waste water pollutants to navigable waters.

§ 427.76 Pretreatment standards for new sources.

The pretreatment standards under section 307(c) of the Act for a source within the asbestos floor tile subcategory,

which is a user of a publicly owned treatment works (and which would be a new source subject to section 306 of the Act, if it were to discharge pollutants to the navigable waters), shall be the standard set forth in 40 CFR Part 128, except that, for the purpose of this section, 40 CFR 128.133 shall be amended to read as follows:

In addition to the prohibitions set forth in 40 CFR 128.131, the pretreatment standard for incompatible pollutants introduced

into a publicly owned treatment works shall be the standard of performance for new sources specified in 40 CFR 427.75: *Provided*, That, if the publicly owned treatment works which receives the pollutants is committed, in its NPDES permit, to remove a specified percentage of any incompatible pollutant, the pretreatment standard applicable to users of such treatment works shall, except in the case of standards providing for no discharge of pollutants, be correspondingly reduced in stringency for that pollutant.

[FR Doc.74-4363 Filed 2-25-74;8:45 am]