



GRACE

Construction Products Division

TO: E. S. Wood
J. W. Wolter ✓
B. R. Williams ✓
W. R. Hanlon
H. C. Duecker

DATE: August 4, 1978

FROM: R. C. Ericson

SUBJECT: M.S.D.S. MONOKOTE

CC: R. A. Merther

FILE: M.S.D.S. MONOKOTE

There appears to be agreement that we ought to have a Material Safety Data Sheet on MONOKOTE. The purpose of this memo is to present two options for the format with the objective of accepting one of the two, so that we can respond to pending requests. It may also be possible to use option 1 plus the technical bulletin on a selective basis.

Both versions face up to the two key issues "Airborne Asbestos Fiber and Free Silica" in the manner outlined below:

M.S.D.S. SECTION II - HAZARDOUS INGREDIENTS

Option #1

The physical handling of MONOKOTE fireproofing during application can create a nuisance dust level in excess of OSHA Standards. Normal industrial dust control practices should be followed.

Option #2

Contains trace quantities of Tremolite, a natural occurring impurity, classifiable as asbestos by OSHA Regulation 1910.1001 (refer to attached Technical Bulletin).

The physical handling of MONOKOTE fireproofing during application can create a nuisance dust level in excess of OSHA Standards. Normal industrial dust control practices should be followed.

M.S.D.S. SECTION V - HEALTH HAZARD DATA

Option #1

TLV: Dust - Respirable Fraction 5 MGM/M³ - Total Dust 15 MGM/M³

Option #2

TLV: Dust - (Respirable Fraction 5 MGM/M³ - Total Dust 15 MGM/M³)
TLV: Asbestos 2 Fibers/cc 8 hr. TWA 10 Fibers/cc max.
(See Attached Technical Bulletin)

D009391

15193136