OCCUPATIONAL SAFETY AND HEALTH STANDARDS
SUBPART G—OCCUPATIONAL HEALTH AND ENVIRONMENTAL CONTROL

(Code of Federal Regulations, Title 29, Chapter XVII, Part 1910, 36 FR 10466, May 29, 1971; 36 FR 15104, August 13, 1971; 36 FR 23208, December 7, 1971; 37 FR 332, January 11, 1972; 37 FR 6576, March 31, 1972; 37 FR 11320, June 7, 1972; 37 FR 22139, October 18, 1972; 37 FR 24749, November 21, 1972; 38 FR *10929*, May 3, 1973; 38 FR 20074, July 7, 1973, 39 FR 3755, January 29, 1974, 39 FR 12343, April 5, 1974; 39 FR 19468, June 3, 1974; 39 FR 35896, October 4, 1974; 39 FR 41848, December 3, 1974)

Subpart G—Occupational Health and Environmental Control

§ 1910.93 Air contaminants.

An employee's exposure to any material listed in table G–1, G–2, or G–3 of this section shall be limited in accordance with the requirements of the following paragraphs of this section.

(a) *Table G–1:*

(1) *Materials with names preceded by "C"—Ceiling Values.* An employee's exposure to any material in table G–1, the name of which is preceded by a "C" (e.g., C Boron trifluoride), shall at no time exceed the ceiling value given for that material in the table.

(2) *Other materials—8-hour time weighted averages.* An employee's exposure to any material in table G–1, the name of which is not preceded by "C", in any 8-hour work shift of a 40-hour work week, shall not exceed the 8-hour time weighted average given for that material in the table.

(b) *Table G–2:*

(1) *8-hour time weighted averages.* An employee's exposure to any material listed in table G–2, in any 8-hour work shift of a 40-hour work week, shall not exceed the 8-hour time weighted average limit given for that material in the table.

(2) *Acceptable ceiling concentrations.* An employee's exposure to a material listed in table G–2 shall not exceed at any time during an 8-hour shift the acceptable ceiling concentration limit given for the material in the table, except for a time period, and up to a concentration not exceeding the maximum duration and concentration allowed in the column under "acceptable maximum peak above the acceptable ceiling concentration for an 8-hour shift".

(3) *Example.* During an 8-hour work shift, an employee may be exposed to a concentration of Benzene above 25 p.p.m. (but never above 50 p.p.m.) only for a maximum period of 10 minutes. Such exposure must be compensated by exposures to concentrations less than 10 p.p.m. so that the cumulative exposure for the entire 8-hour work shift does not exceed a weighted average of 10 p.p.m.

(c) *Table G–3:* An employee's exposure to any material listed in table G–3, in any 8-hour work shift of a 40-hour work week, shall not exceed the 8-hour time weighted average limit given for that material in the table.

(d) Computation formulae:

(1) (i) The cumulative exposure for an 8-hour work shift shall be computed as follows:

$$E = \frac{C_1T_1 + C_2T_2 + \ldots C_nT_n}{8}$$

where:

E is the equivalent exposure for the working shift.

C is the concentration during any period of time T where the concentration remains constant.

T is the duration in hours of the exposure at the concentration C.

The value of E shall not exceed the 8-hour time weighted average limit in table

MONS 060194

Copyright © 1974 by The Bureau of National Affairs, Inc.

G–1, G–2, or G–3 for the material involved.

(ii) To illustrate the formula prescribed in subdivision (i) of this subparagraph, note that isoamyl acetate has an 8-hour time weighted average limit of 100 p.p.m. (table G–1). Assume that an employee is subject to the following exposure:

Two hours exposure at 150 p.p.m.
Two hours exposure at 75 p.p.m.
Four hours exposure at 50 p.p.m.

Substituting this information in the formula, we have

$$\frac{2\times 150+2\times 75+4\times 50}{8}=81.25 \text{ p.p.m.}$$

Since 81.25 p.p.m. is less than 100 p.p.m., the 8-hour time weighted average limit, the exposure is acceptable.

(3) (i) In case of a mixture of air contaminants an employer shall compute the equivalent exposure as follows:

$$E_m=\frac{C_1}{L_1}+\frac{C_2}{L_2}+\cdots\frac{C_n}{L_n}$$

Where:

E_m is the equivalent exposure for the mixture.

C is the concentration of a particular contaminant.

L is the exposure limit for that contaminant, from table G–1, G–2, or G–3.

The value of E_m shall not exceed unity (1).

(ii) To illustrate the formula prescribed in subdivision (i) of this subparagraph, consider the following exposures:

Material	Actual concentration of 8-hour exposure	8-hour time weighted average exposure limit
Acetone (Table G–1)	500 p.p.m.	1,000 p.p.m.
2-Butanone (Table G–1)	45 p.p.m.	200 p.p.m.
Toluene (Table G–1)	40 p.p.m.	200 p.p.m.

Substituting in the formula, we have:

$$E_m=\frac{500}{1,000}+\frac{45}{200}+\frac{40}{200}$$

$E_m=0.500+0.225+0.200$

$E_m=0.925$

Since E_m is less than unity (1), the exposure combination is within acceptable limits.

(c) To achieve compliance with paragraph (a) through (d) of this section, administrative or engineering controls must first be determined and implemented whenever feasible. When such controls are not feasible to achieve full compliance, protective equipment or any other protective measures shall be used to keep the exposure of employees to air contaminants within the limits prescribed in this section. Any equipment and/or technical measures used for this purpose must be approved for each particular use by a competent industrial hygienist or other technically qualified person. Whenever respirators are used, their use shall comply with § 1910.134.

TABLE G–1

Substance	p.p.m.*	mg./M³ †
Acetaldehyde	200	360
Acetic acid	10	25
Acetic anhydride	5	20
Acetone	1,000	2,400
Acetonitrile	40	70
Acetylene dichloride, see 1, 2-Dichloroethylene.		
Acetylene tetrabromide	1	14
Acrolein	0.1	0.25
Acrylamide—Skin		0.3
Acrylonitrile—Skin	20	45
Aldrin—Skin		0.25
Allyl alcohol—Skin	2	5
Allyl chloride	1	3
**C Allyl glycidyl ether (AGE)	10	45
Allyl propyl disulfide	2	12
2-Aminoethanol, see Ethanolamine		
2-Aminopyridine	0.5	2
**Ammonia	50	36
Ammonium sulfamate (Ammate)		15
n-Amyl acetate	100	525
sec-Amyl acetate	125	650
Aniline—Skin	5	19
Anisidine (o, p-isomers)—Skin		0.5
Antimony and compounds (as Sb)		0.5
ANTU (alpha naphthyl thiourea)		0.3
Arsenic and compounds (as As)		0.5
Arsine	0.05	0.2
Azinphos-methyl—Skin		0.2
Barium (soluble compounds)		0.5
p-Benzoquinone, see Quinone.		
Benzoyl peroxide		5
Benzyl chloride	1	5
Biphenyl, see Diphenyl.		
Bisphenol A, see Diglycidyl ether.		
Boron oxide		15
C Boron trifluoride	1	3
Bromine	0.1	0.7
Bromoform—Skin	0.5	5
Butadiene (1, 3-butadiene)	1,000	2,200
Butanethiol, see Butyl mercaptan.		
2-Butanone	200	590
2-Butoxy ethanol (Butyl Cellosolve)—Skin	50	240
n-Butyl acetate	150	710
sec-Butyl acetate	200	950
tert-Butyl acetate	200	950
n-Butyl alcohol	100	300
tert-Butyl alcohol	100	300
C Butylamine—Skin	5	15
O tert-Butyl chromate (as CrO_3)—Skin		0.1
n-Butyl glycidyl ether (BGE)	50	270
*Butyl mercaptan	10	35
p-tert-Butyltoluene	10	60
Calcium arsenate		1
Calcium oxide		5
**Camphor	2	
Caprolactam (Dry) (9)		5
Carbon black		3.5
Carbon dioxide	5,000	9,000
Carbon monoxide	35	40
Chlordane—Skin		0.5
Chlorinated camphene—Skin		0.5
Chlorinated diphenyl oxide		0.5
Chlorine	1	3
Chlorine dioxide	0.1	0.3
C Chlorine trifluoride	0.1	0.4
C Chloroacetaldehyde	1	3
α-Chloroacetophenone (phenacylchloride)	0.05	0.3
Chlorobenzene (monochlorobenzene)	75	350
o-Chlorobenzylidene malononitrile (OCBM)	0.05	0.4
Chlorobromomethane	200	1,050
2-Chloro-1,3-butadiene, see Chloroprene.		
Chlorodiphenyl (42% Chlorine)		1
Chlorodiphenyl (54% Chlorine)		0.5
1-Chloro-2,3-epoxypropane, see Epichlorohydrin.		
2-Chloroethanol, see Ethylene chlorohydrin.		
Chloroethylene, see Vinyl chloride.		
C Chloroform (trichloromethane)	50	240
1-Chloro-1-nitropropane	20	100
Chloropicrin	0.1	0.7
Chloroprene (2-chloro-1,3-butadiene)—Skin	25	90

TABLE G–1—Continued

Substance	p.p.m.*	mg./M³ †
Chromium, sol. chromic, chromous salts as Cr		0.5
Metal and insol. salts		1
Coal tar pitch volatiles (benzene soluble fraction) anthracene, BaP, phenanthrene, acridine, chrysene, pyrene		0.2
Cobalt, metal fume and dust		0.1
Copper fume		0.1
Dusts and Mists		1
Cotton dust (raw)		1
Crag® herbicide		10
Cresol (all isomers)—Skin	5	22
Crotonaldehyde	2	6
Cumene—Skin	50	245
Cyanide (as CN)—Skin		5
Cyclohexane	300	1,050
Cyclohexanol	50	200
Cyclohexanone	50	200
Cyclohexene	300	1,015
Cyclopentadiene	75	200
2, 4-D		10
DDT—Skin		1
DDVP, see Dichlorvos.		
Decaborane—Skin	0.05	0.3
Demeton® - Skin		0.1
Diacetone alcohol (4-hydroxy-4-methyl-2-pentanone)	50	240
1,2-diaminoethane, see Ethylenediamine.		
Diatomaceous earth	6.7	0.4
Diborane	0.1	0.1
Dibutylphthalate		5
C o-Dichlorobenzene	50	300
p-Dichlorobenzene	75	450
Dichlorodifluoromethane	1,000	4,950
1,3-Dichloro-5,5-dimethyl hydantoin		0.2
1,1-Dichloroethane	100	400
1,2-Dichloroethylene	200	790
C Dichloroethyl ether—Skin	15	90
Dichloromethane, see Methylenechloride.		
Dichlorotetrafluoroethane	1,000	6,990
C 1,1-Dichloro-1-nitroethane	10	60
1,2-Dichloropropane, see Propylenedichloride.		
Dichlorvos (DDVP)—Skin	1,000	7,000
Dieldrin—Skin		0.25
Diethylamine	25	75
Diethylamine ethanol—Skin	10	50
Diethylether, see Ethyl ether.		
Difluorodibromomethane	100	860
C Diglycidyl ether (DGE)	0.5	2.8
Dihydrosybenzene, see Hydroquinone.		
Diisobutyl ketone	50	290
Diisopropylamine—Skin	5	20
Dimethoxymethane, see Methylal.		
Dimethyl acetamide—Skin	10	35
Dimethylamine	10	18
Dimethylaminobenzene, see Xylidene.		
Dimethylaniline (N-dimethylaniline)—Skin	5	25
Dimethylbenzene, see Xylene.		
Dimethyl 1,2-dibromo-2,2-dichloroethyl phosphate, (Dibrom)		3
Dimethylformamide—Skin	10	30
2,6-Dimethylheptanone, see Diisobutyl ketone.		
1,1-Dimethylhydrazine—Skin	0.5	1
Dimethylphthalate		5
Dimethylsulfate—Skin	1	5
Dinitrobenzene (all isomers)—Skin		1
Dinitro-o-cresol—Skin		0.2
Dinitrotoluene—Skin		1.5
Dioxane (Diethylene dioxide)—Skin	100	360
Diphenyl	0.2	1
Diphenylmethane diisocyanate (see Methylene bisphenyl isocyanate (MDI).		
Dipropylene glycol methyl ether—Skin	100	600
Di-sec. octyl phthalate (Di-2-ethylhexylphthalate)		5
Emtrin—Skin		0.1
Epichlorohydrin—Skin	5	19
EPN—Skin		0.5
1,2-Epoxypropane, see Propylene oxide.		
2,3-Epoxy-1-propanol, see Glycidol.		

See footnotes at end of table.

MCNS 060195

TABLE G-8

Material	8-hour time weighted average	Acceptable ceiling concentration	Acceptable maximum peak above the acceptable ceiling concentration for an 8-hour shift.	
			Concentration	Maximum duration
[redacted]				
(Z37.28-1970).	0.1 mg./M³	5 mg./M³		30 minutes.
Cadmium fume (Z37.5-1970)	0.2 mg./M³	0.6 mg./M³		
Cadmium dust (Z37.5-1970)	0.2 mg./M³	0.6 mg./M³		
Carbon disulfide (Z37.3-1968)	20 p.p.m	30 p.p.m	100 p.p.m	Do.
Carbon tetrachloride (Z37.17-1967)	10 p.p.m	25 p.p.m	200 p.p.m	5 minutes in any 4 hours.
Ethylene dibromide (Z37.31-1970)	25 p.p.m	25 p.p.m	50 p.p.m	5 minutes.
Ethylene dichloride (Z37.21-1969)	50 p.p.m	100 p.p.m	200 p.p.m	5 minutes in any 3 hours.
Formaldehyde (Z37.16-1967)	3 p.p.m	5 p.p.m	10 p.p.m	30 minutes.
Hydrogen fluoride (Z37.28-1969)	do			
Fluoride as dust (Z37.28-1969)	2.5 mg./M³			
Lead and its inorganic compounds (Z37.11-1969).	0.2 mg./M³			
Methyl chloride (Z37.18-1969)	100 p.p.m	300 p.p.m	300 p.p.m	5 minutes in any 3 hours.
Methylene Chloride (Z37.3-1968)	500 p.p.m	1,000 p.p.m	2,000 p.p.m	5 minutes in any 2 hours.
[redacted]				any 3 hours.
Trichloroethylene (Z37.19-1967)	do	do	300 p.p.m	5 minutes in any 3 hours.
Tetrachloroethylene (Z37.22-1967)	do	do	do	5 minutes in any 3 hours.
Toluene (Z37.12-1967)	200 p.p.m	300 p.p.m	500 p.p.m	10 minutes.
Hydrogen sulfide (Z37.2-1966)		20 p.p.m	50 p.p.m	10 minutes once only if no other measurable exposure occurs.
Mercury (Z37.8-1971)			1 mg./10M³ [1]	
Chromic acid and chromates (Z37.7-1971)		do [2]		

TABLE G-9—MINERAL DUSTS

Substance	Mppcf [3]	Mg/M³
Silica:		
Crystalline:		
Quartz (respirable)	250 [4]	10mg/M³ ÷
	%SiO₂+5	%SiO₂+2
Quartz (total dust)		30mg/M³ ÷
		%SiO₂+2
Cristobalite: Use ½ the value calculated from the count or mass formulas for quartz.		
Tridymite: Use ½ the value calculated from the formulae for quartz.		
Amorphous, including natural diatomaceous earth	20	20mg/M³
		%SiO₂
Silicates (less than 1% crystalline silica):		
Mica	20	
Soapstone	20	
Talc (non-asbestos form)	20[5]	
Talc (fibrous). Use asbestos limit.		
Tremolite (non talc, fibrous)		
Portland cement	50	
Graphite (natural)	15	
Coal dust (respirable fraction less than 5% SiO₂)		2.4mg/M³ or
For more than 5% SiO₂		10mg/M³
		%SiO₂+2
Inert or Nuisance Dust:		
Respirable fraction	15	5mg/M³
Total dust	50	15mg/M³

Note: Conversion factors—mppcf/35.3=million particles per cubic meter
=particles per c.c.

[1] Millions of particles per cubic foot of air, based on impinger samples counted by light-field techniques.

[2] The percentage of crystalline silica in the formula is the amount determined from air-borne samples, except in those instances in which other methods have been shown to be applicable.

[3] As determined by the membrane filter method at 430X dry-static contrast magnification.

[4] Both concentration and percent quartz for the application of this limit are to be determined from the fraction passing a size-selector with the following characteristics: Containing < 1% quartz; if > 1% quartz, use quartz limit.

Aerodynamic diameter (unit density sphere)	Percent passing selector
2	90
2.5	75
3.5	50
5.0	25
10	0

The measurements under this note refer to the use of an AEC instrument. If the respirable fraction of coal dust is determined with a MRE the figure corresponding to that of 2.4 Mg/M³ in the table for coal dust is 4.5 Mg/M³.

§ 1910.93a Asbestos.

(a) *Definitions.* For the purpose of this section, (1) "Asbestos" includes chrysotile, amosite, crocidolite, tremolite, anthophyllite, and actinolite.

(2) "Asbestos fibers" means asbestos fibers longer than 5 micrometers.

(b) *Permissible exposure to airborne concentrations of asbestos fibers.*—(1) *Standard effective July 7, 1972.* The 8-hour time-weighted average airborne concentrations of asbestos fibers to which any employee may be exposed shall not exceed five fibers, longer than 5 micrometers, per cubic centimeter of air, as determined by the method prescribed in paragraph (e) of this section.

(2) *Standard effective July 1, 1976.* The 8-hour time-weighted average airborne concentrations of asbestos fibers to which any employee may be exposed shall not exceed two fibers, longer than 5 micrometers, per cubic centimeter of air, as determined by the method prescribed in paragraph (e) of this section.

(3) *Ceiling concentration.* No employee shall be exposed at any time to airborne concentrations of asbestos fibers in excess of 10 fibers, longer than 5 micrometers, per cubic centimeter of air, as determined by the method prescribed in paragraph (e) of this section.

(c) *Methods of compliance.*—(1) *Engineering methods.* (i) *Engineering controls.* Engineering controls, such as, but not limited to, isolation, enclosure, exhaust ventilation, and dust collection, shall be used to meet the exposure limits prescribed in paragraph (b) of this section.

(ii) *Local exhaust ventilation.* (a) Local exhaust ventilation and dust collection systems shall be designed, constructed, installed, and maintained in accordance with the American National Standard Fundamentals Governing the Design and Operation of Local Exhaust Systems, ANSI Z9.2–1971, which is incorporated by reference herein.

(b) See § 1910.8 concerning the availability of ANSI Z9.2–1971, and the maintenance of a historic file in connection therewith. The address of the American National Standards Institute is given in § 1910.100.

(iii) *Particular tools.* All hand-operated and power-operated tools which may produce or release asbestos fibers in excess of the exposure limits prescribed in paragraph (b) of this section, such as, but not limited to, saws, scorers, abrasive wheels, and drills, shall be provided with local exhaust ventilation systems in accordance with subdivision (ii) of this subparagraph.

(2) *Work practices.*—(i) *Wet methods.* Insofar as practicable, asbestos shall be handled, mixed, applied, removed, cut scored, or otherwise worked in a wet state sufficient to prevent the emission of airborne fibers in excess of the exposure limits prescribed in paragraph (b) of this section, unless the usefulness of the product would be diminished thereby.

(ii) *Particular products and operations.* No asbestos cement, mortar, coating, grout, plaster, or similar material containing asbestos shall be removed from bags, cartons, or other containers in which they are shipped, without being either wetted, or enclosed, or ventilated so as to prevent effectively the release of airborne asbestos fibers in excess of the limits prescribed in paragraph (b) of this section.

(iii) *Spraying, demolition, or removal.* Employees engaged in the spraying of asbestos, the removal, or demolition of pipes, structures, or equipment covered or insulated with asbestos, and in the removal or demolition of asbestos insulation or coverings shall be provided with respiratory equipment in accordance with paragraph (d)(2)(iii) of this section and with special clothing in accordance with paragraph (d)(3) of this section.

(d) *Personal protective equipment.*—(1) Compliance with the exposure limits prescribed by paragraph (b) of this section may not be achieved by the use of respirators or shift rotation of employees, except:

(i) During the time period necessary to install the engineering controls and to institute the work practices required by paragraph (c) of this section;

(ii) In work situations in which the methods prescribed in paragraph (c) of

MONS C6C196

TABLE G-1—Continued

Substance	p.p.m.[a]	mg./M³ [b]
Ethanethiol, see Ethylmercaptan		
Ethanolamine	3	6
2-Ethoxyethanol—Skin	200	740
2-Ethoxyethyl acetate (Cellosolve acetate)—Skin	100	540
Ethyl acetate	400	1,400
Ethyl acrylate—Skin	25	100
Ethyl alcohol (ethanol)	1,000	1,900
Ethylamine	10	18
Ethyl sec-amyl ketone (5-methyl-3-heptanone)	25	130
Ethyl benzene	200	870
Ethyl bromide	200	890
Ethyl butyl ketone (3-heptanone)	50	230
Ethyl chloride	1,000	2,600
Ethyl ether	400	1,200
Ethyl formate	100	300
C Ethyl mercaptan	10	25
Ethyl silicate	100	850
Ethylene chlorohydrin—Skin	5	16
Ethylenediamine	10	25
Ethylene dibromide, see 1,2-Dibromoethane		
Ethylene dichloride, see 1,2-Dichloroethane		
C Ethylene glycol dinitrate and/or Nitroglycerin—Skin	◇0.2	1
Ethylene glycol monomethyl ether acetate, see Methyl cellosolve acetate		
Ethylene imine—Skin	0.5	1
Ethylene oxide	50	90
Ethylidine chloride, see 1,1-Dichloroethane		
N-Ethylmorpholine—Skin	20	94
Fenbane		15
Ferbam (as Fe)		15
Ferrovanadium dust		1
Fluorides (as F)		2.5
Fluorine	0.1	0.2
Fluorotrichloromethane	1,000	5,600
Formic acid	5	9
Furfural—Skin	5	20
Furfuryl alcohol	50	200
Glycidol (2,3-Epoxy-1-propanol)	50	150
Glycol monoethyl ether, see 2-Ethoxyethanol		
Guthion ®, see Azinphosmethyl		
Heptane		0.5
Hexachloroethane—Skin		0.5
Hexane (n-hexane)	500	2,000
Hexachlorobutadiene—Skin	1	10
Hexachlorocyclopentadiene—Skin		0.2
Hexane (n-hexane)	500	1,800
2-Hexanone	100	410
Hexone (Methyl isobutyl ketone)	100	410
sec-Hexyl acetate	50	300
Hydrazine—Skin	1	1.3
Hydrogen bromide	3	10
Hydrogen cyanide—Skin	10	11
Hydrogen peroxide (90%)	1	1.4
Hydrogen selenide	0.05	0.2
Hydroquinone		2
C Iodine	0.1	1
Iron oxide fume		10
Isoamyl acetate	100	525
Isoamyl alcohol	100	360
Isobutyl acetate	150	700
Isobutyl alcohol	100	300
Isophorone	25	140
Isopropyl acetate	250	950
Isopropyl alcohol	400	980
Isopropylamine	5	12
Isopropylether	500	2,100
Isopropyl glycidyl ether (IGE)	50	240
Ketene	0.5	0.9
Lead arsenate		0.15
Lindane—Skin		0.5
Lithium hydride		0.025
L.P.G. (liquefied petroleum gas)	1,000	1,800
Magnesium oxide fume		15
Malathion—Skin		15
Maleic anhydride	0.25	1
C Mesityl oxide	25	100
Methyl acetate	200	610
Methyl acetylene (propyne)	1,000	1,650
Methyl acetylene-propadiene mixture (MAPP)	1,000	2,000
Methyl acrylate—Skin	10	35
Methylal (dimethoxymethane)	1,000	3,100
Methyl alcohol (methanol)	200	260
Methylamine	10	12
Methyl amyl alcohol, see Methyl isobutyl carbinol		
Methyl amyl ketone (2-Heptanone)	100	465
C Methyl bromide—Skin	20	80
Methyl butyl ketone, see 2-Hexanone		
Methyl cellosolve—Skin	25	80
Methyl cellosolve acetate—Skin	25	120
Methyl chloroform	350	1,900
Methylcyclohexane	500	2,000
Methylcyclohexanol	100	470
o-Methylcyclohexanone—Skin	100	460
Methyl ethyl ketone (MEK)		
Methyl formate	100	250
Methyl hydrazine—Skin	5	35
Methyl iodide—Skin	25	100
Methyl isobutyl carbinol—Skin		
Methyl isobutyl ketone, see Hexone		
Methyl isocyanate—Skin	0.02	0.05
C Methyl mercaptan	10	20
Methyl methacrylate	100	410
Methyl propyl ketone, see 2-Pentanone		
C Methylene bisphenyl isocyanate (MDI)	0.02	0.2
Molybdenum:		
Soluble compounds		5
Insoluble compounds		15
Monomethyl aniline—Skin	2	9
C Monomethyl hydrazine—Skin	0.2	0.35
Morpholine—Skin	20	70
Naphthalene (tar)—Skin	100	400
Naphthalene	10	50
Nickel carbonyl	0.001	0.007
Nickel, metal and soluble compds, as Ni		1
Nicotine—Skin		0.5
Nitric acid	2	5
Nitric oxide	25	30
p-Nitroaniline—Skin	1	5
Nitrobenzene—Skin	1	5
p-Nitrochlorobenzene—Skin		1
Nitroethane	100	310
Nitrogen dioxide	5	9
Nitrogen trifluoride	10	29
Nitroglycerin—Skin	0.2	2
Nitromethane	100	250
1-Nitropropane	25	90
2-Nitropropane	25	90
Nitrotoluene—Skin	5	30
Nitrotrichloromethane, see Chloropicrin		
Octachloronaphthalene—Skin		0.1
*Octane	500	2,350
*Oil mist, mineral		◇5
Osmium tetroxide		0.002
Oxalic acid		1
Oxygen difluoride	0.05	0.1
Ozone	0.1	0.2
Paraquat—Skin		0.5
Parathion—Skin		0.1
Pentaborane	0.005	0.01
Pentachloronaphthalene—Skin		0.5
Pentachlorophenol—Skin		0.5
*Pentane	1,000	2,950
2-Pentanone	200	700
Perchloromethyl mercaptan	0.1	0.8
Perchloryl fluoride	3	13.5
Petroleum distillates (naphtha)	500	2,000
Phenol—Skin	5	19
Phenothiazine—Skin		5
Phenylacetylene		
Phenylethylene, see Styrene		
Phenylhydrazine—Skin	5	22
Phosdrin (Mevinphos ®)—Skin		0.1
Phosgene (carbonyl chloride)	0.1	0.4
Phosphine	0.3	0.4
Phosphoric acid		1
Phosphorus (yellow)		0.1
Phosphorus pentachloride		1
Phosphorus pentasulfide		1
Phosphorus trichloride	0.5	3
Phthalic anhydride	2	12
Picric acid—Skin		0.1
Pival (2-Pivalyl-1,3-indandione)		0.1
Platinum (Soluble Salts) as Pt		0.002
Propargyl alcohol—Skin	1	2
Propane	1,000	1,800
n-Propyl acetate	200	840
Propyl alcohol	200	500
n-Propyl nitrate	25	110
Propylene dichloride	75	350
Propylene imine—Skin	2	5
Propylene oxide	100	240
Propyne, see Methylacetylene		
Pyrethrum		5
Pyridine	5	15
Quinone	0.1	0.4
RDX—Skin		1.5
Rhodium, Metal fume and dusts, as Rh		0.1
Soluble salts		0.001
Rosinol		10
Rotenone (commercial)		5
Selenium compounds (as Se)		0.2
Selenium hexafluoride	0.05	0.4
Silver, metal and soluble compounds		0.01
Sodium fluoroacetate (1080)—Skin		0.05
Sodium hydroxide		2
Stibine	0.1	0.5
*Stoddard solvent	500	2,900
Strychnine		0.15
Sulfur dioxide	5	13
Sulfur hexafluoride	1,000	6,000
Sulfuric acid		1
Sulfur monochloride	1	6
Sulfur pentafluoride	0.025	0.25
Sulfuryl fluoride	5	20
Systox, see Demeton ®		
2,4,5-T		10
Talc—Skin		5
TEDP—Skin		0.2
Tellurium		0.1
Tellurium hexafluoride	0.02	0.2
TEPP—Skin		0.05
1,1,1,2-Tetrachloro-2,2-difluoroethane	500	4,170
1,1,2,2-Tetrachloro-1,2-difluoroethane	500	4,170
1,1,2,2-Tetrachloroethane—Skin	5	35
Tetrachloroethylene, see Perchloroethylene		
Tetrachloromethane, see Carbon tetrachloride		
Tetrachloronaphthalene—Skin		2
Tetraethyl lead (as Pb)—Skin		0.075
Tetrahydrofuran	200	590
Tetramethyl lead (as Pb)—Skin		0.07
Tetramethyl succinonitrile—Skin	0.5	3
Tetranitromethane	1	8
Tetryl (2,4,6-Trinitrophenylmethylnitramine)—Skin		1.5
Thallium (soluble compounds)—Skin as Tl		0.1
Thiram		5
Tin (inorganic cmpds, except oxides		2
Tin (organic cmpds)		0.1
C Toluene-2,4-diisocyanate	0.02	0.14
o-Toluidine—Skin	5	22
Toxaphene, see Chlorinated camphene		
Tributyl phosphate		5
1,1,1-Trichloroethane see Methyl chloroform		
1,1,2-Trichloroethane—Skin	10	45
Trichloroethylene		10
Trichloromethane, see Chloroform		
Trichloronaphthalene—Skin		5
1,2,3-Trichloropropane	50	300
1,1,2-Trichloro 1,2,2-trifluoroethane	1,000	7,600
Triethylamine	25	100
Trifluoromonobromomethane	1,000	6,100
2,4,6-Trinitrophenol, see Picric acid		
2,4,6-Trinitrophenylmethylnitramine, see Tetryl		
Trinitrotoluene—Skin		1.5
Uranium (soluble compounds)		0.05
Uranium (insoluble compounds)		0.25
C Vanadium:		
V_2O_5 dust		0.5
V_2O_5 fume		0.1
Vinyl benzene, see Styrene		
Vinylcyanide, see Acrylonitrile		
Vinyl toluene	100	480
Warfarin		0.1
Xylic Acid	100	435
Xylidine—Skin	5	25
Yttrium		1
Zinc chloride fume		1
Zinc oxide fume		5
Zirconium compounds (as Zr)		5

[a]1970 Addition.

[b] Parts of vapor or gas per million parts of contaminated air by volume at 25° C. and 760 mms. Hg pressure.

[c] Approximate milligrams of particulate per cubic meter of air.

(No footnote "c" is used to avoid confusion with ceiling value notations.)

[d] An atmospheric concentration of not more than 0.02 p.p.m., or personal protection may be necessary to avoid headache.

[e] As sampled by method that does not collect vapor.

[f] For control of general room air, biologic monitoring is essential for personnel control.

[Vinyl chloride deleted at 39 FR 12343, April 5, 1974]

Copyright © 1975 by The Bureau of National Affairs, Inc.

MONS 060197