

Shea 40410
Emergency Telephone
(614) 431-6600

MATERIAL SAFETY DATA SHEET



Consumer Products Division, Division of Borden, Inc.
180 EAST BROAD STREET, COLUMBUS, OHIO 43215

For ordering information, additional copies of MSDS, etc., 800-848-9400
For technical information only, 614-431-6680

PC014

THE OSHA HAZARD COMMUNICATION STANDARD 29 CFR 1910.1200 REQUIRES THAT
THE INFORMATION CONTAINED ON THIS SHEET BE MADE AVAILABLE TO YOUR WORKERS.

INSTRUCT YOUR WORKERS TO HANDLE THIS PRODUCT PROPERLY

DESCRIPTION: KRYLON INT/EXT. ENAMEL
PRODUCT TYPE: SPARY PAINT "AEROSOL"
APPLICATION: ITEMS 1501 THRU 2503 — 1501 GLOSSY WHITE, 1502 FLAT WHITE, 1503 ANTIQUE WHITE, 1504 IVORY, 1506 ALMOND, 1802 PASTEL YELLOW, 1906 SLATE BLUE, 1929 PLUM (SAFETY PURPLE), 2413 CORAL, 2415 ROSE, 2502 LIGHT BEIGE, 2503 TAUPE, 15012 GLOSSY WHITE, 15022 FLAT WHITE, 15032 ANTIQUE WHITE, 15062 ALMOND

10-Apr-89

SIGNAL WORD DANGER!

THIS MATERIAL IS A "HEALTH HAZARD" AND/OR A "PHYSICAL HAZARD" AS DETERMINED WHEN REVIEWED ACCORDING TO THE REQUIREMENTS OF THE OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION 29 CFR PART 1910.1200 "HAZARD COMMUNICATION" STANDARD.

CHEMICAL HAZARD RATING
HEALTH=2(MODERATE)
FIRE=4(EXTREME)
REACTIVITY=0(LEAST)
CHRONIC=*

ACGIH TLV: 50 PPM (205 MG/M3) TWA; 75 PPM (300 MG/M3) STEL
OSHA PEL: 50 PPM (205 MG/M3) TWA; 75 PPM (300 MG/M3) STEL
NIOSH DOCUMENT NUMBER: 76-173

108-65-6 2-PROPANOL 1-METHOXY- ACETATE 5-10

—SEE FOOTNOTE C.

ACGIH TLV: NONE ESTABLISHED

OSHA PEL: NONE ESTABLISHED

100-68-3 *TOLUENE 1-5

NOTE REVISED OSHA PEL

CAN CAUSE LIVER DAMAGE.

CAN CAUSE KIDNEY DAMAGE.

CAN CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION. SIGNS AND SYMPTOMS

MAY INCLUDE HEADACHE, DIZZINESS, NAUSEA, VOMITING.

UNCONSCIOUSNESS AND ASPHYXIATION

REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL

OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS

SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY

CONCENTRATING AND INHALING THE CONTENTS MAY LEAD TO ADDICTION

AND MAY BE HARMFUL OR FATAL

—SEE FOOTNOTE C

ACGIH TLV: 100 PPM (375 MG/M3) TWA; 150 PPM (560 MG/M3) STEL

OSHA PEL: 100 PPM (375 MG/M3) TWA; 150 PPM (560 MG/M3) STEL

NIOSH DOCUMENT NUMBER: 73-11023

1330-20-7 *XYLENE 10-30

NOTE REVISED OSHA PEL

CAN CAUSE LIVER DAMAGE

CAN CAUSE KIDNEY DAMAGE

CAN CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION. SIGNS AND SYMPTOMS

MAY INCLUDE HEADACHE, DIZZINESS, NAUSEA, VOMITING.

UNCONSCIOUSNESS AND EVEN ASPHYXIATION.

—SEE FOOTNOTE C

ACGIH TLV: 100 PPM (435 MG/M3) TWA; 150 PPM (655 MG/M3) STEL

OSHA PEL: 100 PPM (435 MG/M3) TWA; 150 PPM (655 MG/M3) STEL

NIOSH DOCUMENT NUMBER: 75-168

13463-67-7 *TITANIUM DIOXIDE 5-10

NOTE REVISED OSHA PEL

CAN CAUSE LUNG FIBROSIS. PRE-EXISTING RESPIRATORY DISORDERS MAY BE

AGGRAVATED BY EXPOSURE

—SEE FOOTNOTE C

ACGIH TLV: TOTAL DUST 10 MG/M3 TWA

OSHA PEL: RESPIRABLE FRACTION/TOTAL DUST 5/10 MG/M3 TWA

FOOTNOTE C: AS OF THE DATE OF ISSUANCE OF THIS DOCUMENT, THIS MATERIAL HAS NOT BEEN LISTED BY NTP, IARC OR OSHA AS A CARCINOGEN

PHYSICAL DATA

VAPOR PRESSURE — SEE CAN PRESSURE

VAPOR DENSITY HEAVIER THAN AIR

SOLUBILITY IN WATER

SPECIFIC GRAVITY LIGHTER THAN WATER

EVAP RATE FASTER THAN BUTYL ACETATE

BOILING POINT: APPEARANCE: ODOR

PERCENT VOLATILE BY WEIGHT

PERCENT NON-VOLATILE BY WEIGHT

PRESSURE IN CONTAINER, PSIG @ 70 F.

SLIGHT

SAL 000009852

81 TO 89

11 TO 19

APPROX 60

SEE REVERSE SIDE

DISCLAIMER—SEE REVERSE SIDE

CURRENT ISSUE: 10-APR-89 KD-1501E

IMMEDIATE HEALTH HAZARD DATA

SKIN ABSORPTION: NO HAZARDS KNOWN TO BORDEN.
 INGESTION: NOT EXPECTED TO BE HARMFUL UNDER NORMAL CONDITIONS OF USE.
 IF ACCIDENTALLY SWALLOWED, BURNS OR IRRITATION TO MUCOUS MEMBRANES, ESOPHAGUS OR GI TRACT CAN RESULT.
 INHALATION: MAY BE HARMFUL IF INHALED. LIQUID OR VAPOR MAY CAUSE IRRITATION OF NOSE, THROAT AND LUNGS.
 CAN CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION.
 SKIN: CAUSES IRRITATION.
 EYES: CAUSES IRRITATION.

HANDLING PRECAUTIONS

INHALATION: AVOID BREATHING VAPOR OR MIST.
 USE WITH ADEQUATE VENTILATION.
 SKIN: AVOID CONTACT WITH SKIN.
 EYES: AVOID CONTACT WITH EYES.
 HANDLE IN ACCORDANCE WITH GOOD INDUSTRIAL HYGIENE AND SAFETY PRACTICES. THESE PRACTICES INCLUDE AVOIDING UNNECESSARY EXPOSURE AND REMOVAL OF THE MATERIAL FROM EYES, SKIN AND CLOTHING.
 WASH THOROUGHLY AFTER HANDLING.

EMERGENCY AND FIRST AID PROCEDURES

INGESTION: IF ACCIDENTALLY SWALLOWED, DILUTE BY DRINKING LARGE QUANTITIES OF WATER. IMMEDIATELY CONTACT POISON CONTROL CENTER OR HOSPITAL EMERGENCY ROOM FOR ANY OTHER ADDITIONAL TREATMENT DIRECTIONS.
 INHALATION: IF INHALED, REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION, PREFERABLY MOUTH-TO-MOUTH.
 SKIN CONTACT: FLUSH SKIN WITH PLENTY OF WATER.
 REMOVE CONTAMINATED CLOTHING. CALL A PHYSICIAN IF IRRITATION PERSISTS.
 EYE CONTACT: IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. EYELIDS SHOULD BE HELD APART DURING IRRIGATION TO INSURE WATER CONTACT WITH ENTIRE SURFACE OF EYES AND LIDS. CALL A PHYSICIAN.

FIRE AND EXPLOSION HAZARD DATA

EXTREMELY FLAMMABLE.
DO NOT INCINERATE (BURN) CONTAINER.
AVOID HEAT. KEEP CONTAINER BELOW 120 F. HIGH TEMPERATURES MAY CAUSE BURSTING. DO NOT PLACE CONTAINER ON RADIATOR, STOVE, IN DIRECT SUNLIGHT OR NEAR OTHER HEAT SOURCES. **DO NOT PUNCTURE CONTAINER.** CONTENTS UNDER PRESSURE WILL DISCHARGE. **AVOID OPEN FLAMES, SPARKS, PILOT LIGHTS. DO NOT SMOKE.** VAPOR MAY IGNITE EXPLOSIVELY. SPRAY MIST OR VAPOR EVAPORATING FROM A DEPOSITED FILM IS HEAVIER THAN AIR AND MAY SETTLE IN LOW PLACES OR TRAVEL OUTWARD TO A SOURCE OF IGNITION AND FLASHBACK.
 IN CASE OF FIRE, USE DRY CHEMICAL, FOAM OR CO₂. WATER MAY BE INEFFECTIVE BUT SHOULD BE USED TO KEEP FIRE-EXPOSED CONTAINERS COOL.

REACTIVITY DATA

NORMALLY STABLE AS DEFINED IN NFPA 704-12 (4-3.1).
 HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.
 DECOMPOSITION PRODUCTS MAY INCLUDE: OXIDES OF CARBON.

CONTROL MEASURES

IF AIRBORNE CONTAMINANTS ARE GENERATED WHEN THE MATERIAL IS HEATED OR HANDLED, SUFFICIENT VENTILATION IN VOLUME AND AIR FLOW PATTERNS SHOULD BE PROVIDED TO KEEP AIR CONTAMINANT CONCENTRATION LEVELS BELOW ACCEPTABLE CRITERIA.

ENGINEERING CONTROLS: THE FOLLOWING EXPOSURE CONTROL TECHNIQUES MAY BE USED TO EFFECTIVELY MINIMIZE EMPLOYEE EXPOSURE: LOCAL EXHAUST VENTILATION, ENCLOSED SYSTEM DESIGN, PROCESS ISOLATION AND REMOTE CONTROL IN COMBINATION WITH APPROPRIATE USE OF PERSONAL PROTECTIVE EQUIPMENT AND PRUDENT WORK PRACTICES. THESE TECHNIQUES MAY NOT NECESSARILY ADDRESS ALL ISSUES PERTAINING TO YOUR OPERATIONS. WE THEREFORE RECOMMEND THAT YOU CONSULT WITH EXPERTS OF YOUR CHOICE TO DETERMINE WHETHER OR NOT YOUR PROGRAMS ARE ADEQUATE.

PERSONAL PROTECTION INFORMATION

WHERE AIR CONTAMINANTS CAN EXCEED ACCEPTABLE CRITERIA, USE NIOSH/MSHA APPROVED RESPIRATORY PROTECTION EQUIPMENT. RESPIRATORS SHOULD BE SELECTED BASED ON THE FORM AND CONCENTRATION OF CONTAMINANTS IN AIR IN ACCORDANCE WITH OSHA 29 CFR 1910.134 OR OTHER APPLICABLE STANDARDS OR GUIDELINES. USE GOGGLES IF CONTACT IS LIKELY. WEAR IMPERVIOUS GLOVES AS REQUIRED TO PREVENT SKIN CONTACT.

SPILL OR LEAK PROCEDURES

ELIMINATE ALL IGNITION SOURCES.
 SOAK UP WITH ABSORBENT MATERIAL AND REMOVE TO A CHEMICAL DISPOSAL AREA.
 PREVENT ENTRY INTO NATURAL BODIES OF WATER.

WASTE DISPOSAL

DISPOSE OF ACCORDING TO LOCAL, STATE, PROVINCIAL, AND FEDERAL REQUIREMENTS.
 EMPTY CONTAINER MAY CONTAIN EXPLOSIVE VAPORS. DO NOT CUT, PUNCTURE OR WELD ON OR NEARBY.
 INCINERATION WILL CAUSE CONTAINER TO BURST VIOLENTLY.

STORAGE PRECAUTIONS

DO NOT STORE AT TEMPERATURES ABOVE 120 F.

DOT CLASSIFICATION

ORM-D CONSUMER COMMODITY.

SARA TITLE III SECTION 313
 AND 40 CFR PART 372
 TOXIC CHEMICAL NOTIFICATION SHEET

KRYLON INT/EXT. ENAMEL

THIS PRODUCT CONTAINS THE FOLLOWING TOXIC CHEMICALS SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1995 AND SUBPART C-SUPPLIER NOTIFICATION REQUIREMENT OF 40 CFR PART 372.

CAS REGISTRY NUMBER	CHEMICAL NAME	PCT. BY WEIGHT
57-64-1	ACETONE	36.71
78-93-3	METHYL ETHYL KETONE	8.34
108-10-1	METHYL ISOBUTYL KETONE	2.34
108-65-6	2-PROPANOL, 1-METHOXY- ACETATE	7.51
108-88-3	TOLUENE	1.68
1330-20-7	XYLENE (MIXED ISOMERS)	10.66

THIS TOXIC CHEMICAL NOTIFICATION SHEET MUST NOT BE DETACHED FROM THE MATERIAL SAFETY DATA SHEET (MSDS). ANY COPYING AND REDISTRIBUTION OF THE MSDS SHALL INCLUDE COPYING AND REDISTRIBUTION OF THIS NOTIFICATION SHEET ATTACHED TO COPIES OF THE MSDS SUBSEQUENTLY REDISTRIBUTED.

CURRENT ISSUE: 10-APR-89 KD-1501E

DISCLAIMER

SELLER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY BORDEN, except that the product shall conform to contracted specifications, and that the product does not infringe any valid United States patent. The information provided herein was believed by Borden to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of product and to determine the suitability of the product for its intended use. Buyer's exclusive remedy shall be for damages and no claim of any kind, whether as to product delivered or for non-delivery of product, and whether based on contract, breach of warranty, negligence or otherwise shall be greater in amount than the purchase price of the quantity of product in respect of which damages are claimed. In no event shall Seller be liable for incidental or consequential damages, whether Buyer's claim is based on contract, breach of warranty, negligence or otherwise.

SAL 000009853