
How To Keep Your Therminol® FR System Leak-Free

Therminol FR is a stable, long-lasting heat transfer fluid. Consequently, measures to avoid environmental contamination through spillage, leakage or careless disposal should be observed.

Since your Therminol FR heat transfer system is a non-pressurized, closed system, fluid leakage is easily controlled. If a leakage problem does occasionally occur, there are some suggestions that will help you correct it. If leakage has caused an excessive elevation of fluid, please refer to "How To Dispose Of Therminol FR" on the back of this bulletin.



CHECK THESE SOURCES FOR LEAKAGE

Generally, there are four sources of leaks in a system:

1 **FITTINGS:** Weld all connections. Flange fittings where accessibility is desired.

2 **PUMP SEALS:** Canned pumps and pumps without seals or glands are the best protection against leakage. If mechanical seals are used, enclose them or provide a drip pan with a drain to a collection system.

3 **USER SEALS:** Direct all drains to a collection system. Install drip pans at leaky joints.

4 **EXPANSION TANK VENT:** Direct vent to either a cold trap, carbon canister or drum to contain vapor condensation and keep out rain water.

WHEN YOUR SYSTEM IS UNDER DESIGN specify valves as pictured above. The valve stem packing should be capable of withstanding temperatures to 700°F. Valves should be specified with extended bonnets to keep packing cool. Use flanged valves where possible. Bolted bonnet valves are also recommended.

0025525

TOWOLDMON0021129
WATER_PCB-00005598

How To Dispose Of Therminol FR

If leakage has occurred, collect the fluid and place it in drums. You may return the fluid to Monsanto for disposal. To do this you must have an RGA number.

DISPOSAL: Pack the drums properly.

[redacted]

Please advise your Monsanto fluid specialist that material is being returned for disposal so proper papers can be prepared. You will be invoiced a nominal charge for this service.

RECONDITIONING: Therminol FR can be easily and quickly reconditioned for re-use if it is within certain limits on moisture, acid number viscosity and contaminants. Your Monsanto fluid specialist can refer you to an approved reclaimer.

Monsanto

0025526

[redacted]

TOWOLDMON0021130
WATER_PCB-00005599