

DATE: MAY -0-81 E-1223

(A) YC-016-B ()

FWP 03/13/81

ESTIMATED WEIGHT: 3130#

COMTYP JOB NAME: 01YC016BMA

EQUIP MENT	NAME: MOLYBDATE ORANGE	USE LBS	N-CODE	ACCT LBS
PREP	1 WEIGH FOR S 35	90	3-A	90
1	2 WEIGH FOR S-43	80	3-A	80
	3 WEIGH IN DRUM FOR S-39	145	32-D	145
	4 WEIGH FOR S-29	250	4-A	250
	5 WEIGH IN PAILS FOR S-30	225	28-D	22
	6 WEIGH FOR S-41	225	15-A	225
356	7 RUN 25" (451 G) WATER INTO V-356			
2	8 TURN ON AGITATOR AND STEAM			
	9 WEIGH AND SIFT IN	270	131-B	270
	10 HEAT TO AND MAINTAIN 60-66* C FOR S 37			
359	11 WEIGH IN OPTR <u>58</u> , MK <u>46</u> , <u>34.2%</u>	<u>547</u>	423-D	<u>244</u>
3	OPTR _____, MK _____, _____%			<u>187</u>
351	12 WEIGH IN OPTR <u>58</u> , MK <u>005</u> , <u>37.77%</u>	<u>3071</u>	10-D	<u>444</u>
4	OPTR _____, MK _____, _____%			<u>1160</u>
	13 RUN IN V-359			
358	14 RUN 10" (473 G) WATER INTO V-358			
5	15 PUMP V-351 INTO V-358			
	16 ADJ TO 68" (3216 G) AT 67-69*F. RECORD: _____			
	17 STIR 3 MIN. RECORD: <u>67</u> *F & PH <u>9.5</u>			
	18 IF NECESSARY, ADJ TO PH 9.8-9.9 ASSUME 50%	<u>2</u>	7-D	<u>1</u>
	RECORD: PH <u>9.8</u> ASSUME 66%		33-D	
	19 RECORD: G/ML <u>1047</u> (1.044-1.047)			
SV	20 RUN 40" (1908 G) WATER INTO V- <u>242</u>			
6	21 RUN IN FROM V-354			
	OPTR <u>58</u> , MK <u>440</u> , <u>28.26%</u>	<u>10782</u>	41-D	3047
	OPTR _____, MK _____, _____%			
	22 ADJ TO 3148 G AT 67-69*F (64" IN V-240 & V-246; 66" IN V-241, V-242, & V-245)			
	23 STIR 3 MIN RECORD: _____ *F		57-A	
	24 RECORD: PH <u>3.6</u> (2.8-3.6)			
	25 ADJ TO PH 4.0-4.1 ASSUME 66%		33-D	
	RECORD: PH <u>4.1</u> & VOL <u>66</u> ASSUME 50%		7-D	
	NOTE: DILUTE N-7-D 10:1 WITH WATER			
	26 RECORD: G/ML <u>1098</u> (1.097-1.100)			
	27 OBTAIN 1 QT SAMPLES OF S-19 & S-26 SOLUTIONS & TITRATE TWICE			
	RECORD: LOWEST PH <u>3.18</u> & ML N-10-D <u>8.26</u>			
	LOWEST PH <u>3.05</u> & ML N-10-D <u>8.26</u>			
	NOTIFY SUPV IF ML N-10-D IS NOT IN RANGE 8.0-8.6 OR IF THE TWO TITRATIONS DIFFER BY MORE THAN 0.10 ML N-10-D (IF YES, FLUSH ALL EQUIPMENT & REPEAT TITRATIONS) DO NOT PROCEED IF N-10-D TITRATION IS OUT OF RANGE			

PROCEED TO PAGE 2

EC

EQUIP MENT	PAGE 02 OF 2 CG 01 CODE YC-016-B	USE LBS	N-CODE	ACCT LBS
28	RUN V-358 AT 67-69°F THRU BOTH UNDERSURFACE DISTRIBUTORS INTO SV AT 67-69°F IN 17-19 MIN			
	RECORD: START <u>2 AM</u> M & TOTAL MIN <u>18</u>			
	NOTE: V-358 STRIKE TIME UP WHEN 1/2 VAT BOTTOM SHOWS MT			
SV 6	WHEN S 28 COMPLETED AND BEFORE WASHING IN V-358, DUMP IN N-4-A FROM S-4			
(CONT)	IMMEDIATELY POUR IN N-28-D FROM S 5			
31	DURING S'S 29 AND 30 (IF ALONE, AFTER S'S 29 & 30) WASH IN V-358			
32	STIR 2 MIN			
33	RECORD: PH <u>2.3</u> (2.2-2.5) & PB XS <u>+</u> (+)			
34	STIR TOTAL OF 15 MIN FROM COMPLETION OF S 28 RECORD: START <u>2:20</u> TOTAL MIN <u>15</u>			
35	DUMP IN N-3-A FROM S 1			
36	STIR 3 MIN			
37	RUN IN N-131-B FROM S 3 IN 7 MIN			
38	STIR 3 MIN			
39	POUR IN N-983-D FROM S-3			
40	STIR 2 MIN			
41	DUMP IN N-15-A FROM S 6			
42	STIR 3 MIN			
43	DUMP IN N-3-A FROM S 2			
44	STIR 3 MIN			
45	RECORD: PH <u>6.0</u> (5.8-6.0)			
46	IF NECESSARY, ADJ TO PH 5.8-6.0 ASSUME 50%		7-D	
	RECORD: PH _____ ASSUME 66%		33-D	
47	FLOOD TO 153" (7298 G)			
48	STOP AGITATOR			
	START <u>1730</u>	FINISH <u>3 AM</u>	GPTR <u>282-169</u>	