

ONE U. S. STANDARD GALLON



Dutch Boy

NALPL

FLAT WALL FINISH

72-12—OFF WHITE

0000-NAL-0000209

N13858

Dutch Boy NALPLEX—new acrylic latex flat wall finish

Simple
as...

Here is the new, easy, quick and certain way to fresh, beautiful, colorful interiors. The latest scientific developments have made possible a remarkable degree of hiding power, which makes it easy to cover the surface evenly and thoroughly and obtain smooth, uniform, finished results. Dries in 1-2 hours. Truly washable. Odorless.

No Paint Preparation Needed—Nalplex is ready to use as soon as it has been stirred and thoroughly mixed. Nalplex can be thinned with up to one cup of clean water per gallon; on unusually rough and porous surfaces or in very hot, dry weather this will aid application. Do not use turpentine or other thinners.

No Special Time to Paint—Paint when you want to—no disagreeable odor to bother eating or sleeping. Stop when you want to—and start again. Just be sure to put your brush or roller in water where you use it. Nalplex is insoluble in water when dry.

No Special Equipment Needed—Just apply evenly and cover surfaces with a solid, uniform color. Any spots you miss can be touched up the next day. One coat is usually enough, but a second coat can be applied after four hours or later if you wish.

No Tinting Needed—Nalplex colors are factory-prepared and ready to use. They can be inter-mixed with each other to produce an unlimited number of attractive shades. Do not add regular tinting colors or mix with other types of paint.

No Special Equipment Needed—All you need is a good brush or roller to apply Nalplex.

No Messy Clean Up—Just wash brushes, rollers, or other equipment in warm, soapy water, rinse and dry. Spills or splatters should be removed immediately with soap and warm water.

No Waiting Time—Nalplex dries firm and hard in one or two hours. Pictures and drapes can then be hung without damaging either the Nalplex or the drapes. No bothersome, disagreeable odor to delay you. And no prolonged "curing" time of 30 days or more, before the paint is washable. Nalplex rapidly forms a tough, durable film which is water and alkali resistant, ready for service.

Apply Nalplex directly to any painted, unpainted or papered interior wall surface which is clean, sound and in good condition. Dirt, grease, scaling paint and loose wallpaper should be removed. Pre-coat filled cracks and patched areas about 15 minutes beforehand. Bare metal should be primed. Do not paint over "kelonine" if wallpaper has bled through, apply a coat of thin shellac. Sand glossy surfaces to provide adhesion. Use plenty of paint. Allow about one gallon for each 500 square feet. Stir thoroughly from bottom of can. Do not paint in cold or damp weather without providing heat and ventilation. Matching colors are available in Dutch Boy Satin Eggshell for kitchens, bathrooms and woodwork.

PROTECT FROM FREEZING.

NATIONAL LEAD COMPANY

GENERAL OFFICES: NEW YORK, N. Y.

COMPOSITION OF PAINT BY WEIGHT

Acrylic Latex	
Acrylic Latex**	100.0%
*Less Than 5% Of The Total	
Nalplex (Acrylic)	27.2%
Resin (Water)	72.8%

0000-NLI-000020557