

SEP 28 1982 K2135
(DATE) (LOT NUMBER)

EST. WT. 2225* LBS. TYPED BY: DB STANDARD HRS. TIME 11 P.M.

N-8900 A use Cat C-533, 4/16

EQUIP MENT	NAME: "MONASTRAL" BLUE R	02 PAGES	USE LBS.	N-CODE	ACCT LBS
	NOTE: FOR PROCESSING N-8900-A & N-8802-A, PRESET WATER METER PER CHART FOR WATER ADDITION TO FULL TOTES. USE MODE 3 FOR FULL TOTES & MODE 2 FOR STUMPING TOTES				
SV 1	RUN 2-3" (+ OR - 200 G) WATER INTO V-1				
2	STATION # 2 WEIGH & PUMP IN				
	GALS OF WATER				
	SEQUENCER STEPS				
	LOT	6	11	16	#100% %
					416 21.9
					1900
3	STATION # 2 TOTAL 416 #100% WEIGH & PUMP IN				
	GALS OF WATER				
	SEQUENCER STEPS				
	LOT	6	11	16	#100% %
	529				607 26.2
	A-41A				798 9.5
	516				689 23.1
	516A				261 16.7
					2545 2500 2983 1563
					1855 #100%
4	TURN ON AGITATOR				
313	RUN IN 14" (207 G) WATER INTO V-313 & HEAT				
2	TO 80-100 DEG F				
	NOTE: VENT ON SOD.DRESINATE TANK OR VAT				
	USED FOR THIS SOL'N SHOULD BE CHECKED FOR				
	DRAFT PRIOR TO DUMPING THE SOD.DRESINATE				
6	ADD IN 3-4 MIN				
7	STIR 5 MIN & RECORD: PH 9.0 (10.0-10.5)				
8	STIR 15 MIN OR LONGER TO DISSOLVE FOR S 15				
304	RUN IN 10" (122 G) WATER INTO V-304				
3	WEIGH & DUMP IN				
11	STIR TO DISSOLVE FOR S 17				
SV 12	RECORD: PH 9.0 (8.0-10.0)				
4	IF NECESSARY, ADJ TO PH 8.0-10.0 ASSUME 50%				
	& RECORD: PH ASSUME 77%				

11/29

EQUIP MENT		PAGE 02 OF 02 CG 20 CODE BT-427-D (J)	USE LBS	N-CODE	ACCT LBS
	14	HEAT TO 170-175 DEG F IN 20-25 MIN			
		RECORD: TIME START ----- TEMP <u>170</u> *F			
SV	15	RUN IN V-313 FROM S 8 THRU A 20 MESH SCREEN			
4	16	STIR 10 MIN			
CONT.	17	RUN IN V-304 FROM S 11 THRU A 20 MESH			
		SCREEN			
	18	STIR 15 MIN			
	19	FLOOD TO <u>87</u>			
	20	STOP AGITATOR			
		SV 200 202 204 210 213 261			
		S19 77" 87" 88" 74" 52" 60"			
		GAL 5205 5150 5174 5143 5153 5220			
		START 3:00 PM 11:00 AM			
		FIN 11:00 AM 1:00 PM			
		OPTR 322 301			