
ONE
GALLON
O'BRIEN'S
Satin Finish
(A SEMI-GLOSS ENAMEL)
PLUM TINT
made with patented
Pre-Shrunk
Thermolyzed Oils
MADE IN U.S.A. • MANUFACTURED BY THE O'BRIEN CORPORATION • SOUTH BEND, INDIANA

SATIN FINISH

REGISTERED
REG'N. No. 1513
DATE 12-6-51

• This rich, eggshell finish is ideally suited for interior use on wood, metal, brick, plaster, wallboard, etc. and over any old painted surfaces that are in good condition. It combines the glare-free beauty of flat paint with the fullness and richness of enamel.

• O'Brien's Satin Finish is easy to apply. It is easy working, long wearing and unexcelled in hiding power. Its uniform, dull lustre finish is highly washable and gives years of service. Satin Finish is available in fourteen colors and is a Keyed Color Finish. Dries overnight.

DIRECTIONS

"STIR THOROUGHLY BEFORE USE"

• *Before painting* — sandpaper all rough surfaces thoroughly. Fill all cracks and nail holes. Shake contents in the can well before opening and stir well after the can is opened. Apply Satin Finish to a clean, dry surface with a good, soft bristle brush.

• NEW PLASTER, CANVAS, AND WALLBOARD — Three coats are necessary for a good job. Apply one coat of Liquid Velvet Primer.

Inflammable—Keep away from fire.

Follow with a second coat of Liquid Velvet Primer tinted to approximate the finish color. Complete the job with a coat of Satin Finish.

• OLD PAINTED WALLS — If the walls are in bad condition, apply two coats—one coat of Liquid Velvet Primer tinted to approximate the finish color and one coat of Satin Finish. If the walls are in good, clean condition and the color is not to be radically changed, apply only one coat of Satin Finish.

• NEW WOOD — Three coats are required for a good job. First apply one coat of O'Brien's White Surfacer and follow with two coats of Satin Finish.

• PREVIOUSLY PAINTED WOOD, AND NEW METAL — Apply one or two coats of Satin Finish, whichever is required for a satisfactory job.

• *NOTE — All undercoats in any of the above systems may be thinned 10% with pure Turpentine. Apply Satin Finish for finish coat just as it comes from the can. However, should it prove to be too heavy, thin with pure Turpentine.*

THE O'BRIEN CORPORATION
SOUTH BEND INDIANA

49 TOC 001139