

Occupational Safety and Health Administration

N/A = Not Applicable.

MATERIAL SAFETY DATA SHEET

PLAINTIFF'S EXHIBIT

SH-1867

Required under USDL Safety and Health Regulations for Ship Repairing,
Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)**SECTION I**

MANUFACTURER'S NAME Garlock, Inc.		EMERGENCY TELEPHONE NO: (315) 597-4811
ADDRESS (Number, Street, City, State, and ZIP Code) 1666 Division Street, Palmyra, New York 14522		
CHEMICAL NAME AND SYNONYMS N/A	TRADE NAME AND SYNONYMS Style 8748 Compressed Asbestos Sheet	
CHEMICAL FAMILY N/A	FORMULA N/A	

SECTION II - HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS		N/A	BASE METAL		N/A
CATALYST		N/A	ALLOYS		N/A
VEHICLE		N/A	METALLIC COATINGS		N/A
SOLVENTS		N/A	FILLER METAL PLUS COATING OR CO.	LUX	N/A
ADDITIVES		N/A	OTHERS		N/A
OTHERS		N/A			
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES				%	TLV (Units)
Style 8748 contains about 73% of Chrysotile (White) Asbestos.					
It also contains a Nitrile elastomer. The elastomer does not					
present a hazard in itself, but there is a possibility that					
acrylonitrile monomer may be generated on burning the product.					
(See Attached Sheet)					

SECTION III - PHYSICAL DATA

BOILING POINT (°F.)	N/A	SPECIFIC GRAVITY (H ₂ O=1)	N/A
VAPOR PRESSURE (mm Hg.)	N/A	PERCENT, VOLATILE BY VOLUME (%)	N/A
VAPOR DENSITY (AIR=1)	N/A	EVAPORATION RATE (_____ =1)	N/A
SOLUBILITY IN WATER	Insoluble		
APPEARANCE AND ODOR	Dark grey to black sheet or gasket - slight odor.		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used)	N/A	FLAMMABLE LIMITS	N/A	Lel	Uel
EXTINGUISHING MEDIA Water, foam, carbon dioxide, dry chemical.					
SPECIAL FIRE FIGHTING PROCEDURES None. When fire involves large quantities of product, self contained breathing apparatus should be used due to smoke produced and possible production of acrylonitrile monomer fumes.					
UNUSUAL FIRE AND EXPLOSION HAZARDS None. Produces considerable smoke and fumes when large quantities are involved in a fire. Burning may generate some acrylonitrile monomer fumes.					

LAM 004781

SECTION V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE N/A to the sheet. For free asbestos fibers: Not more than 2 fibers longer than 5 micrometers per cubic centimeter of air.

EFFECTS OF OVEREXPOSURE

N/A to the sheet.

EMERGENCY AND FIRST AID PROCEDURES

N/A to the sheet.

SECTION VI - REACTIVITY DATA

STABILITY

UNSTABLE

CONDITIONS TO AVOID

STABLE

X

Direct flame will ignite elastomer compound.

INCOMPATIBILITY (Materials to avoid)

Avoid storage with strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS Carbon monoxide, under certain conditions. Possibly some acrylonitrile monomer fumes. There may be others unknown to us.

HAZARDOUS POLYMERIZATION

MAY OCCUR

CONDITIONS TO AVOID

WILL NOT OCCUR

X

None.

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

No special action.

WASTE DISPOSAL METHOD

(See Attached Sheet)

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (Specify type)

No special requirement. Mouth and nose mask

may be worn when cutting large quantities.

VENTILATION

LOCAL EXHAUST

No special requirement.

SPECIAL

None

MECHANICAL (General)

No special requirement.

OTHER

None.

PROTECTIVE GLOVES

Not required.

EYE PROTECTION As generally good practice, safety glasses may be worn.

OTHER PROTECTIVE EQUIPMENT

Not required.

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Store in clean, dry place away from

strong oxidizing agents.

OTHER PRECAUTIONS

Asbestos is bonded by elastomer compound, however, protect against un-

necessary release of fiber when cutting or handling. See OSHA Regulations

(29CFR, Paragraph 1910.1001).

GPO 934-110

Form OSHA-20

Rev. May 72

NOTE: The information furnished herein is accurate to the best of our knowledge but no warranty, express or implied, is made.

Prepared by:

H. R. Hughes, Senior Chemist

2/13/81

DPMC-02419

LAM 004782

Addendum to Section II Form OSHA-20

It is our view that our product No. 8748 is exempted from OSHA labeling requirements in accordance with the provisions of (29 C.F.R. §1910.1001(g)(2)(i)). Nonetheless, our product No. 8748 carries the OSHA warning label so that our customers may be alerted to the fact that they are purchasing a product containing asbestos.

Addendum to Section VII Form OSHA-20

Waste Disposal Method

Place waste in a plastic bag. Since the asbestos in this product is secured with a binder and is not friable or loose, we do not consider that it presents any disposal hazard under ordinary circumstances. However, the user is responsible for complying with existing local, state and/or federal hazardous waste disposal regulations .

LAM 004783

DPMC-02420

MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing,
Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)

SECTION I

MANUFACTURER'S NAME Garlock Inc.		EMERGENCY TELEPHONE NO. (315) 597-4811
ADDRESS (Number, Street, City, State, and ZIP Code) 1666 Division Street, Palmyra, New York 14522		
CHEMICAL NAME AND SYNONYMS N/A		TRADE NAME AND SYNONYMS Style 7705 Compressed Asbestos Sheet
CHEMICAL FAMILY N/A	FORMULA N/A	

SECTION II - HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS		N/A	BASE METAL		N/A
CATALYST		N/A	ALLOYS		N/A
VEHICLE		N/A	METALLIC COATINGS		N/A
SOLVENTS		N/A	FILLER METAL PLUS COATING OR CORE FLUX		N/A
ADDITIVES		N/A	OTHERS		N/A
OTHERS		N/A			
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES				%	TLV (Units)
Style 7705 typically contains about 60% of Crocidolite (Blue)					
Asbestos. The asbestos is bound and encapsulated by an					
elastomeric binder which inhibits the generation of free					
asbestos fiber or dust. (See Attached Sheet					

SECTION III - PHYSICAL DATA

BOILING POINT (°F.)	N/A	SPECIFIC GRAVITY (H ₂ O=1)	N/A
VAPOR PRESSURE (mm Hg.)	N/A	PERCENT VOLATILE BY VOLUME (%)	N/A
VAPOR DENSITY (AIR=1)	N/A	EVAPORATION RATE (_____ =1)	N/A
SOLUBILITY IN WATER	Insoluble		
APPEARANCE AND ODOR Grey-black colored sheet or gasket -- slight odor.			

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used)	N/A	FLAMMABLE LIMITS	N/A	Lel	Uel
EXTINGUISHING MEDIA Water, foam, carbon dioxide, dry chemical.					
SPECIAL FIRE FIGHTING PROCEDURES None. When fire involves large quantities of product, self contained breathing apparatus would be desirable due to smoke produced.					
UNUSUAL FIRE AND EXPLOSION HAZARDS None. Produces thick smoke when large quantities are burned.					

LAM 004784

SECTION V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE N/A to the sheet. For free asbestos fibers: Not more than 2 fibers longer than 5 micrometers per cubic centimeter of air.
EFFECTS OF OVEREXPOSURE N/A to the sheet.

EMERGENCY AND FIRST AID PROCEDURES N/A to the sheet.

SECTION VI - REACTIVITY DATA

STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	X	Direct flame will ignite elastomer compound.
INCOMPATIBILITY (Materials to avoid) Avoid storage with strong oxidizing agents.			
HAZARDOUS DECOMPOSITION PRODUCTS Carbon monoxide under certain circumstances. There may be others unknown to us.			
HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID
	WILL NOT OCCUR	X	None

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED No special action.

WASTE DISPOSAL METHOD Normal landfill; waste may be placed in plastic bag to reduce generation of asbestos fiber to a minimum.

(See Attached Sheet)

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (Specify type) No special requirement. Mouth and nose mask may be worn when cutting large quantities.

VENTILATION	LOCAL EXHAUST	No special requirement.	SPECIAL	None.
	MECHANICAL (General)	No special requirement.	OTHER	None.

PROTECTIVE GLOVES Not required. EYE PROTECTION AS generally good practice, safety glasses may be worn.

OTHER PROTECTIVE EQUIPMENT Not required.

LAM 004785

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING Store in clean, dry place away from strong oxidizing agents.

OTHER PRECAUTIONS Asbestos is bonded by elastomer compound, however, protect against unnecessary release of fiber when cutting or handling. See OSHA Regulations (29CFR, Paragraph 1910.1001).

PAGE (2)

Form OSHA-20

NOTE: The information furnished herein is accurate to the best of our knowledge, but no warranty, express or implied, is made.

Prepared by: H. R. Hughes
H. R. Hughes, Senior Chemist

DPMC-02422 3/12/81

Addendum to Section II Form OSHA-20

It is our view that our product No. 7705 is exempted from OSHA labeling requirements in accordance with the provisions of (29 C.F.R. §1910.1001(g)(2)(i)). Nonetheless, our product No. 7705 carries the OSHA warning label so that our customers may be alerted to the fact that they are purchasing a product containing asbestos.

Addendum to Section VII Form OSHA-20

Waste Disposal Method

Place waste in a plastic bag. Since the asbestos in this product is secured with a binder and is not friable or loose, we do not consider that it presents any disposal hazard under ordinary circumstances. However, the user is responsible for complying with existing local, state and/or federal hazardous waste disposal regulations .

LAM 004786

DPMC-02423

Not Applicable Occupational Safety and Health Administration

MATERIAL SAFETY DATA SHEETRequired under USDL Safety and Health Regulations for Ship Repairing,
Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)**SECTION I**

MANUFACTURER'S NAME Garlock Inc.		EMERGENCY TELEPHONE NO. (315) 597-4811
ADDRESS (Number, Street, City, State, and ZIP Code) 1666 Division Street, Palmyra, New York 14522		
CHEMICAL NAME AND SYNONYMS N/A		TRADE NAME AND SYNONYMS Style 7021 Compressed Asbestos Sheet
CHEMICAL FAMILY N/A	FORMULA N/A	

SECTION II - HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS		N/A	BASE METAL		N/A
CATALYST		N/A	ALLOYS		N/A
VEHICLE		N/A	METALLIC COATINGS		N/A
SOLVENTS		N/A	FILLER METAL PLUS COATING OR CORE FLUX		N/A
ADDITIVES		N/A	OTHERS		N/A
OTHERS		N/A			
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES				%	TLV (Units)
Style 7021 contains in excess of 80% of Chrysotile (White)					
Asbestos. Typically the level is about 82%.					
The asbestos					
is bound and encapsulated by an elastomeric binder which					
inhibits the generation of free asbestos fiber or dust.					

(See Attached Sheet)

SECTION III - PHYSICAL DATA

BOILING POINT (°F.)	N/A	SPECIFIC GRAVITY (H ₂ O=1)	N/A
VAPOR PRESSURE (mm Hg.)	N/A	PERCENT VOLATILE BY VOLUME (%)	N/A
VAPOR DENSITY (AIR=1)	N/A	EVAPORATION RATE (_____ =1)	N/A
SOLUBILITY IN WATER	Insoluble		
APPEARANCE AND ODOR	Black colored sheet or gasket - slight odor.		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used)	N/A	FLAMMABLE LIMITS	N/A	Lel	Uel
EXTINGUISHING MEDIA	Water, foam, carbon dioxide, dry chemical.				
SPECIAL FIRE FIGHTING PROCEDURES	None. When fire involves large quantities of product, self contained breathing apparatus would be desirable due to smoke produced.				
UNUSUAL FIRE AND EXPLOSION HAZARDS	None. Produces thick smoke when large quantities are burned.				

LAM 004787

SECTION V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE N/A to the sheet. For free asbestos fibers: Not more than 2 fibers longer than 5 micrometers per cubic centimeter of air.
EFFECTS OF OVEREXPOSURE N/A to the sheet.

EMERGENCY AND FIRST AID PROCEDURES N/A to the sheet.

SECTION VI - REACTIVITY DATA

STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	X	Direct flame will ignite elastomer compound.

INCOMPATIBILITY (Materials to avoid) Avoid storage with strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS Carbon monoxide under certain circumstances. There may be others unknown to us.

HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID
	WILL NOT OCCUR	X	None

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED No special action.

WASTE DISPOSAL METHOD See attached sheet.

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (Specify type) No special requirement. Mouth and nose mask may be worn when cutting large quantities.

VENTILATION	LOCAL EXHAUST	No special requirement.	SPECIAL	None
	MECHANICAL (General)	No special requirement.	OTHER	None

PROTECTIVE GLOVES Not required. EYE PROTECTION AS generally good practice, safety glasses may be worn.

OTHER PROTECTIVE EQUIPMENT Not required.

SECTION IX - SPECIAL PRECAUTIONS

LAM 004788

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING Store in clean, dry place away from strong oxidizing agents.

OTHER PRECAUTIONS Asbestos is bonded by elastomer compound, however, protect against unnecessary release of fiber when cutting or handling. See OSHA Regulations (29CFR, Paragraph 1910.100(d) 24-110)

NOTE: The information furnished herein is accurate to the best of our knowledge, but no warranty, express or implied, is made.

Prepared by: H. R. Hughes, Senior Chemist DPMC-02425 2/13/81

Form OSHA-20
Rev. May 72

Addendum to Section II Form OSHA-20

It is our view that our product No. 7091 is exempted from OSHA labeling requirements in accordance with the provisions of (29 C.F.R. §1910.1001(g)(2)(i)). Nonetheless, our product No. 7021 carries the OSHA warning label so that our customers may be alerted to the fact that they are purchasing a product containing asbestos.

Addendum to Section VII Form OSHA-20

Waste Disposal Method

Place waste in a plastic bag. Since the asbestos in this product is secured with a binder and is not friable or loose, we do not consider that it presents any disposal hazard under ordinary circumstances. However, the user is responsible for complying with existing local, state and/or federal hazardous waste disposal regulations .

LAM 004789

DPMC-02426

723
November 6, 1978 AS2207

1. R. P. Frutiger - Review
2. J. D. Ransdell

JDR/si

J. D. RANDELL

LAM 004790

DPMC-02427

D R A F T

November 6, 1978

ASBESTOS

Asbestos is a mineral silicate occurring naturally as a variously colored fiber. The health hazard of asbestos dust was described in a previous bulletin. Briefly, it can produce a type of lung disease (asbestosis), lung cancer, mesothelioma (cancer of the chest lining), and cancer of the stomach, colon and rectum. Cigarette smokers are particularly susceptible to the effects of asbestos.

These effects develop slowly, and usually do not become evident until many years after initial exposure. The rise in asbestos-related diseases is now occurring in shipyard workers and others exposed to asbestos during World War II and the following years. The asbestos hazard was not recognized at that time and exposures were much severer than they are today. The incidence and seriousness of asbestos health effects has prompted the Department of Health, Education, and Welfare (HEW) to issue notifications to some 400,000 physicians. Also in the past year, HEW has stepped up efforts to inform industry and workers on the subject.

LAM 004791

Several months ago an asbestos safety order was issued in the Refinery (S-125) and was updated in the Chemical Plant (S-35). The safety order covers the required work practices for handling

DPMC-02428

and disposal of asbestos-containing materials.

The phase-out of asbestos-containing materials began in 1973 with asbestos insulation. Substitution for asbestos materials has proceeded but is not yet complete. Materials such as transite and some types of cement, mortar, plaster, etc. contain asbestos. Also the asbestos type insulation is still intact in various process areas. It is especially important for those who handle these materials and who remove old insulation to follow all precautions. Prevent exposure to yourself and others.

An annual medical examination program for insulators and others who have worked with asbestos extensively was initiated several years ago. Employees who regularly work with asbestos materials shall be retained annually using the asbestos safety order.

Asbestos-related disease can be traced to the inadequate work practices which resulted in substantial exposure. Today's work practices are stringent but should effectively eliminate the risk of future asbestos health problems.

LAM 004792

DPMC-02429

N/A = Not Applicable.
Occi

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

Form Approved
OSHA No. 44-R1387

MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing,
Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)

SECTION I

MANUFACTURER'S NAME <u>Garlock, Inc.</u>		EMERGENCY TELEPHONE NO. <u>(315) 597-4811</u>
ADDRESS (Number, Street, City, State, and ZIP Code) <u>1666 Division Street, Palmyra, New York 14522</u>		
CHEMICAL NAME AND SYNONYMS <u>N/A</u>	TRADE NAME AND SYNONYMS <u>Styles 900 & 7735 Compressed Asbestos Sheet</u>	
CHEMICAL FAMILY <u>N/A</u>	FORMULA <u>N/A</u>	

SECTION II - HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS		N/A	BASE METAL		N/A
CATALYST		N/A	ALLOYS		N/A
VEHICLE		N/A	METALLIC COATINGS		N/A
SOLVENTS		N/A	FILLER METAL PLUS COATING OR CORE FLUX		N/A
ADDITIVES		N/A	OTHERS		N/A
OTHERS		N/A			
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES				%	TLV (Units)
Style 900/7735 contains about 83% of Chrysotile (White)					
Asbestos. The asbestos is bound and encapsulated by an					
elastomeric binder which inhibits generation of free asbestos					
fiber or dust. (See Attached Sheet)					

SECTION III - PHYSICAL DATA

BOILING POINT (°F.)	N/A	SPECIFIC GRAVITY (H ₂ O=1)	N/A
VAPOR PRESSURE (mm Hg.)	N/A	PERCENT VOLATILE BY VOLUME (%)	N/A
VAPOR DENSITY (AIR=1)	N/A	EVAPORATION RATE (_____ =1)	N/A
SOLUBILITY IN WATER	Insoluble		
APPEARANCE AND ODOR	Pale grey-cream colored sheet or gasket - slight characteristic odor.		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used)	N/A	FLAMMABLE LIMITS	N/A	LeI	UeI
EXTINGUISHING MEDIA	Water, foam, carbon dioxide, dry chemical.				
SPECIAL FIRE FIGHTING PROCEDURES	None. When fire involves large quantities of product, self contained breathing apparatus would be desirable due to smoke produced.				
UNUSUAL FIRE AND EXPLOSION HAZARDS	None. Produces thick smoke when large quantities are burned.				

LAM 004793

SECTION V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE N/A to the sheet. For free asbestos fibers: Not more than 2 fibers longer than 5 micrometers per cubic centimeter of air.
EFFECTS OF OVEREXPOSURE N/A to the sheet.

EMERGENCY AND FIRST AID PROCEDURES N/A to the sheet.

SECTION VI - REACTIVITY DATA

STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	X	Direct flame will ignite elastomer compound.

INCOMPATIBILITY (Materials to avoid) Avoid storage with strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS

Carbon monoxide under certain circumstances. There may be others unknown

HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID
	WILL NOT OCCUR	X	to us. None

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED
No special action.

WASTE DISPOSAL METHOD
Normal landfill; waste may be placed in plastic bag to reduce generation of asbestos fiber to a minimum.

SEE ATTACHED SHEET

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (Specify type) No special requirement. Mouth and nose mask may be worn when cutting large quantities.

VENTILATION	LOCAL EXHAUST	SPECIAL	None
	MECHANICAL (General)	OTHER	None

PROTECTIVE GLOVES Not required. EYE PROTECTION As generally good practice, safety glasses may be worn.

OTHER PROTECTIVE EQUIPMENT Not required.

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING Store in clean, dry place away from strong oxidizing agents.

OTHER PRECAUTIONS

Asbestos is bonded by elastomer compound, however, protect against unnecessary release of fiber when cutting or handling. See OSHA Regulations (29CFR, Paragraph 1910.1001) 934.110

NOTE: The information furnished herein is accurate to the best of our knowledge but no warranty, express or implied, is made.

Prepared by: H. R. Hughes, Senior Chemist

LAM 004794

8/6/79

DPMC-02431

Addendum to Section II Form OSHA-20

It is our view that our product No. ⁹⁰⁰¹7735 is exempted from OSHA labeling requirements in accordance with the provisions of (29 C.F.R. §1910.1001(g)(2)(i)). Nonetheless, our product No. ⁷⁴⁶¹7735 carries the OSHA warning label so that our customers may be alerted to the fact that they are purchasing a product containing asbestos.

Addendum to Section VII Form OSHA-20

Waste Disposal Method

Place waste in a plastic bag. Since the asbestos in this product is secured with a binder and is not friable or loose, we do not consider that it presents any disposal hazard under ordinary circumstances. However, the user is responsible for complying with existing local, state and/or federal hazardous waste disposal regulations .

LAM 004795

DPMC-02432