

SUBJECT: Sistersville Plant Philosophies and Guidelines for Maintaining/
Removing Asbestos Insulation

Following is the Sistersville Plant's philosophy concerning asbestos insulation:

"The Plant does not intend to enter into a program for the wholesale removal of installed insulation for no other reason than that it contains asbestos."

Reasoning:

In many cases the risks created by the removal would far exceed any which would arise if the insulation were left in place effectively sealed.

Maintenance Guidelines:

- (1) If the installed asbestos insulation has damage that can be patched, and sealed, do it rather than complete removal.
- (2) If the installed asbestos insulation can be effectively sealed, do it versus replacement.
- (3) If a repair job on pipe, equipment, or a tank requires the removal of asbestos insulation in order to get at the work, then replace the asbestos insulation with approved, non-asbestos type insulation. Proper procedures must be followed during the removal, and proper disposal methods used for the asbestos insulation.
- (4) Maintenance Coordinators should fill out their Shop Order requests with all the above in mind.

Information and Clarification:

The Sistersville Plant is 30 years old, and being that old the piping and other equipment were originally insulated with asbestos. Much of the asbestos has been removed and safely disposed of in the landfill as repairs and replacements have occurred. No insulation containing asbestos has been purchased since 1973, but asbestos still remains. Some of you have expressed concern that plant personnel are continually exposed to airborne asbestos fibers from unsealed insulation and dust from the entire plant surface.

Monitoring conducted in a number of Plant locations, including some having unsealed asbestos nearby, has shown below the detectable limit of the analytical method. Sampling downwind of asbestos removal operations shows the same non-detectable levels. We believe this is because the insulator mechanics carefully follow the procedures that have been developed to prevent contamination of the environment and themselves while removing asbestos.

Information and clarification

~~Being a 30 year~~

The Sisterville Plant is 30 years old and being that ~~old~~ the piping and other equipment were ^{originally} insulated with asbestos. Much of the asbestos has been removed and safely disposed of in the land fill, as repairs and re-placements have occurred. ^{no asbestos insulation containing white asbestos} ~~asbestos~~ still remains. Some of you have expressed concern that ~~the~~ plant personnel are continually exposed to airborne asbestos fibers from unsealed insulation, and dust from the entire plant surface.

has been purchased since 1973,

Monitoring ~~conducted over a period of~~ conducted in a number of plant locations, including some having unsealed asbestos nearby, has shown below the detectable limit of the analytical method. Sampling downwind of asbestos removal operations shows the same non-detectable levels. We believe this is because the insulator mechanics carefully follow the procedures that have been developed to prevent contamination of the environment ^{and clean up} while removing asbestos.

are confident

UNION CARBIDE CORPORATION

Silicones and Urethane Intermediates

Sistersville, WV

MEMO TO: W. V. Summers

COPY TO: A. W. Boyd
Department Heads
1st Line Maintenance Supervisors
2nd Line Maintenance Supervisors
Maintenance Coordinators

DATE: July 18, 1984

SUBJECT: Sistersville Plant Philosophies and Guidelines for
Maintaining/Removing Asbestos Insulation

Following is the Sistersville Plant's philosophy concerning
asbestos insulation:

"The Plant does not intend to enter into a program for the
wholesale removal of installed insulation for no other reason than
that it contains asbestos."

Reasoning:

In many cases the risks created by the removal would far
exceed any which would arise if the insulation were left in place
effectively sealed.

Maintenance Guidelines:

- (1) If the installed asbestos insulation has damage that can be
patched, and sealed, do it rather than complete removal.
- (2) If the installed asbestos insulation can be effectively sealed,
do it versus replacement.
- (3) If a repair job on pipe, equipment, or a tank requires the re-
moval of asbestos insulation in order to get at the work, then
replace the asbestos insulation with approved, non-asbestos type
insulation. Proper procedures must be followed during the re-
moval, and proper disposal methods used for the asbestos insula-
tion.
- (4) Maintenance Coordinators should fill out their Shop Order re-
quests with all the above in mind.


Clarification of the Safety & Health Insulation Capital Project:

"This project provides for the upgrade of critical insulation in
the Steam Plant and Monomers Areas. Existing exposed asbestos insula-
tion will be repaired or replaced to insure a weatherproof system and
correct the safety and health concern of exposed airborne asbestos."

Sistersville Plant Philosophies & Guidelines
for Maintaining/Removing Asbestos Insulation

Page 2 of 2

Many believe this project was for the "elimination of asbestos insulation" and this is not the case. It turns out that much of the insulation is beyond repair, and for this reason is being replaced.


George W. Wulfert
Maintenance/Materials
Management Dept. Head

GWG/tas

