

INTER-OFFICE LETTER

FROM Chicago #6 OFFICE Lacquer DEPT.

FOR Cleveland OFFICE DATE March 12, 1969
 MR. F. I. Zehnder SUBJECT Label Cautions
 REFER TO LETTER OF DICTATED BY

We would appreciate answers to the following questions:

1. Should both label cautions AND red label stickers (see attached) be applied to fives and drums containing material with -
 - a. A flash point below 80°F
 - b. A flash point above 80°F
2. What label cautions should be applied to fives and drums when the proper label cautions are not available? The Technical Laboratory has instructed us to apply whatever label caution is specified on the formula. We only stock cautions 1b, 2ba, 6bw, and 6b (see attached). Are all the many others, such as 1a, 1at, 1aw, to 6c, 6ct, and 6cw available? If so, how or where can they be obtained? If not, what label cautions are acceptable replacements, especially for material requiring a "C", (flash point below 20°F), such as 6c, 6ct, 6cw, etc.

E. T. Kulish
 E. T. Kulish/db
 Production Supervisor
 Attach.

J. A. Hutchinson, Superintendent
 Chicago Lacquer Department

But 3 - add 1

1) ~~Flash point below 80°F~~ -
 not flashy below 80°F require both.
 no 80°F only Drums
 Label Cautions.

2) ~~Red label~~ at 3-add replace
 this - 4 label to each
 all cautions.

SPRING FORWARD IN '67

N23352