



Dow U.S.A.

The Dow Chemical Company
P.O. Box 150
Plaquemine, Louisiana 70765-0150

May 5, 1992

Daniel Cortez Petrin Building 4106
Eddie Guillory Petrin

cc: Wayne Russell Cellulose Building 4501

Asbestos Monitoring

Enclosed are sample results for potential exposure to asbestos.

The OSHA 8-hour permissible exposure limit for asbestos is 0.2 f/cc >5 microns and the 30-minute short term exposure limit is 1 f/cc >5 microns.

The results displayed are based on sampling duration.

The data sheet shows the results of exposure using two methods, the Limit of Detection (LOD) and the Limit of Quantitation (LOQ). Included on the data sheet is an explanation of the method Limit of Quantitation.

Thank you,

Darlene S. Creel
Industrial Hygiene
Ext. 6181
Building 3502-E

Attachment

dsc

PRODUCED FOR THE ASBESTOS DATABASE

DATE: 5-7-92

MASTER No. 433871

DO A 114983
CONFIDENTIAL

EXPOSURE GUIDELINES

8-HR. TWA LIMIT - 0.20 FIB/CC

30-MINUTE LIMIT = 1.0 FIB/CC

LIMIT OF DETECTION = 7 FIB/MM2

LIMIT OF QUANTITATION = 100 FIB/MM2

**LOD

***LOQ

ASBESTOS MONITORING DATA RESULTS: CELLULOSE 1992

DATE	SAMPLE #	PERSONNEL	DESCRIPTION	DUR(MIN)	VOL(L)	** LOD FIB/CC	***LOQ FIB/CC
4/30/92	13534	*551-17-4410	Insulator: Removing asbestos insulation from an exchange on wash deck - WET METHOD USED	30	76	0.03	<0.51

* The proper protective clothing was worn during the job. North 7700 Respirator with HEPA filters were worn during the job.

Note: The Limit of Quantitation has been defined as 100 Fibers/MM2 using the minimum fiber loading criteria specified. In the NIOSH analytical method 7400, the stated range of the method is 100 to 1300 Fibers/MM2 filter area. Although samples below this range can be analyzed, the method has not been validated below 100 Fibers/MM2. However, the NIOSH method 7400 also establishes the estimated Limit of Detection as 7 Fibers/MM2 (Reference OSHA Std. 1910.1001, Appendix B). Based on this information, we will establish 100 Fibers/MM2 filter area as our Limit of Quantitation and 7 Fibers/MM2 filter area as our Limit of Detection (which is more representative of the actual fibers present) for asbestos monitoring. We will report both Limit of Quantitation and Limit of Detection.

If only Limit of Quantitation were expressed, the minimum reportable result would calculate to be 0.04 Fibers per cc for an 8-hr. Time weighted average sample at a flow rate of 2 liters per minute and 0.6 fibers per cc for a 30 minute time weighted average short term sample at a flow rate of 2 liters per minute.

DO A 114984
CONFIDENTIAL



LOUISIANA DIVISION INDUSTRIAL HYGIENE SAMPLE RECORD

SAMPLE No 13534

PLANT/DEPT. Cellulose
MONITORING FOR: Asbestos fibersDATE 4-30-92
OTHER CHEMICALS PRESENT: _____

SAMPLE COLLECTION MEDIA:

- ☐ BADGE NO. _____ TYPE _____
TEMP/HUMIDITY: (REQUIRED FOR BADGES) _____
☐ CHARCOAL TUBE SIZE _____
☒ FILTER CASSETTE SIZE 25 mm
☐ SILICA TUBE SIZE _____
☐ DRAGER TUBE TYPE _____
☐ OTHER _____

PUMP SERIAL NO. 2817
CALIBRATION DEVICE: ☐ BUBBLEMETER ☐ ROTAMETER
☐ OTHER _____

PUMP FLOW RATE CALIBRATION:

BEGIN: 1. 2514 2503
2. 2502
3. 2508BEGINNING FLOW RATE AVG. 2504 ☒ CC/MIN ☐ L/MIN 2506ENDING: 1. 2599
2. 2592 2506
3. 2586ENDING FLOW RATE AVG. 2586 ☒ CC/MIN ☐ L/MIN 2592SAMPLE AVERAGE FLOW RATE 2295 2549TIME STARTED 11:00 AM
TIME STOPPED 11:30 AM
TOT. RUNNING TIME(MIN) 30 minSAMPLE VOLUME (AVG FLOW X RUN TIME) 69 76SHIFT: ☒ 8 HR. ☐ 12 HR. ☒ PERSONNEL SAMPLE ☐ AREA SAMPLE

- ☐ FULL SHIFT TWA
☐ STEL/TASK

EMPLOYEE NAME Gary Brooks
EMPLOYEE I.D.# 551-170440
JOB CLASSIFICATION insulator
IH JOB CODE # _____
CONTRACTOR COMPANY Petco Corp.RESPIRATOR USED? ☒ YES ☐ NO
RESPIRATOR MODEL / CANISTER TYPE North 7700 w/hgac
☐ MOUTH-BIT ☐ DUST ☒ HALF-FACE
☐ FULL-FACE ☐ AIR-LINE ☐ SCBADESCRIPTION OF AREA SAMPLED/JOB PERFORMED DURING MONITORING Removing Asbestos insulation from
a exchange on wash duct - wet methodANALYTICAL REPORT REFERENCE # 20-3363
ANALYTICAL RESULTS: 1.962 0.03

* RESTRICTED FOR USE WITHIN DOW ONLY *

VP-124

FORM FILLED IN BY: Eddie MilkeyDO 4 114985
CONFIDENTIAL