

bulletin

BUILDING MATERIALS DIVISION Charleston, South Carolina

To: All Southeastern Division Customers,
Salesmen, Managers and Office List

General Bulletin #71
August 18, 1982

Effective August 23, 1982

PLAINTIFF'S EXHIBIT

BIR-810

PRICE CHANGE

CEMENTS AND COATINGS

Effective with all shipments made on and after August 23, 1982,
the following prices will apply:

<u>Product</u>	<u>Gallons Per Unit</u>	<u>Price Per Gallon</u>	<u>Unit List Price</u>
Bird Buca Adhesive	5	2.331	11.655
Plastic Cement	1	2.942	2.942
	5	2.291	11.455
Quick Set Cement	1	3.279	3.279
	5	2.358	11.790
Fibre Roof Coating (Fibrated)	5	2.291	11.455
Foundation Coating	5	2.264	11.320
Reflecto Coat (Aluminum Surfacing)	5	5.234	26.170
Roof Primer	5	2.385	11.925
*Climatite Emulsified Asphalt	5	1.998	9.990
*Waterdyke Emulsion	5	1.998	9.990

*No Change

Prices subject to change without notice.

BIRD & SON, inc.

BIRD 013171

BIRD & SON, inc.
PRODUCT LINE - CHARLESTON, SC

PRODUCT GROUPS CEMENTS AND COATINGS

Reflecto-Coat TM Aluminum Surfacing	Easy to apply brush or spray. Use over surface coated with asphalt emulsion or mineral surfaced roofing in good condition. Also for metal roofs, concrete, or masonry. Use on mobile home and truck-trailer roofs. Coverage - Appx. 1 gallon per 100 sq. ft.	Container size 5 gals. Appx. wt. per pkg. 48 lbs. ASTM D-2824
Fibre Roof Coating (Fibrated)	Reinforced with asbestos fibre-protects asphalt or metal roofing, dampproofing concrete in home, farm or factory. Coverage - 1 to 2 gallons per 100 sq. ft.	Container size 5 gals. Appx. wt. per pkg. 46 lbs. ASTM D-2823
Foundation Coating	Black, Non-Fibrated	Container size 5 gals. Appx. wt. per pkg. 43 lbs. ASTM - None
Asphalt Plastic Cement	Indispensable for Flashings around Chimneys, Sidewalls, Vent Pipes, Skylights and General Caulking. Will make any valley tight.	Container size 1 gal. 6 Cans Per Case Pkg. Appx. wt. per pkg. 66 lbs. Container size 5 gals. Appx. wt. per pkg. 54 lbs. ASTM D-2822
Concrete Roof Primer	Pure asphalt-base primer for building a bonding foundation on concrete decks or walls. Use as first coat before application of bonding agent under a built-up roof. Use also under application of roof coatings or other asphalt coatings. Sets in an hour under average conditions. Coverage - Appx. 1 gallon per 100 sq. ft.	Container size 5 gals. Appx. wt. per pkg. 44 lbs. ASTM D-41-73

BIRD & SON, inc.
PRODUCT LINE - CHARLESTON, SC

PRODUCT GROUPS CEMENTS AND COATINGS

Buca ^R Adhesive	Heavy bodied asphaltic base cement. Quick setting. Recommended for cold process built-up roof construction, instead of hot asphalt, for bonding the plies together. Coverage - 2 gallons per 100 sq. ft. per brushing between plies.	Container size 5 gals. Appx. wt. per pkg. 42 lbs. ASTM D-3019
Climatite ^R Emulsified Asphalt	A clay type emulsion used as a top seal on cold application roofs. Coverage - 3 gallons per 100 sq. ft.	Container size 5 gals. Appx. wt. per pkg. 46 lbs. ASTM D-1227, Type I
Waterdyke ^R Asphalt Emulsion	Specially formulated for use on dead level roofs or those subject to severe moisture conditions. Coverage - 3 gallons per 100 sq. ft.	Container size 5 gals. Appx. wt. per pkg. 48 lbs. ASTM D-1227, Type I
Asphalt Quick-Set TM Cement	Recommended for sealing laps on prepared asphalt roofing applied by concealed nailing method. It may also be used for exposed nailing method.	Container size 5 gals. Appx. wt. per pkg. 46 lbs. ASTM D-2822

Notes