

RADE"

W.C.

TIME TESTED

PAINTS · VARNISHES · LACQUERS · ENAMELS

13

WORKS

ANY
A *

DIXIE-TONE FLAT

A soft, velvety finish. Preferred for bedrooms, living rooms and dining rooms. Easily washed and rubbed. Dixie-Tone Flat can be used on all plaster surfaces—rough, smooth or finished, on types of wall board, burlap, interior metal, sidewalls and ceilings and wood surfaces.

DIRECTIONS


Stir well before using.

OLD PAINTED SURFACES. Where old surface has become porous and worn from repeated washings, first apply a coat of Interior Base Coat. Then apply the new paint given for New Unpainted Surfaces. If old paint is in good condition one coat of flat is usually sufficient but if two coats are necessary apply a first coat of a mixture of one part Interior Base Coat and two parts of Dixie-Tone Flat of color selected. All to dry overnight and then apply a coat of Dixie-Tone Flat as it comes from the can.


NEW UNPAINTED SURFACES. New plaster and cement surfaces that show indications of alkali or active lime by test with phenolphthalein should be given a wash coat of Zinc Subphosphate solution (two pounds of commercial Zinc Subphosphate dissolved in one gallon of water) and then allowed to dry. Then apply one coat of Interior Base Coat. Allow overnight for drying, then apply one or two coats of Dixie-Tone Flat. Two coats are suggested for highest class work. Where two coats are applied use a mixture of one quart Interior Base Coat to the gallon of Dixie-Tone Flat for the first coat. Then apply the final and finishing coat without reduction. Wood or metal surfaces do not require a primer.

COVERAGE.—New work 300 to 400 square feet per gallon. Old work 500 to 550 square feet per gallon.

"DIXIE MADE FOR DIXIE TRADE"



Climatic



TIME

PAINTS • VARNISHES •

DIXIE-TONE

FLAT

4700 WHITE

THE AMERICAN PAINT WORKS

DIVISION

THE GLIDDEN COMPANY

★ NEW ORLEANS, LOUISIANA ★

DIXIE-TONE
A soft, velvety finish. Preferred for bedrooms, nurseries, and children's rooms. Gives a smooth, or unfinished, all types of wall, ceilings and wood surfaces.

DIRECT

OLD PAINTED SURFACES.—Where old or repeated washings first apply a coat of Int. given for New Unpainted Surfaces. If old is usually sufficient but if two coats are necessary Interior Base Coat and two parts of this overnight and then apply a coat of Dixie-Tone. **NEW UNPAINTED SURFACES.**—New plaster of alkali or other lime, by test with pH. (pH. 10 or above) or ammonia (pH. 11 or above) or water (pH. 7 or below). Make sure the surface is clean. Allow overnight for drying, then apply Coat. Two coats are suggested for highest class mixture of one quart Interior Base Coat to one quart of Dixie-Tone. Then apply the final and finishing surface. Do not require a primer. **COVERAG.**—New work 300 to 400 square feet per gallon.



Pyrene 64% → Lithium 84.6%
Calcium Carbide 7.7%
Magnesium Silicate 7.7%

GLD31599