



file

Inter Office

Personnel and Organization Staff

July 9, 1980

Mr. Arthur S. Tobiassen
Environmental and Safety Manager
Troy Tractor General Office

PLAINTIFF'S EXHIBIT

FD-193

Subject: Parts Labeling for Asbestos-Containing Clutch Plates

The enclosed plastic bag is used to package small tractor clutch plates. Previous compositional analysis indicated that dust from these clutch plates contained 14 - 15 percent chrysotile; a form of asbestos.

Appropriate warning should be given to users whether they are Ford employees or members of the general public (refer to attached OSHA excerpt). Please advise of any revisions or modifications you recommend.

Mark R. Francis

Mark R. Francis, Industrial Hygienist
Industrial Hygiene & Toxicology Department
Employee Health Services

jb
Enclosures

SCF-FORD-2067

5007 0955


PRODUCED BY FORD



Tractor Parts

202227

2 PCS.



FORD TRACTOR OPERATIONS, TROY, MICHIGAN 48064

CPR. © FORD MOTOR COMPANY, 1967

CONTAINER MADE IN U.S.A.
CONTENTS MADE IN U.S.A.

3007 0956

PRODUCED BY FORD

Title 29—Labor

Chapter XVII—Occupational Safety and Health Administration § 1910.1001

section, samples shall be of such frequency and pattern as to represent with reasonable accuracy the levels of exposure of employees. In no case shall the sampling be done at intervals greater than 6 months for employees whose exposure to asbestos may reasonably be foreseen to exceed the limits prescribed by paragraph (b) of this section.

(3) **Environmental monitoring**—(1) Samples shall be collected from areas of a work environment which are representative of the airborne concentrations of asbestos fibers which may reach the breathing zone of employees. Samples shall be collected on a membrane filter of 0.8 micrometer porosity mounted in an open-face filter holder. Samples shall be taken for the determination of the 8-hour time-weighted average airborne concentrations and of the ceiling concentrations of asbestos fibers.

(11) **Sampling frequency and patterns**. After the initial determinations required by paragraph (f)(1) of this section, samples shall be of such frequency and pattern as to represent with reasonable accuracy the levels of exposure of the employees. In no case shall sampling be at intervals greater than 6 months for employees whose exposure to asbestos may reasonably be foreseen to exceed the exposure limits prescribed in paragraph (b) of this section.

(4) **Employee observation of monitoring**. Affected employees, or their representatives, shall be given a reasonable opportunity to observe any monitoring required by this paragraph and shall have access to the records hereof.

(g) **Caution signs and labels**. (1) **Caution signs**. (i) **Posting**. Caution signs shall be provided and displayed at each location where airborne concentrations of asbestos fibers may be in excess of the exposure limits prescribed in paragraph (b) of this section. Signs shall be posted at such a distance from such a location so that an employee may read the signs and take necessary protective steps before entering the area marked by the signs. Signs shall be posted at all approaches

to areas containing excessive concentrations of airborne asbestos fibers.

(ii) **Sign specifications**. The warning signs required by paragraph (g)(1)(i) of this section shall conform to the requirements of 20" x 14" vertical format signs specified in § 1910.145(d)(4), and to this subdivision. The signs shall display the following legend in the lower panel, with letter sizes and styles of a visibility at least equal to that specified in this subdivision.

Legend	Notation
Asbestos	1 Sans Serif, Gothic or Block
Dust Hazard	1/2 Sans Serif, Gothic or Block
Avoid Breathing Dust	1/2 Gothic
Wear Assigned Protective Equipment	1/2 Gothic
Do Not Remain In Area Unless Your Work Requires It	1/2 Gothic
Breathing Asbestos Dust May Be Hazardous To Your Health	14 point Gothic

Spacing between lines shall be at least equal to the height of the upper of any two lines.

(2) **Caution labels**—(1) **Labeling**. Caution labels shall be affixed to all raw materials, mixtures, scrap, waste, debris, and other products containing asbestos fibers, or to their containers, except that no label is required where asbestos fibers have been modified by a bonding agent, coating, binder, or other material so that during any reasonably foreseeable use, handling, storage, disposal, processing, or transportation, no airborne concentrations of asbestos fibers in excess of the exposure limits prescribed in paragraph (b) of this section will be released.

(ii) **Label specifications**. The caution labels required by paragraph (g)(2)(i) of this section shall be printed in letters of sufficient size and contrast as to be readily visible and legible. The label shall state:

CAUTION

Contains Asbestos Fibers

Avoid Creating Dust

Breathing Asbestos Dust May Cause Serious Bodily Harm

(h) **Housekeeping**—(1) **Cleaning**. All external surfaces in any place of em-

ployment shall be maintained free of accumulations of asbestos fibers if, with their dispersion, there would be an excessive concentration.

(2) **Waste disposal**. Asbestos waste, scrap, debris, bags, containers, equipment, and asbestos-contaminated clothing, consigned for disposal, which may produce in any reasonably foreseeable use, handling, storage, processing, disposal, or transportation airborne concentrations of asbestos fibers in excess of the exposure limits prescribed in paragraph (b) of this section shall be collected and disposed of in sealed impermeable bags, or other closed, impermeable containers.

(1) **Recordkeeping**—(1) **Exposure records**. Every employer shall maintain records of any personal or environmental monitoring required by this section. Records shall be maintained for a period of at least 20 years and shall be made available upon request to the Assistant Secretary of Labor for Occupational Safety and Health, the Director of the National Institute for Occupational Safety and Health, and to authorized representatives of either.

(2) **Employee access**. Every employee and former employee shall have reasonable access to any record required to be maintained by paragraph (1)(1) of this section, which indicates the employee's own exposure to asbestos fibers.

(3) **Employee notification**. Any employee found to have been exposed at any time to airborne concentrations of asbestos fibers in excess of the limits prescribed in paragraph (b) of this section shall be notified in writing of the exposure as soon as practicable but not later than 5 days of the finding. The employee shall also be timely notified of the corrective action being taken.

(j) **Medical examinations**—(1) **General**. The employer shall provide or make available at his cost, medical examinations relative to exposure to asbestos required by this paragraph.

(2) **Preplacement**. The employer shall provide or make available to each of his employees, within 30 calendar days following his first employment in an occupation exposed to air-