



Tiger Brand High Temperature



**TB1-106
HIGH TEMPERATURE**

**Type AVA
Power Cable
Table F**

**Single Conductor
2000 VOLTS**

Date Issued: June 1972

Applications:

For use in open or conduit general power wiring around ovens, furnaces, tenter frames, boiler rooms or steel mills, or for any similar power application where the insulation may be subjected to heat, heat and moisture, oil, grease, corrosive fumes or fire hazard.

This cable can withstand continuous high temperature without deterioration and has sufficient moisture-repelling properties to meet normal moisture conditions due to condensation in conduit installations. If parts of a circuit are liable to be submerged in water for long periods, however, lead sheathed AVL cables (Table EL) should be utilized.

Conductor Temperature

110°C (230°F)

Specifications:

Copper Conductor—Annealed uncoated

Insulation—Asbestos

Varnish cambric

Outer Covering—Asbestos braid

Finish—Black FHM (flame, heat, and moisture-resistant) compound

This product is manufactured and tested in accordance with Underwriters' Laboratories requirements and conforms to IPCEA Pub. S-28-357 where applicable.



Size AWG or MCM	Number of Strands	Insulation Thickness Mils			Asbestos Braid Thickness Mils	Ø Approx. Outer Diameter Inches	Approx. Net Weight Lbs. per 1,000 Ft.	Standard Packing
		Inner Asbestos	V.C.	2nd Asbestos				
14	7	15	60	25	45	.36	69	500' Coil
12	7	15	60	25	45	.38	81	500' Coil
10	7	15	60	25	45	.41	99	500' Coil
8	7	15	60	25	45	.44	126	1000' Reel
6	7	15	60	25	45	.47	167	1000' Reel
4	7	15	60	25	45	.52	231	1000' Reel
2	7	15	60	25	45	.58	323	1000' Reel
1	19	20	60	30	45	.64	398	1000' Reel
1/0	19	20	60	30	45	.68	486	1000' Reel
2/0	19	20	60	30	45	.73	580	1000' Reel
3/0	19	20	60	30	45	.78	704	1000' Reel
4/0	19	20	60	30	45	.84	854	1000' Reel
250	37	25	60	40	45	.92	1020	500' Reel
300	37	25	60	40	45	.97	1190	500' Reel
350	37	25	60	40	45	1.02	1360	500' Reel
400	37	25	60	40	45	1.07	1530	500' Reel
500	37	25	60	40	45	1.15	1870	500' Reel
600	61	30	60	40	45	1.24	2210	500' Reel
750	61	30	60	40	45	1.35	2720	500' Reel
1000	61	30	60	40	45	1.50	3540	500' Reel

Ø Diameter subject to $\pm 5\%$ tolerance. For ampacities refer to Page TB1-801.

Cable Identification via Surface Legend showing "U.S.S. Corp. Tiger Brand UL Type AVA (size) 2000 Volts Table F"

ARCHITECTS/ENGINEERS

How to specify this product for purchasing purposes:

"Cable shall be U. S. Steel Tiger Brand TB1-106 or approved equal"

U.S.S. AND TIGER BRAND ARE REGISTERED TRADEMARKS.





Tiger Brand High Temperature



**TB1-106
HIGH TEMPERATURE**

**Type AVA
Power Cable
Table F**

**Single Conductor
2000 VOLTS**

Date Issued: June 1972

Applications:

For use in open or conduit general power wiring around ovens, furnaces, tenter frames, boiler rooms or steel mills, or for any similar power application where the insulation may be subjected to heat, heat and moisture, oil, grease, corrosive fumes or fire hazard.

This cable can withstand continuous high temperature without deterioration and has sufficient moisture-repelling properties to meet normal moisture conditions due to condensation in conduit installations. If parts of a circuit are liable to be submerged in water for long periods, however, lead sheathed AVL cables (Table EL) should be utilized.

Conductor Temperature

110°C (230°F)

Specifications:

- Copper Conductor—Annealed uncoated
- Insulation—Asbestos
- Varnish cambric
- Outer Covering—Asbestos braid
- Finish—Black FHM (flame, heat, and moisture-resistant) compound

This product is manufactured and tested in accordance with Underwriters' Laboratories requirements and conforms to IPCEA Pub. S-28-357 where applicable.



Size AWG or MCM	Number of Strands	Insulation Thickness Mils			Asbestos Braid Thickness Mils	Approx. Outer Diameter Inches	Approx. Net Weight Lbs. per 1,000 Ft.	Standard Packing
		Inner Asbestos	V.C.	2nd Asbestos				
14	7	15	60	25	45	.36	69	500' Coil
12	7	15	60	25	45	.38	81	500' Coil
10	7	15	60	25	45	.41	99	500' Coil
8	7	15	60	25	45	.44	126	1000' Reel
6	7	15	60	25	45	.47	167	1000' Reel
4	7	15	60	25	45	.52	231	1000' Reel
2	7	15	60	25	45	.58	323	1000' Reel
1	19	20	60	30	45	.64	398	1000' Reel
1/0	19	20	60	30	45	.68	486	1000' Reel
2/0	19	20	60	30	45	.73	580	1000' Reel
3/0	19	20	60	30	45	.78	704	1000' Reel
4/0	19	20	60	30	45	.84	854	1000' Reel
250	37	25	60	40	45	.92	1020	500' Reel
300	37	25	60	40	45	.97	1190	500' Reel
350	37	25	60	40	45	1.02	1360	500' Reel
400	37	25	60	40	45	1.07	1530	500' Reel
500	37	25	60	40	45	1.15	1870	500' Reel
600	61	30	60	40	45	1.24	2210	500' Reel
750	61	30	60	40	45	1.35	2720	500' Reel
1000	61	30	60	40	45	1.50	3540	500' Reel

Ⓢ Diameter subject to $\pm 5\%$ tolerance. For ampacities refer to Page TB1-801.

Cable Identification via Surface Legend showing "U.S.S. Corp. Tiger Brand UL Type AVA (size) 2000 Volts Table F"

ARCHITECTS/ENGINEERS

How to specify this product for purchasing purposes:

"Cable shall be U. S. Steel Tiger Brand TB1-106 or approved equal"

U.S.S. AND TIGER BRAND ARE REGISTERED TRADEMARKS.

