SINCE 1875

O'BRIEN'S



Pen-tex

RUBBER BASE

CONCRETE FLOOR ENAMEL

GREEN

MANUFACTURED BY THE O'BRIEN CORPORATION

SOUTH BEND, IND. · BALTIMORE, MD. · OKLAHOMA CITY, OKLA. · SAN FRANCISCO, CAL. · LOS ANGELES, CAL.

49 TOC 001124

O'BRIEN'S PEN-TEX CONCRETE FLOOR ENAMEL

O'Brien's Pen-Tex is a new rubber base floor enamel recommended for use on interior and exterior concrete and cement surfaces—on floors and walls. It is particularly recommended for concrete surfaces where alkali conditions prevail and for use on surfaces exposed to grease, oil, moisture, acids, soaps, etc. It is easy to apply and dries in 1-4 hours to a hard, durable, lustrous coating. It is ideal for basement floors, walls, concrete steps and for use in dairies, filling stations, garages, schools, food markets, institutions. May also be used for swimming pools.

SURFACE PREPARATION

Surfaces must be clean — free from moisture, wax, soap, grease, loose dirt, oil.

Old painted surfaces should be washed with a non-soap cleaner, rinsed with clean water and allowed to dry thoroughly.

Extremely smooth cement floors should be etched to provide sufficient "grip" for the paint. Use a solution consisting of one part muriatic acid to eight parts water. Use wooden bucket and apply with a stiff fiber brush. Allow solution to remain on surface until bubbling stops — then rinse off with clean water and allow to dry.

THE O'BRIEN CORPORATION
SOUTH BEND, IND. OKLAHOMA CITY, OKLA.
BALTIMORE, MD. SAN FRANCISCO, CALIF.
LOS ANGELES, CALIF.

DIRECTIONS FOR USE

Stir the paint thoroughly before using and stir contents occasionally during use.

Apply the material with a good brush — flowing out to a uniform coating.

No special primers are required under Pen-Tex. Apply direct to concrete or cement surfaces.
Unpainted Surfaces — apply two coats of Pen-Tex. If possible, allow 12-24 hours drying between coats.

Painted Surfaces — apply one or two coats of Pen-Tex, whichever is necessary for a satisfactory job.

Note — the material comes ready to use. If thinning is necessary, use a small amount of turpentine. Pen-Tex covers approximately 500 square feet per gallon, one coat.

CAUTION — Gasoline and certain petroleum solvents might soften paint film. If spilled on Pen-tex coated surfaces, "blot" up with rag or waste material. Don't wipe or rub too hard or too excessively.

CAUTION! COMBUSTIBLE
KEEP AWAY FROM HEAT AND OPEN FLAME
CONTAINS LEAD OR OTHER COMPOUNDS HARMFUL IF EATEN
Do not apply on toys, furniture or interior surfaces which might be chewed by children. Use with adequate ventilation. Avoid breathing vapor or spray mist. Avoid prolonged contact with the skin. Wash thoroughly after handling and before eating or smoking. Keep container closed when not in use.

PENTEX—GREEN

Pigment		11.39%
C. P. Chrome Green	84.61%	
Aluminum Silicate	15.39%	
	100.00%	
Vehicle		88.61%
Chlor. sated Rubber	25.30%	
Polychlorinated Polyphenyl	8.07%	
Mineral Spirits	50.72%	
Hydrocarbon Naphtha	32.80%	
China Wood Oil	1.88%	
	100.00%	

ONE GALLON

49 TOC 001125