

NEG. NO. O-6A

TRADEMARK FILE INFORMATION

Trademark:	Rexalt
Trademark Owner:	The Flintkote Company
Last Assignee:	None
Date of First Use in Commerce:	July 15, 1928
Registration No.:	619,303
Date Trademark Registered:	January 17, 1956
Size of Label in Trademark File:	N/A

Receipt of Pictured Label by Patent Office: N/A

**CAUTION—COMBUSTIBLE
MIXTURE.**
N. Y. F. D. C. of A. #1516

DIRECTIONS
Clean surface carefully by sweeping or scraping. Be sure surface is dry. Stir well before using. May be applied by brush or spray. Use large brush, or if sprayed, use a nozzle designed for heavy-bodied material. Apply at rate of 3 gallons per 100 sq. ft. of surface. Best results are obtained with heavy coating. Do not heat material over 100°F. Do not heat over direct flame.

Keep container covered when not in use. Follow manufacturer's instructions in use of spray equipment.

NOTICE: Our recommendations for the use of this product are based on experience and tests believed to be reliable. However, since the use of the product is beyond its control, the manufacturer hereby expressly disclaims all warranties either expressed or implied.

THE FLINTKOTE COMPANY
Building Materials Division
30 ROCKEFELLER PLAZA
NEW YORK 20, N. Y.



FLINTKOTE

REXALT[®]
ROOF COATING

FIBRATED

For resurfacing old composition roofs,
steep or flat.

CAUTION—Combustible Mixture. Use in well ventilated place. AVOID prolonged breathing of vapor. AVOID prolonged or repeated contact with skin. HARMFUL if swallowed.

A superior roof coating, containing Celaprite, blended with highest quality Asphalts, Mica, Petroleum Spirits and Asbestos Fiber to provide extra long life, weathering, and strength properties.

USES
For resurfacing all types of roofs whether steep or flat. Recommended especially for resurfacing of old composition roofs, as a rejuvenator, lengthening life by putting back into the old roofing those properties which have been destroyed by exposure. Also as a protection against deterioration through exposure, insuring greater service. An excellent product for relining gutters, coating metal roofs, and as an exterior waterproofing of foundation walls. Use whenever a durable asphalt coating is required. Do not apply over tar coatings that have not fully oxidized.

This Underwriters' Label is applicable only when this material is used in the construction of built-up roof coverings.

Underwriters' Laboratories, Inc.
MAKES
ROOFING MATERIAL
FOR BUILT-UP COVERINGS
R-1190 BU-49,163

MANUFACTURER OF AMERICA'S BROADEST LINE OF BUILDING PRODUCTS
5 GALLONS