ONE

GALLON

O'BRIEN'S

Flexico®

QUICK DRYING SUPER-ENAMEL

OYSTER WHITE

CONTAINS O'BRIEN'S EXCLUSIVE Alki-therm

MADE IN U. S. A. • MANUFACTURED BY THE O'BRIEN CORPORATION • SOUTH BEND, INDIANA

40 TOO SOFT

O'BRIEN'S FLEXICO ENAMEL

Flexico is America's finest Enamel. Made with exclusive *Alki-Therm*, it may be used indoors or outdoors—on wood, plaster, metal, cement, hard wallboard, etc. Excellent for walls, woodwork, cabinets, furniture, boats, automobiles, etc. Use Brilliant White (non-yellowing) for touching up chipped stoves and refrigerators. Easy to apply. Dries quickly. Extremely durable and weather resistant. Apply with brush or spray.

DIRECTIONS FOR USE

NEW WOOD — apply one coat of O'Brien's White Surfacer or Double-Up Undercoat and finish with one or two coats of Flexico.

NEW PLASTER — apply one coat of O'Brien's Liquid Velvet Wall Primer and Sealer. Finish with one or two coats of Flexico.

NEW METAL — one coat of O'Brien's White Surfacer or Double-Up Undercoat followed with one or two coats of Flexico.

OLD PAINTED SURFACES IN GOOD CONDITION — one or two coats of Flexico.

GENERAL DIRECTIONS — mix the enamel thoroughly before using and apply with a soft bristle brush. Sand and dust carefully between coats.

REGISTERED
REGN. No. 45172
DATE 10-11-37

SURFACE PREPARATION — surfaces should be clean and dry, free of wax, oil, grease or soap compounds.

THINNING — Flexico is ready for use. If it appears too heavy and easier brushing is desired, thin accordingly with turpentine or O'Brien's Reducit.

DRYING — allow overnight drying between coats.

TINTING — Flexico Brilliant White may be tinted to light shades with O'Brien's Pure Liquid Oil colors.

CAUTION — don't intermix Flexico with conventional type enamels.

WARNING! FLAMMABLE
Keep Away from
Heat, Sparks, and Open Flame
CONTAINS LEAD OR OTHER
COMPOUNDS HARMFUL IF EATEN
Do not apply on toys, furniture or interior surfaces which might be chewed by children. Use with adequate ventilation. Avoid breathing vapor or spray mist. Avoid prolonged contact with skin. Wash thoroughly after handling and before eating or smoking. Keep container closed when not in use.

Flexico Super Enamel – Tint Base

Pigment		30.47%
	Titanium Dioxide	66.69%
	Titanium Calcium Pigment	33.31%
		100.00%
Vehicle		69.53%
	Varnish	16.78%
	**Alkyd Resin Solution	73.13%
	Mineral Spirits and Driers	10.09%
		100.00%
	*Non Volatile Modified Phenolic Resin, China Wood Oil	55.02%
	Volatile Mineral Spirits	44.98%
		100.00%
	*Non Volatile: Soya Bean Oil Modified Alkyd Resin	60.00%
	Volatiles Mineral Spirits	40.00%
		100.00%

Less than 5% Tinting Colors Added.

THE O'BRIEN CORPORATION

SOUTH BEND, IND. — BALTIMORE, MD.
OKLA. CITY, OKLA. — SAN FRANCISCO, CAL.

49 TOC 001165