

**MATERIAL SAFETY DATA SHEET****EXXON CHEMICAL AMERICAS**

A Division of EXXON CHEMICAL COMPANY, A Division of EXXON CORPORATION

ISOPAR C SOLVENTPAGE: 1
DATE PREPARED: APR 3, 1995
MSDS NO.: 92834642**SECTION 1 CHEMICAL PRODUCT AND COMPANY IDENTIFICATION****PRODUCT NAME:** ISOPAR C Solvent**CHEMICAL NAME:**

Not Applicable: Blend

CAS 64741-66-8

CHEMICAL FAMILY:

Synthetic Isoparaffinic Hydrocarbon

PRODUCT DESCRIPTION:

Clear colorless liquid.

CONTACT ADDRESS:**EXXON CHEMICAL AMERICAS**

P.O. BOX 3272, HOUSTON, TEXAS 77253-3272

**** EMERGENCY TELEPHONE NUMBERS: (24 Hours) ****
**** CHEMTREC (800) 424-9300 ****
**** EXXON CHEMICAL AMERICAS (800) 726-2015 ******NON EMERGENCY TELEPHONE NUMBERS : (8am-5pm M-F)****FOR HEALTH AND SAFETY INFORMATION CALL : (713) 870-6884****FOR GENERAL PRODUCT INFORMATION CALL : (713) 870-6000****SECTION 2 COMPOSITION/INFORMATION ON INGREDIENTS**

This product is hazardous as defined in 29 CFR 1910.1200.

OSHA HAZARD

Flammable

SECTION 3 HAZARDS IDENTIFICATION**POTENTIAL HEALTH EFFECTS****EYE CONTACT:**

Slightly irritating but does not injure eye tissue.

SKIN CONTACT:

Frequent or prolonged contact may irritate and cause dermatitis.

Low order of toxicity.

Skin contact may aggravate an existing dermatitis condition.

INHALATION:

High vapor/aerosol concentrations (greater than approximately 1000 ppm) are irritating to the eyes and the respiratory tract, may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects, including death.

INGESTION:

Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly progressing to death.

Minimal toxicity.

SECTION 4 FIRST AID MEASURES**EYE CONTACT:**

Flush eyes with large amounts of water until irritation subsides. If irritation persists, get medical attention.

Continues on page 2

DO A 061850
CONFIDENTIAL



MATERIAL SAFETY DATA SHEET

EXXON CHEMICAL AMERICAS

A Division of EXXON CHEMICAL COMPANY, A Division of EXXON CORPORATION

ISOPAR C SOLVENT

PAGE: 2
DATE PREPARED: APR 3, 1995
MSDS NO.: 92834642

SKIN CONTACT:

Flush with large amounts of water; use soap if available.
Remove grossly contaminated clothing, including shoes, and launder before reuse.

INHALATION:

Using proper respiratory protection, immediately remove the affected victim from exposure. Administer artificial respiration if breathing is stopped. Keep at rest. Call for prompt medical attention.

INGESTION:

If swallowed, DO NOT induce vomiting. Keep at rest. Get prompt medical attention.

SECTION 5 FIRE-FIGHTING MEASURES

FLASHPOINT: 18 Deg F. METHOD: TCC NOTE: Typical
FLAMMABLE LIMITS: LEL: 1.5 UEL: 11.6 @ 77 Deg F. NOTE: Approximate
AUTOIGNITION TEMPERATURE: 750 Deg F. NOTE: Approximate

GENERAL HAZARD

Extremely Flammable, material will readily ignite at ambient temperatures. Static Discharge, material can accumulate static charges which can cause an incendiary electrical discharge.

"Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner, or properly disposed of.

FIRE FIGHTING

Use water spray to cool fire exposed surfaces and to protect personnel. Shut off "fuel" to fire. If a leak or spill has not ignited, use water spray to disperse the vapors.

Either allow fire to burn under controlled conditions or extinguish with foam or dry chemical. Try to cover liquid spills with foam. Avoid spraying water directly into storage containers due to danger of boilover.

This liquid is volatile and gives off invisible vapors. Either the liquid or vapor may settle in low areas or travel some distance along the ground or surface to ignition sources where they may ignite or explode.

DECOMPOSITION PRODUCTS UNDER FIRE CONDITIONS

No unusual

SECTION 6 ACCIDENTAL RELEASE MEASURES

LAND SPILL

Eliminate sources of ignition. Prevent additional discharge of material, if possible to do so without hazard. For small spills implement cleanup procedures; for large spills implement cleanup procedures and, if in public area, keep public away and advise authorities. Also, if this product is subject to CERCLA reporting (see Section 15 REGULATORY INFORMATION) notify the National Response Center.

Prevent liquid from entering sewers, watercourses, or low areas. Contain spilled liquid with sand or earth. Do not use combustible materials such as sawdust.

Recover by pumping (use an explosion proof or hand pump) or with a

Continues on page 3

DO A 061851
CONFIDENTIAL

**MATERIAL SAFETY DATA SHEET****EXXON CHEMICAL AMERICAS**

A Division of EXXON CHEMICAL COMPANY, A Division of EXXON CORPORATION

ISOPAR C SOLVENTPAGE: 3
DATE PREPARED: APR 3, 1995
MSDS NO.: 92834642

suitable absorbent.

Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.

WATER SPILL

Eliminate sources of ignition. Warn occupants and shipping in surrounding and downwind areas of fire and explosion hazard and request all to stay clear.

Remove from surface with suitable adsorbents. If allowed by local authorities and environmental agencies, sinking and/or suitable dispersants may be used in non-confined waters.

Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.

SECTION 7 STORAGE AND HANDLING**ELECTROSTATIC ACCUMULATION HAZARD:**

Yes, use proper grounding procedure

STORAGE TEMPERATURE, °F:

Ambient

STORAGE/TRANSPORT PRESSURE, mmHg:

Atmospheric

LOADING/UNLOADING TEMPERATURE, °F:

Ambient

LOADING/UNLOADING VISCOSITY, cSt:

0.9

STORAGE AND HANDLING:

Keep container closed. Handle and open containers with care.

Store in a cool, well ventilated place away from incompatible materials.

Do NOT handle or store near an open flame, heat or other sources of ignition. Protect material from direct sunlight.

Material will accumulate static charges which may cause an electrical spark (ignition source). Use proper grounding procedures.

Do NOT pressurize, cut, heat, or weld containers. Empty product containers may contain product residue. Do NOT reuse empty containers without commercial cleaning or reconditioning.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION**EXPOSURE CONTROLS**

The use of mechanical dilution ventilation is recommended whenever this product is used in a confined space, is heated above ambient temperatures, or is agitated.

Use explosion-proof ventilation equipment.

PERSONAL PROTECTION

For open systems where contact is likely, wear safety glasses with side shields, long sleeves, and chemical resistant gloves.

Where contact may occur, wear safety glasses with side shields.

Where concentrations in air may exceed the limits given in this Section and engineering, work practice or other means of exposure reduction are not adequate, NIOSH/MSHA approved respirators may be necessary to prevent overexposure by inhalation.

WORKPLACE EXPOSURE GUIDELINES**EXXON RECOMMENDS THE FOLLOWING OCCUPATIONAL EXPOSURE LIMITS:**

400 ppm total hydrocarbon based on composition.

Continues on page 4

DO A 061852
CONFIDENTIAL

**MATERIAL SAFETY DATA SHEET****EXXON CHEMICAL AMERICAS**

A Division of EXXON CHEMICAL COMPANY, A Division of EXXON CORPORATION

ISOPAR C SOLVENTPAGE: 4
DATE PREPARED: APR 3, 1995
MSDS NO.: 92834642**SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES**

SPECIFIC GRAVITY, at °F: 0.70 at 60	VAPOR PRESSURE, mmHg at °F: 63 at 68 Approximate
SOLUBILITY IN WATER, wt. % at °F: Less than 0.01 at 77	VISCOSITY OF LIQUID, cSt at °F: 0.7 at 77 Approximate
SP. GRAV. OF VAPOR, at 1 atm (Air=1): 3.90 Calculated	FREEZING/MELTING POINT, °F: Less than -76
EVAPORATION RATE, n-Bu Acetate=1: 5.6 Approximate	BOILING POINT, °F: 205 to 225

SECTION 10 STABILITY AND REACTIVITY**STABILITY:**

Stable

CONDITIONS TO AVOID INSTABILITY:

Not Applicable

HAZARDOUS POLYMERIZATION:

Will not occur

CONDITIONS TO AVOID HAZARDOUS POLYMERIZATION:

Not Applicable

MATERIALS AND CONDITIONS TO AVOID INCOMPATIBILITY:

Strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS:

None

SECTION 11 TOXICOLOGICAL INFORMATION

Please refer to Section 3 for available information on potential health effects.

SECTION 12 ECOLOGICAL INFORMATION

No specific ecological data are available for this product. Please refer to Section 6 for information regarding accidental releases and Section 15 for regulatory reporting information.

SECTION 13 DISPOSAL CONSIDERATIONS

Please refer to Sections 5, 6, and 15 for disposal and regulatory information.

SECTION 14 TRANSPORT INFORMATION**DEPARTMENT OF TRANSPORTATION (DOT):**

DOT SHIPPING DESCRIPTION: PETROLEUM DISTILLATE, N.O.S., 3, UN 1268, II

SECTION 15 REGULATORY INFORMATION**TSCA:**

This product is listed on the TSCA Inventory at CAS Registry Number 64741-66-8

Continues on page 5

DO A 061853
CONFIDENTIAL

**MATERIAL SAFETY DATA SHEET****EXXON CHEMICAL AMERICAS**

A Division of EXXON CHEMICAL COMPANY, A Division of EXXON CORPORATION

ISOPAR C SOLVENTPAGE: 5
DATE PREPARED: APR 3, 1995
MSDS NO.: 92834642**Clean Water Act/Oil Pollution Act:**

This product is classified as an oil under Section 311 of the Clean Water Act (40 CFR 110) and the Oil Pollution Act of 1990. Discharge or spills which produce a visible sheen on either surface water, or in waterways/sewers which lead to surface water, must be reported to the National Response Center at 800-424-8802.

CERCLA:

This product, as sold, is derived from a fraction of crude oil and is excluded from the spill reporting requirements by CERCLA Section 101(14)(F). When this product is used in a mixture or as an ingredient in another product or in a manufacturing operation, the petroleum exclusion may terminate and an accidental spill may require reporting to the National Response Center at 800-424-8802.

This product contains approximately 80% of 2,2,4 Trimethylpentane.

The reportable quantity of 2,2,4 Trimethylpentane is 1 pounds.

SARA TITLE III:

Under the provisions of Title III, Sections 311/312 of the Superfund Amendments and Reauthorization Act, this product is classified into the following hazard categories: Fire.

This information may be subject to the provisions of the Community Right-to-Know Reporting Requirements (40 CFR 370) if threshold quantity criteria are met.

This product does not contain Section 313 Reportable Ingredients.

SECTION 16 OTHER INFORMATION**HAZARD RATING SYSTEMS:**

This information is for people trained in:

National Paint & Coatings Association's (NPCA)

Hazardous Materials Identification System (HMIS)

National Fire Protection Association (NFPA 704)

Identification of the Fire Hazards of Materials

	NPCA-HMIS	NFPA 704	KEY
HEALTH	1	1	4 = Severe
FLAMMABILITY	3	3	3 = Serious
REACTIVITY	0	0	2 = Moderate
			1 = Slight
			0 = Minimal

REVISION SUMMARY:

Since March 1, 1995 this MSDS has been revised in Section(s):
7, 14, 15

REFERENCE NUMBER:

MDHA-C-25035

SUPERSEDES ISSUE DATE:

March 1, 1995

THIS INFORMATION RELATES TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. SUCH INFORMATION IS TO THE BEST OF OUR KNOWLEDGE AND BELIEF, ACCURATE AND RELIABLE AS OF THE DATE COMPILED. HOWEVER, NO REPRESENTATION, WARRANTY OR GUARANTEE IS MADE AS TO ITS ACCURACY, RELIABILITY OR COMPLETENESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY HIMSELF AS TO THE SUITABILITY AND COMPLETENESS OF SUCH INFORMATION FOR HIS OWN PARTICULAR USE. WE DO NOT ACCEPT LIABILITY FOR ANY LOSS OR DAMAGE THAT MAY OCCUR FROM THE USE OF THIS INFORMATION NOR DO WE OFFER WARRANTY AGAINST PATENT INFRINGEMENT.

LAST PAGE

DO A 061854
CONFIDENTIAL

TOTAL P.08