

MEMORANDUM

San Francisco, California
July 27, 1972

TF 110.1 islet
PLAINTIFF'S
EXHIBIT

CHV-134

OSHA ASBESTOS STANDARD

TO ALL SAFETY ENGINEERS:

The "permanent" standard for exposure to asbestos fibers was published in the June 7, 1972 Federal Register. A copy of that publication and the Environmental Health and Toxicology Section's detailed summary is attached. To briefly highlight the standard:

1. The permissible time-weighted average concentration will remain at 5 fibers/cc until 7/1/76, when it will drop to 2 fibers/cc. The maximum permissible concentration for any period of time is 10 fibers/cc.
2. Engineering controls "shall be used to meet the exposure limits." The use of respirators is limited to the time necessary to install controls, where adequate control is not feasible, or in emergencies.
3. For any removal of asbestos-containing insulation from pipes, etc., the workers must be provided with supplied-air respirators.
4. Schedule 21B respirators are only good up to 10 times the permissible fiber concentration.
5. Hand- and power-operated tools which may produce fiber concentrations in excess of the exposure limits must be provided with local exhaust ventilation system.
6. All asbestos operations must be monitored by December 7, 1972 to determine whether exposures are below the permissible limits. Periodic follow-up sampling is also required in some cases.
7. Preplacement, annual, and termination medical examinations are required for all employees who are exposed to airborne asbestos.
8. Other requirements involve caution signs, labels, protective clothing, record-keeping, notification of employees with exposure in excess of the limits, and waste disposal.

We suggest that you acquaint yourselves with all of your operations which involve asbestos, and become thoroughly familiar with the new standards. If you will send us a summary of the nature of asbestos exposures in your plants, we will advise on how to comply with item 6 above.

D. H. BARBER
D.H.B.

DETAILED SUMMARY OF ASBESTOS STANDARD

OCCUPATIONAL SAFETY & HEALTH ACT

29 CFR 1910.93a

7/20/72 S. L. Dryden

I. Permissible Exposure Limit

- A. Time weighted average (TWA)
 - 1. Effective July 7, 1972: 5 fibers, longer than 5 microns, per cubic centimeter of air (f/cc)
 - 2. Effective July 2, 1976: 2 f/cc
- B. Ceiling concentration: 10 f/cc
- C. Measurement standard: Collection on membrane filter of 0.8 micron porosity in an open-face holder, analysis by light microscopy.

II. Methods of Limiting Exposures

- A. General: Engineering controls shall be the means for achieving compliance.
- B. Specific requirements
 - 1. Local exhaust ventilation - ANSI Z9.2-1971.
 - 2. All tools for cutting, shaping, and molding asbestos materials shall be provided with local exhaust ventilation systems.
 - 3. Use wet methods "insofar as practicable".
 - 4. Handling of dry asbestos-containing cements in a loose state prohibited.
 - 5. Workers engaged in removal of asbestos-containing insulation shall be provided with supplied-air respirators and special clothing.
- C. Respirators
 - 1. Use of respirators to achieve compliance is permissible only in limited cases:
 - a. During the time necessary to install engineering controls.
 - b. Engineering controls sufficient to comply with exposure standards are not technically feasible.
 - c. In emergencies
 - 2. Respirators must approved by Bureau of Mines or NIOSH.
 - 3. Permissible range of usage
 - a. Air purifying respirators: where concentrations are expected to be up to 10 times the permissible limits.
 - b. Powered air purifying respirators: up to 100 times
 - c. Supplied-air respirators: unlimited
 - 4. Employer shall establish "respirator program" in accordance with ANSI Z88.2-1969.

5. No employer shall be assigned a job requiring the use of a respirator if judged medically unfit to function normally in one.

D. Special Clothing

1. Required when concentrations exceed 10 f/cc.
2. Coveralls, head covering, gloves, and foot coverings are included.
3. Change rooms and two separate lockers are required when concentrations exceed TWA or ceiling limits.
4. Special handling is prescribed for laundering.

III. Requirements for Monitoring Airborne Asbestos Concentrations

- A. By December 7, 1972 - survey all locations "where asbestos fibers are released"
- B. Frequency of periodic monitoring - 6 months, or more often as necessary, where exposures "may reasonably be foreseen to exceed the exposure limits".
- C. Sampling locations, both
 1. Breathing zone of workers, and
 2. Fixed locations
- D. Record keeping
 1. Must be retained at least 3 years
 2. Access must be granted to
 - a. OSHA
 - b. NIOSH
 - c. Employees (current & former)
 3. Overexposed employees must be notified of that fact.

IV. Warnings

A. Caution Signs

1. Required "at all approaches to areas containing excessive concentrations"
2. Specifies size and exact wording
3. Unlike in the temporary standard, the requirement does not include the words "danger" or "cancer".

B. Caution Labels

1. Required for raw materials, mixtures, scraps, and other products containing asbestos
2. Excludes products where asbestos is bound or coated sufficiently to prevent release of fibers
3. Specifies exact wording

V. Medical examinations

A. Timing

1. Preplacement
2. Annual
3. Termination of employment

B. Prescribed tests

1. Chest roentgenogram
2. History to elicit symptomatology of respiratory disease.
3. Forced vital capacity
4. Forced expiratory volume at one second.

C. Records

1. Must be retained at least 20 years.
2. Access must be granted to:
 - a. OSHA
 - b. NIOSH
 - c. Employee's physician

VI. Miscellaneous

- A. Waste Disposal: Any asbestos-contaminated waste which may produce dust in excess of the limits "in any reasonably foreseeable" handling, must be disposed of in sealed impermeable containers.
- B. House keeping: Workplaces must be kept free of accumulations of asbestos dust.

tions for an Occupational Exposure Standard for Asbestos by the National Institute for Occupational Safety and Health (NIOSH). Public notice was given of the receipt of the recommendations and their availability for inspection and copying. On or about February 23, 1972, the Advisory Committee on Asbestos Dust submitted its written recommendations to the Assistant Secretary of Labor for Occupational Safety and Health.

Pursuant to the notice of rule making, a hearing was held on March 14 through 17, 1972, for the purpose of receiving oral data, views, and arguments concerning the proposed standard. On or about March 31, 1972, the presiding hearing examiner certified to the Assistant Secretary of Labor for Occupational Safety and Health the record of the proceeding. The record includes prehearing written comments, a transcript of the oral presentations made at the hearing, and numerous exhibits received during the course of the hearing or within the period allowed after the close of the hearing.

The proposed standard dealt with (1) permissible concentrations of asbestos fibers; (2) methods of compliance; (3) warning signs; (4) monitoring; (5) medical examinations; and (6) recordkeeping. Each of these major proposals elicited comments, arguments, objections, and counterproposals. They all have been examined and considered.

1. *Acceptable concentrations of asbestos dust.* The proposed standard would limit occupational exposure to 8-hour time-weighted average (TWA) airborne concentrations of asbestos dust not exceeding five fibers longer than five micrometers per milliliter. Concentrations above five fibers but not to exceed 10 fibers (ceiling concentration) would be permitted up to 15 minutes in an hour, but for not more than 5 hours in any one 8-hour day.

NIOSH in effect has recommended that the five-fiber TWA and 10-fiber peak concentrations be permitted only for 2 years; thereafter, TWA concentrations should be not more than 2 fibers per cubic centimeter (cm^3) of air, and peak concentrations should not exceed 10 fibers/ cm^3 , with no time restriction. Numerous objections and counterproposals have been made, with regard to both the limits of asbestos fiber concentrations and the time periods to comply with them. Some, for example, have recommended return to a 12-fiber standard of an earlier day; i.e., a level adopted under the Walsh-Healey Public Contracts Act in 1969. Others have recommended a two-fiber standard to become effective in 6 months, then a one-fiber standard for 2 years, and finally a zero-fiber standard after 3 years. These recommendations give a fair indication of the wide spread of the counterproposals.

No one has disputed that exposure to asbestos of high enough intensity and long enough duration is causally related to asbestosis and cancers. The dispute is as to the determination of a specific level below which exposure is safe. Various studies attempting to establish quantitative relations between specific levels of

exposure to asbestos fibers and the appearance of adverse biological manifestations, such as asbestosis, lung cancer and mesothelioma, have given rise to controversy as to the validity of the measuring techniques used and the reliability of the relations attempted to be established. Because of the long lag of time between onset of exposure and biological manifestations, we have no evidence of the consequences of exposure but we do not have, in general, accurate measures of the levels of exposure occurring 20 or 30 years ago, which has given rise to these consequences. There are also controversies concerning the relative toxicity of the various kinds of asbestos, and varying hazards in different workplaces.

It is fair to say that the controversy has centered in the area between a two-fiber TWA concentration and five-fiber TWA concentration, with variations of the time needed for compliance. Many employers support a five-fiber TWA. Most medical opinion is divided between a two-fiber standard and a five-fiber standard.

In view of the undisputed grave consequences from exposure to asbestos fibers, it is essential that the exposure be regulated now, on the basis of the best evidence available now, even though it may not be as good as scientifically desirable. An asbestos standard can be re-evaluated in the light of the results of ongoing studies, and future studies, but cannot wait for them. Lives of employees are at stake.

It is concluded that there should be one minimum standard of exposure to asbestos applicable to all workplaces exposed to any kind, or mixture of kinds, of asbestos. Reasons of practical administration preclude a variety of standards for different kinds of asbestos and of workplaces. Also, while the evidence tends to show that crocidolite, for instance, is more harmful than chrysotile the evidence is not sufficient to establish separate standards for varieties of asbestos.

Because there must be one standard governing exposure to all varieties of asbestos, and in workplaces apparently more hazardous than others; because some present employees with regular exposure to asbestos have probably already accumulated great doses of asbestos fibers, due to higher levels of exposure in the past; because it appears that levels of exposure which may be safe with regard to asbestosis are not safe with regard to mesothelioma; because the statute requires the protection of every employee, even of one who may have regular exposure to asbestos during a working life which may reach, or even exceed, 40 years; and because of several other considerations which have been urged and are reflected in the record of the proceeding, the conflict in the medical evidence is resolved in favor of the health of employees. As of July 1, 1976, TWA concentrations of asbestos fibers longer than 5 micrometers will not be allowed to exceed two fibers/ cc , with a ceiling value of 10 fibers/ cc . The current TWA concentrations of five fibers, and

Title 29—LABOR

Chapter XVII—Occupational Safety and Health Administration, Department of Labor

PART 1910—OCCUPATIONAL SAFETY AND HEALTH STANDARDS

Standard for Exposure to Asbestos Dust

On December 7, 1971, an emergency temporary standard concerning exposure to asbestos fibers was published in the *Federal Register* (36 F.R. 23207). In accordance with section 6(c) (3) of the Williams-Steiger Occupational Safety and Health Act of 1970, a notice of proposed rulemaking regarding a permanent standard for exposure to asbestos fibers was published in the *Federal Register* on January 12, 1972 (37 F.R. 466). The notice invited interested persons to submit both orally and in writing, data, views, and arguments concerning the proposal.

On or about January 24, 1972, the Advisory Committee on Asbestos Dust was established and requested to make written recommendations with regard to the proposed standard on asbestos. On or about February 1, 1972, the Department of Health, Education, and Welfare transmitted to the Secretary of Labor a criteria document containing Recommendations

ceiling concentrations of 10 fibers/cc. will be permitted until July 1, 1976, during what will be a transitional period deemed necessary to allow employers to make the needed changes for coming into compliance with the more stringent standard.

The record shows that the many work operations subject to the single asbestos standard (textile, manufacturing, industrial, and marine installation, etc.) will meet varying degrees of difficulty in complying with the standard. In some plants, extensive redesign and relocation of equipment may be needed. It appears, however, the delay in the effective date of the two-fiber standard will provide all employers a reasonable time to comply. At the same time, so long as the ceiling limit is complied with, no harm is reasonably expected to result from exposures during the transitional period.

2. *Methods of compliance.* It has been pointed out by many persons, that protection against asbestos fibers is best obtained by controlling the generation of fibers first, and secondly, by controlling the dispersion of released fibers into the ambient air of the workplaces. Therefore, the standard requires feasible technological controls and appropriate work practices as the primary means of compliance. Rotation of employees as a way of meeting the TWA concentration requirement is allowed only in stated exceptional circumstances, because, as a general rule, it would be difficult to implement. Personal protective equipment, such as respirators, cannot be relied upon because, among other reasons, they may be so uncomfortable as to be burdensome, except for short periods of time. Therefore, it is expected that respirators and shift rotation will be used during the period necessary to install engineering controls and to train employees in sound work practices, but, after technological compliance has been achieved, their use must be limited to special work situations and emergencies. Where both are practicable, shift rotation is required.

3. *Labeling.* The proposed standard stopped short of requiring labeling asbestos and asbestos-containing products. The proposed standard would have required only warning signs at locations where asbestos hazards are present. However, labeling, rather than warning signs, has proved to be a point of controversy. Both NIOSH and the Advisory Committee on Asbestos Dust recommended labels for asbestos products and containers, and these recommendations became very controversial in the course of the proceeding. Many counterproposals have been made as to the language of the warning as well as to the products to be subject to the labeling requirements. Employers, in general, strongly contend that (1) finished products which effectively entrap asbestos

fibers, so that these would not be released in the normal use of the products, should not be required to be labeled; and (2) words such as "danger" and "cancer" are unwarrantedly alarming.

Both contentions have merit, and the standard has been changed accordingly.

4. *Monitoring.* The proposed standard would have required personal monitoring and environmental monitoring. Many issues have been raised concerning the availability and reliability of measuring instruments, frequency of monitoring, and conditions in which monitoring should be required. The adopted standard takes the objections into consideration. It requires periodic monitoring at intervals no longer than 6 months, thus allowing considerable time and discretion, and prescribes the use of the membrane filter method, which is an acceptable method for determination of asbestos fibers.

It has also been recommended that employees or their representatives should have an opportunity to observe the monitoring. The recommendation has been accepted.

5. *Medical examinations.* The proposed standard would only require an appropriate medical examination on a periodic basis. The generality of the proposal has attracted many objections and also many helpful comments. The recommendations of NIOSH and of the Advisory Committee on Asbestos Dust were much more specific with respect to both frequency and type of medical examinations to be required. The comments vary as to the class of employees to be examined and as to the frequency of the examinations.

The adopted standard requires medical examinations both at the beginning and the termination of employments exposed to concentrations of asbestos fibers, and also requires annual medical examinations of every employee exposed to airborne concentrations of asbestos. It has been pointed out that in certain industries, such as construction, an employee may work for several employers during the same year. Accordingly, the standard does not require either preemployment, or termination, or periodic examination of any employee who has been examined in accordance with the standard within the past year.

One question which has been raised goes to whether the employer or the employee should be allowed to choose the examining physician. The standard gives the option to the employer. Since some employers already have a medical examination program in operation, and, also, have medical departments with some expertise in the diagnosis of asbestos-related diseases, it seems more reasonable to permit them to utilize the present programs and expertise, than to permit an employee to choose a private general practitioner.

6. *Records.* The standard, as proposed and as adopted, requires maintenance of records of monitoring and of medical examinations. Most of the controversy in this area has revolved around the question whether an employer should be allowed to have access to the results of the required medical examinations. The apprehension of those who have argued against employer access is based on the expectation that some employers will use the medical examinations as a means of screening employment applicants, and worse, as grounds for discharging current employees, who show signs of being affected by exposure to asbestos. Since the purpose of the medical examinations is to monitor the health of employees exposed to the hazards of asbestos, employees cannot in reason be granted the privilege of refusing to disclose to their employers results of occupational exposure. It does not make sense to require employers to provide medical examinations if they cannot know and use the results of the examinations. For these reasons the standard provides that employers may have a restricted access to some medical information.

On the other hand, there is no intention to allow employers to abuse medical information obtained pursuant to the Act, to the detriment of employees. Therefore, the administration of the medical records requirement will be closely watched, and, in cases of abuse, appropriate action will be considered.

The issues discussed above are believed to be the major ones. Numerous other issues have been raised in the rulemaking proceedings. Some have been referred to incidentally. Many recommendations, for instance, about work practices, are so obviously meritorious that their adoption needs no exposition here. Other recommendations and many objections have not been adopted for a variety of reasons which should be manifest. Several, for instance, have recommended the use of respirators only pursuant to a variance, or in cases of emergency and occasional short-term exposures. The recommendation with respect to variances undoubtedly has many merits, but is considered administratively impractical.

Accordingly, after consideration of the whole record of the proceeding, and pursuant to sections 6 (b) and (c) and 8(c) of the Williams-Steiger Occupational Safety and Health Act of 1970 (84 Stat. 1593, 1596, 1599; 29 U.S.C. 655, 657), 29 CFR 1910.4, and to Secretary of Labor's Order No. 12-71 (36 F.R. 8754), Part 1910 of Title 29 of the Code of Federal Regulations is amended as set forth below.

(1) Section 1910.93 is amended by revising Table G-3 to read as follows:

§ 1910.93 Air contaminants.

TABLE G-3—MINERAL DUSTS

Substance	Mppcf	Mg/M ³
Silica:		
Crystalline		
Quartz (respirable).....	250'	10mg/M ³ =
	%SiO ₂ +5	%SiO ₂ +7
Quartz (total dust).....		10mg/M ³
		%SiO ₂ +3
Cristobalite: Use 1/4 the		
value calculated from the		
count or mass formula for		
quartz.		
Tridymite: Use 1/4 the value		
calculated from the for-		
mula for quartz.		
Aerophobes, including natural	20	10mg/M ³
diatomaceous earth.....		%SiO ₂
Silicates (less than 1% crys-		
ta-line silica):		
Mica.....	20	
Serpentine.....	20	
Talc.....	20	
Portland cement.....	80	
Gypsum (natural).....	15	
Coat dust (respirable fraction		2.4mg/M ³
less than 8% SiO ₂).....		or
		10mg/M ³
For more than 8% SiO ₂		%SiO ₂ +3
Inert or Nuisance Dust:		
Respirable fraction.....	15	1mg/M ³
Total dust.....	80	10mg/M ³

Note: Conversion factors—
mppcf (35.4)=million particles per cubic meter
=particles per c.c.

Millions of particles per cubic foot of air, based on
impinger samples counted by light-field techniques.

The percentage of crystalline silica in the formula
is the amount determined from airborne samples,
except in those instances in which other methods have
been shown to be applicable.

As determined by the membrane filter method at
400 X phase contrast magnification.

= Both concentration and percent quartz for the
application of this limit are to be determined from
the fraction passing a size-selector with the following
characteristics:

Aerodynamic diameter (unit density sphere)	Percent passing selector
2	90
2.5	75
3.5	50
5.0	25
10	0

The measurements under this note refer to the use of
an AEC instrument. If the respirable fraction of coal
dust is determined with a MRE the figure corresponding
to that of 2.4 Mg/M³ in the table for coal dust is 4.8 Mg/M³.

2. A new § 1910.93a is added to Part
1910, reading as follows:

§ 1910.93a Asbestos.

(a) **Definitions.** For the purpose of
this section, (1) "Asbestos" includes
chrysotile, amosite, crocidolite, tremo-
lite, anthophyllite, and actinolite.

(2) "Asbestos fibers" means asbestos
fibers longer than 5 micrometers.

(b) **Permissible exposure to airborne
concentrations of asbestos fibers—**(1)
Standard effective July 7, 1972. The
8-hour time-weighted average airborne
concentrations of asbestos fibers to
which any employee may be exposed
shall not exceed five fibers, longer than
5 micrometers, per cubic centimeter of
air, as determined by the method pre-
scribed in paragraph (c) of this section.

(2) **Standard effective July 1, 1976.**
The 8-hour time-weighted average air-
borne concentrations of asbestos fibers

to which any employee may be exposed
shall not exceed two fibers, longer than
5 micrometers, per cubic centimeter of
air, as determined by the method pre-
scribed in paragraph (c) of this section.

(3) **Ceiling concentration.** No em-
ployee shall be exposed at any time to
airborne concentrations of asbestos
fibers in excess of 10 fibers, longer than
5 micrometers, per cubic centimeter of
air, as determined by the method pre-
scribed in paragraph (c) of this section.

(c) **Methods of compliance—**(1) **En-
gineering methods.** (i) **Engineering con-
trols.** Engineering controls, such as, but
not limited to, isolation, enclosure, ex-
haust ventilation, and dust collection,
shall be used to meet the exposure limits
prescribed in paragraph (b) of this
section.

(ii) **Local exhaust ventilation.** (a)
Local exhaust ventilation and dust col-
lection systems shall be designed, con-
structed, installed, and maintained in
accordance with the American National
Standard Fundamentals Governing the
Design and Operation of Local Exhaust
Systems, ANSI Z9.2-1971, which is in-
corporated by reference herein.

(b) See § 1910.6 concerning the avail-
ability of ANSI Z9.2-1971, and the
maintenance of a historic file in connec-
tion therewith. The address of the Amer-
ican National Standards Institute is
given in § 1910.100.

(iii) **Particular tools.** All hand-op-
erated and power-operated tools which
may produce or release asbestos fibers
in excess of the exposure limits pre-
scribed in paragraph (b) of this section,
such as, but not limited to, saws, scrapers,
abrasive wheels, and drills, shall be pro-
vided with local exhaust ventilation sys-
tems in accordance with subdivision (ii)
of this subparagraph.

(2) **Work practices—**(i) **Wet methods.**
Insofar as practicable, asbestos shall be
handled, mixed, applied, removed, cut,
scored, or otherwise worked in a wet
state sufficient to prevent the emission
of airborne fibers in excess of the ex-
posure limits prescribed in paragraph
(b) of this section, unless the usefulness
of the product would be diminished
thereby.

(ii) **Particular products and opera-
tions.** No asbestos cement, mortar, coat-
ing, grout, plaster, or similar material
containing asbestos shall be removed
from bags, cartons, or other containers
in which they are shipped, without being
either wetted, or enclosed, or ventilated
so as to prevent effectively the release of
airborne asbestos fibers in excess of the
limits prescribed in paragraph (b) of
this section.

(iii) **Spraying, demolition, or removal.**
Employees engaged in the spraying of
asbestos, the removal, or demolition of
pipes, structures, or equipment covered
or insulated with asbestos, and in the
removal or demolition of asbestos in-
sulation or coverings shall be provided
with respiratory equipment in accord-
ance with paragraph (d) (2) (iii) of this
section and with special clothing in ac-
cordance with paragraph (d) (3) of this
section.

(d) **Personal protective equipment**
(1) Compliance with the exposure lim-
prescribed by paragraph (b) of this sec-
tion may not be achieved by the use
respirators or shift rotation of em-
ployees, except:

(i) During the time period necessa-
to install the engineering controls and
to institute the work practices requir-
by paragraph (c) of this section;

(ii) In work situations in which the
methods prescribed in paragraph (c) of
this section are either technically in-
feasible or feasible to an extent insuf-
cient to reduce the airborne concentra-
tions of asbestos fibers below the limit
prescribed by paragraph (b) of this
section; or

(iii) In emergencies.

(iv) Where both respirators and per-
sonnel rotation are allowed by subdivi-
sions (i), (ii), or (iii) of this subpara-
graph, and both are practicable, person-
nel rotation shall be preferred and used.

(2) Where a respirator is permitted by
subparagraph (1) of this paragraph, it
shall be selected from among those ap-
proved by the Bureau of Mines, Depart-
ment of the Interior, or the National In-
stitute for Occupational Safety and
Health, Department of Health, Educa-
tion, and Welfare, under the provisions of
30 CFR Part 11 (37 F.R. 6244, Mar. 2,
1972), and shall be used in accordance
with subdivisions (i), (ii), (iii), and (iv)
of this subparagraph.

(i) **Air purifying respirators.** A reusa-
ble or single use air purifying respirator
or a respirator described in subdivision
(ii) or (iii) of this subparagraph, shall
be used to reduce the concentrations of
airborne asbestos fibers in the respirator
below the exposure limits prescribed in
paragraph (b) of this section, when the
ceiling or the 8-hour time-weighted aver-
age airborne concentrations of asbestos
fibers are reasonably expected to exceed
no more than 10 times those limits.

(ii) **Powered air purifying respirators**
A full facepiece powered air purifying
respirator, or a powered air purifying
respirator, or a respirator described in
subdivision (iii) of this subparagraph
shall be used to reduce the concentra-
tions of airborne asbestos fibers in the
respirator below the exposure limits pre-
scribed in paragraph (b) of this section
when the ceiling or the 8-hour time-
weighted average concentrations of
asbestos fibers are reasonably expected to
exceed 10 times, but not 100 times,
those limits.

(iii) **Type "C" supplied-air respirators,**
continuous flow or pressure-demand
class. A type "C" continuous flow or pres-
sure-demand, supplied-air respirator
shall be used to reduce the concentra-
tions of airborne asbestos fibers in the
respirator below the exposure limits pre-
scribed in paragraph (b) of this section,
when the ceiling or the 8-hour time-
weighted average airborne concentra-
tions of asbestos fibers are reasonably
expected to exceed 100 times those limits.

(iv) **Establishment of a respirator pro-
gram.** (a) The employer shall establish
a respirator program in accordance with

the requirements of the American National Standards Practices for Respiratory Protection, ANSI Z88.2-1969, which is incorporated by reference herein.

b. See § 1910.6 concerning the availability of ANSI Z88.2-1969 and the maintenance of an historic file in connection therewith. The address of the American National Standards Institute is given in § 1910.100.

(c) No employee shall be assigned to tasks requiring the use of respirators if, based upon his most recent examination, an examining physician determines that the employee will be unable to function normally wearing a respirator, or that the safety or health of the employee or other employees will be impaired by his use of a respirator. Such employee shall be rotated to another job or given the opportunity to transfer to a different position whose duties he is able to perform with the same employer, in the same geographical area and with the same seniority, status, and rate of pay he had just prior to such transfer, if such a different position is available.

(3) Special clothing: The employer shall provide, and require the use of, special clothing, such as coveralls or similar whole body clothing, head coverings, gloves, and foot coverings for any employee exposed to airborne concentrations of asbestos fibers, which exceed the ceiling level prescribed in paragraph (b) of this section.

(4) Change rooms: (i) At any fixed place of employment exposed to airborne concentrations of asbestos fibers in excess of the exposure limits prescribed in paragraph (b) of this section, the employer shall provide change rooms for employees working regularly at the place.

(ii) Clothes lockers: The employer shall provide two separate lockers or containers for each employee, so separated or isolated as to prevent contamination of the employee's street clothes from his work clothes.

(iii) Laundering: (a) Laundering of asbestos contaminated clothing shall be done so as to prevent the release of airborne asbestos fibers in excess of the exposure limits prescribed in paragraph (b) of this section.

(b) Any employer who gives asbestos-contaminated clothing to another person for laundering shall inform such person of the requirement in (a) of this subdivision to effectively prevent the release of airborne asbestos fibers in excess of the exposure limits prescribed in paragraph (b) of this section.

(c) Contaminated clothing shall be transported in sealed impermeable bags, or other closed, impermeable containers, and labeled in accordance with paragraph (g) of this section.

(e) Method of measurement. All determinations of airborne concentrations of asbestos fibers shall be made by the membrane filter method at 400-450 X (magnification) (4 millimeter objective) with phase contrast illumination.

(f) Monitoring—(1) Initial determinations. Within 6 months of the publication of this section, every employer shall cause every place of employment

where asbestos fibers are released to be monitored in such a way as to determine whether every employee's exposure to asbestos fibers is below the limits prescribed in paragraph (b) of this section. If the limits are exceeded, the employer shall immediately undertake a compliance program in accordance with paragraph (c) of this section.

(2) Personal monitoring—(i) Samples shall be collected from within the breathing zone of the employee, on membrane filters of 0.8 micrometer porosity mounted in an open-face filter holder. Samples shall be taken for the determination of the 8-hour time-weighted average airborne concentrations and of the ceiling concentrations of asbestos fibers.

(ii) Sampling frequency and patterns. After the initial determinations required by subparagraph (1) of this paragraph, samples shall be of such frequency and pattern as to represent with reasonable accuracy the levels of exposure of employees. In no case shall the sampling be done at intervals greater than 6 months for employees whose exposure to asbestos may reasonably be foreseen to exceed the limits prescribed by paragraph (b) of this section.

(3) Environmental monitoring—(i) samples shall be collected from areas of a work environment which are representative of the airborne concentrations of asbestos fibers which may reach the breathing zone of employees. Samples shall be collected on a membrane filter of 0.8 micrometer porosity mounted in an open-face filter holder. Samples shall be taken for the determination of the 8-hour time-weighted average airborne concentrations and of the ceiling concentrations of asbestos fibers.

(ii) Sampling frequency and patterns. After the initial determinations required by subparagraph (1) of this paragraph, samples shall be of such frequency and pattern as to represent with reasonable accuracy the levels of exposure of the employees. In no case shall sampling be at intervals greater than 6 months for employees whose exposures to asbestos may reasonably be foreseen to exceed the exposure limits prescribed in paragraph (b) of this section.

(4) Employee observation of monitoring. Affected employees, or their representatives, shall be given a reasonable opportunity to observe any monitoring required by this paragraph and shall have access to the records thereof.

(g) Caution signs and labels. (1) Caution signs. (i) Posting. Caution signs shall be provided and displayed at each location where airborne concentrations of asbestos fibers may be in excess of the exposure limits prescribed in paragraph (b) of this section. Signs shall be posted at such a distance from such a location so that an employee may read the signs and take necessary protective steps before entering the area marked by the signs. Signs shall be posted at all approaches to areas containing excessive concentrations of airborne asbestos fibers.

(ii) Sign specifications. The warning signs required by subdivision (1) of this

subparagraph shall conform to the requirements of 20" x 14" vertical format signs specified in § 1910.145(d)(4), and to this subdivision. The signs shall display the following legend in the lower panel, with letter sizes and styles of a visibility at least equal to that specified in this subdivision.

Legend	Notation
Asbestos -----	1" Sans Serif, Gothic or Block
Dust Hazard-----	¾" Sans Serif, Gothic or Block
Avoid Breathing Dust....	¾" Gothic.
Wear Assigned Protective Equipment.	¾" Gothic.
Do Not Remain In Area Unless Your Work Requires It.	¾" Gothic.
Breathing Asbestos Dust May Be Hazardous To Your Health.	14 point Gothic.

(Spacing between lines shall be at least equal to the height of the upper of any two lines.)

(2) Caution labels—(i) Labeling. Caution labels shall be affixed to all raw materials, mixtures, scrap, waste, debris, and other products containing asbestos fibers, or to their containers, except that no label is required where asbestos fibers have been modified by a bonding agent, coating, binder, or other material so that during any reasonably foreseeable use, handling, storage, disposal, processing, or transportation, no airborne concentrations of asbestos fibers in excess of the exposure limits prescribed in paragraph (b) of this section will be released.

(ii) Label specifications. The caution labels required by subdivision (1) of this subparagraph shall be printed in letters of sufficient size and contrast as to be readily visible and legible. The label shall state:

CAUTION
Contains Asbestos Fibers
Avoid Creating Dust
Breathing Asbestos Dust May Cause
Serious Bodily Harm

(h) Housekeeping—(1) Cleaning. All external surfaces in any place of employment shall be maintained free of accumulations of asbestos fibers if, with their dispersion, there would be an excessive concentration.

(2) Waste disposal. Asbestos waste, scrap, debris, bags, containers, equipment, and asbestos-contaminated clothing, consigned for disposal, which may produce in any reasonably foreseeable use, handling, storage, processing, disposal, or transportation airborne concentrations of asbestos fibers in excess of the exposure limits prescribed in paragraph (b) of this section shall be collected and disposed of in sealed impermeable bags, or other closed, impermeable containers.

(i) Recordkeeping—(1) Exposure records. Every employer shall maintain records of any personal or environmental monitoring required by this section. Records shall be maintained for a period of at least 3 years and shall be made available upon request to the Assistant Secretary of Labor for Occupational Safety and Health, the Director of the National

Institute for Occupational Safety and Health, and to authorized representatives of either.

(2) *Employee access.* Every employee and former employee shall have reasonable access to any record required to be maintained by subparagraph (1) of this paragraph, which indicates the employee's own exposure to asbestos fibers.

(3) *Employee notification.* Any employee found to have been exposed at any time to airborne concentrations of asbestos fibers in excess of the limits prescribed in paragraph (b) of this section shall be notified in writing of the exposure as soon as practicable but not later than 5 days of the finding. The employee shall also be timely notified of the corrective action being taken.

(j) *Medical examinations.*—(1) *General.* The employer shall provide or make available at his cost, medical examinations relative to exposure to asbestos required by this paragraph.

(2) *Preplacement.* The employer shall provide or make available to each of his employees, within 30 calendar days following his first employment in an occupation exposed to airborne concentrations of asbestos fibers, a comprehensive medical examination, which shall include, as a minimum, a chest roentgenogram (posterior-anterior 14 x 17 inches), a history to elicit symptomatology of respiratory disease, and pulmonary function tests to include forced vital capacity (FVC) and forced expiratory volume at 1 second (FEV_{1.0}).

(3) *Annual examinations.* On or before January 31, 1973, and at least annually thereafter, every employer shall provide, or make available, comprehensive medical examinations to each of his employees engaged in occupations exposed to airborne concentrations of asbestos fibers. Such annual examination shall include, as a minimum, a chest roentgenogram (posterior-anterior 14 x 17 inches), a history to elicit symptomatology of respiratory disease, and pulmonary function tests to include forced vital capacity (FVC) and forced expiratory volume at 1 second (FEV_{1.0}).

(4) *Termination of employment.* The employer shall provide, or make available, within 30 calendar days before or after the termination of employment of any employee engaged in an occupation exposed to airborne concentrations of asbestos fibers, a comprehensive medical examination which shall include, as a minimum, a chest roentgenogram (posterior-anterior 14 x 17 inches), a history to elicit symptomatology of respiratory disease, and pulmonary function tests to include forced vital capacity (FVC) and forced expiratory volume at 1 second (FEV_{1.0}).

(5) *Recent examinations.* No medical examination is required of any employee, if adequate records show that the employee has been examined in accordance with this paragraph within the past 1-year period.

(6) *Medical records.*—(1) *Maintenance.* Employers of employees examined pursuant to this paragraph shall cause to be maintained complete and accurate records of all such medical examina-

tions. Records shall be retained by employers for at least 20 years.

(2) *Access.* The contents of the records of the medical examinations required by this paragraph shall be made available, for inspection and copying, to the Assistant Secretary of Labor for Occupational Safety and Health, the Director of NIOSH, to authorized physicians and medical consultants of either of them, and, upon the request of an employee or former employee, to his physician. Any physician who conducts a medical examination required by this paragraph shall furnish to the employer of the examined employee all the information specifically required by this paragraph, and any other medical information related to occupational exposure to asbestos fibers.

3. A new § 1910.19 is added to Subpart B of Part 1910, reading as follows:

§ 1910.19 Asbestos dust.

Section 1910.93a shall apply to the exposure of every employee to asbestos dust in every employment and place of employment covered by § 1910.12, § 1910.13, § 1910.14, § 1910.15, or § 1910.16, in lieu of any different standard on exposure to asbestos dust which would otherwise be applicable by virtue of any of those sections.

Effective date. Paragraph (b) (2) of § 1910.93a shall become effective July 1, 1976. All other provisions of §§ 1910.93a, 1910.93, and 1910.19 shall become effective July 7, 1972. The current emergency temporary standard remains in effect until July 7, 1972.

(Secs. 6, 8, 84 Stat. 1593, 1596; 29 U.S.C. 655, 657; 29 CFR 1910.4; Secretary of Labor's Order No. 12-71, 36 FR 5734)

Signed at Washington, D.C., this 2d day of June 1972.

G. C. GUENTHER,

Assistant Secretary of Labor.

[FR Doc.72-8574 Filed 6-6-72; 8:48 am]