

Criteria for the minimization of solvent vapor emissions include the elimination of solvent buckets and barrels standing open to the atmosphere, and the repair of gaskets and seals that expose solvent-rich environments to the atmosphere, to be determined through visual inspection.

(Source: Added at 11 Reg. 7296, effective April 3, 1987)

Section 215.609 Program for Inspection and Repair of Leaks

a) The owner or operator of a petroleum solvent dry cleaning facility shall conduct the following visual inspections on a weekly basis:

- 1) Washers, dryers, solvent filters, settling tanks, vacuum stills and containers and conveyors of petroleum solvent shall be inspected for visible leaks of solvent liquid.
- 2) Pipes, hoses and fittings shall be inspected for active dripping or dampness.
- 3) Pumps and filters shall be inspected for leaks around seals and access covers.
- 4) Gaskets and seals shall be inspected for wear and defects.

b) Leaks of petroleum solvent liquid and vapors shall be repaired within three working days of detection, unless necessary replacement parts are not on site.

- 1) If necessary, repair parts shall be ordered within three working days of detection of the leak.
- 2) The leak shall be repaired within three days of delivery of necessary parts.

(Source: Added at 11 Ill. Reg. 7296, effective April 3, 1987)

Section 215.610 Testing and Monitoring

- a) Compliance with Sections 215.607(b)(2), 215.608 and 215.609 shall be determined by visual inspection; and
- b) Compliance with Sections 215.607(a)(2) and (b)(1) shall be determined by methods described in EPA-450/3-82-009 (1982) and does not include any later amendments or editions.
- c) If a control device is used to comply with Section 215.607(a)(1), then compliance shall be determined using 40 CFR 60 Appendix A, Method 25 (1984) and does not include any later amendments or editions.

(Source: Added at 11 Ill. Reg. 7296, effective April 3, 1987)

Section 215.611 Exemption for Petroleum Solvent Dry Cleaners

The provisions of Sections 215.607 through 215.610 shall not apply to petroleum solvent dry cleaning facilities whose emissions of volatile organic material do not exceed 91 megagrams (100 tons) per year in the absence of pollution control equipment or whose emissions of volatile organic material, as limited by the operating permit, will not exceed 91 megagrams (100 tons) per year in the absence of pollution control equipment.

(Source: Added at 11 Ill. Reg. 7296, effective April 3, 1987)

Section 215.612 Compliance Dates and Geographical Areas

Owners and operators of emission sources located in the counties listed below shall comply with the requirements of Sections 215.607 through 215.609 as expeditiously as practicable but no later than December 31, 1987:

Cook	Madison
DuPage	McHenry
Kane	Monroe
Lake	St. Clair
Macoupin	Will

(Source: Added at 11 Ill. Reg. 7296, effective April 3, 1987)

Section 215.613 Compliance Plan

- a) The owner or operator of an emission source subject to Section 215.610(a) shall submit to the Agency a compliance plan, including a project completion schedule where applicable, no later than May 31, 1987.
- b) The plan and schedule shall meet the requirements of 35 Ill. Adm. Code 207.

(Source: Added at 11 Ill. Reg. 7296, effective April 3, 1987)

SUBPART AA: PAINT AND INK MANUFACTURING

Section 215.620 Applicability

- a) This Subpart shall apply to the following counties: Cook, DuPage, Kane, Lake, Macoupin, Madison, McHenry, Monroe, St. Clair and Will.
- b) This Subpart shall apply to all paint and ink manufacturing plants which:
 - 1) include process emission sources not subject to Subparts B, E, F, M, P, Q, R, S, U, V, X, Y or Z of this Part, and which process emission sources as a group would emit 100 tons or more per year of volatile organic material if no air pollution control equipment were used, or