

E.I.E. Corp.

File No. E-31803

WATER-RESISTANT TAPES

Wall Space 1110

TYPE

UL Approved (Recx)

Flame, Heat, and Moisture Resistance. Adhesive. Thickness

SIZE RANGE: #14 thru #8
Solid or Stranded
Bare or Tinned Copper only

ASBESTOS INSULATION:

(U.L. Grade)
(Includes 3 MW only for Tape)
#14 - 30 MW Nom.
#12 thru #8 - 40 MW Nom.

TEMP. RATING:

125°C

TAPE SEPARATOR:

Cellulose Acetate - ONE WRAP

#14 4/16" Wide
#12 9/16" Wide
#8 3/4" Wide

VOLT. RATING:

GRIDS:

Not Required

300V

MARKERS:

1-Black & 1 White (Under Asbestos Ins.)

WAX COMPOUND:

"Standard Toch" #210-105-Colors
"Standard Toch" #210-115-Black



6444

Size	Nominal Diameter	Size (Std. Lay)	Standard Diameter	Size (Std. Lay)	Nominal Diameter
#14 Solid	.130	14/41/30	.140	14/77/0242	.140
#12 Solid	.165	12/35/30	.170	12/77/0300	.160
#10 Solid	.185	10/105/30	.190	10/77/0300	.205
#8 Solid	.215	8/105/30	.220	8/77/0300	.233

TAP MARKING REQUIREMENTS:

Mfr's Name
Mfr's Markers
Type "AI"
Date of Mfr.
AWG Size
Voltage Rating
The words "National Electrical Contractors Association"
UL REEX. LABEL
Affixed to Tap

Refer to Drawing

0074

SC-ELEC-03350