

Begin on page 150



Vapor Heating Corp., 80 E. Jackson, Chicago 4, Illinois

feedwater pump, 7½-hp motor, steam separator, steel coils and all controls are included in a single package. Generator may be used singly or in banks. Master control automatically turns on units necessary to meet demand at a given time. Additional information available from manufacturer.



Stickle Steam Specialties Co.
Indianapolis, Indiana



1226 • New line of gas-fired unit heaters for automatic, direct-fired heating of industrial and commercial areas is available in eight models from 20,000 to 160,000 Btu per hr capacities. Heaters can be used with natural, manufactured, mixed or liquefied petroleum gases and are equipped with motor-driven fans ranging from 1/40 to 1/6 hp as well as automatic safety pilots. Grinnell Co., Inc., 260 W Exchange St., Providence, Rhode Island



1240 • Redesigned portable air heater features new streamlined engine that permits modification in mounting and results in simpler, cleaner arrangement of components at air intake end of heater. Fuel metering valve can reduce capacity of unit from maximum 385,000 Btu per hr to 100,000. Gasoline fired, unit is ideally suited to conditions where electricity is scarce. Portable Heater Sales, American Air Filter Co., Inc., Moline, Illinois




1228 • New molecular vacuum gauge measures pressures without external detectors. Instrument is available in two types, both covering range of 0.20 mm of dry air. Identical except for scale marking, one is calibrated directly for dry air and the other has a linear scale for use where individual calibration for dry air or other gases is preferred. Bulletin GEC-986. General Electric Co., Schenectady 5, New York



A-264

TYPICAL GENERATOR INSTALLATION



Swartwout

POWER PLANT EQUIPMENT
PROCESS INDUSTRY CONTROL
INDUSTRIAL VENTILATION

SEND FOR BULLETIN S-20-E

THE SWARTWOUT COMPANY • 18511 EUCLID AVENUE • CLEVELAND 12, OHIO