Bulletin #402
obsolete ECO 60-5505
11-28-73

PLAINTIFF'S EXHIBIT

MAR-368

RE-2397 REV. 1/65

MAREMONT PRODUCT ENGINEERING DEPARTMENT ENGINEERING BULLETIN	Bulletin No. 402
	Supplement No. 60-5231
Product: FRICTION MATERIALS	Date 7-6-71
Subject: Dimensional Specifications for Bulk Drilled Primary Segments	Page 1 of 16
	Superseding No.
Reference:	

This Engineering Bulletin lists dimensional specifications for Bulk Drilled Primary Segments:

Material Prefix	Description
#286 (MG-08-FE)	Silvertip
#288 (MG-20-FE)	Syncro
#388 (MG-25-FE)	Saftigrip

Distribution:	Issued By: F. C. Skelton	Approved By: F. C. Skelton 7/9/71

DIMENSIONAL SPECIFICATIONS
Drilled Primary Segments

Sheet 2 of 16

Part Number Suffix	Silvertip MG-08-FE	Syncro MG-20-FE	Saftigrip MG-25-FE			APPLICATION	
XXX-	286-	288-	388-	Drum Dia.	DIMENSION (inches) Wide x Thick x Long	F.M.S.I. Lining No.	F.M.S.I. Shoe No.
001	001	001	001	9-1/2	2-1/2x.225x 7-1/2	2102T, 2102BT	241, 246, 258 Pri.
002		002	002*	11	2-1/2x.260x 8-7/8	2116TT	160 Pri.
003	003*	003	003*	11-1/32	2-1/4x.225x 9-3/8	2121TT	263 Pri.
004							
005		005		11	2-3/4x.260x 9	2124TT, 2133TT	260, 313 Pri.
006	006	006	006	11-1/32	2-1/4x.225x 9-3/8	2121T	263 Pri.
007	007	007	007	10	2-1/2x.225x 8-1/2	2089TT	169 Pri.
008	008	008	008	12	1-3/4x.260x10-1/8	286BTT	30 Pri.
009	009*	009	009*	12	2 x.260x10-1/8	296ATT	62 Pri.
010	010*	010	010*	11	2 x.225x10-5/8	2038T	10, 14 Pri.
011	011*	011	011*	9	2-1/4x.260x 7-3/8	2058TT	101 Pri.
012	012*	012	012*	9	2 x.260x 7-5/8	2059TT	100 Pri.
013							
014	014	014	014	9	1-3/4x.260x 9-3/8	2096TT	193 Pri.
015							
016		016	016*	11	2 x.260x 8-7/8	2103TT, 2134TT	191, 228, 272 Pri.
017	017	017	017	10	1-3/4x.225x 8-7/8	2012AT	31 Pri.
018							
019							
020	020	020	020	9	1-1/2x.225x 7-5/8	2072	113, 145, 171, 244 P
021	021	021	021	9	1-1/2x.260x 7-5/8		O/S for C
022	022*	022	022*	9	1-3/4x.260x 7-3/16	2084TT	137, 193 I
023	023*	023	023*	9	1-3/4x.280x 7-3/16		O/S for C
024	024	024	024	9-1/2	1-3/4x.225x 7-1/2	2078TT	136, 196
025	025	025	025	9-1/2	1-3/4x.260x 7-1/2		O/S for
026							
027							
028	028	028	028	10	1-3/4x.225x 8-7/8	2012BT	31, 151

*Obsoleted - listed for reference only.

Date	E.C.O. No.	Line	Description of Change	App
7-6-71	60-5231		Released	FC
7-14-71	60-5233	all	Revised thicknesses	FC
7-20-71	60-5235	006	F.M.S.I. Lining No. 2121T was 2121AT	FC
10-25-71	60-5257	003	F.M.S.I. Lining No. 2121TT was 2121ATT	FC
1-14-72	60-5278	001	7-3/4 Length was 7-1/2	F
1-18-72	60-5279	001	7-1/2 Length was 7-3/4	F
2-4-72	60-5290	002, 005, 016	Obsoleted 286-002, 286-005, 286-016, 388-005 and 388-016	FC
	60-5319		(*) denotes listed for reference only	I

MAR

DIMENSIONAL SPECIFICATIONS
Drilled Primary Segments

Part Number Suffix	Silvertip MG-08-FE	Syncro MG-20-FE	Saftigrip MG-25-FE			APPLICATION	
				Drum Dia.	DIMENSION (inches) Wide x Thick x Long	F.M.S.I. Lining No.	F.M.S.I. Shoe No.
XXX-	286-	288-	388-				
029	029	029	029	10	1-3/4x.260x 8-7/8		O/S for 0
030							
031							
032							
033							
034	034*	034	034*	10	1-3/4x.225x 9-5/8	2093T	151 Pri.
035	035*	035	035*	10	1-3/4x.260x 9-5/8		O/S for 0
036							
037							
038	038	038	038	11	1-3/4x.225x10-5/8	2002A,2002ATT	9,12,55 P
039	039*	039	039	11	1-3/4x.260x10-5/8		O/S for 0
040							
041							
042	042*	042	042*	11	1-3/4x.225x11-7/8	284,284T	9,55 Pri.
043	043*	043	043*	11	1-3/4x.260x11-7/8		O/S for 0
044	044	044	044	9-1/2	2 x.225x 7-1/2	2077AT,2077TT, 2117TT	135,195,2 245 Pri.
045	045	045	045	9-1/2	2 x.260x 7-1/2		O/S for 0
046	046	046	046	9	2 x.225x 7-5/8	2059,2059T	5,100 Pri
047	047	047	047	9	2 x.260x 7-5/8		O/S for 0
048		048	048*	9	2 x.225x 7-5/8	2059A	114 Pri.
049		049	049*	9	2 x.260x 7-5/8		O/S for 0
050	050	050	050	11	2 x.225x 9-3/8	2006,2006T, 2119TT,2138TT	10,11,42, 80,262 Pr
051	051	051	051	11	2 x.260x 9-3/8	2006BTT,2006TT	42,161 Pr. O/S for 0
052							
053	053*	053	053*	11	2 x.280x 9-3/8		O/S for 0
054	054	054	054	10	2 x.225x 9-5/8	2091T,2135T	152,153 P
055	055	055	055	10	2 x.260x 9-5/8		O/S for 0

* Obsoleted- listed for reference only.

Date	E.C.O. No.	Line	Description of Change	App.
7-6-71	60-5231		Released	FCS
7-14-71	60-5233	all	Revised thicknesses	FCS
7-20-71	60-5235	035	Thickness .260 was .225	FCS
2-4-72	60-5290	034,048,049	Obsoleted 388-034,286-048 & 286-049	FCS
3-23-72	60-5319		(*) denotes listed for reference only	FCS

DIMENSIONAL SPECIFICATIONS
Drilled Primary Segments

Part Number Suffix	Silvertip MG-08-FE	Syncro MG-20-FE	Saftigrip MG-25-FE			APPLICATION	
XXX-	286-	288-	388-	Drum Dia.	DIMENSION (inches) Wide x Thick x Long	F.M.S.I. Lining No.	F.M.S.I. Shoe No.
056	056*	056	056*	9	2 x.225x 9-7/8	2046	5 Pri.
057	057*	057	057*	9	2 x.260x 9-7/8		O/S for C
058	058*	058	058*	9-1/2	2 x.225x 9-7/8	2107TT	242 Pri.
059	059*	059	059*	9-1/2	2 x.260x 9-7/8		O/S for C
060							
061							
062							
063							
064	064	064	064	12	2 x.260x10-1/8	296BTT, 2114TT	138, 194, 340 Pri.
065	065	065	065	12	2 x.280x10-1/8		O/S for C
066	066		066	9	2 x.225x 6-1/8	2144T, 2144AT	362 Pri.
067	067		067	9	2 x.260x 6-1/8		O/S for C
068	068*	068	068*	11	2 x.225x11-7/8	287	10, 11 Pri
069	069*	069	069*	11	2 x.260x11-7/8		O/S for C
070							
071							
072							
073							
074							
075							
076	076	076	076	9	2-1/4 x.225x 7-5/8	2071, 2071T	115, 146, 243 Pri.
077	077	077	077	9	2-1/4x.260x 7-5/8		O/S for C
078	078	078	078	10	2-1/4x.225x 8-7/8	2051AT	154 Pri.
079	079	079	079	10	2-1/4x.260x 8-7/8		O/S for C
080	080	080	080	11	2-1/4x.225x 9-3/8	2015AT	6 Pri.
081	081	081	081	11	2-1/4x.260x 9-3/8		O/S for C
082	082*	082	082*	10	2-1 4x.225x 9-5/8	2092T	154 Pri.
083	083*	083	083*	10	2-1/4x.260x 9-5/8		O/S for C

*Obsoleted - listed for reference only.

Date	E.C.O. No.	Line	Description of Change	App.
7-6-71	60-5231		Released	FCS
7-14-71	60-5233	all 066-067	Revised Thicknesses, Released 388-066 and 388-067	FCS
11-30-71	60-5264	066	Removed FMSI Lining No. 2144AT	FCS
11-30-71	60-5264	070-071	Released 388-070 and 388-071	FCS
1-6-72	60-5271	066	Added 2144AT FMSI Lining No.	FCS
1-6-72	60-5271	070-071	Removed 388-070 and 388-071	FCS
2-4-72	60-5290	082	Obsoleted 388-082	FCS
3-23-72	60-5319		(*) denotes listed for reference only	FCS
5-11-72	60-5341	066,067	Added 286-066 and 286-067	FCS

DIMENSIONAL SPECIFICATIONS
Drilled Primary Segments

Part Number Suffix	Silvertip MG-08-FE	Syncro MG-20-FE	Saftigrip MG-25-FE			APPLICATION	
XXX-	286-	288-	388-	Drum Dia.	DIMENSION (inches) Wide x Thick x Long	F.M.S.I. Lining No.	F.M.S.I. Shoe No.
084	084	084	084	12	2-1/4x.225x10-1/8	2005B	70 Pri.
085	085	085	085	12	2-1/4x.260x10-1/8	2005BTT,2113TT	20,197 Pr O/S for 0
086							
087	087*	087	087*	12	2-1/4x.280x10-1/8		O/S for 0
088	088	088	088	11	2-1/4x.225x10-5/8	2053,2053T	12 Pri.
089	089	089	089	11	2-1/4x.260x10-5/8		O/S for 0
090							
091							
092	092*	092	092*	11	2-1/4x.225x11-7/8	2047AT	12 Pri.
093	093*	093	093*	11	2-1/4x.260x11-7/8		O/S for 0
094							
095							
096	096	096	096	10	2-1/2x.225x 8-7/8	2066T	78 Pri.
097	097	097	097	10	2-1/2x.260x 8-7/8		O/S for 0
098	098	098	098	11	2-1/2x.225x 9-3/8	2025T,2025CTT, 2080T,2081T, 2120TT	19,126,13 156,160,1 261 Pri.
099	099	099	099	11	2-1/2x.260x 9-3/8	2025TT	81 Pri. O/S for 0
100							
101	101*	101	101*	11	2-1/2x.280x 9-3/8		O/S for 0
102	102*	102	102*	11	2-1/2x.225x 9-3/8	2025AT,2080AT, 2081AT	13,126,17 264 Pri.
103	103*	103	103*	11	2-1/2x.260x 9-3/8		O/S for 1
104	104	104	104	11-3/32	2-1/2x.260x 9-3/8	2100T	183 Pri.
105	105	105	105	11-3/32	2-1/2x.280x 9-3/8		O/S for 1
106	106*	106	106*	10	2-1/2x.225x 9-5/8	2090T	169,170 P
107	107*	107	107*	10	2-1/2x.260x 9-5/8		O/S for 1
108		108	108*	9-1/2	2-1/2x.225x 9-7/8	2110TT	241 Pri.

*Obsoleted - listed for reference only.

Date	E.C.O. No.	Line	Description of Change	App.
7-6-71	60-5231		Released	FCS
7-14-71	60-5233	all	Revised thicknesses	FCS
2-4-72	60-5290	106,108	Obsoleted 286-108 and 388-106	FCS
3-23-72	60-5319		(*) denotes listed for reference only	FCS

DIMENSIONAL SPECIFICATIONS
Drilled Primary Segments

Part Number Suffix	Silvertip MG-08-FE	Syncro MG-20-FE	Saftigrip MG-25-FE			APPLICATION	
XXX-	286-	288-	388-	Drum Dia.	DIMENSION (inches) Wide x Thick x Long	F.M.S.I. Lining No.	F.M.S.I. Shoe No.
109	109*	109	109*	9-1/2	2-1/2x.260x 9-7/8		O/S for 1
110	----	110	110*	12	2-1/2x.280x10-1/8	2035	64,65,127
111	111*	111	111*	12	2-1/2x.310x10-1/8		O/S for 1
112	112*	112	112*	12	2-1/2x.225x10-1/4	2054	74 Pri.
113	113*	113	113*	12	2-1/2x.260x10-1/4		O/S for 1
114	114*	114	114*	11	2-1/2x.225x10-5/8	2030,2030T	13,15,19, 126,131 P
115	115*	115	115*	11	2-1/2x.260x10-5/8		O/S for 1
116	116		116	11	2-1/2x.280x11-1/2		69 Pri.
117							
118	118	118	118	12	2-1/2x.280x11-1/2	2044A,2125, 2125T,2139TT	64,127, 345 Pri.
119	119	119	119	12	2-1/2x.310x11-1/2		O/S for 1
120							
121							
122							
123							
124	124*	124	124*	12	2-1/2x.280x13	2036A	69 Pri.
125	125*	125	125*	12	2-1/2x.310x13		O/S for 1
126	126	126	126	11	2-3/4x.225x 9	2118TT	260,313 P
127	127	127	127	11	2-3/4x.260x 9		O/S for 1
128							
129							
130	130	130	130	11	3 x.225x 9-3/8	2055T,2082T, 2083T	16,125,14 148,157, 265 Pri.
131	131	131	131	11	3 x.260x 9-3/8		O/S for 1
132	132	132	132	11-3/32	3 x.260x 9-3/8	2099T	184 Pri.
133	133	133	133	11-3/32	3 x.280x 9-3/8		O/S for 1
134	134*	134	134*	11	3 x.260x10-5/8	2074T	16,125, 148 Pri.

*Obsoleted - listed for reference only.

Date	E.C.O. No.	Line	Description of Change	App.
7-6-71	60-5231		Released	FCS
7-14-71	60-5233	all	Revised thicknesses	FCS
2-4-72	60-5290	110	Obsoleted 286-110 and 388-110	FCS
3-23-72	60-5319		(*) denotes listed for reference only	FCS

DIMENSIONAL SPECIFICATIONS
Drilled Primary Segments

Part Number Suffix	Silvertip MG-08-FE	Syncro MG-20-FE	Saftigrip MG-25-FE			APPLICATION	
XXX-	286-	288-	388-	Drum Dia.	DIMENSION (inches) Wide x Thick x Long	F.M.S.I. Lining No.	F.M.S.I. Shoe No.
135	135*	135	135*	11	3 x.280x10-5/8		O/S for 13
136							
137							
138							
139							
140	140	140	140	11-1/16	3-1/2x.260x 9-3/8	2061TT,2076T	24,124 Pri
141	141	141	141	11-1/16	3-1/2x.280x 9-3/8		O/S for 14
142	142		142	9	1-1/2x.225x 6-1/8	2145T	356 Pri.
143	143		143	9	1-1/2x.260x 6-1/8		O/S for 14
144							
145							
146							
147							
148							
149							
150	150*	150	150*	11	1-3/4x.225x 9-3/8	292A,292ATT	17 Pri.
151	151*	151	151*	11	1-3/4x.260x 9-3/8		O/S for 15
152							
153							
154	154*	154	154*	11	2 x.225x 9-3/8	2006A	10, 182 Pr
155	155*	155	155*	11	2 x.260x 9-3/8		O/S for 15
156							
157							
158							
159							
160							
161							
162							
163	163*	163	163*	11	2-3/4x.225x11-5/8	2132TT	284 Pri.

*Obsoleted - listed for reference only.

Date	E.C.O. No.	Line	Description of Change	App.
7-6-71	60-5231		Released	FCS
7-14-71	60-5233	all	Revised thicknesses,	FCS
		142-143	Released 388-142 and 388-143	
1-14-72	60-5278	142-143	1-1/2 Width was 1-3/8.	FCS
3-23-72	60-5319		(*) denotes listed for reference only	FCS
5-11-72	60-5341	142,143	Added 286-142 and 286-143	FCS

DIMENSIONAL SPECIFICATIONS
Drilled Primary Segments

Part Number Suffix	Silvertip MG-08-FE	Syncro MG-20-FE	Saftigrip MG-25-FE			APPLICATION	
XXX-	286-	288-	388-	Drum Dia.	DIMENSION (inches) Wide x Thick x Long	F.M.S.I. Lining No.	F.M.S.I. Shoe No.
164	164*	164	164*	11	2-3/4x.260x11-5/8		O/S for 16
165							
166							
167							
168							
169							
170							
171							
172							
173							
174							
175							
176							
177							
178							
179							
180							
181							
182							
183							
184							
185							
186							
187							
188							
189							
190							
191							
192							

*Obsoleted - listed for reference only.

Date	E.C.O. No.	Line	Description of Change	App
7-6-71	60-5231		Released	FCS
7-14-71	60-5233	164	Revised thickness	FCS
3-23-72	60-5319		(*) denotes listed for reference only	FCS

DIMENSIONAL SPECIFICATIONS
Drilled Primary Segments

Part Number Suffix	Silvertip MG-08-FE	Syncro MG-20-FE	Saftigrip MG-25-FE			APPLICATION	
XXX-	286-	288-	388-	Drum Dia.	DIMENSION (inches) Wide x Thick x Long	F.M.S.I. Lining No.	F.M.S.I. Shoe No.
193							
194							
195							
196							
197							
198							
199							
200							
201	201	201	201	9-1/2	2-1/2x.260x 7-1/2		O/S for 0(
202	202*	202	202*	11	2-1/2x.280x 8-7/8		O/S for 0(
203							
204							
205	205*	205	205*	11	2-3/4x.280x 9		O/S for 0(
206	206	206		11-1/32	2-1/4x.260x 9-3/8		O/S for 0(and 0(
207	207	207	207	10	2-1/2x.260x 8-1/2		O/S for 0(
208	208	208	208	12	1-3/4x.280x10-1/8		O/S for 0(
209	209*	209	209*	12	2 x.280x10-1/8		O/S for 0(
210	210*	210	210*	11	2 x.260x10-5/8		O/S for 0
211	211*	211	211*	9	2-1/4x.280x 7-3/8		O/S for 0
212	212*	212	212*	9	2 x.280x 7-5/8		O/S for 0
213							
214	214	214	214	9	1-3/4x.280x 9-3/8		O/S for 0
215							
216	216*	216	216*	11	2 x.280x 8-7/8		O/S for 0
217	217	217	217	10	1-3/4x.260x 8-7/8		O/S for 0
218							
219							
220							

*Obsoleted - listed for reference only.

Date	E.C.O. No.	Line	Description of Change	App.
7-6-71	60-5231		Released	FCS
7-14-71	60-5233	all	Revised thicknesses	FCS
7-20-71	60-5235	201	Thickness .260 was .280	FCS
1-14-72	60-5278	201	7-3/4 Length was 7-1/2	FCS
1-18-72	60-5279	201	7-1/2 Length was 7-3/4	FCS
2-4-72	60-5290	206	Obsoleted 286-206 and 388-206	FCS
3-23-72	60-5319		(*) denotes listed for reference only	FCS
9-15-72	60-5380	206	Added 286-206	FCS

DIMENSIONAL SPECIFICATIONS
Drilled Primary Segments

Part Number Suffix	Silvertip MG-08-FE	Syncro MG-20-FE	Saftigrip MG-25-FE			APPLICATION	
XXX-	286-	288-	388-	Drum Dia.	DIMENSION (inches) Wide x Thick x Long	F.M.S.I. Lining No.	F.M.S.I. Shoe No.
221							
222							
223							
224							
225							
226							
227							
228							
229							
230							
231							
232							
233							
234							
235							
236							
237							
238							
239							
240							
241							
242							
243							
244							
245							
246							
247							
248							
249							
250							

Date	E.C.O. No.	Line	Description of Change	App.
7-6-71	60-5231		Released	FCS

DIMENSIONAL SPECIFICATIONS
Drilled Primary Segments

Part Number Suffix	Silvertip MG-08-FE	Syncro MG-20-FE	Saftigrip MG-25-FE			APPLICATION	
XXX-	286-	288-	388-	Drum Dia.	DIMENSION (inches) Wide x Thick x Long	F.M.S.I. Lining No.	F.M.S.I. Shoe No.
251							
252							
253							
254							
255							
256							
257							
258							
259							
260							
261							
262							
263							
264							
265							
266							
267							
268							
269							
270							
271							
272							
273							
274							
275							
276							
277							
278							
279							
280							

Date	E.C.O. No.	Line	Description of Change	App.
7-6-71	60-5231		Released	FCS

DIMENSIONAL SPECIFICATIONS
Drilled Primary Segments

Part Number Suffix	Silvertip MG-08-FE	Syncro MG-20-FE	Saftigrip MG-25-FE			APPLICATION	
XXX-	286-	288-	388-	Drum Dia.	DIMENSION (inches) Wide x Thick x Long	F.M.S.I. Lining No.	F.M.S.I. Shoe No.
281							
282							
283							
284							
285							
286							
287							
288							
289							
290							
291							
292							
293							
294							
295							
296							
297							
298							
299							
300							
301							
302							
303							
304							
305							
306							
307							
308							
309							
310							

Date	E.C.O. No.	Line	Description of Change	App.
7-6-71	60-5231		Released	FCS

DIMENSIONAL SPECIFICATIONS
Drilled Primary Segments

Part Number Suffix	Silvertip MG-08-FE	Syncro MG-20-FE	Saftigrip MG-26-FE			APPLICATION	
XXX-	286-	288-	388-	Drum Dia.	DIMENSION (inches) Wide x Thick x Long	F.M.S.I. Lining No.	F.M.S.I. Shoe No.
311							
312							
313							
314							
315							
316							
317							
318							
319							
320							
321							
322							
323							
324							
325							
326							
327							
328							
329							
330							
331							
332							
333							
334							
335							
336							
337							
338							
339							
340							

Date	E.C.O. No.	Line	Description of Change	App.
7-6-71	60-5231		Released	FCS

DIMENSIONAL SPECIFICATIONS
Drilled Primary Segments

Part Number Suffix	Silvertip MG-08-FE	Syncro MG-20-FE	Saftigrip MG-25-FE			APPLICATION	
XXX-	286-	288-	388-	Drum Dia.	DIMENSION (inches) Wide x Thick x Long	F.M.S.I. Lining No.	F.M.S.I. Shoe No.
341							
342							
343							
344							
345							
346							
347							
348							
349							
350							
351							
352							
353							
354							
355							
356							
357							
358							
359							
360							
361							
362							
363							
364							
365							
366							
367							
368							
369							
370							

Date	E.C.O. No.	Line	Description of Change	App.
7-6-71	60-5231		Released	FCS

DIMENSIONAL SPECIFICATIONS
Drilled Primary Segments

Part Number Suffix	Silvertip MG-08-FE	Syncro MG-20-FE	Saftigrip MG-25-FE			APPLICATIONS	
XXX-	286-	288-	388-	Drum Dia.	DIMENSION (inches) Wide x Thick x Long	F.M.S.I. Lining No.	F.M.S.I. Shoe No.
371							
372							
373							
374							
375		375		7-7/8	1-1/16x.195x 7-3/4	8085	351 Pri.&S
376		376		7-7/8	1-1/16x.225x 7-3/4		O/S for 37
377		377		9-1/16	1-5/32x.175x 9-1/4	881	162,163,16
							270 Pri.&S
378		378		9-1/16	1-5/32x.195x 9-1/4		O/S for 37
379							
380							
381		381		7-7/8	1-3/8 x.195x7-3/4	8084	354 Pri.&S
382		382		7-7/8	1-3/8 x.225x7-3/4		O/S for 38
383		383		9-1/16	1-17/32x.175x9-3/8	882A	164,167,26
							315 Pri.&S
384		384		9-1/16	1-17/32x.195x9-3/8		O/S for 38
385							
386							
387		387		9-1/16	1-17/32x.195x9-7/8	8025	166 Pri.&S
388		388		9-1/16	1-17/32x.225x9-7/8		O/S for 38
389		389		9-27/32	1-3/4 x.175x10-3/8	8078	268 Pri.&S
390		390		9-27/32	1-3/4 x.195x10-3/8	8081	298 Pri.&S
							O/S for 38
391		391		9-27/32	1-3/4 x.225x10-3/8		O/S for 39
392		392		9-1/16	1-29/32x.195x9-7/8	8008	165 Pri.&S
393		393		9-1/16	1-29/32x.225x9-7/8		O/S for 39
394		394		9-27/32	1-29/32x.175x10-3/8	8079	271 Pri.&S
395		395		9-27/32	1-29/32x.195x10-3/8		O/S for 39
396		396		9-27/32	2-1/8x.195x10-5/8	8080	297 Pri.&S
397		397		9-27/32	2-1/8x.225x10-5/8		O/S for 39

Date	E.C.O. No.	Line	Description of Change	Ap.
7-6-71	60-5231		Released	FC
7-14-71	60-5233	376,382, 388,391, 393,397	Revised .215 thickness to .225	FC
9-30-71	60-5250	375 thru 397	Removed 389-375 thru 389-397.. Foreign Car applications use MG-26-FF Sec.mtrl.	FC
1-21-72	60-5284	383	FMSI Lining No. 882A was 882	FC
2-11-72	60-5296	389-390-391 381-382	Revised Width- 1-3/4 was 1-23/32 Revised Width: 1-3/8 was 1-11/32 and	FC

DIMENSIONAL SPECIFICATIONS
Drilled Primary Segments

Part Number Suffix	Silvertip MG-08-FE	Syncro MG-20-FE	Saftigrip MG-25-FE	Drum Dia.	DIMENSION (inches) Wide x Thick x Long	APPLICATION F.M.S.I. Lining No.	APPLICATION F.M.S.I. Shoe No.
XXX-	286-	288-	388-				

Date	E.C.O. No.	Line	Description of Change	App.
7-6-71	60-5231		Released	FCS

DIMENSIONAL SPECIFICATIONS
Drilled Primary Segments

Part Number Suffix	Silvertip MG-08-FE	Syncro MG-20-FE	Saftigrip MG-25-FE			APPLICATION	
XXX-	286-	288-	388-	Drum Dia.	DIMENSION (inches) Wide x Thick x Long	F.M.S.I. Lining No.	F.M.S.I. Shoe No.
371							
372							
373							
374							
375		375	375	7-7/8	1-1/16x.195x 7-3/4	8085	Fwd.& Rev.
376		376	376	7-7/8	1-1/16x.225x 7-3/4		O/S for 37
377		377	377	9-1/16	1-5/32x.175x 9-1/4	881	162,163,16 271 Fwd.&R
378		378	378	9-1/16	1-5/32x.195x 9-1/4		O/S for 37
379							
380							
381		381	381	7-7/8	1-11/32x.195x7-3/4	8084	Fwd. & Rev
382		382	382	7-7/8	1-11/32x.225x7-3/4		O/S for 38
383		383	383	9-1/16	1-17/32x.175x9-3/8	882	164,167,26 315 Fwd & R
384		384	384	9-1/16	1-17/32x.195x9-3/8		O/S for 38
385							
386							
387		387	387	9-1/16	1-17/32x.195x9-7/8	8025	166 Fwd & R
388		388	388	9-1/16	1-17/32x.225x9-7/8		O/S for 38
389		389	389	9-27/32	1-23/32x.175x10-3/8	8078	268 Fwd & R
390		390	390	9-27/32	1-23/32x.195x10-3/8	8081	298 Fwd & R O/S for 38
391		391	391	9-27/32	1-23/32x.225x10-3/8		O/S for 39
392		392	392	9-1/16	1-29/32x.195x9-7/8	8008	165 Fwd & R
393		393	393	9-1/16	1-29/32x.225x9-7/8		O/S for 39
394		394	394	9-27/32	1-29/32x.175x10-3/8	8079	271 Fwd & R
395		395	395	9-27/32	1-29/32x.195x10-3/8		O/S for 39
396		396	396	9-27/32	2-1/8x.195x10-5/8	8080	297 Fwd & R
397		397	397	9-27/32	2-1/8x.225x10-5/8		O/S for 39

Date	E.C.O. No.	Line	Description of Change	App
7-6-71	60-5231		Released	FCS
7-14-71	60-5233	376,382 388,391 393,397	Revised .215 thickness to .225	FCS