GEN 58 REV. 1 (3-68)

INTERNAL LETTERHEAD

PLAINTIFF'S EXHIBIT
CEL-1037

TO (NAME AND LOCATION)
J. M. Mullins

REFERENCE NO.

FROM (NAME AND LOCATION)
W. A. Morgan

REFERENCE NO.
WAM-1786

DATE
June 29, 1976

SUBJECT: Handling Asbestos Material

A meeting was held June 29, 1976 to discuss handling asbestos material to comply with E.P.A. and OSHA regulations. Those in attendance were: Messers Garner, Mullins, Pulse, and the writer.

There are some rather stringent regulations regarding handling materials that contain asbestos fibres. No longer does the Pampa Plant purchase or install insulation containing asbestos. Transite siding and roofing materials containing asbestos is still purchased and used.

It is assumed that 160 sq.ft. of old asbestos insulation is not removed in a year and it will not be necessary to notify EPA unless there is a line 260 lin. ft. or more on which asbestos insulation is removed. It was stated by the writer that every effort will be made to comply with existing regulations.

The following rules will be followed in the handling of asbestos materials:

1. Old insulation removed will be wetted, prior to removal, placed in plastic bags and buried.

2. Old insulation material accumulated near the solids burial pits will be placed in the pits and buried.

3. No asbestos insulation will be reclaimed or reused, but will be buried.

4. A tank type vacuum pump with disposable bags will be provided and hoses connected to electric saws to prevent asbestos dust from escaping.

5. No transite or other asbestos material will be sawed on the Do-All radial or band saws.

6. Necessary precautions, e.g. barricades, fresh air masks, etc. will be used to protect workers when asbestos materials are being removed or installed.

W. A. Morgan
Maintenance Manager

cc: R. G. Brandt
T. L. Garner
E. C. Pulse
C. E. Steel
H. A. Thomas
P. A. Turek

010568