

63

RESPIRATORY PROTECTIVE EQUIPMENT

SAFETY ENGINEERING STANDARD

ISSUED	JAN 1964
THIS PAGE REVISED	OCT 1960
STANDARD REAFFIRMED	DEC 1978

S 2 H

Page 1 of 9

This standard includes requirements of the Occupational Safety and Health Act of 1970 (OSHA) as published in the Federal Register. OSHA information is printed in red.

1. SCOPE

This standard provides information for the selection, use, and care of respiratory protective equipment (respirators). The term "respirator" in this standard is used inclusively and applies to atmosphere-supplying and air-purifying devices that provide breathable air to the wearer within the limits of the equipment, whatever the source of air. This standard does not apply for exposure to airborne radioactive contamination for which special consideration may be necessary.

2. GENERAL

2.1 Respirators should not be used as a substitute for adequate exhaust ventilation or other engineering control methods.

2.2 Respirators shall be worn at all times where the atmosphere may be harmful to employees due to unusual conditions, and where work is necessary in contaminated or oxygen-deficient, confined areas.

2.2.1 When the air is deficient in oxygen, the symptoms range from increased volume of breathing and acceleration of pulse rate to unconsciousness and death, depending upon oxygen content and the degree of a person's activity. Unconsciousness is immediate when a man breathes pure nitrogen and death may follow in a few minutes.

2.2.2 An oxygen deficiency may indicate a hazard other than inert gas; e.g., flammability (see 4.6), skin toxicity, or absorption through the skin, particularly hydrogen cyanide. Threshold limit values (TLV's) of air contaminants are given in S2T. Portable oxygen and toxic-gas detectors are covered in S3T.

2.3 Pure oxygen shall not be used in open circuit, self contained, atmosphere-supplying respirators, or in air-line type respirators.

2.4 A closed circuit (rebreathing) system recirculates exhaled air, makes up oxygen and removes undesirable gases such as carbon dioxide. Pure oxygen must be used with these systems. Systems approved by the National

Portions printed in red are from OSHA regulations, Section 1910.134.

Vendors and merchandise designations are given to describe materials and may not include all acceptable products. Substitutions by suppliers are to be made only on approval of the local authority initiating the use of this standard.

SEE COMMITTEE NO. 28

Institute for Occupational Safety and Health (NIOSH) which utilize a high-pressure cylinder for oxygen may be used. Closed circuit oxygen generating type equipment shall not be used.

2.5 Each location shall develop written procedures covering the selection, use, and maintenance of respirators.

3. APPROVED RESPIRATORS

3.1 Only equipment approved by the National Institute for Occupational Safety and Health/Mine Safety Health Administration (NIOSH/MSHA) shall be used.

3.1.1 Respirators purchased after September 30, 1974 shall be manufactured per quality control plan approved under Title 30, Code of Federal Regulations, Part 11. Such equipment will bear an approval label bearing the letters "TC" instead of "UM."

3.1.1.1 Exceptions. Self-contained breathing apparatus approved by Bureau of Mines under Schedule 13 through 13-E equipped with an audible end-of-service life indicator and gas masks approved by Bureau of Mines under Schedule 14F are approved for use until further notice provided they (1) were fabricated, assembled, or built under an approval or any modification thereof issued by the U. S. Bureau of Mines, Department of the Interior, (2) were purchased on or before June 30, 1975, and (3) are maintained in an approved condition.

3.2 A list of the respirators and their manufacturers, certified by NIOSH may be obtained by requesting HEW Publication No. NIOSH 75-119 plus cumulative supplements from:

NIOSH Testing and Certification Laboratory
944 Chestnut Ridge Road
Morgantown, WV 26505

Division of Technical Services
NIOSH
Robert A. Taft Laboratories
4616 Columbia Parkway
Cincinnati, OH 45226

DUP 0960535

THIS DOCUMENT IS THE PROPERTY OF E. I. DU PONT DE NEMOURS AND COMPANY. THE TECHNICAL INFORMATION HEREIN MAY NOT BE USED NOR REPRODUCED WITHOUT THE PERMISSION OF E. I. DU PONT.

NOTE

CONFIDENTIAL

REV JUL 1983



DU 040745

3.3 At the present time, there are no approval schedules for air-supplied suits.

3.4 A list of the several types of respiratory protective equipment, method of operation, use, limitations, and remarks is given in Table 1. For additional information in this regard, reference should be made to:

"Practices for Respiratory Protection," ANSI Z88.2, American National Standards Institute, Inc. 1430 Broadway, New York, NY 10018

Respiratory Protective Equipment, Data Sheet D-444, National Safety Council, 425 North Michigan Avenue, Chicago, IL 60611

"Respiratory Protection Program, A Manual and Guideline," American Industrial Hygiene Association, 475 Wolf Ledges Parkway, Akron, OH 44311

4. USES AND LIMITATIONS

4.1 Users of respiratory protective equipment shall have medical approval.

4.2 The air-purifying respirators; i.e., canister gas masks, chemical cartridge respirators, and mechanical filter respirators (Table 1C) shall not be used for rescue work, or for emergency work of any nature. This is because these respirators do not supply oxygen and therefore do not protect against possible oxygen deficiencies. Other reasons for this requirement are that:

a. Gas masks are intended for use with no more than 2 percent by volume of most toxic gases.

b. Chemical cartridge respirators are intended for use in significantly lower toxic gas concentrations than canister gas masks. Limits vary from 0.05 percent maximum to 0.1 percent maximum.

4.3 The following warning signs require immediate return to fresh air:

a. Uncomfortable heat in the inhaled air. (A properly operating canister will become warm on exposure to certain gases or vapors, but a canister which becomes extremely hot indicates that concentrations above the canister limit have been encountered.)

b. If nausea, dizziness or signs of distress develop.

c. If the canister has a window indicator which shows the specified color change.

d. If any leakage is detected by smell, taste, eyes, nose or throat irritation.

e. If high breathing resistance develops.

4.4 Air purifying respirators should not be used in atmospheres immediately dangerous to life and health or when the contaminant has poor warning properties, except for escape.

4.5 Users should select canisters and cartridges specifically approved for the toxic gas and concentration to be encountered. Canister masks that bear the label "All-Service," "All-Purpose," or "Universal" should not be used for a specific gas or vapor if a canister is available for that specific gas or vapor.

4.6 Although self-contained breathing apparatus or combination air-line and self-contained breathing apparatus have no concentration limit in regard to toxicity, many toxic gases and vapors are flammable and the user could be exposed to a potential fire or explosion. The 2-percent concentration limits approved for toxic gas removal with canister-type masks is within the flammable range for some gases. Work in atmospheres in or near the flammable range is prohibited. When the possibility of flammable atmospheres exists, a check should be made with an explosimeter and permissible concentrations confirmed prior to entry. Standard F6J provides information and instructions for use of portable flammable vapor and gas detectors.

4.7 Respiratory protection is required for cancer suspect agents. Refer to OSHA regulations for specific requirements, Section 1910.1000 series, and to S2T.

4.8 An uncontaminated supply of air must be assured when using a hose mask with blower.

5. SELECTION

5.1 In selecting a respirator, the following factors (5.1 - 5.1.8.1) and Tables 1 and 2 should be considered. Engineering Dept Report, Accession No. 15167 "Respirator Selection," also will provide guidance.

- Nature of the hazard
- Severity of the hazard
- Type of contaminant
- Concentration of the contaminant
- Period protection is required
- Location of the contaminated area with respect to a source of respirable air

Portions printed in red are from OSHA regulations, Section 1910.1000 series.

CONFIDENTIAL



DUP 0960536

REV. OCT 1980

REV 111

- g. Expected activity of the wearer
- h. Operating characteristics and limitations of the available respirators

- i. Safety regulations of state or local governments

5.1.1 Self-contained breathing apparatus rated for at least 30-minute service time should be used for entry into an irrespirable atmosphere.

5.1.2 Self-contained breathing apparatus with less than a 30-minute air supply shall be used only for emergency egress and not for rescue work or reentry.

5.1.3 Operating time for self-contained apparatus is based on moderate work rates. Operating time is reduced by increased respiration required by heavy exertion.

5.1.4 Only self-contained breathing apparatus, or combination air-line respirator and self-contained breathing apparatus, shall be used in oxygen-deficient atmospheres or where the contaminant is, or might be, immediately dangerous to life. The air in the self-contained unit of the combination air-line respirator and self-contained breathing apparatus shall be used only for egress in event the hose-line supply of air is interrupted. The volume of this exit supply may vary for different applications, but shall be ample to allow the worker sufficient air to escape from the contaminated area. In any case, this supply shall not be less than 3 minutes. Consideration should be given to using only positive pressure units.

5.1.5 Escape masks are used only while the wearer leaves a contaminated area. They are approved under Subpart I, 30 CFR Part 11 and have a half mask facepiece or a mouthpiece. Where eye irritation is a consideration, a full facepiece should be used. For escape or emergency purposes from unknown concentrations of extremely hazardous atmospheres (any gas or vapor having a rated lethal concentration LC 50 of less than 10 ppm), a pressure demand self-contained breathing apparatus or combination pressure demand supplied air respirator with pressure demand self-contained breathing apparatus shall be used.

5.1.6 Entry Masks. Use self-contained breathing apparatus with at least a 30-minute air supply or a combination supplied air respirator with self-contained breathing air apparatus. Unit shall be of the pressure demand type. The entry masks should be located outside of the potentially affected area in a noncontaminated area and properly identified and protected.

5.1.7 Fire Fighting. Use self-contained breathing apparatus with at least a 30-minute air supply. Unit shall be the pressure demand type.

5.1.8 Schedule 13E of the U. S. Bureau of Mines on self-contained breathing apparatus requires a remaining service-life indicator or warning for compressed breathing air (except for self-rescue). Some equipment now on plants may not have these alarms. These can and should be obtained from equipment suppliers for apparatus not so equipped.

5.1.8.1 When the device is a combination self-contained breathing apparatus and air-line respirator (supplied-air respirator), either a manual or automatic valve(s) shall be provided to change to the self-contained air supply if the air-line supply fails, and to prevent the wearer breathing contaminated air from the outside atmosphere. If a manual valve is provided, it shall be easily operable and located in a position which is convenient to the wearer. If an automatic valve is provided, a warning also shall be provided to alert the wearer that he is breathing from the self-contained air supply. (1) when his normal air-line supply fails, or (2) when the self-contained air supply falls below 95 percent of its full container pressure. A quick disconnect and check valve shall be provided between the apparatus and the air-line supply hose to permit ready escape from the area, and to prevent loss of breathing air from the device or inhaling the surrounding atmosphere, respectively.

6. BREATHING AIR

6.1 Both purchased and manufactured breathing air shall meet or exceed the requirements of the specification for Grade D breathing air as described in Compressed Gas Association Commodity Specification G-7.1-1966*. See table below for Grade D analysis summary, and G-7.1 for details including sampling and analytical procedures.

Gas	Breathing Air Analysis
O ₂	19 percent min to 23 percent max†
CO	20 ppm max
CO ₂	1,000 ppm max
Hydrocarbons (condensed)	5 mg/m ³
H ₂ O	Dew point less than the lowest probable temperature to be encountered
N ₂	Balance
Odor	Free of pronounced odors

† See S&T for data on direct reading portable oxygen analyzers. This is necessary to prevent freeze-up and stoppage of air flow to the mask. For tables refer to "Handbook of Compressed Gases."

* Available from Compressed Gas Association Inc., 500 Fifth Ave., New York, NY 10036

Portions printed in red are from OSHA regulations, Section 1910.134.



DUP 0960537

CONFIDENTIAL

6.2 A reliable supplier should be chosen. Visit his facilities to determine his degree of control over the operation. If an air compressor is used, it should be maintained. If a lubricated compressor is used, it must have a carbon monoxide or high temperature (or both) alarm. Annual contacts should be made to assure equipment and procedures have not changed.

6.3 Alternatively, certified breathing air should be purchased from a reliable supplier. If a choice has to be made between certified air from a questionable supplier and uncertified air from a reliable supply, the latter would be the recommended choice.

6.4 Determine if the air is provided by compression or reconstitution (mixing nitrogen and oxygen) and analyze as follows:

Method of Preparation	Analysis Recommendation
Compressor - supplier owns all cylinders with and gases other than air	Check 10 percent of cylinders from each lot for ppm CO and odor.
Compressor - supplier fills cylinders with gases other than air	Analyze all cylinders for percent O ₂ . Check 10 percent of cylinders from each lot for ppm CO and odor.
Reconstitution	Analyze all cylinders for percent O ₂ . Check 10 percent of cylinders from each lot for ppm CO and odor.

6.5 In addition a complete analysis should be conducted periodically to assure compliance with table in 6.1.

7. PRECAUTIONS

7.1 An extensive list of instructions in use and precautions for each type of respirator is given in ANSI Z88.2. Some precautions are given in Table 1 under headings of Limitations and Remarks.

7.2 The manufacturer's instructions or precautions of the ANSI standard should be posted with the respiratory device.

7.3 All persons who may have occasion to use respiratory devices, or cause them to be used, shall be properly trained in their use. Also, in execution of plant disaster plans, proper training in use of respiratory protective equipment will aid in the performance of mouth and safe rescue or repair operations.

7.4 A slight negative pressure occurs inside the facepiece of face-fitting air-purifying respirators (Table 1C). Care must be taken to obtain an effective seal between the facepiece and face to prevent inward contaminant leakage.

Also, demand-type air-supplied respirators and demand-type self-contained respirators operate under negative pressure when the wearer inhales. Since some inward leakage of contaminant may be possible, these types provide much less protection. When purchasing new air-supplied, self-contained or combination type, pressure-demand should be specified.

7.4.1 A pressure-demand type self-contained respirator or air-supplied combination self-contained should be used in atmospheres containing contaminants which cannot be detected by smell or where special precautions must be taken to prevent the wearer from inhaling any trace of contaminant. In this type equipment, a small positive pressure is maintained inside the facepiece at all times, such that if a leak should develop, there would be no leakage of contaminant into the facepiece.

7.5 A proper seal cannot be established if the temple bars of eye glasses extend through the sealing edge of full-face masks.

7.6 Contact lenses shall not be worn with full-face masks. See S4H.

7.7 All eyepieces in full-face masks approved by the Bureau of Mines will pass the ball drop test, but some plastic eyepieces may not pass the needle drop test (S4H). Current schedules of the Bureau of Mines, however, require that eyepieces shall meet the pertinent requirements for impact and penetration specified in the most recent ANSI Z87.1 Safety Code for Eye Protection.

7.7.1 Full-face masks have been developed with systems for mounting corrective lenses inside the facepiece. Contact the manufacturers for assistance.

7.8 Major problems in the use of full-face masks at low temperatures are poor visibility and freezing of exhalation valves. Antifog compounds can be used to coat the inside and outside of the eyepiece to prevent its fogging down to about 32°F. Below 0°F, however, antifog compound will not prevent severe fogging. Antifog compounds break down and require reapplication periodically.

7.9 A half-mask facepiece should not interfere with the wearer's use of spectacles or goggles. Proper selection of equipment normally will eliminate any problem of proper fit when using a combination of half-mask facepiece and spectacles or goggles.

7.10 Persons required to wear respirators must be clean shaven in the area of the respirator seal.

7.11 Conventional respirators do not constitute an absolute barrier to transmission of speech. The respirator exhalation valve usually provides a satisfactory pathway for speech transmission over short distances in relatively

Continued on the next page from OSHA regulations, Section 1010.134

DUPONT

CONFIDENTIAL

DUP 0960538

REV. JUN 1982

REV. JUN 1982

TABLE 1 - TYPES OF RESPIRATORY PROTECTIVE EQUIPMENT (CONT'D ON PAGE 7)
Table 1A - Air-Supplied Suit

Method of Operation	Air supply from supplied-air breathing apparatus. See S1H on air-distribution system.
Use	Operating or repair work where there is exposure to substances that are irritating or corrosive to the skin and mucous membranes, but where the atmosphere is not immediately dangerous to life. If immediately dangerous to life, the respiratory equipment should be provided as in S1.4 and the air-supplied suit should be kept with a slight positive pressure. In any case the air supply should not be less than 18 minutes to allow the worker sufficient air to escape from the contaminated area. A body harness is required to handle the hose line and the life line, which always should be worn as a rescue device. Helper (wearing similar air-supplied suit, body harness, and life line) should be assigned with no other duties than to observe the man in the hazardous area, attend the life line and in emergency, ask for help and be ready to rescue the worker. (See S16G).
Limitations	The wearing of an impervious suit for any extended period is extremely fatiguing and dangerous unless it is well ventilated. The suit must be impervious to the substance encountered. With the longest hose length for which use is intended assembled to the respirator, and the lowest inlet pressure intended for operation introduced to the air-supply hose, constant flow units must deliver at least 4 cfm measured at the facepiece. The exhalation resistance at 85 liters per minute shall not exceed 1 inch of water. When helmets or hoods are used, the same requirements must be met except that the flow rate must be at least 8 cfm. For both types of assemblies with the highest inlet pressure and shortest hose length, the maximum flow shall not exceed 15 cfm.
Remarks	No NIOSH* approval. For additional information, see Fleming, A. J., D'Aonzo, C. A., and Zapp, J. A., "Modern Occupational Medicine," Chapter 7, "Protective Clothing for the Chemical Industry," Lea and Febiger, Philadelphia (1960). A Ranque-Hilsch vortex tube** worn as a portable refrigerator can satisfactorily cool compressed air for personnel wearing industrial protective clothing. The vortex tube is light and small, and can be strapped to the belt where it does not interfere with physical movement. The tube operates on 20 to 25 cfm of compressed air at 80 to 100 psi and delivers 15 to 18 cfm of air cooled 50 to 60°F below the inlet air temperature. The tube can be reversed and used as a heater.

* National Institute for Occupational Safety and Health, U. S. Dept. of Health, Education and Welfare

** Available from
Encon Manufacturing Company
P. O. Box 9826-TR
Houston, TX 77001

CONFIDENTIAL



DUP 0960540

DU 040750

CONFIDENTIAL

JANUARY 1964

RESPIRATORY PROTECTIVE EQUIPMENT

S 2 F

This Page Rev Oct 1960

Page 1

TABLE 1 - TYPES OF RESPIRATORY PROTECTIVE EQUIPMENT (CONTD ON PAGE 6)

Table 1B - Atmosphere Supplying Respirators

Self-Contained Type			Supplied-Air Respirator				
Method of operation	Rebreathing	Demand Type	With Blower (Type A Supplied-Air Respirator)	Without Blower (Type B Supplied-Air Respirator)	Air-Line Respirator (Type C Supplied-Air Respirator)		
					Continuous Flow Air-Line Respirator	Al-silicate Breathing Hose	Demand Class Air-Line Respirator
		Air from high pressure cylinders (normally 2000 psi) supplied to a closed circuit system which recirculates exhaled air. CO ₂ is absorbed.	Respirable air is forced through a large-diameter hose by a hand blower to a full facepiece (U. S. Bureau of Mines has schedule with electric motor on blower)	Respirable air is drawn through a large flexible hose by wearer's breathing effort	Pressurized air supplied through a small-diameter hose to full-facepiece, full facepiece, or a loose fitting hood or hood	Source of air: Attached by small hose to demand valve actuated by slight negative pressure when wearer inhales	
Use	Required under conditions immediately dangerous to life and at distances over 300 ft from a source of respirable air-protection for limited periods		Up to 300 ft of travel from source of respirable air. Protection provided for an unlimited period	Nonemergency work, up to 75 ft of travel from source of respirable air. Protection provided for an unlimited period	Limits set by manufacturer for air supply hose length and range of air pressure. Protection for unlimited periods	Desirable to protect head and face from flying particles, labile, active blasting, spraying of molten air or paint	
Limitations	No environmental limitation in regard to toxicity or an O ₂ content. Absorption through the skin or skin irritations are possible. Limitations: Extensive training in use and care is required. Fatiguing due to weight		Limitation in regard to toxicity or an oxygen content. Absorption through the skin or skin irritations are possible. Limitations: Worker must return to fresh air by reaching only route. As uncontaminated supply of fresh air must be assured.	See limitations for Type A at full facepiece for emergency use. Not approved in any situation where inhalation resistance exceeds 25 in. H ₂ O or where inhalation resistance exceeds 1 in. H ₂ O. These tests shall be tested with a flow (200) much SST across, and shall be followed in a zone of clean air	When used alone, this device is limited to concentrations of gases or vapors that are not immediately dangerous to life, or from which the wearer can escape unharmed without the aid of the respirator. Not to be worn in oxygen-deficient atmospheres. Travel is limited by the length of the air-supply hose. Rescues must be effected. Absorption through the skin or skin irritation are possible. Limitations: Combination air-line respirator and self-contained breathing apparatus may be used in an irrespirable atmosphere (See 5.1.4)		
Remarks	Approved for 30 min only. Scott Air Pak is an example	* Pressure demand masks maintain the facepiece under a slight positive pressure during the entire breathing cycle to further protect against leakage of toxic atmospheres	Blower must permit free entrance of air when it is not operating. Helper should be assigned with no other duties than to observe the man in the hazardous atmosphere, stand by the life line and, in emergency, operate the blower. A helper operator also should be provided. A body harness is required to handle the life line and the life line, which always should be worn as a rescue device	See remarks for Type A at full facepiece for emergency use. Not approved in any situation where inhalation resistance exceeds 25 in. H ₂ O or where inhalation resistance exceeds 1 in. H ₂ O. These tests shall be tested with a flow (200) much SST across, and shall be followed in a zone of clean air	Nonrespirable hose should be used if operating pressure is greater than 5 psi (see 5.1.4)	Al-silicate hose can be attached to the wearer and the whole head detached rapidly and sometimes the torso. See SMH on air distribution system	Headsets or hoods are not used with this respirator. See SMH on air distribution system

† Closed circuit oxygen generating type equipment is not approved for use

DUP 0960541

Closed circuit oxygen generating type equipment is not approved for use

DUP 0960541

DU 040751

TABLE 1 - TYPES OF RESPIRATORY PROTECTIVE EQUIPMENT (CONTD FROM PAGE 7)
Table 1C - Air Purifying Respirators
 (Not for use in oxygen-deficient atmospheres or where the contaminant is, or might be, immediately dangerous to life)

CONFIDENTIAL

Method of operation	Chemical Filter Type			Mechanical Filter Type Respirators	Combination Chemical and Mechanical Filter Respirators
	Canister Gas Mask (Full Facepiece Respirator)	Chemical Cartridge Respirator (Half Mask Respirator)	Self-Contained Breathing Apparatus		
	Tonic gases or vapors removed from inspired air by absorption, adsorption, chemical reaction, or catalysis, or a combination of these in a packed solvent bed of the canister or cartridge. Exhausted breath goes to atmosphere			Respirators remove particulate matter such as dust, fumes, or mist, from inspired air by capture on the filter, which is usually a fibrous pad.	Some gas mask canisters contain special filters which provide respiratory protection against particulate matter, as well as against gases and vapors. Some chemical cartridge respirators contain filters for the same purpose.
Use	Provides respiratory protection against single or combination of 2 or more gases and vapors.	For escape only. Provides greatest protection available with size of device.		Designed to provide respiratory protection against a single specific dust, fume, or mist, a single class such as toxic dusts or a combination of several classes of particulate matter such as dusts, fumes, and mists. It offers no protection against gases or vapors.	For particulate matter, gases and vapors in concentration within capacity of the device.
Limitations	See Section 4. Cannot be used in atmospheres irritating to the skin.	Limited to use in atmospheres containing at least 15.5% oxygen and to the maximum gas concentration for which the specific cartridge is recommended (generally 6 1/2% maximum or less). Cannot be used in atmospheres irritating to the skin or eyes.		Practical limit of concentration is determined by time required to plug filter. But these respirators should not be used in high concentrations of particulate matter. Not to be used when flying particles may cause injury for which condition the abrasive blasting respirator should be used; see Table 1B. Does not protect against oxygen deficiency and toxic vapors or gases.	The limitations of the combination are generally the same as for each type of respirator given on the list. The limitation of dust filters in regard to protection against gases and vapors in mechanical filter type is modified by the protection afforded by the chemical filter respirator against gases and vapors. See Section 4.
Remarks	Canisters are color coded for identification, per ANSI Z39.1	See 8.3.6.		See 8.3.7. Fineness of the particles to be filtered out of the air controls the fineness of the filtering element, and nature of the toxicity hazard is a governing factor in selection of equipment. * NIOSH approves mechanical filter respirators according to the following classification: (1) "Pneumotoxics" - Producing and Harboring - Dust Respirators (2) "Toxic" - Dust Respirators (not significantly more toxic than lead) (3) "Dust" Respirators (not significantly more toxic than lead) (4) "Toxic" Respirators (not significantly more toxic than lead)	

* Dust - Dispersoids or particulate matter, smaller than 100 microns, formed when solid materials are disintegrated by such processes as crushing, grinding, and abrading.

Fume - Solid dispersoids formed when vapors are condensed from heated metals and other substances.

Mist - Liquid dispersoids formed when liquid is atomized as in spraying, coating, and blending.

** All approved under (1) and (2) are approved under (1) and (2). Some approved under (1) are approved for protection of dusts that are not significantly more toxic than lead.

DUP 0960542

DU 040752

JANUARY 1964

RESPIRATORY PROTECTIVE EQUIPMENT

S 2 H

This Page Rev Sept 1978

Page 9

TABLE 2 - SELECTION OF RESPIRATORY PROTECTIVE DEVICE

Hazard	Respirator
Oxygen deficiency	Self-contained breathing apparatus Combination air-line respirator and self-contained breathing apparatus
Gaseous contaminant immediately dangerous to life (see 3.1.4)	Self-contained breathing apparatus Combination air-line respirator and self-contained breathing apparatus
Not immediately dangerous to life	Air-line respirator Hose mask without blower Chemical-cannister respirator
Particulate contaminant immediately dangerous to life (see 3.1.4)	Self-contained breathing apparatus Combination air-line respirator and self-contained breathing apparatus
Not immediately dangerous to life	Mechanical filter respirator Air-line respirator Abrasive-blasting respirator Hose mask without blower
Combination gaseous and particulate contaminant immediately dangerous to life (see 3.1.4)	Self-contained breathing apparatus Combination air-line respirator and self-contained breathing apparatus
Not immediately dangerous to life	Air-line respirator Hose mask without blower Combination chemical and mechanical filter respirators

Note: The self-contained breathing apparatus, combination air-line respirator and self-contained breathing apparatus, would give respiratory protection against any of the hazards listed, but these devices are not included in the list of respirators that could be used in the listed hazardous situations.

CONFIDENTIAL



DUP 0960543

DU 040753