

ONE

GALLON

O'BRIEN'S



75⁰⁰

EXTERIOR EGGSHELL PAINT

FOR WOOD AND ASBESTOS SHINGLES • MASONRY • SIDING

SUNCREST

MADE IN U.S.A. BY THE O'BRIEN CORPORATION • SOUTH BEND, INDIANA • BALTIMORE, MARYLAND

#75 EXTERIOR EGGSHELL	
Pigment	48.97%
SUNCREST	26.38%
Azo Nucle Yellow	42.28%
Sinc Oxide	1.74%
Aluminum Stearate	1.74%
Vehicle	100.00%
Heat Treated Methacrylate	31.03%
Oil	3.21%
Alkyd Resin Solution	59.66%
Mineral Spirits	14.15%
Driers	22.94%
Volatile	100.00%
Non-Volatile Resin	
Treated Linseed, Fish Oil, Thermolyzed Tung Oil	43.75%
Volatile	
Alkyd Resin Solution	100.00%
Non-Volatile; Modified Soya Oil, Alkyd	60.00%
Volatile; Mineral Spirits	40.00%
	100.00%

"75" EXTERIOR EGGSHELL PAINT

For Wood & Asbestos Shingles—Stucco— Concrete—Wood Siding and Trim

A new, all-purpose outside eggshell paint for use on wood and asbestos shingles, stucco, concrete, masonry, metal, wood siding and trim. It provides a rich, durable finish to exterior surfaces where a dull coating is preferred to the conventional high lustre. This material works easy under the brush; has excellent coverage and unsurpassed hiding. Made with Pre-Shrunk Oils, it beautifies, protects and waterproofs. A "breather type" paint — it reduces paint blistering and peeling.

O'Brien's "75" Exterior Eggshell Paint Sealer is a special clear sealer for mixing with the paint, making an excellent primer for use on stucco, concrete, shingles and other porous surfaces where a two coat job is necessary. It helps to prevent paint troubles due to varying porosity or the presence of free alkali in stucco and masonry surfaces.

THINNING NOTE — to retard drying and setup of paint during hot weather, one pint of "75" Ex. Egg. Pt. Thinner should be added to each gal. of paint.

CAUTION! COMBUSTIBLE
Keep Away from Heat and Open Flame
CONTAINS LEAD OR OTHER
POISONOUS MATERIAL. IF EATEN
OR SWALLOWED, IT MAY BE
DANGEROUS TO LIFE. Keep
interior surfaces which might be
chewed by children. Use with ad-
equate ventilation. Avoid breathing
vapors. Wash thoroughly after work
before eating or smoking. Keep
children away from when not in use.

DIRECTIONS FOR USE

Asbestos Shingles (unpainted*) — two coats are necessary. Under pastel colors of "75" Exterior Eggshell, use a prime coat of O'Brien's A.R. Primer (may be tinted with Tone-All Colors, not more than two tubes per gal.) Under dark colors of Exterior Eggshell, use prime coat consisting of equal part mixture of "75" Exterior Eggshell Paint Sealer and Exterior Eggshell Paint. Finish with one coat of "75" Exterior Eggshell Paint.

***IMPORTANT** — this material is not recommended for use over unpainted asbestos shingles unless the shingles have weathered at least five years. Do not use over glazed type shingles.

Asbestos Shingles (old, previously painted) surfaces in good condition normally require only one coat of "75" Exterior Eggshell. Over badly weathered surfaces, follow specifications under "Wood Shingles, Siding, Trim (New Unpainted)."

Wood Shingles, Siding, Trim (new, unpainted) — one coat "75" House Paint Primer followed with one coat "75" Exterior Eggshell

Wood Shingles, Siding, Trim (previously painted) — same specifications as listed under "Asbestos Shingles (Old, Previously Painted)."

Stucco, Concrete, Masonry — follow same specifications as listed above under "Asbestos Shingles, Unpainted." **NOTE** — allow new masonry to age six months, if possible, before painting. Do not paint wet or chronically damp masonry with an oil base paint.

Special Note — before painting over stained shingles or shakes, paint a small test area and allow to dry several days to determine whether stain will "bleed" through. If no discoloration occurs, proceed with painting.

THE O'BRIEN CORPORATION
SOUTH BEND, IND. OKLAHOMA CITY, OKLA.
BALTIMORE, MD. SAN FRANCISCO, CAL.

RECEIVED
NOV 18 1956
REC'D No. 6518
DATE 7-18-57

NOV 17 1956

ONE

GALLON



75⁰⁰

EXTERIOR EGGSHELL
PAINT

FOR WOOD AND ASBESTOS SHINGLES • MASONRY • SIDING

OLIVE

#75 EXTERIOR EGGSHELL	
Pigment, OLIVE	49.35%
Zinc Oxide	41.63%
Titanium Dioxide	16.65%
Carbon Yellow Iron Oxide	1.97%
Chromium Oxide	4.00%
C. P. Chrome Yellow	4.83%
Aluminum Stearate	1.70%
Silicone	33.22%
Vehicle	100.00%
Varnish	50.62%
Alkyd Resin Solution	45.89%
Mineral Spirits A	14.20%
Driers	20.51%
	100.00%
Varnish	
Non-Volatile, Heat	
Treated Linseed Oil	
Fish & Thermolyzed	
Vegetable Oil	57.48%
Vegetable Mineral	42.52%
Solvents	
	100.00%
Alkyd Resin Solution	
Soya Alkyd Resin	60.00%
Vegetable Mineral	40.00%
Solvents	
	100.00%

MADE IN U.S.A. BY THE O'BRIEN CORPORATION • SOUTH BEND, INDIANA • BALTIMORE, MARYLAND

"75" EXTERIOR EGGSHELL PAINT

For Wood & Asbestos Shingles—Stucco—
Concrete—Wood Siding and Trim

A new, all-purpose outside eggshell paint for use on wood and asbestos shingles, stucco, concrete, masonry, metal, wood siding and trim. It provides a rich, durable finish to exterior surfaces where a dull coating is preferred to the conventional high lustre. This material works easy under the brush; has excellent coverage and unsurpassed hiding. Made with Pre-Shrunk Oils, it beautifies, protects and waterproofs. A "breather type" paint — it reduces paint blistering and peeling.

O'Brien's "75" Exterior Eggshell Paint Sealer is a special clear sealer for mixing with the paint, making an excellent primer for use over stucco, concrete, shingles and other porous surfaces where a two coat job is necessary. It helps to prevent paint troubles due to varying porosity or the presence of free alkali in stucco and masonry surfaces.

THINNING NOTE — to retard drying and setup of paint during hot weather, one pint of "75" Ex. Egg. Pt. Thinner should be added to each gal. of paint.

CAUTION! COMBUSTIBLE

Keep Away from Heat and Open Flame. **COMBUSTIBLE** — Do not use on interior surfaces which might be reached by children. Use with care. Avoid prolonged contact with skin. Wash thoroughly after handling and keep container closed when not in use.

RECEIVED
REQD. NO. 6513.81
DATE 7-18-56

DIRECTIONS FOR USE

Asbestos Shingles (unpainted*) — two coats are necessary. Under pastel colors of "75" Exterior Eggshell, use a prime coat of O'Brien's A.R. Primer (may be tinted with Tone-All Colors, not more than two tubes per gal.) Under dark colors of Exterior Eggshell, use prime coat consisting of equal part mixture of "75" Exterior Eggshell Paint Sealer and Exterior Eggshell Paint. Finish with one coat of "75" Exterior Eggshell Paint.

***IMPORTANT** — this material is not recommended for use over unpainted asbestos shingles unless the shingles have weathered at least five years. Do not use over glazed type shingles.

Asbestos Shingles (old, previously painted) surfaces in good condition normally require only one coat of "75" Exterior Eggshell. Over badly weathered surfaces, follow specifications under "Wood Shingles, Siding, Trim (New Unpainted)."

Wood Shingles, Siding, Trim (new, unpainted) — one coat "75" House Paint Primer followed with one coat "75" Exterior Eggshell

Wood Shingles, Siding, Trim (previously painted) — same specifications as listed under "Asbestos Shingles (Old, Previously Painted)."

Stucco, Concrete, Masonry — follow same specifications as listed above under "Asbestos Shingles, Unpainted." **NOTE**—allow new masonry to age six months, if possible, before painting. Do not paint wet or chronically damp masonry with an oil base paint.

Special Note — before painting over stained shingles or shakes, paint a small test area and allow to dry several days to determine whether stain will "bleed" through. If no discoloration occurs, proceed with painting.

THE O'BRIEN CORPORATION
SOUTH BEND, IND. OKLAHOMA CITY, OKLA.
BALTIMORE, MD. SAN FRANCISCO, CAL.