

FILE NAME: Kaiser Gypsum (KG)

DATE: 1973 Oct

DOC#: KG112

DOCUMENT DESCRIPTION: Technical Bulletin - Cover-Tex Wall Texture

TECHNICAL BULLETIN

**KAISER
GYPSUM**

DATE: October 1973

BULLETIN NO. 5707

WALLBOARD ACCESSORIES - COVER-TEX WALL TEXTURE

DESCRIPTION

Kaiser Cover-Tex Wall Texture is a specially formulated dry powder which, when mixed with water, will provide various texture patterns when applied over gypsum wallboard surfaces. The texture is formulated for easy mixing, maximum coverage, excellent hide, easy application, and a white surface as a base for final decoration of walls or ceilings.

USES

Kaiser Cover-Tex is a dry powder texture designed for either hand or spray application for use as a base or final texture on gypsum wallboard walls or ceilings. It is particularly formulated to have good spraying qualities for both "fog" application and for heavy "splatter" patterns, with no sag or running of the texture. Color matched so that when used as a spray wall texture, it will match K-Spray Ceiling Texture.

A wide range of textures may be obtained by hand applying with a brush, sponge, roller, whisk broom, scrub brush, wadded paper, or cloth. A trowel dragged over a stippled area to knock down high spots will produce a brocade effect. Cover-Tex is shipped in 25- or 50-pound sacks. Depending upon the type and thickness of texture, a good approximation of coverage is 20 square feet per pound of dry powder.

APPLICATION INSTRUCTIONS

SURFACE PREPARATION

All joints, fasteners, and irregularities shall be finished with Kaiser Joint Treatment Products; and the wallboard surface shall be clean and dry. For best results, seal all surfaces with a primer-sealer before applying the texture to equalize the suction between the wallboard and the joint treatment.

MIXING

Mix Cover-Tex using 2-1/2 gallons of clean, cool water per 25-pound sack. Add powder to water with continuous stirring with a mechanical mixer until the paste is smooth and lump-free. After letting stand for 15 to 30 minutes, remix and adjust paste to desired consistency. Mix only sufficient material for use within 24 hours and keep paste covered when not being used. Avoid exposure to direct sunlight or temperatures above 90° F.

White sand may be added to Cover-Tex when a sand finish is desired.

APPLICATION

Maintain a minimum of 55° F. with adequate ventilation in the structure during application and drying.

Spray Application

Use a commercial spray unit including an air compressor, pump, connecting hoses, and spray gun with nozzle. Adjust air pressure on spray gun to produce type of textured finish desired, such as a thin coat (fog spray), stipple finish or orange peel finish. Apply an even coat of texture material by moving the nozzle at a uniform rate across the surface. Spray ceilings first and then sidewalls. Use respirator and eye protection during spray application.