


908-STANDARD TACHOMETERS



0-6000 R.P.M.
Size : 3 in. Dia.
6 or 12 Volt


3-5660 - 6 or 8 cyl.
3-5661 - 4 cyl.

Operates on 6 or 12 Volt Ignition with Negative or Positive Ground Individually Calibrated for Accuracy. Tested on an Actual Engine Ignition System.

Balkamp tachometers are constructed with jeweled D'Arsonval meter for maximum resistance to vibration and shock. Engineered with zener-diode regulation and transistor circuit for maximum accuracy, reliability and long life.

SHIFT POINTER

The adjustable shift pointer lets you show the R.P.M. at which the engine delivers maximum useful power. Shifting at the right time can easily cut your elapsed time (ET) by seconds. In race competition this can mean a great deal. Also when driving in high gear the shift pointer can prevent lugging and unnecessary engine abuse.




0-8000 R.P.M.
Size: 3 in. Dia.
6 or 12 Volt

3-5665 - 6 or 8 cyl.
3-5666 - 4 cyl.

HIGHEST ACCURACY ELECTRIC TACHOMETER

- Operates on 6 or 12 volts
Negative or positive battery ground.
Also from most negative ground transistor ignitions.
- Long Readable Scale
- Steady R.P.M. Pointer
- Clean Modern Styling
- Indirect Illumination
Green light inside tachometer.



0-4000 R.P.M.
Size: 3 in. Dia.
6 or 12 Volt

3-5662 - 8 cyl.
3-5663 - 6 cyl.
3-5664 - 4 cyl.

AUTOMOTIVE, INBOARD MARINE AND OTHER FOUR-CYCLE ENGINES

No.	Cyl.	Ign. Volt	R.P.M.
3-5660	6 or 8	6 or 12	0-6000
3-5661	4	6 or 12	0-6000
3-5662	8	6 or 12	0-4000
3-5663	6	6 or 12	0-4000
3-5664	4	6 or 12	0-4000
3-5665	6 or 8	6 or 12	0-8000
3-5666	4	6 or 12	0-8000

OUTBOARD (2 CYCLE) ENGINES

4 Cylinder Magneto Ignition
3-5667 0-6000 R.P.M.

Fits:


Mercury - 4 cyl. Johnson - V-4
Evinrude - V-4 Gale - V-4

DISPLAY STAND

3-5670



Standard Tachometer mounted in all chrome housing displayed on black metal stand suitable for counter top.



Display Contains:

1 Chrome Housing
3-5690

1 Tachometer
3-5665

MOUNT IN PANEL, ON DASH OR STEERING COLUMN

Replacement Parts