

Size 2 Horizontal, Open Type

- Catalog number
- Voltage and frequency

3 PHASE REDUCED VOLTAGE & MULTISPEED MOTOR CONTROL

Maximum Horsepower 60-50-25 Cycle					NEMA Size	① No. of Poles	General Purpose NEMA 1			Watertight NEMA 3-4		Dusttight— Industrial NEMA 5-12		Open Type Separate Control		
2 or 3 Phase			Single Phase				Ver- tical	Hori- zontal	Price	② Vertical				Ver- tical	Hori- zontal	Price
208/220 Volts	440 Volts	550 Volts	115 Volts	230 Volts						Cat. No.	Cat. No.	Cat. No.	Price			
---	---	---	½	---	00	2	---	9595- H2118	\$62.	9595- W21	\$108.	---	---	---	9595- W28	\$58.
---	---	---	---	¾		2	---	H2119	62.	W22	108.	---	---	---	W29	58.
---	---	---	½	---		3	---	H2112	64.	W23	110.	---	---	---	W30	60.
---	---	---	---	¾		3	---	H2113	64.	W24	110.	---	---	---	W31	60.
1	---	---	---	---		3	---	H2100	64.	W25	110.	---	---	---	H1869	60.
---	1	---	---	---		3	---	H2101	64.	W26	110.	---	---	---	H1870	60.
---	---	1	---	---	3	---	H2102	64.	W27	110.	---	---	---	H1871	60.	
---	---	---	1	2	0	2	9656- H15	9656- H22	74.	9656- W44	120.	9656- W45	\$92.	9656- H1	9656- H8	70.
---	---	---	1	2		3	H43	H61	76.	W46	122.	W47	94.	W48	W49	72.
3	5	5	---	---		3	H16	H23	76.	H30	122.	H536	94.	H59	H60	72.
3	5	5	---	---		4	H17	H24	96.	H31	142.	H552	114.	H3	H10	92.
---	---	---	2	3	1	2	H115	H122	86.	W50	150.	W51	104.	H101	H108	80.
7½	10	10	---	---		3	H116	H123	88.	H130	152.	H538	106.	H158	H159	82.
7½	10	10	---	---		4	H117	H124	109.	H131	173.	H553	127.	H103	H110	105.
15	25	25	---	---	2	3	H211	H216	172.	H221	276.	H226	202.	H244	H241	156.
15	25	25	---	---		4	H212	H217	214.	H222	324.	H227	244.	H207	H202	198.
30	50	50	---	---	3	3	H306	H316	287.	H331	441.	H336	353.	H341	H344	259.
30	50	50	---	---		4	H307	H317	358.	H332	510.	H337	422.	H302	H312	328.
50	100	---	---	---	4	3	H418	---	698.	H426	970.	H434	800.	H458	H464	646.
---	---	100	---	---		3	H419	---	698.	H427	970.	H435	800.	H459	H465	646.
50	---	---	---	---		4	H420	---	888.	H428	1162.	H436	992.	H404	H412	834.
100	200	---	---	---	5	3	H498	---	1466.	H504	1818.	H501	1818.	H522	H524	1165.
---	---	200	---	---		3	H499	---	1466.	H505	1818.	H502	1818.	H523	H525	1165.
100	---	---	---	---		4	H500	---	1757.	H506	2327.	H503	2109.	H487	H474	1455.
200	400	400	---	---	6	3	W52	---	3650.	W53	4150.	W54	4150.	W55	---	3150.
300	600	600	---	---	7	3	W56	---	4543.	W57	5043.	W58	5043.	W59	---	4043.

① 60 cycles only. Order 50 or 25 cycles by description and complete motor data.

② Except size 00.

AC-DC CONTACTORS,
RELAYS & TIMERS

Contacts	Catalog Numbers					Price
	Size 0	Size 1	Size 2	Size 3	Size 4 & 5	
Normally Open.....	10933-H1	10933-H1	10933-H7	10933-H7	10933-H7	\$6.
Normally Closed.....	H2	H3	H8	H9	H21	6.
Normally Closed						
Late Opening.....	H4	H4	H10	H10	H10	6.
③ Normally Open & Normally Closed.....	H5	H6	---	---	---	8.

③ Both normally open and normally closed contacts must be of same polarity.


**PUSHBUTTONS & LIGHTS,
LIMIT SWITCHES,
FOOT SWITCHES**

No. of Poles	Contactor Size		
	0 & 1	2 & 3	4 & 5
2	2	---	---
3	1	2	3
4	1	2	3

**MISCELLANEOUS
ACCESSORIES &
COMPONENTS**

Maximum horsepower where operation is interrupted more than five times per minute

Phase	Volts	Size 00	Size 0	Size 1	Size 2	Size 3	Size 4	Size 5	Size 6	Size 7
2 or 3 Phase	208/220 440-550	½ ½	1 1	3 5	10 15	20 30	30 60	75 150	150 300	225 450
Single Phase	115 230	¼ ⅓	½ ¾	1 2	---	---	---	---	---	---



Size 1 Vertical, Open Type

DISCOUNT SCHEDULE 1 CD