

RPM

INTER-ORGANIZATION

MEMORANDUM

PLAINTIFF'S EXHIBIT

BOND-398

S-51

FROM Louis J. Gillich

Always provide address to which reply is to be sent

TO Julius Nemeth

DATE September 11, 1972

SUBJECT

Please use a separate sheet for each subject treated

Herewith your memo of August 22nd regarding labels. We are constantly correcting labels and are now going over all the RPM labels so that they comply with all laws. The labels and all products containing asbestos fiber should read:

Contains asbestos fiber. Do not spray in localities where asbestos-containing coatings are prohibited.

We are also adding the flammable-warning paragraph because some of the asphalt we receive has a flash point of around 80 or 90°F.

Also, as you will note on our #301 label attached, we indicate that if applied in rainy weather, the product will give "unsatisfactory results" -- rather than "an unsatisfactory appearance." If you wish, please let us have one each of your Alcoatings and Bondex labels and we will go over them.

LJG

gjlw

Attachment

BON - 00997

ALUMINATHIO

301

ASBESTOS FIBRED ALUMINUM ROOFING

NET CONTENTS *3 Gallons* Liquid - U.S. Measure

REPAIRS POWDERED METALS - METAL ROOFING - METAL SCAFFOLDING

DIRECTIONS FOR USE

Remove all debris, clean roof thoroughly, patch split seams, waterproof parapet walls, reset coping where loose, nail down loose felt or paper, replace badly rusted flashing, repair skylights and vents, caulk windows, flush drains, etc. Do not apply if rainy weather is imminent or if a heavy dew is expected as water on the surface will disperse the ALUMINUM flakes, uncover the asphalt and gilsonite and give unsatisfactory appearance.

No thinner is required and when applying in cold weather, loosen cover and store previous day in heated room or warehouse. Use a stiff bristled brush, squeegee or spray gun for application, the spray gun to have at least 80 lbs. pressure.

Coverage is 2 to 2½ gallons per square over smooth surfaces and up to 4 to 5 gallons over slag and gravel. Drying time is 20 to 24 hours depending on weather.

Warranty for
Manufactured by

REPUBLIC POWDERED METALS - MEDINA, OHIO 44256, U.S.A.

STIR WELL
BEFORE SPRAYING
APPLICATION