

Y-5022
HOUSE PAINT

Glidden

PROTECTIVE PAINTS and CO.

NO. 22 HOUSE PAINT
FOR TRIM AND TINTING
5022 WHITE

CAUTION! COMBUSTIBLE!

CONTAINS LEAD. HARMFUL IF SWALLOWED.

Keep away from heat and open flame.
Do not apply on toys, furniture, window
sills, or other interior surfaces of rooms
which may be used by children. Avoid
prolonged contact with skin and breath-
ing of vapor or spray mist. Close con-
tainer after each use.

Use With Adequate Ventilation.
KEEP OUT OF THE REACH OF CHILDREN.

ONE GALLON
3.785 LITRES

11-65

1917-989



GLD01

HOUSE PAINT TRIM & TINTING WHITE

5022

No. 5022 House Paint is non-chalking and has unusual whiteness and elasticity. It has been formulated for use as a brilliant, lasting trim white and will not chalk on other colors or foundations. May be tinted with Glidden Dramatone Multi-Purpose Tinting Colors or Colors-In-Oil to produce light tints. Its extra high hiding and exceptional ease of brushing make No. 5022 House Paint especially suitable for professional painter use.

DIRECTIONS

SURFACE PREPARATION:

New Wood — Must be cured, dry and clean. Shellac all knots. Prime with No. 5051 House Paint Primer as directed for usage. Putty all cracks, nail holes and open joints. Caulk casings and chimneys where necessary.

Previously Painted Wood — Surfaces in good repaint condition need only be clean. Painted surfaces that are badly worn, heavily chalked, cracked, blistered, flaking or peeling should be wire brushed, scraped or burned off to the bare wood. Prime these areas with No. 5051 House Paint Primer. Finish coats — follow directions for new wood.

Finish Coats — Apply finish coats of No. 5022 House Paint unthinned. If two finish coats are to be applied, thin the first coat with 1/2 pint of turpentine or mineral spirits per gallon. Allow 48 hours drying time between coats.

MATERIAL PREPARATION:

Mix thoroughly by boxing. No. 5022 House Paint should be applied without thinning, although thinning with 1/2 pint of turpentine or mineral spirits per gallon is permissible when using over extremely hot or very cool surfaces. Always box after thinning. Do not add driers. May be tinted to light tints with Glidden Dramatone Multi-Purpose Tinting Colors or Colors-In-Oil.

MATERIAL APPLICATION:

Paint only when weather conditions are favorable and temperature is above 50°F. Apply liberally, brushing until coating is smooth and free of sags. For best performance, do not cover more than 550 square feet of surface with each gallon of paint. To spray, reduce 10% - 15% with turpentine or mineral spirits and use 30 to 40 pounds of air pressure. L.C. 5621

THE GLIDDEN COMPANY • CLEVELAND, OHIO • U.S.A.

MADE IN U.S.A.

GLD0117