



JEANNETTE, PA.

## MATERIAL SPECIFICATION No. 378

Date June 14, 1963

Sheet 1 No. SHEETS 2

Title: Asbestos Yarn - Plain

I. Scope: This specification covers a fire resistant product known as single asbestos yarn which is made from an asbestos roving.

II. Asbestos Content:


Min. - 95%  
Max. - 98%

III. Service Temperature: The material supplied to this specification shall be capable of withstanding a maximum temperature of 750°F.


IV. Grade and Sizes: The material supplied shall be ASTM D-299 AAA Grade.

Sizes available shall be between 5 and 18 "cut" inclusive.

V. Standard Specification: All provisions and requirements of ASTM D-299, latest revision, shall apply.



Approved 

Approved 

Approved \_\_\_\_\_

ET-00364

SC-ETM-3141

6C1



JEANNETTE, PA.

MATERIAL SPECIFICATION No. 378

Date June 14, 1963

Sheet 2

No. SHEETS 2


Title: Asbestos Yarn - Plain

Note: This sheet not to be sent to suppliers.

Approved Source:

Johns Manville Corporation

Note that size (cut) must be specified on the purchase order.  
At present our only stock size is 16 cut, but other sizes may be  
required for future requirements.



Approved [Signature]  
Approved [Signature]  
Approved [Signature]

ET-00365

602